

# Information technology —Programming languages — Ada

## AMENDMENT 1 (Draft 10)

*Technologies de l'information —Langages de programmation — Ada*

AMENDEMENT 1

Amendment 1 to International Standard ISO/IEC 8652:1995 was prepared by AXE Consultants.

© 2005, AXE Consultants. All Rights Reserved.

This document may be copied, in whole or in part, in any form or by any means, as is, or with alterations, provided that (1) alterations are clearly marked as alterations and (2) this copyright notice is included unmodified in any copy. Compiled copies of standard library units and examples need not contain this copyright notice so long as the notice is included in all copies of the source code and documentation. Any other use or distribution of this document is prohibited without the prior express permission of AXE.

---

## Introduction

International Standard ISO/IEC 8652:1995 defines the Ada programming language.

This amendment modifies Ada by making changes and additions that improve:

- The safety of applications written in Ada;
- The portability of applications written in Ada;
- Interoperability with other languages and systems; and
- Accessibility and ease of transition from idioms in other programming and modeling languages.

This amendment incorporates the following major additions to the International Standard:

- The Ravenscar profile to provide a simplified tasking system for high-integrity systems (see clause D.13);
- A non-preemptive task dispatching policy (see clause D.2.4);
- Aggregates, constructor functions, and constants for limited types (see clauses 4.3.1, 6.5, and 7.5);
- Control of overriding to eliminate errors (see clause 8.3);
- Improvements for access types, such as null excluding subtypes (see clause 3.10), additional uses for anonymous access types (see clauses 3.6 and 8.5.1), and anonymous access-to-subprogram subtypes to support 'downward closures' (see clauses 3.10 and 3.10.2);
- Additional context clause capabilities: limited views to allow mutually dependent types (see clauses 3.10.1 and 10.1.2) and private context clauses that apply only in the private part of a package (see clause 10.1.2);
- Added standard packages, including time management (see 9.6), file directory and name management (see clause A.16), containers (see clause A.17), execution-time clocks (see clause D.14), timing events (see clause D.15), and array and vector operations (see clause G.3);
- Interfaces, to provide a limited form of multiple inheritance of operations (see clause 3.9.4); and
- A mechanism for writing C unions to make interfaces with C systems easier (see clause B.3.3).

This Amendment is organized by sections corresponding to those in the International Standard. These sections include wording changes and additions to the International Standard. Clause and subclause headings are given for each clause that contains a wording change. Clauses and subclauses that do not contain any change or addition are omitted.

For each change, an *anchor* paragraph from the International Standard (as corrected by Technical Corrigendum 1) is given. New or revised text and instructions are given with each change. The anchor paragraph can be replaced or deleted, or text can be inserted before or after it. When a heading immediately precedes the anchor paragraph, any text inserted before the paragraph is intended to appear under the heading.

Typographical conventions:

**Instructions about the text changes are in this font.** The actual text changes are in the same fonts as the International Standard - this font for text, this font for syntax, and this font for Ada source code.

### Disclaimer:

**This document is a draft of a possible amendment to Ada 95 (International Standard ISO/IEC 8652:1995). This draft contains only proposals substantially approved by the ISO/IEC JTC 1/SC 22/WG 9 Ada Rapporteur Group (ARG). Many other important proposals are under**

consideration by the ARG. Neither the ARG nor any other group has determined which, if any, of these proposals will be included in the amendment. Any proposal may be substantially changed or withdrawn before this document begins standardization, and other proposals may be added. This document is not an official publication or work product of the ARG.

## Forward and Introduction

### Introduction

#### Replace paragraph 3: [AI95-00387-01]

- Rationale for the Ada Programming Language -- 1995 edition, which gives an introduction to the new features of Ada, and explains the rationale behind them. Programmers should read this first.

by:

- Ada 95 Rationale. This gives an introduction to the new features of Ada incorporated in the 1995 edition of this Standard, and explains the rationale behind them. Programmers unfamiliar with Ada 95 should read this first.
- Ada 2005 Rationale. This gives an introduction to the changes and new features in Ada 2005 (compared with the 1995 edition), and explains the rationale behind them. Programmers should read this rationale before reading this Standard in depth.

#### Replace paragraph 5: [AI95-00387-01]

- The Annotated Ada Reference Manual (AARM). The AARM contains all of the text in the RM95, plus various annotations. It is intended primarily for compiler writers, validation test writers, and others who wish to study the fine details. The annotations include detailed rationale for individual rules and explanations of some of the more arcane interactions among the rules.

by:

- The Annotated Ada Reference Manual (AARM). The AARM contains all of the text in the consolidated Ada Reference Manual, plus various annotations. It is intended primarily for compiler writers, validation test writers, and others who wish to study the fine details. The annotations include detailed rationale for individual rules and explanations of some of the more arcane interactions among the rules.

#### Replace paragraph 6: [AI95-00387-01]

Ada was originally designed with three overriding concerns: program reliability and maintenance, programming as a human activity, and efficiency. This revision to the language was designed to provide greater flexibility and extensibility, additional control over storage management and synchronization, and standardized packages oriented toward supporting important application areas, while at the same time retaining the original emphasis on reliability, maintainability, and efficiency.

by:

Ada was originally designed with three overriding concerns: program reliability and maintenance, programming as a human activity, and efficiency. The 1995 revision to the language was designed to provide greater flexibility and extensibility, additional control over storage management and synchronization, and standardized packages oriented toward supporting important application areas, while at the same time retaining the original emphasis on reliability, maintainability, and efficiency. This amended version provides further flexibility and adds more standardized packages within the framework provided by the 1995 revision.

#### Replace paragraph 32: [AI95-00285-01; AI95-00387-01]

An enumeration type defines an ordered set of distinct enumeration literals, for example a list of states or an alphabet of characters. The enumeration types Boolean, Character, and Wide\_Character are predefined.

by:

An enumeration type defines an ordered set of distinct enumeration literals, for example a list of states or an alphabet of characters. The enumeration types Boolean, Character, Wide\_Character, and Wide\_Wide\_Character are predefined.

**Replace paragraph 34: [AI95-00285-01; AI95-00387-01]**

Composite types allow definitions of structured objects with related components. The composite types in the language include arrays and records. An array is an object with indexed components of the same type. A record is an object with named components of possibly different types. Task and protected types are also forms of composite types. The array types `String` and `Wide_String` are predefined.

**by:**

Composite types allow definitions of structured objects with related components. The composite types in the language include arrays and records. An array is an object with indexed components of the same type. A record is an object with named components of possibly different types. Task and protected types are also forms of composite types. The array types `String`, `Wide_String`, and `Wide_Wide_String` are predefined.

**Insert after paragraph 38: [AI95-00387-01]**

From any type a new type may be defined by derivation. A type, together with its derivatives (both direct and indirect) form a derivation class. Class-wide operations may be defined that accept as a parameter an operand of any type in a derivation class. For record and private types, the derivatives may be extensions of the parent type. Types that support these object-oriented capabilities of class-wide operations and type extension must be tagged, so that the specific type of an operand within a derivation class can be identified at run time. When an operation of a tagged type is applied to an operand whose specific type is not known until run time, implicit dispatching is performed based on the tag of the operand.

**the new paragraph:**

Interface types provide abstract models from which other interfaces and types may be composed and derived. This provides a reliable form of multiple inheritance. Interface types may also be implemented by synchronized types (task types and protected types) thereby enabling concurrent programming and inheritance to be merged.

**Replace paragraph 41: [AI95-00387-01]**

Representation clauses can be used to specify the mapping between types and features of an underlying machine. For example, the user can specify that objects of a given type must be represented with a given number of bits, or that the components of a record are to be represented using a given storage layout. Other features allow the controlled use of low level, nonportable, or implementation-dependent aspects, including the direct insertion of machine code.

**by:**

Aspect clauses can be used to specify the mapping between types and features of an underlying machine. For example, the user can specify that objects of a given type must be represented with a given number of bits, or that the components of a record are to be represented using a given storage layout. Other features allow the controlled use of low level, nonportable, or implementation-dependent aspects, including the direct insertion of machine code.

**Replace paragraph 42: [AI95-00387-01]**

The predefined environment of the language provides for input-output and other capabilities (such as string manipulation and random number generation) by means of standard library packages. Input-output is supported for values of user-defined as well as of predefined types. Standard means of representing values in display form are also provided. Other standard library packages are defined in annexes of the standard to support systems with specialized requirements.

**by:**

The predefined environment of the language provides for input-output and other capabilities by means of standard library packages. Input-output is supported for values of user-defined as well as of predefined types. Standard means of representing values in display form are also provided.

The predefined standard library packages provide facilities such as string manipulation, containers of various kinds (vectors, lists, maps etc.), mathematical functions, random number generation, and access to the execution environment.

The specialized annexes define further predefined library packages and facilities with emphasis on areas such as real-time scheduling, interrupt handling, distributed systems, numerical computation, and high-integrity systems.

**Replace paragraph 44: [AI95-00387-01]**

This International Standard replaces the first edition of 1987. In this edition, the following major language changes have been incorporated:

**by:**

This amended International Standard updates the edition of 1995 which replaced the first edition of 1987. In the 1995 edition, the following major language changes were incorporated:

**Replace paragraph 45: [AI95-00387-01]**

- Support for standard 8-bit and 16-bit character sets. See Section 2, 3.5.2, 3.6.3, A.1, A.3, and A.4.

**by:**

- Support for standard 8-Bit and 16-bit characters was added. See clauses 2.1, 3.5.2, 3.6.3, A.1, A.3, and A.4.

**Replace paragraph 46: [AI95-00387-01]**

- Object-oriented programming with run-time polymorphism. See the discussions of classes, derived types, tagged types, record extensions, and private extensions in clauses 3.4, 3.9, and 7.3. See also the new forms of generic formal parameters that are allowed by 12.5.1, ``Formal Private and Derived Types" and 12.7, ``Formal Packages".

**by:**

- The type model was extended to include facilities for object-oriented programming with dynamic polymorphism. See the discussions of classes, derived types, tagged types, record extensions, and private extensions in clauses 3.4, 3.9, and 7.3. Additional forms of generic formal parameters were allowed as described in clauses 12.5.1 and 12.7.

**Replace paragraph 47: [AI95-00387-01]**

- Access types have been extended to allow an access value to designate a subprogram or an object declared by an object declaration (as opposed to just a heap-allocated object). See 3.10.

**by:**

- Access types were extended to allow an access value to designate a subprogram or an object declared by an object declaration as opposed to just an object allocated on a heap. See clause 3.10.

**Replace paragraph 48: [AI95-00387-01]**

- Efficient data-oriented synchronization is provided via protected types. See Section 9.

**by:**

- Efficient data-oriented synchronization was provided by the introduction of protected types. See clause 9.4.

**Replace paragraph 49: [AI95-00387-01]**

- The library units of a library may be organized into a hierarchy of parent and child units. See Section 10.

by:

- The library structure was extended to allow library units to be organized into a hierarchy of parent and child units. See clause 10.1.

**Replace paragraph 50: [AI95-00387-01]**

- Additional support has been added for interfacing to other languages. See Annex B.

by:

- Additional support was added for interfacing to other languages. See Annex B.

**Replace paragraph 51: [AI95-00387-01]**

- The Specialized Needs Annexes have been added to provide specific support for certain application areas:

by:

- The Specialized Needs Annexes were added to provide specific support for certain application areas:

**Replace paragraph 57: [AI95-00387-01]**

- Annex H, "Safety and Security"

by:

- Annex H, "High Integrity Systems"

Amendment 1 modifies the 1995 International Standard by making changes and additions that improve the capability of the language and the reliability of programs written in the language. In particular the changes were designed to improve the portability of programs, interfacing to other languages, and both the object-oriented and real-time capabilities.

The following significant changes with respect to the 1995 edition are incorporated:

- Support for program text is extended to cover the entire ISO/IEC 10646:2003 repertoire. Execution support now includes the 32-bit character set. See clauses 2.1, 3.5, 3.6, A.1, A.3, and A.4.
- The object-oriented model has been improved by the addition of an interface facility which provides multiple inheritance and additional flexibility for type extensions. See clauses 3.4, 3.9, and 7.3. An alternative notation for calling operations more akin to that used in other languages has also been added. See clause 4.1.3.
- Access types have been further extended to unify properties such as the ability to access constants and to exclude null values. See clause 3.10. Anonymous access types are now permitted more freely and anonymous access-to-subprogram types are introduced. See clauses 3.3, 3.6, 3.10, and 8.5.1.
- The control of structure and visibility has been enhanced to permit mutually dependent references between units and finer control over access from the private part of a package. See clauses 3.10.1 and 10.1.2. In addition, limited types have been made more useful by the provision of aggregates, constants, and constructor functions. See clauses 4.3, 6.5, and 7.5.
- The predefined environment has been extended to include additional time and calendar operations, improved string handling, a comprehensive container library, file and directory management, and access to environment variables. See clauses 9.6.1, A.4, A.16, A.17, and A.18.
- Two of the Specialized Needs Annexes have been considerably enhanced:
  - The Real-Time Systems Annex now includes the Ravenscar profile for high-integrity systems, further dispatching policies such as Round Robin and Earliest Deadline First, support for timing events, and support for control of CPU time utilization. See clauses D.2, D.13, D.14, and D.15.

## **ISO/IEC 8652:1995/WD.1:2005**

- The Numerics Annex now includes support for real and complex vectors and matrices as previously defined in ISO/IEC 13813:1997 plus further basic operations for linear algebra. See clause G.3.
- The overall reliability of the language has been enhanced by a number of improvements. These include new syntax which detects accidental overloading, as well as pragmas for making assertions and giving better control over the suppression of checks. See clauses 6.1, 11.4.2, and 11.5.



## Section 1: General

### 1.1.2 Structure

Replace paragraph 13: [AI95-00347-01]

- Annex H, "Safety and Security"

by:

- Annex H, "High Integrity Systems"

### 1.1.4 Method of Description and Syntax Notation

Insert after paragraph 14: [AI95-00285-01]

- If the name of any syntactic category starts with an italicized part, it is equivalent to the category name without the italicized part. The italicized part is intended to convey some semantic information. For example *subtype\_name* and *task\_name* are both equivalent to *name* alone.

the new paragraph:

The delimiters, compound delimiters, reserved words, and *numeric\_literals* are exclusively made of the characters whose code position is between 16#20# and 16#7E#, inclusively. The special characters for which names are defined in this International Standard (see 2.1) belong to the same range. For example, the character E in the definition of exponent is the character whose name is "LATIN CAPITAL LETTER E", not "GREEK CAPITAL LETTER EPSILON".

## 1.2 Normative References

Insert after paragraph 5: [AI95-00351-01]

ISO/IEC 6429:1992, *Information technology - Control functions for coded graphic character sets*.

the new paragraph:

ISO 8601:2004, *Data elements and interchange formats - Information interchange - Representation of dates and times*.

Replace paragraph 8: [AI95-00285-01]

ISO/IEC 10646-1:1993, *Information technology - Universal Multiple-Octet Coded Character Set (UCS) - Part 1: Architecture and Basic Multilingual Plane*, supplemented by Technical Corrigendum 1:1996.

by:

ISO/IEC 10646:2003, *Information technology - Universal Multiple-Octet Coded Character Set (UCS)*

## Section 2: Lexical Elements

### 2.1 Character Set

**Replace paragraph 1: [AI95-00285-01]**

The only characters allowed outside of comments are the `graphic_characters` and `format_effectors`.

**by:**

The character repertoire for the text of an Ada program consists of the collection of characters described by the ISO/IEC 10646:2003 Universal Multiple-Octet Coded Character Set.

**Delete paragraph 2: [AI95-00285-01]**

`character ::= graphic_character | format_effector | other_control_function`

**Replace paragraph 3: [AI95-00285-01]**

`graphic_character ::= identifier_letter | digit | space_character | special_character`

**by:**

A character is any character defined within ISO/IEC 10646:2003 other than those whose code position is 16#FFFE# or 16#FFFF#.

**Replace paragraph 4: [AI95-00285-01]**

The character repertoire for the text of an Ada program consists of the collection of characters called the Basic Multilingual Plane (BMP) of the ISO 10646 Universal Multiple-Octet Coded Character Set, plus a set of `format_effectors` and, in comments only, a set of `other_control_functions`; the coded representation for these characters is implementation defined (it need not be a representation defined within ISO-10646-1).

**by:**

The coded representation for characters is implementation defined (it need not be a representation defined within ISO/IEC 10646:2003). The characters whose code position is 16#FFFE# or 16#FFFF# are not allowed anywhere in the text of a program.

The semantics of an Ada program whose text is not in Normalization Form KC (as defined by section 24 of ISO/IEC 10646:2003) is implementation defined.

**Replace paragraph 5: [AI95-00285-01]**

The description of the language definition in this International Standard uses the graphic symbols defined for Row 00: Basic Latin and Row 00: Latin-1 Supplement of the ISO 10646 BMP; these correspond to the graphic symbols of ISO 8859-1 (Latin-1); no graphic symbols are used in this International Standard for characters outside of Row 00 of the BMP. The actual set of graphic symbols used by an implementation for the visual representation of the text of an Ada program is not specified.

**by:**

The description of the language definition in this International Standard uses the character properties General Category, Simple Uppercase Mapping, Uppercase Mapping, and Special Case Condition of the documents referenced by the note in section 1 of ISO/IEC 10646:2003. The actual set of graphic symbols used by an implementation for the visual representation of the text of an Ada program is not specified.

**Replace paragraph 6: [AI95-00285-01]**

The categories of characters are defined as follows:

**by:**

Characters are categorized as follows:

**Delete paragraph 7: [AI95-00285-01]**

identifier\_letter  
 upper\_case\_identifier\_letter | lower\_case\_identifier\_letter

**Replace paragraph 8: [AI95-00285-01]**

upper\_case\_identifier\_letter  
 Any character of Row 00 of ISO 10646 BMP whose name begins ``Latin Capital Letter".

by:

letter\_uppercase  
 Any character whose General Category is defined to be "Letter, Uppercase".

**Replace paragraph 9: [AI95-00285-01]**

lower\_case\_identifier\_letter  
 Any character of Row 00 of ISO 10646 BMP whose name begins ``Latin Small Letter".

by:

letter\_lowercase  
 Any character whose General Category is defined to be "Letter, Lowercase".

letter\_titlecase  
 Any character whose General Category is defined to be "Letter, Titlecase".

letter\_modifier  
 Any character whose General Category is defined to be "Letter, Modifier".

letter\_other  
 Any character whose General Category is defined to be "Letter, Other".

mark\_non\_spacing  
 Any character whose General Category is defined to be "Mark, Non-Spacing".

mark\_spacing\_combining  
 Any character whose General Category is defined to be "Mark, Spacing Combining".

**Replace paragraph 10: [AI95-00285-01]**

digit  
 One of the characters 0, 1, 2, 3, 4, 5, 6, 7, 8, or 9.

by:

number\_decimal\_digit  
 Any character whose General Category is defined to be "Number, Decimal Digit".

number\_letter  
 Any character whose General Category is defined to be "Number, Letter".

**Replace paragraph 11: [AI95-00285-01]**

space\_character  
 The character of ISO 10646 BMP named ``Space".

by:

separator\_space  
 Any character whose General Category is defined to be "Separator, Space".

**Replace paragraph 12: [AI95-00285-01]**

special\_character  
 Any character of the ISO 10646 BMP that is not reserved for a control function, and is not the space\_character, an identifier\_letter, or a digit.

**by:**

`separator_line`

Any character whose General Category is defined to be "Separator, Line".

`separator_paragraph`

Any character whose General Category is defined to be "Separator, Paragraph".

**Replace paragraph 13: [AI95-00285-01]**

`format_effector`

The control functions of ISO 6429 called character tabulation (HT), line tabulation (VT), carriage return (CR), line feed (LF), and form feed (FF).

**by:**

`format_effector`

The characters whose code positions are 16#09# (CHARACTER TABULATION), 16#0A# (LINE FEED(LF)), 16#0B# (LINE TABULATION), 16#0C# (FORM FEED(FF)), 16#0D# (CARRIAGE RETURN(CR)), 16#85# (NEXT LINE(NEL)), and the characters in categories `separator_line` and `separator_paragraph`. The names mentioned in parentheses in this list are not defined by ISO/IEC 10646:2003; they are only used for convenience in this International Standard.

`other_control`

Any character whose General Category is defined to be "Other, Control", and which is not defined to be a `format_effector`.

`other_format`

Any character whose General Category is defined to be "Other, Format".

`other_private_use`

Any character whose General Category is defined to be "Other, Private Use".

`other_surrogate`

Any character whose General Category is defined to be "Other, Surrogate".

`punctuation_connector`

Any character whose General Category is defined to be "Punctuation, Connector".

**Replace paragraph 14: [AI95-00285-01]**

`other_control_function`

Any control function, other than a `format_effector`, that is allowed in a comment; the set of `other_control_functions` allowed in comments is implementation defined.

**by:**

`graphic_character`

Any character which is not in the categories `other_control`, `other_private_use`, `other_surrogate`, `other_format`, `format_effector`, and whose code position is neither 16#FFFE# nor 16#FFFF#.

**Replace paragraph 15: [AI95-00285-01]**

The following names are used when referring to certain `special_characters`:

**by:**

The following names are used when referring to certain characters (the first name is that given in ISO/IEC 10646:2003):

**Delete paragraph 16: [AI95-00285-01]**

In a nonstandard mode, the implementation may support a different character repertoire; in particular, the set of characters that are considered `identifier_letters` can be extended or changed to conform to local conventions.

**Replace paragraph 17: [AI95-00285-01]**

1 Every code position of ISO 10646 BMP that is not reserved for a control function is defined to be a `graphic_character` by this International Standard. This includes all code positions other than 0000 - 001F, 007F - 009F, and FFFE - FFFF.

**by:**

1 The characters in categories `other_control`, `other_private_use`, and `other_surrogate` are only allowed in comments.

**2.2 Lexical Elements, Separators, and Delimiters****Replace paragraph 2: [AI95-00285-01]**

The text of a compilation is divided into *lines*. In general, the representation for an end of line is implementation defined. However, a sequence of one or more `format_effectors` other than character tabulation (HT) signifies at least one end of line.

**by:**

The text of a compilation is divided into *lines*. In general, the representation for an end of line is implementation defined. However, a sequence of one or more `format_effectors` other than the character whose code position is 16#09# (CHARACTER TABULATION) signifies at least one end of line.

**Replace paragraph 3: [AI95-00285-01]**

In some cases an explicit *separator* is required to separate adjacent lexical elements. A separator is any of a space character, a format effector, or the end of a line, as follows:

**by:**

In some cases an explicit *separator* is required to separate adjacent lexical elements. A separator is any of a `separator_space`, a `format_effector` or the end of a line, as follows:

**Replace paragraph 4: [AI95-00285-01]**

- A space character is a separator except within a comment, a `string_literal`, or a `character_literal`.

**by:**

- A `separator_space` is a separator except within a comment, a `string_literal`, or a `character_literal`.

**Replace paragraph 5: [AI95-00285-01]**

- Character tabulation (HT) is a separator except within a comment.

**by:**

- The character whose code position is 16#09# (CHARACTER TABULATION) is a separator except within a comment.

**Replace paragraph 8: [AI95-00285-01]**

A delimiter is either one of the following special characters:

**by:**

A delimiter is either one of the following characters:

**2.3 Identifiers****Replace paragraph 2: [AI95-00285-01]**

`identifier ::=`

identifier\_letter {[underline] letter\_or\_digit}

by:

```
identifier_start ::=  
    letter_uppercase  
    | letter_lowercase  
    | letter_titlecase  
    | letter_modifier  
    | letter_other  
    | number_letter
```

```
identifier_extend ::=  
    identifier_start  
    | mark_non_spacing  
    | mark_spacing_combining  
    | number_decimal_digit  
    | other_format
```

identifier ::= identifier\_start {[punctuation\_connector] identifier\_extend}

**Delete paragraph 3: [AI95-00285-01]**

letter\_or\_digit ::= identifier\_letter | digit

**Replace paragraph 5: [AI95-00285-01]**

All characters of an identifier are significant, including any underline character. Identifiers differing only in the use of corresponding upper and lower case letters are considered the same.

by:

Two identifiers are considered the same if they consist of the same sequence of characters after applying the following transformations (in this order):

- The characters in category `other_format` are eliminated.
- Locale-independent full case folding, as defined by documents referenced in the note in section 1 of ISO/IEC 10646:2003, is applied to obtain the uppercase version of each character.

**Insert after paragraph 6: [AI95-00285-01]**

In a nonstandard mode, an implementation may support other upper/lower case equivalence rules for identifiers, to accommodate local conventions.

the new paragraph:

NOTES

3 Identifiers differing only in the use of corresponding upper and lower case letters are considered the same.

## 2.4.1 Decimal Literals

**Insert after paragraph 5: [AI95-00285-01]**

exponent ::= E [+] numeral | E - numeral

the new paragraph:

digit ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9

## 2.6 String Literals

**Insert after paragraph 7: [AI95-00285-01]**

NOTES

6 An end of line cannot appear in a `string_literal`.

the new paragraph:

7 No transformation is performed on the sequence of characters in a `string_literal`.

## 2.9 Reserved Words

In the list in paragraph 2, add: [AI95-00284-02]

`interface`

`overriding`

`synchronized`

## Section 3: Declarations and Types

### 3.1 Declarations

Replace paragraph 3: [AI95-00348-01]

```
basic_declaration ::=
    type_declaration | subtype_declaration
    | object_declaration | number_declaration
    | subprogram_declaration | abstract_subprogram_declaration
    | package_declaration | renaming_declaration
    | exception_declaration | generic_declaration
    | generic_instantiation
```

by:

```
basic_declaration ::=
    type_declaration | subtype_declaration
    | object_declaration | number_declaration
    | subprogram_declaration | abstract_subprogram_declaration
    | null_procedure_declaration | package_declaration
    | renaming_declaration | exception_declaration
    | generic_declaration | generic_instantiation
```

### 3.2 Types and Subtypes

Replace paragraph 4: [AI95-00326-01]

The composite types are the *record* types, *record extensions*, *array* types, *task* types, and *protected* types. A *private* type or *private extension* represents a partial view (see 7.3) of a type, providing support for data abstraction. A partial view is a composite type.

by:

The composite types are the *record* types, *record extensions*, *array* types, *task* types, and *protected* types.

There can be multiple views of a type with varying sets of operations. An *incomplete* type represents an incomplete view (see 3.10.1) of a type with a very restricted usage, providing support for recursive data structures. A *private* type or *private extension* represents a partial view (see 7.3) of a type, providing support for data abstraction. The full view (see 3.2.1) of a type represents its complete definition. An incomplete or partial view is considered a composite type, even if the full view is not.

Replace paragraph 5: [AI95-00326-01]

Certain composite types (and partial views thereof) have special components called *discriminants* whose values affect the presence, constraints, or initialization of other components. Discriminants can be thought of as parameters of the type.

by:

Certain composite types (and views thereof) have special components called *discriminants* whose values affect the presence, constraints, or initialization of other components. Discriminants can be thought of as parameters of the type.

Replace paragraph 6: [AI95-00366-01]

The term *subcomponent* is used in this International Standard in place of the term *component* to indicate either a component, or a component of another subcomponent. Where other subcomponents are excluded, the term *component* is used instead. Similarly, a *part* of an object or value is used to mean the whole object or value, or any set of its subcomponents.



by:

The term *subcomponent* is used in this International Standard in place of the term *component* to indicate either a component, or a component of another subcomponent. Where other subcomponents are excluded, the term *component* is used instead. Similarly, a *part* of an object or value is used to mean the whole object or value, or any set of its subcomponents. The terms *component*, *subcomponent*, and *part* are also applied to a type meaning the component, subcomponent, or part of objects and values of the type.

**Replace paragraph 7: [AI95-00231-01]**

The set of possible values for an object of a given type can be subjected to a condition that is called a *constraint* (the case of a *null constraint* that specifies no restriction is also included); the rules for which values satisfy a given kind of constraint are given in 3.5 for *range\_constraints*, 3.6.1 for *index\_constraints*, and 3.7.1 for *discriminant\_constraints*.

by:

The set of possible values for an object of a given type can be subjected to a condition that is called a *constraint* (the case of a *null constraint* that specifies no restriction is also included); the rules for which values satisfy a given kind of constraint are given in 3.5 for *range\_constraints*, 3.6.1 for *index\_constraints*, and 3.7.1 for *discriminant\_constraints*. The set of possible values for an object of an access type can also be subject to a condition that is called a *null exclusion* (see 3.10).

**Replace paragraph 8: [AI95-00231-01]**

A *subtype* of a given type is a combination of the type, a constraint on values of the type, and certain attributes specific to the subtype. The given type is called the type *of* the subtype. Similarly, the associated constraint is called the constraint *of* the subtype. The set of values of a subtype consists of the values of its type that satisfy its constraint. Such values *belong* to the subtype.

by:

A *subtype* of a given type is a combination of the type, a constraint on values of the type, and certain attributes specific to the subtype. The given type is called the type *of* the subtype. Similarly, the associated constraint is called the constraint *of* the subtype. The set of values of a subtype consists of the values of its type that satisfy its constraint@Chg{Version=[2],New=[ and, in the case of a subtype of an access type, any applicable null exclusion],Old=[]}. Such values *belong* to the subtype.

### 3.2.1 Type Declarations

**Replace paragraph 4: [AI95-00251-01]**

```
type_definition ::=
    enumeration_type_definition | integer_type_definition
    | real_type_definition | array_type_definition
    | record_type_definition | access_type_definition
    | derived_type_definition
```

by:

```
type_definition ::=
    enumeration_type_definition | integer_type_definition
    | real_type_definition | array_type_definition
    | record_type_definition | access_type_definition
    | derived_type_definition | interface_type_definition
```

**Replace paragraph 7: [AI95-00230-01]**

A type defined by a *type\_declaration* is a *named* type; such a type has one or more nameable subtypes. Certain other forms of declaration also include type definitions as part of the declaration for an object (including a parameter or a discriminant). The type defined by such a declaration is *anonymous* - it has no nameable subtypes. For explanatory purposes, this International Standard sometimes refers to an anonymous type by a pseudo-name, written in italics, and uses such pseudo-names at places where the syntax normally

requires an identifier. For a named type whose first subtype is T, this International Standard sometimes refers to the type of T as simply "the type T."

by:

A type defined by a `type_declaration` is a *named* type; such a type has one or more nameable subtypes. Certain other forms of declaration also include type definitions as part of the declaration for an object. The type defined by such a declaration is *anonymous* - it has no nameable subtypes. For explanatory purposes, this International Standard sometimes refers to an anonymous type by a pseudo-name, written in italics, and uses such pseudo-names at places where the syntax normally requires an identifier. For a named type whose first subtype is T, this International Standard sometimes refers to the type of T as simply "the type T."

**Replace paragraph 8: [AI95-00230-01; AI95-00326-01]**

A named type that is declared by a `full_type_declaration`, or an anonymous type that is defined as part of declaring an object of the type, is called a *full type*. The `type_definition`, `task_definition`, `protected_definition`, or `access_definition` that defines a full type is called a *full type definition*. Types declared by other forms of `type_declaration` are not separate types; they are partial or incomplete views of some full type.

by:

A named type that is declared by a `full_type_declaration`, or an anonymous type that is defined as part of declaring an object (or view of an object) of the type, is called a *full type*. The declaration of a full type also declares the *full view* of the type. The `type_definition`, `task_definition`, `protected_definition`, or `access_definition` that defines a full type is called a *full type definition*. Types declared by other forms of `type_declaration` are not separate types; they are partial or incomplete views of some full type.

### 3.2.2 Subtype Declarations

**Replace paragraph 3: [AI95-00231-01]**

`subtype_indication ::= subtype_mark [constraint]`

by:

`subtype_indication ::= [null_exclusion] subtype_mark [constraint]`

### 3.2.3 Classification of Operations

**Insert after paragraph 6: [AI95-00335-01]**

- For a specific type declared immediately within a `package_specification`, any subprograms (in addition to the enumeration literals) that are explicitly declared immediately within the same `package_specification` and that operate on the type;

**the new paragraph:**

- For a specific type, the stream-oriented attributes of the type that are available (see 13.13.2) at the end of the list of `declarative_items` where the type is declared;

**Replace paragraph 7: [AI95-00200-01]**

- Any subprograms not covered above that are explicitly declared immediately within the same declarative region as the type and that override (see 8.3) other implicitly declared primitive subprograms of the type.

by:

- In the case of a nonformal type, any subprograms not covered above that are explicitly declared immediately within the same declarative region as the type and that override (see 8.3) other implicitly declared primitive subprograms of the type.

### 3.3.1 Object Declarations

#### Replace paragraph 2: [AI95-00385-01]

```
object_declaration ::=
  defining_identifier_list : [aliased] [constant] subtype_indication [:= expression]
| defining_identifier_list : [aliased] [constant] array_type_definition [:= expression]
| single_task_declaration
| single_protected_declaration
```

by:

```
object_declaration ::=
  defining_identifier_list : [aliased] [constant] subtype_indication [:= expression]
| defining_identifier_list : [constant] access_definition [:= expression]
| defining_identifier_list : [aliased] [constant] array_type_definition [:= expression]
| single_task_declaration
| single_protected_declaration
```

#### Replace paragraph 5: [AI95-00287-01]

An `object_declaration` without the reserved word **constant** declares a variable object. If it has a `subtype_indication` or an `array_type_definition` that defines an indefinite subtype, then there shall be an initialization expression. An initialization expression shall not be given if the object is of a limited type.

by:

An `object_declaration` without the reserved word **constant** declares a variable object. If it has a `subtype_indication` or an `array_type_definition` that defines an indefinite subtype, then there shall be an initialization expression.

#### Replace paragraph 8: [AI95-00373-01; AI95-00385-01]

The `subtype_indication` or full type definition of an `object_declaration` defines the nominal subtype of the object. The `object_declaration` declares an object of the nominal subtype.

by:

The `subtype_indication`, `access_definition`, or full type definition of an `object_declaration` defines the nominal subtype of the object. The `object_declaration` declares an object of the nominal subtype.

A component of an object is said to *require late initialization* if it has an access discriminant value constrained by a per-object expression, or if it has an initialization expression which includes a name denoting the current instance of the type or denoting an access discriminant.

#### Replace paragraph 9: [AI95-00363-01]

If a composite object declared by an `object_declaration` has an unconstrained nominal subtype, then if this subtype is indefinite or the object is constant or aliased (see 3.10) the actual subtype of this object is constrained. The constraint is determined by the bounds or discriminants (if any) of its initial value; the object is said to be *constrained by its initial value*. In the case of an aliased object, this initial value may be either explicit or implicit; in the other cases, an explicit initial value is required. When not constrained by its initial value, the actual and nominal subtypes of the object are the same. If its actual subtype is constrained, the object is called a *constrained object*.

by:

If a composite object declared by an `object_declaration` has an unconstrained nominal subtype, then if this subtype is indefinite or the object is constant the actual subtype of this object is constrained. The constraint is determined by the bounds or discriminants (if any) of its initial value; the object is said to be *constrained by its initial value*. When not constrained by its initial value, the actual and nominal subtypes of the object are the same. If its actual subtype is constrained, the object is called a *constrained object*.

**Replace paragraph 16: [AI95-00385-01]**

1. The subtype\_indication, array\_type\_definition, single\_task\_declaration, or single\_protected\_declaration is first elaborated. This creates the nominal subtype (and the anonymous type in the latter three cases).

**by:**

1. The subtype\_indication, access\_definition, array\_type\_definition, single\_task\_declaration, or single\_protected\_declaration is first elaborated. This creates the nominal subtype (and the anonymous type in the last four cases).

**Replace paragraph 18: [AI95-00373-01]**

3. The object is created, and, if there is not an initialization expression, any per-object expressions (see 3.8) are elaborated and any implicit initial values for the object or for its subcomponents are obtained as determined by the nominal subtype.

**by:**

3. The object is created, and, if there is not an initialization expression, any per-object expressions (see 3.8) are elaborated and any implicit initial values for the object or for its subcomponents are obtained as determined by the nominal subtype. Any initial values (whether explicit or implicit) are assigned to the object or to the corresponding subcomponents. As described in 5.2 and 7.6, Initialize and Adjust procedures can be called.

**Delete paragraph 19: [AI95-00373-01]**

4. Any initial values (whether explicit or implicit) are assigned to the object or to the corresponding subcomponents. As described in 5.2 and 7.6, Initialize and Adjust procedures can be called.

**Replace paragraph 20: [AI95-00373-01]**

For the third step above, the object creation and any elaborations and evaluations are performed in an arbitrary order, except that if the default\_expression for a discriminant is evaluated to obtain its initial value, then this evaluation is performed before that of the default\_expression for any component that depends on the discriminant, and also before that of any default\_expression that includes the name of the discriminant. The evaluations of the third step and the assignments of the fourth step are performed in an arbitrary order, except that each evaluation is performed before the resulting value is assigned.

**by:**

For the third step above, evaluations and assignments are performed in an arbitrary order subject to the following restrictions:

- Assignment to any part of the object is preceded by the evaluation of the value that is to be assigned.
- The evaluation of a default\_expression that includes the name of a discriminant is preceded by the assignment to that discriminant.
- The evaluation of the default\_expression for any component that depends on a discriminant is preceded by the assignment to that discriminant.
- The assignments to any components, including implicit components, not requiring late initialization must precede the initial value evaluations for any components requiring late initialization; if two components both require late initialization, then assignments to parts of the component occurring earlier in the order of the component declarations must precede the initial value evaluations of the component occurring later.

### 3.4 Derived Types and Classes

#### Replace paragraph 2: [AI95-00251-01]

`derived_type_definition ::= [abstract] new parent_subtype_indication [record_extension_part]`

by:

`interface_list ::= interface_subtype_mark {and interface_subtype_mark}`

`derived_type_definition ::=`  
`[abstract] new parent_subtype_indication [[and interface_list] record_extension_part]`

#### Replace paragraph 3: [AI95-00251-01]

The *parent\_subtype\_indication* defines the parent subtype; its type is the parent type.

by:

The *parent\_subtype\_indication* defines the parent subtype; its type is the parent type. A derived type has one parent type and zero or more interface ancestor types.

#### Replace paragraph 8: [AI95-00251-01]

- Each class of types that includes the parent type also includes the derived type.

by:

- Each class of types that includes the parent type or an interface ancestor type also includes the derived type.

#### Insert after paragraph 23: [AI95-00251-01]

If a primitive subprogram of the parent type is visible at the place of the `derived_type_definition`, then the corresponding inherited subprogram is implicitly declared immediately after the `derived_type_definition`. Otherwise, the inherited subprogram is implicitly declared later or not at all, as explained in 7.3.1.

#### the new paragraph:

If a type declaration names an interface type in an `interface_list`, then the declared type inherits any user-defined primitive subprograms of the interface type in the same way.

#### Replace paragraph 27: [AI95-00391-01]

For the execution of a call on an inherited subprogram, a call on the corresponding primitive subprogram of the parent type is performed; the normal conversion of each actual parameter to the subtype of the corresponding formal parameter (see 6.4.1) performs any necessary type conversion as well. If the result type of the inherited subprogram is the derived type, the result of calling the parent's subprogram is converted to the derived type.

by:

For the execution of a call on an inherited subprogram, a call on the corresponding primitive subprogram of the parent type is performed; the normal conversion of each actual parameter to the subtype of the corresponding formal parameter (see 6.4.1) performs any necessary type conversion as well. If the result type of the inherited subprogram is the derived type, the result of calling the parent's subprogram is converted to the derived type, or in the case of a null extension, extended to the derived type using the equivalent of an `extension_aggregate` with the original result as the `ancestor_part` and **null record** as the `record_component_association_list`.

#### Insert after paragraph 35: [AI95-00251-01]

17 If the reserved word **abstract** is given in the declaration of a type, the type is abstract (see 3.9.3).

#### the new paragraph:

18 An interface type which has an interface ancestor "is derived from" that type, and therefore is a derived type. A `derived_type_definition`, however, never defines an interface type.

### 3.4.1 Derivation Classes

#### Replace paragraph 2: [AI95-00251-01]

A derived type is *derived from* its parent type *directly*; it is derived *indirectly* from any type from which its parent type is derived. The derivation class of types for a type *T* (also called the class *rooted at T*) is the set consisting of *T* (the *root type* of the class) and all types derived from *T* (directly or indirectly) plus any associated universal or class-wide types (defined below).

by:

A derived type is *derived from* its parent type *directly*; it is derived *indirectly* from any type from which its parent type is derived. A derived type or interface type is also derived from each of its interface ancestor types, if any. The derivation class of types for a type *T* (also called the class *rooted at T*) is the set consisting of *T* (the *root type* of the class) and all types derived from *T* (directly or indirectly) plus any associated universal or class-wide types (defined below).

#### Replace paragraph 6: [AI95-00230-01]

Universal types

Universal types are defined for (and belong to) the integer, real, and fixed point classes, and are referred to in this standard as respectively, *universal\_integer*, *universal\_real*, and *universal\_fixed*. These are analogous to class-wide types for these language-defined numeric classes. As with class-wide types, if a formal parameter is of a universal type, then an actual parameter of any type in the corresponding class is acceptable. In addition, a value of a universal type (including an integer or real *numeric\_literal*) is ``universal" in that it is acceptable where some particular type in the class is expected (see 8.6).

by:

Universal types

Universal types are defined for (and belong to) the integer, real, fixed point, and access classes, and are referred to in this standard as respectively, *universal\_integer*, *universal\_real*, *universal\_fixed*, and *universal\_access*. These are analogous to class-wide types for these language-defined elementary classes. As with class-wide types, if a formal parameter is of a universal type, then an actual parameter of any type in the corresponding class is acceptable. In addition, a value of a universal type (including an integer or real *numeric\_literal*, or the literal **null**) is ``universal" in that it is acceptable where some particular type in the class is expected (see 8.6).

#### Replace paragraph 10: [AI95-00230-01; AI95-00351-01]

A specific type *T2* is defined to be a *descendant* of a type *T1* if *T2* is the same as *T1*, or if *T2* is derived (directly or indirectly) from *T1*. A class-wide type *T2*'Class is defined to be a descendant of type *T1* if *T2* is a descendant of *T1*. Similarly, the universal types are defined to be descendants of the root types of their classes. If a type *T2* is a descendant of a type *T1*, then *T1* is called an *ancestor* of *T2*. The *ultimate ancestor* of a type is the ancestor of the type that is not a descendant of any other type.

by:

A specific type *T2* is defined to be a *descendant* of a type *T1* if *T2* is the same as *T1*, or if *T2* is derived (directly or indirectly) from *T1*. A class-wide type *T2*'Class is defined to be a descendant of type *T1* if *T2* is a descendant of *T1*. Similarly, the numeric universal types are defined to be descendants of the root types of their classes. If a type *T2* is a descendant of a type *T1*, then *T1* is called an *ancestor* of *T2*. An *ultimate ancestor* of a type is an ancestor of that type that is not itself a descendant of any other type. Each untagged type has a unique ultimate ancestor.

### 3.5 Scalar Types

#### Insert after paragraph 27: [AI95-00285-01]

For an enumeration type, the function returns the value whose position number is one less than that of the value of *Arg*; *Constraint\_Error* is raised if there is no such value of the type. For an integer type, the function returns the result of subtracting one from the value of *Arg*. For a fixed point type, the function returns the result of subtracting small from the value of *Arg*. For a floating point type, the function returns the machine number (as defined in 3.5.7) immediately below the value of *Arg*; *Constraint\_Error* is raised if there is no such machine number.

#### the new paragraphs:

*S'Wide\_Wide\_Image*

*S'Wide\_Wide\_Image* denotes a function with the following specification:

```
function S'Wide_Wide_Image(Arg : S'Base)
return Wide_Wide_String
```

The function returns an *image* of the value of *Arg*, that is, a sequence of characters representing the value in display form. The lower bound of the result is one.

The image of an integer value is the corresponding decimal literal, without underlines, leading zeros, exponent, or trailing spaces, but with a single leading character that is either a minus sign or a space.

The image of an enumeration value is either the corresponding identifier in upper case or the corresponding character literal (including the two apostrophes); neither leading nor trailing spaces are included. For a *nongraphic character* (a value of a character type that has no enumeration literal associated with it), the result is a corresponding language-defined name in upper case (for example, the image of the nongraphic character identified as *nul* is "NUL" -- the quotes are not part of the image).

The image of a floating point value is a decimal real literal best approximating the value (rounded away from zero if halfway between) with a single leading character that is either a minus sign or a space, a single digit (that is nonzero unless the value is zero), a decimal point, *S'Digits-1* (see 3.5.8) digits after the decimal point (but one if *S'Digits* is one), an upper case E, the sign of the exponent (either + or -), and two or more digits (with leading zeros if necessary) representing the exponent. If *S'Signed\_Zeros* is True, then the leading character is a minus sign for a negatively signed zero.

The image of a fixed point value is a decimal real literal best approximating the value (rounded away from zero if halfway between) with a single leading character that is either a minus sign or a space, one or more digits before the decimal point (with no redundant leading zeros), a decimal point, and *S'Aft* (see 3.5.10) digits after the decimal point.

#### Replace paragraph 30: [AI95-00285-01]

The function returns an *image* of the value of *Arg*, that is, a sequence of characters representing the value in display form. The lower bound of the result is one.

by:

The function returns an image of the value of *Arg* as a *Wide\_String*, that is, a sequence of characters representing the value in display form. The lower bound of the result is one. The image has the same sequence of character as defined for *S'Wide\_Wide\_Image* if all the graphic characters are defined in *Wide\_Character*; otherwise the sequence of characters is implementation defined (but no shorter than that of *S'Wide\_Wide\_Image* for the same value of *Arg*).

#### Delete paragraph 31: [AI95-00285-01]

The image of an integer value is the corresponding decimal literal, without underlines, leading zeros, exponent, or trailing spaces, but with a single leading character that is either a minus sign or a space.

**Delete paragraph 32: [AI95-00285-01]**

The image of an enumeration value is either the corresponding identifier in upper case or the corresponding character literal (including the two apostrophes); neither leading nor trailing spaces are included. For a *nongraphic character* (a value of a character type that has no enumeration literal associated with it), the result is a corresponding language-defined or implementation-defined name in upper case (for example, the image of the nongraphic character identified as *nul* is "NUL" -- the quotes are not part of the image).

**Delete paragraph 33: [AI95-00285-01]**

The image of a floating point value is a decimal real literal best approximating the value (rounded away from zero if halfway between) with a single leading character that is either a minus sign or a space, a single digit (that is nonzero unless the value is zero), a decimal point, S'Digits-1 (see 3.5.8) digits after the decimal point (but one if S'Digits is one), an upper case E, the sign of the exponent (either + or -), and two or more digits (with leading zeros if necessary) representing the exponent. If S'Signed\_Zeros is True, then the leading character is a minus sign for a negatively signed zero.

**Delete paragraph 34: [AI95-00285-01]**

The image of a fixed point value is a decimal real literal best approximating the value (rounded away from zero if halfway between) with a single leading character that is either a minus sign or a space, one or more digits before the decimal point (with no redundant leading zeros), a decimal point, and S'Aft (see 3.5.10) digits after the decimal point.

**Replace paragraph 37: [AI95-00285-01]**

The function returns an image of the value of *Arg* as a String. The lower bound of the result is one. The image has the same sequence of graphic characters as that defined for S'Wide\_Image if all the graphic characters are defined in Character; otherwise the sequence of characters is implementation defined (but no shorter than that of S'Wide\_Image for the same value of *Arg*).

by:

The function returns an image of the value of *Arg* as a String. The lower bound of the result is one. The image has the same sequence of character as defined for S'Wide\_Wide\_Image if all the graphic characters are defined in Character; otherwise the sequence of characters is implementation defined (but no shorter than that of S'Wide\_Wide\_Image for the same value of *Arg*).

S'Wide\_Wide\_Width

S'Wide\_Wide\_Width denotes the maximum length of a Wide\_Wide\_String returned by S'Wide\_Wide\_Image over all the values of S. It denotes zero for a subtype that has a null range. Its type is *universal\_integer*.

**Insert after paragraph 39: [AI95-00285-01]**

S'Width

S'Width denotes the maximum length of a String returned by S'Image over all values of the subtype S. It denotes zero for a subtype that has a null range. Its type is *universal\_integer*.

**the new paragraphs:**

S'Wide\_Wide\_Value

S'Wide\_Wide\_Value denotes a function with the following specification:

```
function S'Wide_Wide_Value(Arg : Wide_Wide_String)
return S'Base
```

This function returns a value given an image of the value as a Wide\_Wide\_String, ignoring any leading or trailing spaces.

For the evaluation of a call on S'Wide\_Wide\_Value for an enumeration subtype S, if the sequence of characters of the parameter (ignoring leading and trailing spaces) has the syntax of an enumeration



literal and if it corresponds to a literal of the type of S (or corresponds to the result of S'Wide\_Wide\_Image for a nongraphic character of the type), the result is the corresponding enumeration value; otherwise Constraint\_Error is raised.

For the evaluation of a call on S'Wide\_Wide\_Value for an integer subtype S, if the sequence of characters of the parameter (ignoring leading and trailing spaces) has the syntax of an integer literal, with an optional leading sign character (plus or minus for a signed type; only plus for a modular type), and the corresponding numeric value belongs to the base range of the type of S, then that value is the result; otherwise Constraint\_Error is raised.

For the evaluation of a call on S'Wide\_Wide\_Value for a real subtype S, if the sequence of characters of the parameter (ignoring leading and trailing spaces) has the syntax of one of the following:

- numeric\_literal
- numeral.[exponent]
- .numeral[exponent]
- base#based\_numeral#[exponent]
- base#.based\_numeral#[exponent]

with an optional leading sign character (plus or minus), and if the corresponding numeric value belongs to the base range of the type of S, then that value is the result; otherwise Constraint\_Error is raised. The sign of a zero value is preserved (positive if none has been specified) if S'Signed\_Zeros is True.

**Replace paragraph 43: [AI95-00285-01]**

For the evaluation of a call on S'Wide\_Value for an enumeration subtype S, if the sequence of characters of the parameter (ignoring leading and trailing spaces) has the syntax of an enumeration literal and if it corresponds to a literal of the type of S (or corresponds to the result of S'Wide\_Image for a nongraphic character of the type), the result is the corresponding enumeration value; otherwise Constraint\_Error is raised.

**by:**

For the evaluation of a call on S'Wide\_Value for an enumeration subtype S, if the sequence of characters of the parameter (ignoring leading and trailing spaces) has the syntax of an enumeration literal and if it corresponds to a literal of the type of S (or corresponds to the result of S'Wide\_Image for a nongraphic character of the type), the result is the corresponding enumeration value; otherwise Constraint\_Error is raised. For a numeric subtype S, the evaluation of a call on S'Wide\_Value with *Arg* of type Wide\_String is equivalent to a call on S'Wide\_Wide\_Value for a corresponding *Arg* of type Wide\_Wide\_String.

**Delete paragraph 44: [AI95-00285-01]**

For the evaluation of a call on S'Wide\_Value (or S'Value) for an integer subtype S, if the sequence of characters of the parameter (ignoring leading and trailing spaces) has the syntax of an integer literal, with an optional leading sign character (plus or minus for a signed type; only plus for a modular type), and the corresponding numeric value belongs to the base range of the type of S, then that value is the result; otherwise Constraint\_Error is raised.

**Delete paragraph 45: [AI95-00285-01]**

For the evaluation of a call on S'Wide\_Value (or S'Value) for a real subtype S, if the sequence of characters of the parameter (ignoring leading and trailing spaces) has the syntax of one of the following:

**Delete paragraph 46: [AI95-00285-01]**

- numeric\_literal

**Delete paragraph 47: [AI95-00285-01]**

- numeral.[exponent]

**Delete paragraph 48: [AI95-00285-01]**

- .numeral[exponent]

**Delete paragraph 49: [AI95-00285-01]**

- base#based\_numeral#[exponent]

**Delete paragraph 50: [AI95-00285-01]**

- base#.based\_numeral#[exponent]

**Delete paragraph 51: [AI95-00285-01]**

with an optional leading sign character (plus or minus), and if the corresponding numeric value belongs to the base range of the type of S, then that value is the result; otherwise Constraint\_Error is raised. The sign of a zero value is preserved (positive if none has been specified) if S'Signed\_Zeros is True.

**Replace paragraph 55: [AI95-00285-01]**

For the evaluation of a call on S'Value for an enumeration subtype S, if the sequence of characters of the parameter (ignoring leading and trailing spaces) has the syntax of an enumeration literal and if it corresponds to a literal of the type of S (or corresponds to the result of S'Image for a value of the type), the result is the corresponding enumeration value; otherwise Constraint\_Error is raised. For a numeric subtype S, the evaluation of a call on S'Value with Arg of type String is equivalent to a call on S'Wide\_Value for a corresponding Arg of type Wide\_String.

**by:**

For the evaluation of a call on S'Value for an enumeration subtype S, if the sequence of characters of the parameter (ignoring leading and trailing spaces) has the syntax of an enumeration literal and if it corresponds to a literal of the type of S (or corresponds to the result of S'Image for a value of the type), the result is the corresponding enumeration value; otherwise Constraint\_Error is raised. For a numeric subtype S, the evaluation of a call on S'Value with Arg of type String is equivalent to a call on S'Wide\_Wide\_Value for a corresponding Arg of type Wide\_Wide\_String.

**Replace paragraph 56: [AI95-00285-01]**

An implementation may extend the Wide\_Value, Value, Wide\_Image, and Image attributes of a floating point type to support special values such as infinities and NaNs.

**by:**

An implementation may extend the Wide\_Wide\_Value, Wide\_Value, Value, Wide\_Wide\_Image, Wide\_Image, and Image attributes of a floating point type to support special values such as infinities and NaNs.

**Replace paragraph 59: [AI95-00285-01]**

21 For any value V (including any nongraphic character) of an enumeration subtype S, S'Value(S'Image(V)) equals V, as does S'Wide\_Value(S'Wide\_Image(V)). Neither expression ever raises Constraint\_Error.

**by:**

21 For any value V (including any nongraphic character) of an enumeration subtype S, S'Value(S'Image(V)) equals V, as do S'Wide\_Value(S'Wide\_Image(V)) and S'Wide\_Wide\_Value(S'Wide\_Wide\_Image(V)). None of these expressions ever raise Constraint\_Error.

### 3.5.2 Character Types

#### Replace paragraph 2: [AI95-00285-01]

The predefined type `Character` is a character type whose values correspond to the 256 code positions of Row 00 (also known as Latin-1) of the ISO 10646 Basic Multilingual Plane (BMP). Each of the graphic characters of Row 00 of the BMP has a corresponding `character_literal` in `Character`. Each of the nongraphic positions of Row 00 (0000-001F and 007F-009F) has a corresponding language-defined name, which is not usable as an enumeration literal, but which is usable with the attributes `(Wide_)Image` and `(Wide_)Value`; these names are given in the definition of type `Character` in A.1, "The Package Standard", but are set in *italics*.

by:

The predefined type `Character` is a character type whose values correspond to the 256 code positions of Row 00 (also known as Latin-1) of the ISO/IEC 10646:2003 Basic Multilingual Plane (BMP). Each of the graphic characters of Row 00 of the BMP has a corresponding `character_literal` in `Character`. Each of the nongraphic positions of Row 00 (0000-001F and 007F-009F) has a corresponding language-defined name, which is not usable as an enumeration literal, but which is usable with the attributes `Image`, `Wide_Image`, `Wide_Wide_Image`, `Value`, `Wide_Value`, and `Wide_Wide_Value`; these names are given in the definition of type `Character` in A.1, "The Package Standard", but are set in *italics*.

#### Replace paragraph 3: [AI95-00285-01]

The predefined type `Wide_Character` is a character type whose values correspond to the 65536 code positions of the ISO 10646 Basic Multilingual Plane (BMP). Each of the graphic characters of the BMP has a corresponding `character_literal` in `Wide_Character`. The first 256 values of `Wide_Character` have the same `character_literal` or language-defined name as defined for `Character`. The last 2 values of `Wide_Character` correspond to the nongraphic positions FFFE and FFFF of the BMP, and are assigned the language-defined names *FFFE* and *FFFF*. As with the other language-defined names for nongraphic characters, the names *FFFE* and *FFFF* are usable only with the attributes `(Wide_)Image` and `(Wide_)Value`; they are not usable as enumeration literals. All other values of `Wide_Character` are considered graphic characters, and have a corresponding `character_literal`.

by:

The predefined type `Wide_Character` is a character type whose values correspond to the 65536 code positions of the ISO/IEC 10646:2003 Basic Multilingual Plane (BMP). Each of the graphic characters of the BMP has a corresponding `character_literal` in `Wide_Character`. The first 256 values of `Wide_Character` have the same `character_literal` or language-defined name as defined for `Character`. Each of the `graphic_characters` has a corresponding `character_literal`.

The predefined type `Wide_Wide_Character` is a character type whose values correspond to the 2147483648 code positions of the ISO/IEC 10646:2003 character set. Each of the `graphic_characters` has a corresponding `character_literal` in `Wide_Wide_Character`. The first 65536 values of `Wide_Wide_Character` have the same `character_literal` or language-defined name as defined for `Wide_Character`.

In types `Wide_Character` and `Wide_Wide_Character`, the characters whose code positions are 16#FFFE# and 16#FFFF# are assigned the language-defined names *FFFE* and *FFFF*. The other characters whose code position is larger than 16#FF# and which are not `graphic_characters` have language-defined names which are formed by appending to the string "Character\_" the representation of their code position in hexadecimal as eight extended digits. As with other language-defined names, these names are usable only with the attributes `(Wide_)Wide_Image` and `(Wide_)Wide_Value`; they are not usable as enumeration literals.

#### Delete paragraph 4: [AI95-00285-01]

In a nonstandard mode, an implementation may provide other interpretations for the predefined types `Character` and `Wide_Character`, to conform to local conventions.

**Delete paragraph 5: [AI95-00285-01]**

If an implementation supports a mode with alternative interpretations for `Character` and `Wide_Character`, the set of graphic characters of `Character` should nevertheless remain a proper subset of the set of graphic characters of `Wide_Character`. Any character set "localizations" should be reflected in the results of the subprograms defined in the language-defined package `Characters.Handling` (see A.3) available in such a mode. In a mode with an alternative interpretation of `Character`, the implementation should also support a corresponding change in what is a legal `identifier_letter`.

### 3.5.4 Integer Types

**Replace paragraph 16: [AI95-00340-01]**

For every modular subtype `S`, the following attribute is defined:

**by:**

For every modular subtype `S`, the following attributes are defined:

`S'Mod`

`S'Mod` denotes a function with the following specification:

```
function S'Mod (Arg : universal_integer)
return S'Base
```

This function returns `Arg mod S'Modulus`.

### 3.5.9 Fixed Point Types

**Replace paragraph 8: [AI95-00100-01]**

The set of values of a fixed point type comprise the integral multiples of a number called the *small* of the type. For a type defined by an `ordinary_fixed_point_definition` (an *ordinary* fixed point type), the *small* may be specified by an `attribute_definition_clause` (see 13.3); if so specified, it shall be no greater than the *delta* of the type. If not specified, the *small* of an ordinary fixed point type is an implementation-defined power of two less than or equal to the *delta*.

**by:**

The set of values of a fixed point type comprise the integral multiples of a number called the *small* of the type. The *machine numbers* of a fixed point type are the values of the type that can be represented exactly in every unconstrained variable of the type. For a type defined by an `ordinary_fixed_point_definition` (an *ordinary* fixed point type), the *small* may be specified by an `attribute_definition_clause` (see 13.3); if so specified, it shall be no greater than the *delta* of the type. If not specified, the *small* of an ordinary fixed point type is an implementation-defined power of two less than or equal to the *delta*.

## 3.6 Array Types

**Replace paragraph 7: [AI95-00230-01]**

`component_definition ::= [aliased] subtype_indication`

**by:**

`component_definition ::= [aliased] subtype_indication | access_definition`

**Delete paragraph 11: [AI95-00363-01]**

Within the definition of a nonlimited composite type (or a limited composite type that later in its immediate scope becomes nonlimited -- see 7.3.1 and 7.5), if a `component_definition` contains the reserved word **aliased** and the type of the component is discriminated, then the nominal subtype of the component shall be constrained.

**Replace paragraph 22: [AI95-00230-01]**

The elaboration of a `discrete_subtype_definition` that does not contain any per-object expressions creates the discrete subtype, and consists of the elaboration of the `subtype_indication` or the evaluation of the `range`. The elaboration of a `discrete_subtype_definition` that contains one or more per-object expressions is defined in 3.8. The elaboration of a `component_definition` in an `array_type_definition` consists of the elaboration of the `subtype_indication`. The elaboration of any `discrete_subtype_definitions` and the elaboration of the `component_definition` are performed in an arbitrary order.

by:

The elaboration of a `discrete_subtype_definition` that does not contain any per-object expressions creates the discrete subtype, and consists of the elaboration of the `subtype_indication` or the evaluation of the `range`. The elaboration of a `discrete_subtype_definition` that contains one or more per-object expressions is defined in 3.8. The elaboration of a `component_definition` in an `array_type_definition` consists of the elaboration of the `subtype_indication` or `access_definition`. The elaboration of any `discrete_subtype_definitions` and the elaboration of the `component_definition` are performed in an arbitrary order.

**3.6.2 Operations of Array Types****Replace paragraph 16: [AI95-00287-01]**

48 A component of an array can be named with an `indexed_component`. A value of an array type can be specified with an `array_aggregate`, unless the array type is limited. For a one-dimensional array type, a slice of the array can be named; also, string literals are defined if the component type is a character type.

by:

48 A component of an array can be named with an `indexed_component`. A value of an array type can be specified with an `array_aggregate`. For a one-dimensional array type, a slice of the array can be named; also, string literals are defined if the component type is a character type.

**3.6.3 String Types****Replace paragraph 2: [AI95-00285-01]**

There are two predefined string types, `String` and `Wide_String`, each indexed by values of the predefined subtype `Positive`; these are declared in the visible part of package `Standard`:

by:

There are three predefined string types, `String`, `Wide_String`, and `Wide_Wide_String`, each indexed by the value of the predefined subtype `Positive`; these are declared in the visible part of package `Standard`:

**Replace paragraph 4: [AI95-00285-01]**

```
type String is array (Positive range <>) of Character;
type Wide_String is array (Positive range <>) of Wide_Character;
```

by:

```
type String is array (Positive range <>) of Character;
type Wide_String is array (Positive range <>) of Wide_Character;
type Wide_Wide_String is array (Positive range <>) of Wide_Wide_Character;
```

**3.7 Discriminants****Replace paragraph 1: [AI95-00326-01]**

A composite type (other than an array type) can have discriminants, which parameterize the type. A `known_discriminant_part` specifies the discriminants of a composite type. A discriminant of an object is a component of the object, and is either of a discrete type or an access type. An `unknown_discriminant_part`

in the declaration of a partial view of a type specifies that the discriminants of the type are unknown for the given view; all subtypes of such a partial view are indefinite subtypes.

by:

A composite type (other than an array type) can have discriminants, which parameterize the type. A `known_discriminant_part` specifies the discriminants of a composite type. A discriminant of an object is a component of the object, and is either of a discrete type or an access type. An `unknown_discriminant_part` in the declaration of a view of a type specifies that the discriminants of the type are unknown for the given view; all subtypes of such a view are indefinite subtypes.

**Replace paragraph 5: [AI95-00231-01]**

```
discriminant_specification ::=  
    defining_identifier_list : subtype_mark [:= default_expression]  
    | defining_identifier_list : access_definition [:= default_expression]
```

by:

```
discriminant_specification ::=  
    defining_identifier_list : [null_exclusion] subtype_mark [:= default_expression]  
    | defining_identifier_list : access_definition [:= default_expression]
```

**Replace paragraph 9: [AI95-00231-01; AI95-00254-01]**

The subtype of a discriminant may be defined by a `subtype_mark`, in which case the `subtype_mark` shall denote a discrete or access subtype, or it may be defined by an `access_definition` (in which case the `subtype_mark` of the `access_definition` may denote any kind of subtype). A discriminant that is defined by an `access_definition` is called an *access discriminant* and is of an anonymous general access-to-variable type whose designated subtype is denoted by the `subtype_mark` of the `access_definition`.

by:

The subtype of a discriminant may be defined by an optional `null_exclusion` and a `subtype_mark`, in which case the `subtype_mark` shall denote a discrete or access subtype, or it may be defined by an `access_definition`. A discriminant that is defined by an `access_definition` is called an *access discriminant* and is of an anonymous access type.

**Delete paragraph 10: [AI95-00230-01]**

A `discriminant_specification` for an access discriminant shall appear only in the declaration for a task or protected type, or for a type with the reserved word **limited** in its (full) definition or in that of one of its ancestors. In addition to the places where Legality Rules normally apply (see 12.3), this rule applies also in the private part of an instance of a generic unit.

**Replace paragraph 27: [AI95-00230-01]**

An `access_definition` is elaborated when the value of a corresponding access discriminant is defined, either by evaluation of its `default_expression` or by elaboration of a `discriminant_constraint`. The elaboration of an `access_definition` creates the anonymous access type. When the expression defining the access discriminant is evaluated, it is converted to this anonymous access type (see 4.6).

by:

For an access discriminant of a limited type, its `access_definition` is elaborated when the value of the access discriminant is defined, either by evaluation of its `default_expresssion` or by elaboration of a `discriminant_constraint`. For an access discriminant of a nonlimited type, its `access_definition` is elaborated when the `full_type_declaration` with the `known_discriminant_part` is elaborated. The elaboration of an `access_definition` creates the anonymous access type. When the expression defining the access discriminant is evaluated, it is converted to this anonymous access type (see 4.6).

### 3.7.1 Discriminant Constraints

#### Replace paragraph 7: [AI95-00363-01]

A `discriminant_constraint` is only allowed in a `subtype_indication` whose `subtype_mark` denotes either an unconstrained discriminated subtype, or an unconstrained access subtype whose designated subtype is an unconstrained discriminated subtype. However, in the case of a general access subtype, a `discriminant_constraint` is illegal if there is a place within the immediate scope of the designated subtype where the designated subtype's view is constrained.

by:

A `discriminant_constraint` is only allowed in a `subtype_indication` whose `subtype_mark` denotes either an unconstrained discriminated subtype, or an unconstrained access subtype whose designated subtype is an unconstrained discriminated subtype. However, in the case of an access subtype, a `discriminant_constraint` is illegal if the designated type has a partial view that is constrained or, for a general access subtype, has `default_expressions` for its discriminants. In addition to the places where Legality Rules normally apply (see 12.3), these rules apply also in the private part of an instance of a generic unit. In a generic body, this rule is checked presuming all formal access types of the generic might be general access types, and all untagged discriminated formal types of the generic might have defaults.

### 3.8 Record Types

#### Delete paragraph 8: [AI95-00287-01]

A `default_expression` is not permitted if the component is of a limited type.

#### Replace paragraph 9: [AI95-00366-01]

Each `component_declaration` declares a *component* of the record type. Besides components declared by `component_declarations`, the components of a record type include any components declared by `discriminant_specifications` of the record type declaration. The identifiers of all components of a record type shall be distinct.

by:

Each `component_declaration` declares a component of the record type. Besides components declared by `component_declarations`, the components of a record type include any components declared by `discriminant_specifications` of the record type declaration. The identifiers of all components of a record type shall be distinct.

#### Insert before paragraph 14: [AI95-00318-02]

The `component_definition` of a `component_declaration` defines the (nominal) subtype of the component. If the reserved word **aliased** appears in the `component_definition`, then the component is aliased (see 3.10).

the new paragraph:

If a `record_type_declaration` includes the reserved word **limited**, the type is called a *limited record* type.

#### Replace paragraph 18: [AI95-00230-01]

Within the definition of a composite type, if a `component_definition` or `discrete_subtype_definition` (see 9.5.2) includes a `name` that denotes a discriminant of the type, or that is an `attribute_reference` whose prefix denotes the current instance of the type, the expression containing the `name` is called a *per-object expression*, and the constraint or range being defined is called a *per-object constraint*. For the elaboration of a `component_definition` or a `component_declaration` or the `discrete_subtype_definition` of an `entry_declaration` for an entry family (see 9.5.2), if the constraint or range of the `subtype_indication` or `discrete_subtype_definition` is not a per-object constraint, then the `subtype_indication` or `discrete_subtype_definition` is elaborated. On the other hand, if the constraint or range is a per-object constraint, then the elaboration consists of the evaluation of any included expression that is not part of a per-

object expression. Each such expression is evaluated once unless it is part of a named association in a discriminant constraint, in which case it is evaluated once for each associated discriminant.

by:

Within the definition of a composite type, if a `component_definition` or `discrete_subtype_definition` (see 9.5.2) includes a `name` that denotes a discriminant of the type, or that is an `attribute_reference` whose `prefix` denotes the current instance of the type, the expression containing the `name` is called a *per-object expression*, and the `constraint` or `range` being defined is called a *per-object constraint*. For the elaboration of a `component_definition` or a `component_declaration` or the `discrete_subtype_definition` of an `entry_declaration` for an entry family (see 9.5.2), if the component subtype is defined by an `access_definition` or if the `constraint` or `range` of the `subtype_indication` or `discrete_subtype_definition` is not a per-object constraint, then the `access_definition`, `subtype_indication`, or `discrete_subtype_definition` is elaborated. On the other hand, if the `constraint` or `range` is a per-object constraint, then the elaboration consists of the evaluation of any included expression that is not part of a per-object expression. Each such expression is evaluated once unless it is part of a named association in a discriminant constraint, in which case it is evaluated once for each associated discriminant.

**Replace paragraph 25: [AI95-00287-01]**

61 A component of a record can be named with a `selected_component`. A value of a record can be specified with a `record_aggregate`, unless the record type is limited.

by:

61 A component of a record can be named with a `selected_component`. A value of a record can be specified with a `record_aggregate`.

### 3.9 Tagged Types and Type Extensions

**Replace paragraph 4: [AI95-00344-01]**

The tag of a specific tagged type identifies the `full_type_declaration` of the type. If a declaration for a tagged type occurs within a `generic_package_declaration`, then the corresponding type declarations in distinct instances of the generic package are associated with distinct tags. For a tagged type that is local to a generic package body, the language does not specify whether repeated instantiations of the generic body result in distinct tags.

by:

The tag of a specific tagged type identifies the `full_type_declaration` of the type, and for a type extension, is sufficient to uniquely identify the type among all descendants of the same ancestor. If a declaration for a tagged type occurs within a `generic_package_declaration`, then the corresponding type declarations in distinct instances of the generic package are associated with distinct tags. For a tagged type that is local to a generic package body and with all of its ancestors (if any) also local to the generic body, the language does not specify whether repeated instantiations of the generic body result in distinct tags.

**Replace paragraph 6: [AI95-00260-02; AI95-00362-01]**

```
package Ada.Tags is
  type Tag is private;
```

by:

```
package Ada.Tags is
  pragma Preelaborate(Tags);
  type Tag is private;

  No_Tag : constant Tag;
```

**Insert after paragraph 7: [AI95-00260-02; AI95-00344-01]**

```
function Expanded_Name(T : Tag) return String;
function External_Tag(T : Tag) return String;
```



```
function Internal_Tag(External : String) return Tag;
```

the new paragraphs:

```
function Descendant_Tag(External : String; Ancestor : Tag) return Tag;
function Is_Descendant_At_Same_Level(Descendant, Ancestor : Tag)
    return Boolean;

function Parent_Tag (T : Tag) return Tag;
```

Insert after paragraph 9: [AI95-00260-02]

```
private
    ... -- not specified by the language
end Ada.Tags;
```

the new paragraph:

No\_Tag is the default initial value of type Tag.

Replace paragraph 12: [AI95-00260-02; AI95-00279-01; AI95-00344-01]

The function Internal\_Tag returns the tag that corresponds to the given external tag, or raises Tag\_Error if the given string is not the external tag for any specific type of the partition.

by:

The function Internal\_Tag returns a tag that corresponds to the given external tag, or raises Tag\_Error if the given string is not the external tag for any specific type of the partition. Tag\_Error is also raised if the specific type identified is a library-level type whose tag has not yet been created (see 13.14).

The function Descendant\_Tag returns the (internal) tag for the type that corresponds to the given external tag and is both a descendant of the type identified by the Ancestor tag and has the same accessibility level as the identified ancestor. Tag\_Error is raised if External is not the external tag for such a type. Tag\_Error is also raised if the specific type identified is a library-level type whose tag has not yet been created.

The function Is\_Descendant\_At\_Same\_Level returns True if Descendant tag identifies a type that is both a descendant of the type identified by Ancestor and at the same accessibility level. If not, it returns False.

The function Parent\_Tag returns the tag of the parent type of the type whose tag is T. If the type does not have a parent type (that is, it was not declared by a derived\_type\_declaration), then No\_Tag is returned.

Insert after paragraph 18: [AI95-00260-02]

X

X

the new paragraphs:

The following language-defined generic function exists:

```
generic
    type T (<>) is abstract tagged limited private;
    type Parameters (<>) is limited private;
    with function Constructor (Params : access Parameters)
        return T is abstract;
function Ada.Tags.Generic_Dispatching_Constructor
    (The_Tag : Tag;
     Params : access Parameters) return T'Class;
pragma Preelaborate (Generic_Dispatching_Constructor);
pragma Convention (Intrinsic, Generic_Dispatching_Constructor);
```

Tags.Generic\_Dispatching\_Constructor provides a mechanism to create an object of an appropriate type from just a tag value. The function Constructor is expected to create the object given a reference to an object of type Parameters.

**Insert after paragraph 25: [AI95-00260-02; AI95-00344-01]**

The tag is preserved by type conversion and by parameter passing. The tag of a value is the tag of the associated object (see 6.2).

**the new paragraphs:**

Tag\_Error is raised by a call of Descendant\_Tag, Expanded\_Name, External\_Tag, Is\_Descendant\_At\_Same\_Level, or Parent\_Tag if any tag passed is No\_Tag.

An instance of Tags.Generic\_Dispatching\_Constructor or Tags.Generic\_Limited\_Dispatching\_Constructor raises Tag\_Error if The\_Tag does not represent a concrete descendant of T. Otherwise, it dispatches to the primitive function denoted by the formal Constructor for the type identified by the tag The\_Tag, passing Params, and returns the result. Any exception raised by the function is propagated.

*Erroneous Execution*

If the internal tag provided to an instance of Tags.Generic\_Dispatching\_Constructor or Tags.Generic\_Limited\_Dispatching\_Constructor identifies a specific type whose tag has not been elaborated, or does not exist in the partition at the time of the call, execution is erroneous.

**Replace paragraph 26: [AI95-00279-01]**

The implementation of the functions in Ada.Tags may raise Tag\_Error if no specific type corresponding to the tag passed as a parameter exists in the partition at the time the function is called.

**by:**

The implementation of the functions in Ada.Tags may raise Tag\_Error if no specific type corresponding to the tag or external tag passed as a parameter exists in the partition at the time the function is called.

**Insert after paragraph 30: [AI95-00260-02]**

65 If S denotes an untagged private type whose full type is tagged, then S'Class is also allowed before the full type definition, but only in the private part of the package in which the type is declared (see 7.3.1). Similarly, the Class attribute is defined for incomplete types whose full type is tagged, but only within the library unit in which the incomplete type is declared (see 3.10.1).

**the new paragraph:**

66 The capability provided by Tags.Generic\_Dispatching\_Constructor is sometimes known as a *factory*.

**Delete paragraph 30: [AI95-00326-01]**

65 If S denotes an untagged private type whose full type is tagged, then S'Class is also allowed before the full type definition, but only in the private part of the package in which the type is declared (see 7.3.1). Similarly, the Class attribute is defined for incomplete types whose full type is tagged, but only within the library unit in which the incomplete type is declared (see 3.10.1).

### 3.9.1 Type Extensions

**Replace paragraph 3: [AI95-00344-01; AI95-00345-01]**

The parent type of a record extension shall not be a class-wide type. If the parent type is nonlimited, then each of the components of the record\_extension\_part shall be nonlimited. The accessibility level (see 3.10.2) of a record extension shall not be statically deeper than that of its parent type. In addition to the places where Legality Rules normally apply (see 12.3), these rules apply also in the private part of an instance of a generic unit.

**by:**

The parent type of a record extension shall not be a class-wide type nor shall it be a synchronized tagged type (see 3.9.4). If the parent type is nonlimited, then each of the components of the record\_extension\_part shall be nonlimited.

**Replace paragraph 4: [AI95-00344-01; AI95-00391-01]**

A type extension shall not be declared in a generic body if the parent type is declared outside that body.

**by:**

Within the body of a generic unit, or the body of any of its descendant library units, a tagged type shall not be declared as a descendant of a formal type declared within the formal part of the generic unit.

*Static Semantics*

A record extension is a *null extension* if its declaration has no `known_discriminant_part` and its `record_extension_part` includes no `component_declarations`.

**Replace paragraph 7: [AI95-00344-01]**

The accessibility rules imply that a tagged type declared in a `library package_specification` can be extended only at library level or as a generic formal. When the extension is declared immediately within a `package_body`, primitive subprograms are inherited and are overridable, but new primitive subprograms cannot be added.

**by:**

When an extension is declared immediately within a body, primitive subprograms are inherited and are overridable, but new primitive subprograms cannot be added.

### 3.9.2 Dispatching Operations of Tagged Types

**Replace paragraph 1: [AI95-00260-02]**

The primitive subprograms of a tagged type are called *dispatching operations*. A dispatching operation can be called using a statically determined *controlling* tag, in which case the body to be executed is determined at compile time. Alternatively, the controlling tag can be dynamically determined, in which case the call *dispatches* to a body that is determined at run time; such a call is termed a *dispatching call*. As explained below, the properties of the operands and the context of a particular call on a dispatching operation determine how the controlling tag is determined, and hence whether or not the call is a dispatching call. Run-time polymorphism is achieved when a dispatching operation is called by a dispatching call.

**by:**

The primitive subprograms of a tagged type, and the subprograms declared by a `formal_abstract_subprogram_declaration`, are called *dispatching operations*. A dispatching operation can be called using a statically determined *controlling* tag, in which case the body to be executed is determined at compile time. Alternatively, the controlling tag can be dynamically determined, in which case the call *dispatches* to a body that is determined at run time; such a call is termed a *dispatching call*. As explained below, the properties of the operands and the context of a particular call on a dispatching operation determine how the controlling tag is determined, and hence whether or not the call is a dispatching call. Run-time polymorphism is achieved when a dispatching operation is called by a dispatching call.

**Replace paragraph 2: [AI95-00260-02]**

73 This subclause covers calls on primitive subprograms of a tagged type. Rules for tagged type membership tests are described in 4.5.2. Controlling tag determination for an `assignment_statement` is described in 5.2).

**by:**

73 This subclause covers calls on dispatching subprograms of a tagged type. Rules for tagged type membership tests are described in 4.5.2. Controlling tag determination for an `assignment_statement` is described in 5.2).

**Replace paragraph 2: [AI95-00260-02]**

A *call on a dispatching operation* is a call whose `name` or `prefix` denotes the declaration of a primitive subprogram of a tagged type, that is, a dispatching operation. A *controlling operand* in a call on a dispatching operation of a tagged type T is one whose corresponding formal parameter is of type T or is of an

anonymous access type with designated type *T*; the corresponding formal parameter is called a *controlling formal parameter*. If the controlling formal parameter is an access parameter, the controlling operand is the object designated by the actual parameter, rather than the actual parameter itself. If the call is to a (primitive) function with result type *T*, then the call has a *controlling result* -- the context of the call can control the dispatching.

by:

A call on a dispatching operation is a call whose name or prefix denotes the declaration of a dispatching operation. A *controlling operand* in a call on a dispatching operation of a tagged type *T* is one whose corresponding formal parameter is of type *T* or is of an anonymous access type with designated type *T*; the corresponding formal parameter is called a *controlling formal parameter*. If the controlling formal parameter is an access parameter, the controlling operand is the object designated by the actual parameter, rather than the actual parameter itself. If the call is to a (primitive) function with result type *T*, then the call has a *controlling result* -- the context of the call can control the dispatching.

**Replace paragraph 17: [AI95-00196-01]**

If all of the controlling operands are tag-indeterminate, then:

by:

If all of the controlling operands (if any) are tag-indeterminate, then:

**Replace paragraph 18: [AI95-00196-01; AI95-00239-01]**

- If the call has a controlling result and is itself a (possibly parenthesized or qualified) controlling operand of an enclosing call on a dispatching operation of type *T*, then its controlling tag value is determined by the controlling tag value of this enclosing call;

by:

- If the call has a controlling result and is itself a (possibly parenthesized or qualified) controlling operand of an enclosing call on a dispatching operation of a descendant of type *T*, then its controlling tag value is determined by the controlling tag value of this enclosing call;
- If the call has a controlling result and is the (possibly parenthesized or qualified) expression of an `assignment_statement` whose target is of a class-wide type, then its controlling tag value is determined by the target;

### 3.9.3 Abstract Types and Subprograms

**Replace paragraph 1: [AI95-00345-01]**

An *abstract type* is a tagged type intended for use as a parent type for type extensions, but which is not allowed to have objects of its own. An *abstract subprogram* is a subprogram that has no body, but is intended to be overridden at some point when inherited. Because objects of an abstract type cannot be created, a dispatching call to an abstract subprogram always dispatches to some overriding body.

by:

An *abstract type* is a tagged type intended for use as an ancestor of other types, but which is not allowed to have objects of its own. An *abstract subprogram* is a subprogram that has no body, but is intended to be overridden at some point when inherited. Because objects of an abstract type cannot be created, a dispatching call to an abstract subprogram always dispatches to some overriding body.

*Static Semantics*

Interface types (see 3.9.4) are abstract types. In addition, a tagged type that has the reserved word **abstract** in its declaration is an abstract type. The class-wide type (see 3.4.1) rooted at an abstract type is not itself an abstract type.

**Replace paragraph 2: [AI95-00345-01]**

An abstract type is a specific type that has the reserved word **abstract** in its declaration. Only a tagged type is allowed to be declared **abstract**.

**by:**

Only a tagged type shall have the reserved word **abstract** in its declaration.

**Replace paragraph 3: [AI95-00260-02]**

A subprogram declared by an `abstract_subprogram_declaration` (see 6.1) is an *abstract subprogram*. If it is a primitive subprogram of a tagged type, then the tagged type shall be **abstract**.

**by:**

A subprogram declared by an `abstract_subprogram_declaration` (see 6.1) or declared declared by a `formal_abstract_subprogram_declaration` (see 12.6) is an *abstract subprogram*. If it is a primitive subprogram of a tagged type, then the tagged type shall be **abstract**.

**Replace paragraph 4: [AI95-00251-01; AI95-00334-01]**

For a derived type, if the parent or ancestor type has an abstract primitive subprogram, or a primitive function with a controlling result, then:

**by:**

If a type has an implicitly declared primitive subprogram that is inherited or is the predefined equality operator, and the corresponding primitive subprogram of the parent or ancestor type is **abstract** or is a function with a controlling access result, or if a type other than a null extension inherits a function with a controlling result, then:

**Replace paragraph 5: [AI95-00251-01; AI95-00334-01]**

- If the derived type is **abstract** or **untagged**, the inherited subprogram is *abstract*.

**by:**

- If the type is **abstract** or **untagged**, the implicitly declared subprogram is *abstract*.

**Replace paragraph 6: [AI95-00391-01]**

Otherwise, the subprogram shall be overridden with a nonabstract subprogram; for a type declared in the visible part of a package, the overriding may be either in the visible or the private part. However, if the type is a generic formal type, the subprogram need not be overridden for the formal type itself; a nonabstract version will necessarily be provided by the actual type.

**by:**

Otherwise, the subprogram shall be overridden with a nonabstract subprogram or, in the case of a private extension inheriting a function with a controlling result, have a full type that is a null extension; for a type declared in the visible part of a package, the overriding may be either in the visible or the private part. However, if the type is a generic formal type, the subprogram need not be overridden for the formal type itself; a nonabstract version will necessarily be provided by the actual type.

**Replace paragraph 11: [AI95-00260-02]**

A generic actual subprogram shall not be an abstract subprogram. The prefix of an `attribute_reference` for the `Access`, `Unchecked_Access`, or `Address` attributes shall not denote an abstract subprogram.

**by:**

A generic actual subprogram shall not be an abstract subprogram unless the generic formal subprogram is declared by a `formal_abstract_subprogram_declaration`. The prefix of an `attribute_reference` for the `Access`, `Unchecked_Access`, or `Address` attributes shall not denote an abstract subprogram.

### 3.9.4 Interface Types

**Insert new clause: [AI95-00251-01; AI95-00345-01]**

An interface type is an abstract tagged type that provides a restricted form of multiple inheritance. A tagged, task, or protected type have one or more interface types as ancestors.

*Syntax*

```
interface_type_definition ::=
  [limited | task | protected | synchronized] interface [and interface_list]
```

*Static Semantics*

An interface type (also called an "interface") is a specific abstract tagged type that is defined by an `interface_type_definition`.

An interface with the reserved word **limited**, **task**, **protected**, or **synchronized** in its definition is termed, respectively, a *limited interface*, a *task interface*, a *protected interface*, or a *synchronized interface*. In addition, all task and protected interfaces are synchronized interfaces, and all synchronized interfaces are limited interfaces. A view of an object that is of a task interface type (or of a corresponding class-wide type) is a task object. Similarly, a view of an object that is of a protected interface type (or of a corresponding class-wide type) is a protected object.

A task or protected type derived from an interface is a tagged type. Such a tagged type is called a *synchronized* tagged type, as are synchronized interfaces and private extensions derived from synchronized interfaces.

An interface type has no components.

*Legality Rules*

All user-defined primitive subprograms of an interface type shall be abstract subprograms or null procedures.

The type of a subtype named in an `interface_list` shall be an interface type.

Within the body of a generic unit, or the body of any of its descendant library units, a tagged type shall not be declared as a descendant of a formal type declared within the formal part of the generic unit.

A descendant of a nonlimited interface shall be nonlimited. A descendant of a task interface shall be a task type or a task interface. A descendant of a protected interface shall be a protected type or a protected interface. A descendant of a synchronized interface shall be a task type, a protected type, or a synchronized interface.

A full view shall be a descendant of an interface type if and only if the corresponding partial view (if any) is also a descendant of the interface type.

For an interface type declared in a visible part, a primitive subprogram shall not be declared in the private part.

In addition to the places where Legality Rules normally apply (see 12.3), these rules apply also in the private part of an instance of a generic unit.

*Dynamic Semantics*

The elaboration of an `interface_type_definition` has no effect.

### 3.10 Access Types

**Replace paragraph 2: [AI95-00231-01]**

```
access_type_definition ::=
  access_to_object_definition
  | access_to_subprogram_definition
```

by:

```
access_type_definition ::=
    [null_exclusion] access_to_object_definition
  | [null_exclusion] access_to_subprogram_definition
```

**Replace paragraph 6: [AI95-00231-01; AI95-00254-01]**

```
access_definition ::= access subtype_mark
```

by:

```
null_exclusion ::= not null
access_definition ::=
    [null_exclusion] access [general_access_modifier] subtype_mark
  | [null_exclusion] access [protected] procedure parameter_profile
  | [null_exclusion] access [protected] function parameter_and_result_profile
```

**Replace paragraph 9: [AI95-00225-01; AI95-00363-01]**

A view of an object is defined to be *aliased* if it is defined by an `object_declaration` or `component_definition` with the reserved word **aliased**, or by a renaming of an aliased view. In addition, the dereference of an access-to-object value denotes an aliased view, as does a view conversion (see 4.6) of an aliased view. Finally, the current instance of a limited type, and a formal parameter or generic formal object of a tagged type are defined to be aliased. Aliased views are the ones that can be designated by an access value. If the view defined by an `object_declaration` is aliased, and the type of the object has discriminants, then the object is constrained; if its nominal subtype is unconstrained, then the object is constrained by its initial value. Similarly, if the object created by an `allocator` has discriminants, the object is constrained, either by the designated subtype, or by its initial value.

by:

A view of an object is defined to be *aliased* if it is defined by an `object_declaration` or `component_definition` with the reserved word **aliased**, or by a renaming of an aliased view. In addition, the dereference of an access-to-object value denotes an aliased view, as does a view conversion (see 4.6) of an aliased view. A current instance of a limited tagged type, a protected type, a task type, or a type that has the reserved word **limited** in its full definition is also defined to be aliased. Finally, a formal parameter or generic formal object of a tagged type is defined to be aliased. Aliased views are the ones that can be designated by an access value.

**Replace paragraph 12: [AI95-00230-01; AI95-00231-01; AI95-00254-01]**

An `access_definition` defines an anonymous general access-to-variable type; the `subtype_mark` denotes its *designated subtype*. An `access_definition` is used in the specification of an access discriminant (see 3.7) or an access parameter (see 6.1).

by:

An `access_definition` defines an anonymous general access type or an anonymous access-to-subprogram type. For a general access type, the `subtype_mark` denotes its *designated subtype*; if the `general_access_modifier` **constant** appears, the type is an access-to-constant type; otherwise it is an access-to-variable type. For an access-to-subprogram type, the `parameter_profile` or `parameter_and_result_profile` denotes its *designated profile*. If a `null_exclusion` is present, or the `access_definition` is for a controlling access parameter (see 3.9.2), the `access_definition` defines an access subtype which excludes the null value; otherwise the subtype includes a null value.

**Replace paragraph 13: [AI95-00230-01; AI95-00231-01]**

For each (named) access type, there is a literal **null** which has a null access value designating no entity at all. The null value of a named access type is the default initial value of the type. Other values of an access type are obtained by evaluating an `attribute_reference` for the `Access` or `Unchecked_Access` attribute of an aliased view of an object or non-intrinsic subprogram, or, in the case of a named access-to-object type, an `allocator`, which returns an access value designating a newly created object (see 3.10.2).

by:

For each access type, there is a null access value designating no entity at all, which can be obtained by converting the literal **null** to the access type. The null value of an access type is the default initial value of the type. Other values of an access-to-object type are obtained by evaluating an **allocator**, which returns an access value designating a newly created object (see 3.10.2), or in the case of a general access-to-object type, evaluating an **attribute\_reference** for the **Access** or **Unchecked\_Access** attribute of an aliased view of an object. Other values of an access-to-subprogram type are obtained by evaluating an **attribute\_reference** for the **Access** attribute of a non-intrinsic subprogram.

**Replace paragraph 14: [AI95-00231-01]**

All subtypes of an access-to-subprogram type are constrained. The first subtype of a type defined by an **access\_definition** or an **access\_to\_object\_definition** is unconstrained if the designated subtype is an unconstrained array or discriminated subtype; otherwise it is constrained.

by:

All subtypes of an access-to-subprogram type are constrained. The first subtype of a type defined by an **access\_definition** or an **access\_to\_object\_definition** is unconstrained if the designated subtype is an unconstrained array or discriminated subtype; otherwise it is constrained. The first subtype of a type defined by an **access\_type\_definition** excludes the null value if a **null\_exclusion** is present; otherwise, the first subtype includes the null value.

*Legality Rules*

A **null\_exclusion** is only allowed in a **subtype\_indication** whose **subtype\_mark** denotes an access subtype that includes a null value.

**Replace paragraph 15: [AI95-00231-01]**

A **composite\_constraint** is *compatible* with an unconstrained access subtype if it is compatible with the designated subtype. An access value *satisfies* a **composite\_constraint** of an access subtype if it equals the null value of its type or if it designates an object whose value satisfies the constraint.

by:

A **composite\_constraint** is *compatible* with an unconstrained access subtype if it is compatible with the designated subtype. A **null\_exclusion** is compatible with any access subtype that includes a null value. An access value *satisfies* a **composite\_constraint** of an access subtype if it equals the null value of its type or if it designates an object whose value satisfies the constraint. An access value satisfies a **null\_exclusion** imposed on an access subtype if it does not equal the null value of its type.

**Replace paragraph 17: [AI95-00230-01; AI95-00254-01]**

The elaboration of an **access\_definition** creates an anonymous general access-to-variable type [(this happens as part of the initialization of an access parameter or access discriminant)].

by:

The elaboration of an **access\_definition** creates an anonymous access type.

### 3.10.1 Incomplete Type Declarations

**Replace paragraph 2: [AI95-00326-01]**

**incomplete\_type\_declaration** ::= **type** defining\_identifier [discriminant\_part];

by:

**incomplete\_type\_declaration** ::= **type** defining\_identifier [discriminant\_part] [**is tagged**];

*Static Semantics*



An `incomplete_type_declaration` declares an *incomplete view* of a type, and its first subtype; the first subtype is unconstrained if a `discriminant_part` appears. If the `incomplete_type_declaration` includes the reserved word **tagged**, it declares a *tagged incomplete view*. An incomplete view of a type is a limited view of the type (see 7.5).

Given an access type *A* whose designated type *T* is an incomplete view, a dereference of a value of type *A* also has this incomplete view except when:

- it occurs within the immediate scope of the completion of *T*, or
- it occurs within the scope of a `nonlimited_with_clause` that mentions a library package in whose visible part the completion of *T* is declared.

In these cases, the dereference has the full view of *T*.

**Replace paragraph 4: [AI95-00326-01]**

If an `incomplete_type_declaration` has a `known_discriminant_part`, then a `full_type_declaration` that completes it shall have a fully conforming (explicit) `known_discriminant_part` (see 6.3.1). If an `incomplete_type_declaration` has no `discriminant_part` (or an `unknown_discriminant_part`), then a corresponding `full_type_declaration` is nevertheless allowed to have discriminants, either explicitly, or inherited via derivation.

by:

If an `incomplete_type_declaration` includes the reserved word **tagged**, then a `full_type_declaration` that completes it shall declare a tagged type. If an `incomplete_type_declaration` has a `known_discriminant_part`, then a `full_type_declaration` that completes it shall have a fully conforming (explicit) `known_discriminant_part` (see 6.3.1). If an `incomplete_type_declaration` has no `discriminant_part` (or an `unknown_discriminant_part`), then a corresponding `full_type_declaration` is nevertheless allowed to have discriminants, either explicitly, or inherited via derivation.

**Replace paragraph 5: [AI95-00326-01]**

The only allowed uses of a name that denotes an `incomplete_type_declaration` are as follows:

by:

A name that denotes an incomplete view of a type may be used as follows:

**Delete paragraph 7: [AI95-00326-01]**

- as the `subtype_mark` defining the subtype of a parameter or result of an `access_to_subprogram_definition`;

**Replace paragraph 8: [AI95-00326-01]**

- as the `subtype_mark` in an `access_definition`;

by:

- as the `subtype_mark` in an `access_definition`.

If such a name denotes a tagged incomplete view, it may also be used:

- as the `subtype_mark` defining the subtype of a parameter in a `formal_part`;

**Replace paragraph 9: [AI95-00326-01]**

- as the prefix of an `attribute_reference` whose `attribute_designator` is `Class`; such an `attribute_reference` is similarly restricted to the uses allowed here; when used in this way, the corresponding `full_type_declaration` shall declare a tagged type, and the `attribute_reference` shall occur in the same library unit as the `incomplete_type_declaration`.

by:

- as the prefix of an `attribute_reference` whose `attribute_designator` is `Class`; such an `attribute_reference` is restricted to the uses allowed here; it denotes a tagged incomplete view.

If such a `name` occurs within the list of `declarative_items` containing the completion of the incomplete view, it may also be used:

- as the `subtype_mark` defining the subtype of a parameter or result of an `access_to_subprogram_definition`.

If any of the above uses occurs as part of the declaration of a primitive subprogram of the incomplete view, and the declaration occurs immediately within the private part of a package, then the completion of the incomplete view shall also occur immediately within the private part; it may not be deferred to the package body.

No other uses of a `name` that denotes an incomplete view of a type are allowed.

**Replace paragraph 10: [AI95-00217-06; AI95-00326-01]**

A dereference (whether implicit or explicit -- see 4.1) shall not be of an incomplete type.

by:

A prefix shall not be of an incomplete view.

**Delete paragraph 11: [AI95-00326-01]**

An `incomplete_type_declaration` declares an incomplete type and its first subtype; the first subtype is unconstrained if a `known_discriminant_part` appears.

### 3.10.2 Operations of Access Types

**Replace paragraph 2: [AI95-00235-01]**

For an `attribute_reference` with `attribute_designator` `Access` (or `Unchecked_Access` -- see 13.10), the expected type shall be a single access type; the prefix of such an `attribute_reference` is never interpreted as an `implicit_dereference`. If the expected type is an access-to-subprogram type, then the expected profile of the prefix is the designated profile of the access type.

by:

For an `attribute_reference` with `attribute_designator` `Access` (or `Unchecked_Access` -- see 13.10), the expected type shall be a single access type *A* such that:

- *A* is an access-to-object type with designated type *D* and the type of the prefix is *D*'`Class` or is covered by *D*, or
- *A* is an access-to-subprogram type whose designated profile is type conformant with that of the prefix.

The prefix of such an `attribute_reference` is never interpreted as an `implicit_dereference` or a parameterless `function_call` (see 4.1.4). The designated type or profile of the expected type of the `attribute_reference` is the expected type or profile for the prefix.

**Replace paragraph 3: [AI95-00162-01]**

The accessibility rules, which prevent dangling references, are written in terms of *accessibility levels*, which reflect the run-time nesting of masters. As explained in 7.6.1, a master is the execution of a `task_body`, a `block_statement`, a `subprogram_body`, an `entry_body`, or an `accept_statement`. An accessibility level is *deeper than* another if it is more deeply nested at run time. For example, an object declared local to a called subprogram has a deeper accessibility level than an object declared local to the calling subprogram. The accessibility rules for access types require that the accessibility level of an object designated by an access value be no deeper than that of the access type. This ensures that the object will live at least as long as the

access type, which in turn ensures that the access value cannot later designate an object that no longer exists. The `Unchecked_Access` attribute may be used to circumvent the accessibility rules.

**by:**

The accessibility rules, which prevent dangling references, are written in terms of *accessibility levels*, which reflect the run-time nesting of masters (see 7.6.1). An accessibility level is *deeper than* another if it is more deeply nested at run time. For example, an object declared local to a called subprogram has a deeper accessibility level than an object declared local to the calling subprogram. The accessibility rules for access types require that the accessibility level of an object designated by an access value be no deeper than that of the access type. This ensures that the object will live at least as long as the access type, which in turn ensures that the access value cannot later designate an object that no longer exists. The `Unchecked_Access` attribute may be used to circumvent the accessibility rules.

**Replace paragraph 7: [AI95-00162-01]**

- An entity or view created by a declaration has the same accessibility level as the innermost enclosing master, except in the cases of renaming and derived access types described below. A parameter of a master has the same accessibility level as the master.

**by:**

- An entity or view created by a declaration has the same accessibility level as the innermost enclosing master other than the declaration itself, except in the cases of renaming and derived access types described below. A parameter of a master has the same accessibility level as the master.

**Replace paragraph 10: [AI95-00318-02]**

For a function whose result type is a return-by-reference type, the accessibility level of the result object is the same as that of the master that elaborated the function body. For any other function, the accessibility level of the result object is that of the execution of the called function.

**by:**

For any function, the accessibility level of the result object is that of the execution of the called function.

**Insert after paragraph 11: [AI95-00385-01]**

- The accessibility level of a derived access type is that of its ultimate ancestor.

**the new paragraphs:**

- The accessibility level of the anonymous access type defined by an `access_definition` of an `object_declaration` is the same as that of the declared object.

**Replace paragraph 12: [AI95-00230-01]**

- The accessibility level of the anonymous access type of an access discriminant is the same as that of the containing object or associated constrained subtype.

**by:**

- The accessibility level of the anonymous access type defined by an `access_definition` of an `object_renaming_declaration` is the same as that of the renamed view.
- The accessibility level of the anonymous access type of a component is that of the master that elaborated its `access_definition`. This is the same as the level of the type whose definition encloses the `access_definition` except in the case of an access discriminant specified for a limited type, in which case it is the same as that of the containing object or associated constrained subtype.

**Replace paragraph 13: [AI95-00162-01; AI95-00254-01; AI95-00318-02]**

- The accessibility level of the anonymous access type of an access parameter is the same as that of the view designated by the actual. If the actual is an `allocator`, this is the accessibility level of the execution of the called subprogram.

by:

- The accessibility level of the anonymous access type of an access parameter specifying an access-to-object type is the same as that of the view designated by the actual.
- The accessibility level of the anonymous access type of an access parameter specifying an access-to-subprogram type is infinite.
- The accessibility level of the anonymous access type of an access result type (see 6.5) is the same as that of the associated function or access-to-subprogram type.

**Replace paragraph 19: [AI95-00254-01]**

The statically deeper relationship does not apply to the accessibility level of the anonymous type of an access parameter; that is, such an accessibility level is not considered to be statically deeper, nor statically shallower, than any other.

by:

The statically deeper relationship does not apply to the accessibility level of the anonymous type of an access parameter specifying an access-to-object type; that is, such an accessibility level is not considered to be statically deeper, nor statically shallower, than any other.

**Replace paragraph 26: [AI95-00363-01]**

- The view shall not be a subcomponent that depends on discriminants of a variable whose nominal subtype is unconstrained, unless this subtype is indefinite, or the variable is aliased.

by:

- The view shall not be a subcomponent that depends on discriminants of a variable whose nominal subtype is unconstrained, unless this subtype is indefinite, or the variable is constrained by its initial value.

**Replace paragraph 27: [AI95-00363-01]**

- If *A* is a named access type and *D* is a tagged type, then the type of the view shall be covered by *D*; if *A* is anonymous and *D* is tagged, then the type of the view shall be either *D*'Class or a type covered by *D*; if *D* is untagged, then the type of the view shall be *D*, and *A*'s designated subtype shall either statically match the nominal subtype of the view or be discriminated and unconstrained;

by:

- If *A* is a named access type and *D* is a tagged type, then the type of the view shall be covered by *D*; if *A* is anonymous and *D* is tagged, then the type of the view shall be either *D*'Class or a type covered by *D*; if *D* is untagged, then the type of the view shall be *D*, and either:
  - the designated subtype of *A* shall statically match the nominal subtype of the view; or
  - *D* shall be discriminated in its full view and unconstrained in any partial view, and the designated subtype of *A* shall be unconstrained.

**Replace paragraph 32: [AI95-00229-01; AI95-00254-01]**

P'Access yields an access value that designates the subprogram denoted by P. The type of P'Access is an access-to-subprogram type (*S*), as determined by the expected type. The accessibility level of P shall not be statically deeper than that of *S*. In addition to the places where Legality Rules normally apply (see 12.3), this rule applies also in the private part of an instance of a generic unit. The profile of P shall be subtype-conformant with the designated profile of *S*, and shall not be Intrinsic. If the subprogram denoted by P is declared within a generic body, *S* shall be declared within the generic body.

by:

P'Access yields an access value that designates the subprogram denoted by P. The type of P'Access is an access-to-subprogram type (*S*), as determined by the expected type. The accessibility level of P shall not be statically deeper than that of *S*. In addition to the places where Legality Rules normally apply (see 12.3), this rule applies also in the private part of an instance of a generic unit. The profile of P shall be subtype-conformant with the designated profile of *S*, and shall not be Intrinsic. If the subprogram denoted by P is declared within a generic unit, and the expression P'Access occurs within the body of that generic unit or within the body of a generic unit declared within the declarative region of the generic, then the ultimate ancestor of *S* shall be either a non-formal type declared within the generic unit or an anonymous access type of an access parameter.

**Replace paragraph 34: [AI95-00230-01]**

82 The predefined operations of an access type also include the assignment operation, qualification, and membership tests. Explicit conversion is allowed between general access types with matching designated subtypes; explicit conversion is allowed between access-to-subprogram types with subtype conformant profiles (see 4.6). Named access types have predefined equality operators; anonymous access types do not (see 4.5.2).

by:

82 The predefined operations of an access type also include the assignment operation, qualification, and membership tests. Explicit conversion is allowed between general access types with matching designated subtypes; explicit conversion is allowed between access-to-subprogram types with subtype conformant profiles (see 4.6). Named access types have predefined equality operators; anonymous access types do not, but they can use the predefined equality operators for *universal\_access* (see 4.5.2).

**Replace paragraph 37: [AI95-00254-01]**

The accessibility rules imply that it is not possible to use the Access attribute to implement "downward closures" -- that is, to pass a more-nested subprogram as a parameter to a less-nested subprogram, as might be desired for example for an iterator abstraction. Instead, downward closures can be implemented using generic formal subprograms (see 12.6). Note that *Unchecked\_Access* is not allowed for subprograms.

by:

The Access attribute for subprograms and parameters of an anonymous access-to-subprogram type may together be used to implement "downward closures" -- that is, to pass a more-nested subprogram as a parameter to a less-nested subprogram, as might be appropriate for an iterator abstraction or numerical integration. Downward closures can also be implemented using generic formal subprograms (see 12.6). Note that *Unchecked\_Access* is not allowed for subprograms.

## Section 4: Names and Expressions

### 4.1.3 Selected Components

Insert after paragraph 9: [AI95-00252-01]

- The **prefix** shall resolve to denote an object or value of some task or protected type (after any implicit dereference). The **selector\_name** shall resolve to denote an **entry\_declaration** or **subprogram\_declaration** occurring (implicitly or explicitly) within the visible part of that type. The **selected\_component** denotes the corresponding entry, entry family, or protected subprogram.

the new paragraph:

- A view of a subprogram whose first formal parameter is of a tagged type or is an access parameter whose designated type is tagged: The **prefix** (after any implicit dereference) shall resolve to denote an object or value of a specific tagged type *T* or class-wide type *T*Class. The **selector\_name** shall resolve to denote a view of a subprogram declared immediately within the declarative region in which an ancestor of the type *T* is declared. The first formal parameter of the subprogram shall be of type *T*, or a class-wide type that covers *T*, or an access parameter designating one of these types. The designator of the subprogram shall not be the same as that of a component of the tagged type visible at the point of the **selected\_component**. The **selected\_component** denotes a view of this subprogram that omits the first formal parameter.

Insert after paragraph 13: [AI95-00252-01]

If the **prefix** does not denote a package, then it shall be a **direct\_name** or an expanded name, and it shall resolve to denote a program unit (other than a package), the current instance of a type, a **block\_statement**, a **loop\_statement**, or an **accept\_statement** (in the case of an **accept\_statement** or **entry\_body**, no family index is allowed); the expanded name shall occur within the declarative region of this construct. Further, if this construct is a callable construct and the **prefix** denotes more than one such enclosing callable construct, then the expanded name is ambiguous, independently of the **selector\_name**.

the new paragraph:

*Legality Rules*

If a **selected\_component** other than an expanded name resolves to denote a view of a subprogram whose first parameter is an access parameter, the **prefix** shall denote an aliased view of an object.

Insert after paragraph 15: [AI95-00252-01]

For a **selected\_component** that denotes a component of a **variant**, a check is made that the values of the discriminants are such that the value or object denoted by the **prefix** has this component. The exception **Constraint\_Error** is raised if this check fails.

the new paragraph:

For a **selected\_component** with a tagged **prefix** and a **selector\_name** that denotes a view of a subprogram, a call on the view denoted by the **selected\_component** is equivalent to a call on the subprogram with the first actual parameter being provided by the object or value denoted by the **prefix** (or the **Access** attribute of this object or value if the first formal parameter is an access parameter), and the remaining actual parameters given by the **actual\_parameter\_part**, if any.

In paragraph 17 replace: [AI95-00252-01]

`Control.Seize`      -- an entry of a protected object (see 9.4)

by:

`X.Activate`      -- a procedure call assuming *X* has (see 6.4)  
                     -- a tagged type  
`Control.Seize`      -- an entry of a protected object (see 9.4)

#### 4.1.4 Attributes

##### Replace paragraph 14: [AI95-00235-01]

5 In general, the name in a prefix of an `attribute_reference` (or a `range_attribute_reference`) has to be resolved without using any context. However, in the case of the Access attribute, the expected type for the prefix has to be a single access type, and if it is an access-to-subprogram type (see 3.10.2) then the resolution of the name can use the fact that the profile of the callable entity denoted by the prefix has to be type conformant with the designated profile of the access type.

by:

5 In general, the name in a prefix of an `attribute_reference` (or a `range_attribute_reference`) has to be resolved without using any context. However, in the case of the Access attribute, the expected type for the `attribute_reference` has to be a single access type, and the resolution of the name can use the fact that the type of the object or profile of the callable entity denoted by the prefix has to be match the designated type or be type conformant with the designated profile of the access type.

#### 4.2 Literals

##### Delete paragraph 2: [AI95-00230-01]

The expected type for a literal `null` shall be a single access type.

##### Delete paragraph 7: [AI95-00230-01; AI95-00231-01]

A literal `null` shall not be of an anonymous access type, since such types do not have a null value (see 3.10).

##### Replace paragraph 8: [AI95-00230-01]

An integer literal is of type *universal\_integer*. A real literal is of type *universal\_real*.

by:

An integer literal is of type *universal\_integer*. A real literal is of type *universal\_real*. The literal `null` is of type *universal\_access*.

#### 4.3 Aggregates

##### Replace paragraph 3: [AI95-00287-01; AI95-00389-01]

The expected type for an aggregate shall be a single nonlimited array type, record type, or record extension.

by:

The expected type for an aggregate shall be a single composite type.

##### 4.3.1 Record Aggregates

##### Replace paragraph 4: [AI95-00287-01]

```
record_component_association ::=
  [ component_choice_list => ] expression
```

by:

```
record_component_association ::=
  [ component_choice_list => ] expression
| component_choice_list => <>
```

##### Replace paragraph 8: [AI95-00287-01; AI95-00389-01]

The expected type for a `record_aggregate` shall be a single nonlimited record type or record extension.

by:

The expected type for a `record_aggregate` shall be a single non-array composite type.

**Replace paragraph 16: [AI95-00287-01; AI95-00389-01]**

Each `record_component_association` shall have at least one associated component, and each needed component shall be associated with exactly one `record_component_association`. If a `record_component_association` has two or more associated components, all of them shall be of the same type.

by:

Each `record_component_association` other than an **others** choice with a `<>` shall have at least one associated component, and each needed component shall be associated with exactly one `record_component_association`. If a `record_component_association` with an expression has two or more associated components, all of them shall be of the same type.

**Insert after paragraph 17: [AI95-00287-01; AI95-00389-01]**

If the components of a `variant_part` are needed, then the value of a discriminant that governs the `variant_part` shall be given by a static expression.

**the new paragraphs:**

A `record_component_association` for a discriminant without a `default_expression` shall have an expression rather than `<>`.

If the type of the `record_aggregate` is a partial view of a type, a task type, a protected type, a formal private type, or a formal derived type:

- The `record_component_association_list` shall include **others** `=> <>`; and
- The type of the `record_aggregate` shall have known discriminants or be a tagged, task, or protected, definite type; and
- The `record_component_association_list` shall not include a positional component association.

**Insert before paragraph 20: [AI95-00287-01]**

The expression of a `record_component_association` is evaluated (and converted) once for each associated component.

**the new paragraph:**

For a `record_component_association` with an expression, the expression defines the value for the associated component(s). For a `record_component_association` with `<>`, if the `component_declaration` has a `default_expression`, that `default_expression` defines the value for the associated component(s); otherwise, the associated component(s) are initialized by default as for a stand-alone object of the component subtype (see 3.3.1).

**Insert after paragraph 29: [AI95-00287-01]**

-- *The allocator is evaluated twice: Succ and Pred designate different cells*

**the new paragraphs:**

(Value => 0, Succ|Pred => <>) -- see 3.10.1

-- *Succ and Pred will be set to null*



### 4.3.2 Extension Aggregates

#### Replace paragraph 4: [AI95-00287-01; AI95-00389-01]

The expected type for an `extension_aggregate` shall be a single nonlimited type that is a record extension. If the `ancestor_part` is an expression, it is expected to be of any nonlimited tagged type.

by:

The expected type for an `extension_aggregate` shall be a single type that is a type extension. If the `ancestor_part` is an expression, it is expected to be of any tagged type.

#### Replace paragraph 5: [AI95-00306-01; AI95-00389-01]

If the `ancestor_part` is a `subtype_mark`, it shall denote a specific tagged subtype. The type of the `extension_aggregate` shall be derived from the type of the `ancestor_part`, through one or more record extensions (and no private extensions).

by:

If the `ancestor_part` is a `subtype_mark`, it shall denote a specific tagged subtype. If the `ancestor_part` is an expression, it shall not be dynamically tagged. The type of the `extension_aggregate` shall be a descendant of the type of the `ancestor_part`. If the type of the `extension_aggregate` is derived from the type of the `ancestor_part` through one or more private extensions, then the `record_component_association_list` shall include **others** => <>, and shall not include a positional component association.

### 4.3.3 Array Aggregates

#### Replace paragraph 3: [AI95-00287-01]

```
positional_array_aggregate ::=
  (expression, expression {, expression})
  | (expression {, expression}, others => expression)
```

by:

```
positional_array_aggregate ::=
  (expression, expression {, expression})
  | (expression {, expression}, others => expression)
  | (expression {, expression}, others => <>)
```

#### Replace paragraph 5: [AI95-00287-01]

```
array_component_association ::=
  discrete_choice_list => expression
```

by:

```
array_component_association ::=
  discrete_choice_list => expression
  | discrete_choice_list => <>
```

#### Replace paragraph 7: [AI95-00287-01]

The expected type for an `array_aggregate` (that is not a subaggregate) shall be a single nonlimited array type. The component type of this array type is the expected type for each array component expression of the `array_aggregate`.

by:

The expected type for an `array_aggregate` (that is not a subaggregate) shall be a single array type. The component type of this array type is the expected type for each array component expression of the `array_aggregate`.

**Insert before paragraph 24: [AI95-00287-01]**

The bounds of the index range of an `array_aggregate` (including a subaggregate) are determined as follows:

**the new paragraph:**

Each expression in an `array_component_association` defines the value for the associated component(s).  
For an `array_component_association` with `<>`, the associated component(s) are initialized by default as for a stand-alone object of the component subtype (see 3.3.1).

## 4.5.2 Relational Operators and Membership Tests

**Replace paragraph 3: [AI95-00251-01]**

The *tested type* of a membership test is the type of the `range` or the type determined by the `subtype_mark`.  
If the tested type is tagged, then the `simple_expression` shall resolve to be of a type that covers or is covered by the tested type; if untagged, the expected type for the `simple_expression` is the tested type.

**by:**

The *tested type* of a membership test is the type of the `range` or the type determined by the `subtype_mark`.  
If the tested type is tagged, then then the `simple_expression` shall resolve to be of a type that is convertible (see 4.6) to the tested type; if untagged, the expected type for the `simple_expression` is the tested type.

**Insert after paragraph 7: [AI95-00230-01]**

```
function "=" (Left, Right : T) return Boolean
function "/=" (Left, Right : T) return Boolean
```

**the new paragraphs:**

The following additional equality operators for the *universal\_access* type are declared in package Standard for use with anonymous access types:

```
function "=" (Left, Right : universal_access) return Boolean
function "/=" (Left, Right : universal_access) return Boolean
```

**Insert after paragraph 9: [AI95-00230-01]**

```
function "<" (Left, Right : T) return Boolean
function "<=" (Left, Right : T) return Boolean
function ">" (Left, Right : T) return Boolean
function ">=" (Left, Right : T) return Boolean
```

**the new paragraphs:**

*Name Resolution Rules*

At least one of the operands of the equality operators for *universal\_access* shall be of a specific anonymous access type.

*Legality Rules*

The operands of the equality operators for *universal\_access* shall be convertible to one another (see 4.6).

**Replace paragraph 30: [AI95-00231-01]**

- The tested type is not scalar, and the value of the `@nt<simple_expression>` satisfies any constraints of the named subtype, and, if the type of the `@nt<simple_expression>` is class-wide, the value has a tag that identifies a type covered by the tested type.>

**by:**

- The tested type is not scalar, and the value of the `@nt<simple_expression>` satisfies any constraints of the named subtype, and:>

- if the type of the `simple_expression` is class-wide, the value has a tag that identifies a type covered by the tested type.
- if the tested type is an access type and the named subtype excludes null, the value of the `simple_expression` is not null.

#### 4.5.5 Multiplying Operators

##### Replace paragraph 20: [AI95-00364-01]

###### *Legality Rules*

The above two fixed-fixed multiplying operators shall not be used in a context where the expected type for the result is itself *universal\_fixed* -- the context has to identify some other numeric type to which the result is to be converted, either explicitly or implicitly.

by:

###### *Name Resolution Rules*

The above two fixed-fixed multiplying operators shall not be used in a context where the expected type for the result is itself *universal\_fixed* -- the context has to identify some other numeric type to which the result is to be converted, either explicitly or implicitly. An explicit conversion is required on the result when using the above fixed-fixed multiplication operator when either operand is of a type having a user-defined primitive multiplication operator declared immediately within the same list of declarations as the type and with both formal parameters of a fixed-point type. A corresponding requirement applies to the universal fixed-fixed division operator.

#### 4.6 Type Conversions

##### Replace paragraph 5: [AI95-00330-01]

A `type_conversion` whose operand is the `name` of an object is called a *view conversion* if both its target type and operand type are tagged, or if it appears as an actual parameter of mode **out** or **in out**; other `type_conversions` are called *value conversions*.

by:

A `type_conversion` whose operand is the `name` of an object is called a *view conversion* if both its target type and operand type are tagged, or if it appears as or if it appears in a call as an actual parameter of mode **out** or **in out**; other `type_conversions` are called *value conversions*.

##### Replace paragraph 8: [AI95-00251-01]

If the target type is a numeric type, then the operand type shall be a numeric type.

by:

In a view conversion for an untagged type, the target type shall be convertible (back) to the operand type.

##### Delete paragraph 9: [AI95-00246-01; AI95-00251-01]

If the target type is an array type, then the operand type shall be an array type. Further:

##### Delete paragraph 10: [AI95-00251-01]

- The types shall have the same dimensionality;

##### Delete paragraph 11: [AI95-00251-01]

- Corresponding index types shall be convertible;

**Delete paragraph 12: [AI95-00246-01; AI95-00251-01; AI95-00392-01]**

- The component subtypes shall statically match; and

**Delete paragraph 12.1: [AI95-00246-01; AI95-00251-01; AI95-00363-01]**

- In a view conversion, the target type and the operand type shall both or neither have aliased components.

**Delete paragraph 13: [AI95-00230-01; AI95-00251-01]**

If the target type is a general access type, then the operand type shall be an access-to-object type. Further:

**Delete paragraph 14: [AI95-00251-01]**

- If the target type is an access-to-variable type, then the operand type shall be an access-to-variable type;

**Delete paragraph 15: [AI95-00251-01]**

- If the target designated type is tagged, then the operand designated type shall be convertible to the target designated type;

**Delete paragraph 16: [AI95-00251-01; AI95-00363-01; AI95-00384-01]**

- If the target designated type is not tagged, then the designated types shall be the same, and either the designated subtypes shall statically match or the target designated subtype shall be discriminated and unconstrained; and

**Delete paragraph 17: [AI95-00251-01]**

- The accessibility level of the operand type shall not be statically deeper than that of the target type. In addition to the places where Legality Rules normally apply (see 12.3), this rule applies also in the private part of an instance of a generic unit.

**Delete paragraph 18: [AI95-00230-01; AI95-00251-01]**

If the target type is an access-to-subprogram type, then the operand type shall be an access-to-subprogram type. Further:

**Delete paragraph 19: [AI95-00251-01]**

- The designated profiles shall be subtype-conformant.

**Delete paragraph 20: [AI95-00251-01]**

- The accessibility level of the operand type shall not be statically deeper than that of the target type. In addition to the places where Legality Rules normally apply (see 12.3), this rule applies also in the private part of an instance of a generic unit. If the operand type is declared within a generic body, the target type shall be declared within the generic body.

**Replace paragraph 21: [AI95-00251-01]**

If the target type is not included in any of the above four cases, there shall be a type that is an ancestor of both the target type and the operand type. Further, if the target type is tagged, then either:

**by:**

If there is a type that is an ancestor of both the target type and the operand type, then:

- The target type shall be untagged; or

**Replace paragraph 23: [AI95-00251-01]**

- The operand type shall be a class-wide type that covers the target type.

by:

- The operand type shall be a class-wide type that covers the target type; or
- The operand and target types shall both be class-wide types and the specific type associated with at least one of them shall be an interface type.

**Replace paragraph 24: [AI95-00246-01; AI95-00251-01; AI95-00392-01]**

In a view conversion for an untagged type, the target type shall be convertible (back) to the operand type.

by:

If there is no type that is an ancestor of both the target type and the operand type, then:

- If the target type is a numeric type, then the operand type shall be a numeric type.
- If the target type is an array type, then the operand type shall be an array type. Further:
  - The types shall have the same dimensionality;
  - Corresponding index types shall be convertible;
  - The component subtypes shall statically match;
  - If the component types are anonymous access types, then the accessibility level of the operand type shall not be statically deeper than that of the target type;
  - Neither the target type nor the operand type shall be limited; and
  - In a view conversion: if the target type has aliased components, then so shall the operand type; and the operand type shall not have a tagged, private, or volatile subcomponent.
- If the target type is *universal\_access*, then the operand type shall be an access type.
- If the target type is a general access-to-object type, then the operand type shall be *universal\_access* or an access-to-object type. Further, if not *universal\_access*:
  - If the target type is an access-to-variable type, then the operand type shall be an access-to-variable type;
  - If the target designated type is tagged, then the operand designated type shall be convertible to the target designated type;
  - If the target designated type is not tagged, then the designated types shall be the same, and either:
    - the designated subtypes shall statically match; or
    - the designated type shall be discriminated in its full view and unconstrained in any partial view, and one of the designated subtypes shall be unconstrained;
  - The accessibility level of the operand type shall not be statically deeper than that of the target type. In addition to the places where Legality Rules normally apply (see 12.3), this rule applies also in the private part of an instance of a generic unit.
- If the target type is an access-to-subprogram type, then the operand type shall be *universal\_access* or an access-to-subprogram type. Further, if not *universal\_access*:
  - The designated profiles shall be subtype-conformant.
  - The accessibility level of the operand type shall not be statically deeper than that of the target type. In addition to the places where Legality Rules normally apply (see 12.3), this rule applies also in the private part of an instance of a generic unit. If the operand type is declared within a generic body, the target type shall be declared within the generic body.

**Insert after paragraph 39: [AI95-00392-01]**

- In either array case, the value of each component of the result is that of the matching component of the operand value (see 4.5.2).

**the new paragraph:**

- If the component types of the array types are anonymous access types, then a check is made that the accessibility level of the operand type is not deeper than that of the target type.

**Replace paragraph 49: [AI95-00230-01; AI95-00231-01]**

- If the target type is an anonymous access type, a check is made that the value of the operand is not null; if the target is not an anonymous access type, then the result is null if the operand value is null.

**by:**

- If the operand value is null, the result of the conversion is the null value of the target type.

**Replace paragraph 51: [AI95-00231-01]**

After conversion of the value to the target type, if the target subtype is constrained, a check is performed that the value satisfies this constraint.

**by:**

After conversion of the value to the target type, if the target subtype is constrained, a check is performed that the value satisfies this constraint. If the target subtype excludes the null value, then a check is made that the value is not null.

**Replace paragraph 61: [AI95-00230-01]**

22 A ramification of the overload resolution rules is that the operand of an (explicit) `type_conversion` cannot be the literal `null`, an allocator, an aggregate, a `string_literal`, a `character_literal`, or an `attribute_reference` for an `Access` or `Unchecked_Access` attribute. Similarly, such an expression enclosed by parentheses is not allowed. A `qualified_expression` (see 4.7) can be used instead of such a `type_conversion`.

**by:**

22 A ramification of the overload resolution rules is that the operand of an (explicit) `type_conversion` cannot be an allocator, an aggregate, a `string_literal`, a `character_literal`, or an `attribute_reference` for an `Access` or `Unchecked_Access` attribute. Similarly, such an expression enclosed by parentheses is not allowed. A `qualified_expression` (see 4.7) can be used instead of such a `type_conversion`.

## 4.8 Allocators

**Replace paragraph 5: [AI95-00287-01; AI95-00344-01]**

If the type of the `allocator` is an access-to-constant type, the `allocator` shall be an initialized allocator. If the designated type is limited, the `allocator` shall be an uninitialized allocator.

**by:**

If the type of the `allocator` is an access-to-constant type, the `allocator` shall be an initialized allocator.

If the designated type of the type of the `allocator` is class-wide, the accessibility level of the type determined by the `subtype_indication` or `qualified_expression` shall not be statically deeper than that of the type of the `allocator`.

**Replace paragraph 6: [AI95-00363-01]**

If the designated type of the type of the `allocator` is elementary, then the subtype of the created object is the designated subtype. If the designated type is composite, then the created object is always constrained; if the designated subtype is constrained, then it provides the constraint of the created object; otherwise, the object is constrained by its initial value (even if the designated subtype is unconstrained with defaults).

by:

If the designated type of the type of the **allocator** is elementary, then the subtype of the created object is the designated subtype. If the designated type is composite, then the subtype of the created object is the designated subtype when the designated subtype is constrained or there is a partial view of the designated type that is constrained; otherwise, the created object is constrained by its initial value (even if the designated subtype is unconstrained with defaults).

**Replace paragraph 7: [AI95-00344-01]**

For the evaluation of an **allocator**, the elaboration of the **subtype\_indication** or the evaluation of the **qualified\_expression** is performed first. For the evaluation of an initialized **allocator**, an object of the designated type is created and the value of the **qualified\_expression** is converted to the designated subtype and assigned to the object.

by:

For the evaluation of an **allocator**, the elaboration of the **subtype\_indication** or the evaluation of the **qualified\_expression** is performed first. For the evaluation of an initialized **allocator**, an object of the designated type is created and the value of the **qualified\_expression** is converted to the designated subtype and assigned to the object. If the designated type of the type of the **allocator** is class-wide, then a check is made that the accessibility level of the type identified by the tag of the value of the **qualified\_expression** is not deeper than that of the type of the **allocator**. **Program\_Error** is raised if this check fails.

**Replace paragraph 11: [AI95-00280-01]**

If the created object contains any tasks, they are activated (see 9.2). Finally, an access value that designates the created object is returned.

by:

If the object created by the **allocator** has a controlled or protected part, and the finalization of the collection of the type of the **allocator** (see 7.6.1) has started, **Program\_Error** is raised.

If the created object contains any tasks, and the master of the type of the **allocator** has finished waiting for dependent tasks (see 9.3), **Program\_Error** is raised.

If the created object contains any tasks, they are activated (see 9.2). Finally, an access value that designates the created object is returned.

*Bounded (Run-Time) Errors*

It is a bounded error if the finalization of the collection of the type (see 7.6.1) of the **allocator** has started. If the error is detected, **Program\_Error** is raised. Otherwise, the allocation proceeds normally.

## 4.9 Static Expressions and Static Subtypes

**Replace paragraph 26: [AI95-00263-01]**

A *static subtype* is either a *static scalar subtype* or a *static string subtype*. A static scalar subtype is an unconstrained scalar subtype whose type is not a descendant of a formal scalar type, or a constrained scalar subtype formed by imposing a compatible static constraint on a static scalar subtype. A static string subtype is an unconstrained string subtype whose index subtype and component subtype are static (and whose type is not a descendant of a formal array type), or a constrained string subtype formed by imposing a compatible static constraint on a static string subtype. In any case, the subtype of a generic formal object of mode **in out**, and the result subtype of a generic formal function, are not static.

by:

A *static subtype* is either a *static scalar subtype* or a *static string subtype*. A static scalar subtype is an unconstrained scalar subtype whose type is not a descendant of a formal type, or a constrained scalar subtype formed by imposing a compatible static constraint on a static scalar subtype. A static string subtype is an unconstrained string subtype whose index subtype and component subtype are static, or a constrained string

subtype formed by imposing a compatible static constraint on a static string subtype. In any case, the subtype of a generic formal object of mode **in out**, and the result subtype of a generic formal function, are not static.

**Insert after paragraph 31: [AI95-00311-01]**

- A discriminant constraint is static if each expression of the constraint is static, and the subtype of each discriminant is static.

**the new paragraph:**

In any case, the constraint of the first subtype of a scalar formal type is neither static nor null.

**Replace paragraph 35: [AI95-00269-01]**

- If the expression is not part of a larger static expression, then its value shall be in the base range of its expected type. Otherwise, the value may be arbitrarily large or small.

**by:**

- If the expression is not part of a larger static expression and the expression is expected to be of a single specific type, then its value shall be in the base range of its expected type. Otherwise, the value may be arbitrarily large or small.

**Replace paragraph 37: [AI95-00269-01]**

The last two restrictions above do not apply if the expected type is a descendant of a formal scalar type (or a corresponding actual type in an instance).

**by:**

The last restriction above does not apply if the expected type is a descendant of a formal scalar type (or a corresponding actual type in an instance).

In addition to the places where Legality Rules normally apply (see 12.3), the above restrictions also apply in the private part of an instance of a generic unit.

**Replace paragraph 38: [AI95-00268-01; AI95-00269-01]**

For a real static expression that is not part of a larger static expression, and whose expected type is not a descendant of a formal scalar type, the implementation shall round or truncate the value (according to the `Machine_Rounds` attribute of the expected type) to the nearest machine number of the expected type; if the value is exactly half-way between two machine numbers, any rounding shall be performed away from zero. If the expected type is a descendant of a formal scalar type, no special rounding or truncating is required - normal accuracy rules apply (see Annex G).

**by:**

For a real static expression that is not part of a larger static expression, and whose expected type is not a descendant of a formal scalar type, the implementation shall round or truncate the value (according to the `Machine_Rounds` attribute of the expected type) to the nearest machine number of the expected type; if the value is exactly half-way between two machine numbers, the rounding performed is implementation-defined. If the expected type is a descendant of a formal scalar type, or if the static expression appears in the body of an instance of a generic unit and the corresponding expression is nonstatic in the corresponding generic body, then no special rounding or truncating is required -- normal accuracy rules apply (see Annex G).

*Implementation Advice*

For a real static expression that is not part of a larger static expression, and whose expected type is not a descendant of a formal scalar type, the rounding should be the same as the default rounding for the target system.



### 4.9.1 Statically Matching Constraints and Subtypes

**Replace paragraph 1: [AI95-00311-01]**

A constraint *statically matches* another constraint if both are null constraints, both are static and have equal corresponding bounds or discriminant values, or both are nonstatic and result from the same elaboration of a constraint of a subtype\_indication or the same evaluation of a range of a discrete\_subtype\_definition.

**by:**

A constraint *statically matches* another constraint if:

- both are null constraints;
- both are static and have equal corresponding bounds or discriminant values;
- both are nonstatic and result from the same elaboration of a constraint of a subtype\_indication or the same evaluation of a range of a discrete\_subtype\_definition; or
- both are nonstatic and both come from the same formal\_type\_declaration.

**Replace paragraph 2: [AI95-00231-01; AI95-00254-01]**

A subtype *statically matches* another subtype of the same type if they have statically matching constraints. Two anonymous access subtypes statically match if their designated subtypes statically match.

**by:**

A subtype *statically matches* another subtype of the same type if they have statically matching constraints, and, for access subtypes, either both or neither exclude null. Two anonymous access-to-object subtypes statically match if their designated subtypes statically match, and either both or neither exclude null, and either both or neither are access-to-constant. Two anonymous access-to-subprogram subtypes statically match if their designated profiles are subtype conformant, and either both or neither exclude null.

## Section 5: Statements

### 5.2 Assignment Statements

**Replace paragraph 4: [AI95-00287-01]**

The *variable\_name* of an *assignment\_statement* is expected to be of any nonlimited type. The expected type for the *expression* is the type of the target.

**by:**

The *variable\_name* of an *assignment\_statement* is expected to be of any type. The expected type for the *expression* is the type of the target.

**Replace paragraph 5: [AI95-00287-01]**

The target denoted by the *variable\_name* shall be a variable.

**by:**

The target denoted by the *variable\_name* shall be a variable of a nonlimited type.

## Section 6: Subprograms

### 6.1 Subprogram Declarations

**Replace paragraph 2: [AI95-00218-03]**

subprogram\_declaration ::= subprogram\_specification ;

**by:**

overriding\_indicator ::= [not] overriding  
 subprogram\_declaration ::=  
   [overriding\_indicator]  
   subprogram\_specification ;

**Replace paragraph 3: [AI95-00218-03]**

abstract\_subprogram\_declaration ::= subprogram\_specification **is abstract**;

**by:**

abstract\_subprogram\_declaration ::=  
   [overriding\_indicator]  
   subprogram\_specification **is abstract**;

**Replace paragraph 4: [AI95-00348-01]**

subprogram\_specification ::=  
   **procedure** defining\_program\_unit\_name parameter\_profile  
   | **function** defining\_designator parameter\_and\_result\_profile

**by:**

procedure\_specification ::= **procedure** defining\_program\_unit\_name parameter\_profile  
 function\_specification ::= **function** defining\_designator parameter\_and\_result\_profile  
 subprogram\_specification ::=  
   procedure\_specification  
   | function\_specification

**Replace paragraph 13: [AI95-00231-01; AI95-00318-02]**

parameter\_and\_result\_profile ::= [formal\_part] **return** subtype\_mark

**by:**

parameter\_and\_result\_profile ::=  
   [formal\_part] **return** [null\_exclusion] subtype\_mark  
   | [formal\_part] **return** access\_definition

**Replace paragraph 15: [AI95-00231-01]**

parameter\_specification ::=  
   defining\_identifier\_list : mode subtype\_mark [:= default\_expression]  
   | defining\_identifier\_list : access\_definition [:= default\_expression]

**by:**

parameter\_specification ::=  
   defining\_identifier\_list : mode [null\_exclusion] subtype\_mark [:= default\_expression]  
   | defining\_identifier\_list : access\_definition [:= default\_expression]

**Replace paragraph 23: [AI95-00231-01; AI95-00318-02]**

The nominal subtype of a formal parameter is the subtype denoted by the subtype\_mark, or defined by the access\_definition, in the parameter\_specification.

by:

The nominal subtype of a formal parameter is the subtype determined by the optional `null_exclusion` and the `subtype_mark`, or defined by the `access_definition`, in the `parameter_specification`. The nominal subtype of a function result is the subtype determined by the optional `null_exclusion` and the `subtype_mark`, or defined by the `access_definition`, in the `parameter_and_result_profile`.

**Replace paragraph 24: [AI95-00231-01; AI95-00254-01; AI95-00318-02]**

An *access parameter* is a formal **in** parameter specified by an `access_definition`. An access parameter is of an anonymous general access-to-variable type (see 3.10). Access parameters allow dispatching calls to be controlled by access values.

by:

An *access parameter* is a formal **in** parameter specified by an `access_definition`. An *access result type* is a function result type specified by an `access_definition`. An access parameter or result type is of an anonymous access type (see 3.10). Access parameters of an access-to-object type allow dispatching calls to be controlled by access values. Access parameters of an access-to-subprogram type permit calls to subprograms passed as parameters irrespective of their accessibility level.

**Replace paragraph 27: [AI95-00254-01]**

- For any access parameters, the designated subtype of the parameter type.

by:

- For any access parameters of an access-to-object type, the designated subtype of the parameter type.
- For any access parameters of an access-to-subprogram type, the subtypes of the profile of the parameter type.

**Replace paragraph 28: [AI95-00231-01; AI95-00254-01; AI95-00318-02]**

- For any result, the result subtype.

by:

- For any non-access result, the nominal subtype of the function result.
- For any access result type of an access-to-object type, the designated subtype of the result type.
- For any access result type of an access-to-subprogram type, the subtypes of the profile of the result type.

**Insert after paragraph 30: [AI95-00218-03]**

A subprogram declared by an `abstract_subprogram_declaration` is abstract; a subprogram declared by a `subprogram_declaration` is not. See 3.9.3, "Abstract Types and Subprograms".

**the new paragraph:**

An `overriding_indicator` is used to indicate whether overriding is intended. See 8.3, "Visibility".

## 6.3 Subprogram Bodies

**Replace paragraph 2: [AI95-00218-03]**

```
subprogram_body ::=
  subprogram_specification is
    declarative_part
  begin
    handled_sequence_of_statements
  end [designator];
```

by:

```
subprogram_body ::=
  [overriding_indicator]
  subprogram_specification is
    declarative_part
  begin
    handled_sequence_of_statements
  end [designator];
```

### 6.3.1 Conformance Rules

Replace paragraph 10: [AI95-00252-01]

- a subprogram declared immediately within a `protected_body`.

by:

- a subprogram declared immediately within a `protected_body`;
- the view of a subprogram denoted by a `selected_component` whose `prefix` denotes an object or value of a tagged type, and whose `selector_name` denotes a subprogram operating on the type (see 4.1.3).

Insert after paragraph 13: [AI95-00254-01]

- The default calling convention is *entry* for an entry.

the new paragraph:

- The calling convention for an access parameter of an access-to-subprogram type is *protected* if the reserved word **protected** appears in its definition and otherwise is the convention of the subprogram that contains the parameter.

Replace paragraph 16: [AI95-00318-02]

Two profiles are *mode conformant* if they are type-conformant, and corresponding parameters have identical modes, and, for access parameters, the designated subtypes statically match.

by:

Two profiles are *mode conformant* if they are type-conformant, corresponding parameters have identical modes, and, for access parameters or access result types, the designated subtypes statically match.

Insert after paragraph 24: [AI95-00345-01]

Two `discrete_subtype_definitions` are *fully conformant* if they are both `subtype_indications` or are both `ranges`, the `subtype_marks` (if any) denote the same subtype, and the corresponding `simple_expressions` of the `ranges` (if any) fully conform.

the new paragraph:

Two subprograms or entries are *type conformant* (respectively *mode conformant*, *subtype conformant*, or *fully conformant*) if their profiles are type conformant (respectively mode conformant, subtype conformant, or fully conformant).

### 6.3.2 Inline Expansion of Subprograms

Insert after paragraph 6: [AI95-00309-01]

For each call, an implementation is free to follow or to ignore the recommendation expressed by the pragma.

the new paragraph:

An implementation may allow a `pragma Inline` that has an argument which is a `direct_name` denoting a `subprogram_body` of the same `declarative_part`.

## 6.4 Subprogram Calls

Replace paragraph 8: [AI95-00310-01]

The name or prefix given in a `procedure_call_statement` shall resolve to denote a callable entity that is a procedure, or an entry renamed as (viewed as) a procedure. The name or prefix given in a `function_call` shall resolve to denote a callable entity that is a function. When there is an `actual_parameter_part`, the prefix can be an `implicit_dereference` of an access-to-subprogram value.

by:

The name or prefix given in a `procedure_call_statement` shall resolve to denote a callable entity that is a procedure, or an entry renamed as (viewed as) a procedure. The name or prefix given in a `function_call` shall resolve to denote a callable entity that is a function. The name or prefix shall not resolve to denote an abstract subprogram unless it is also a dispatching subprogram. When there is an `actual_parameter_part`, the prefix can be an `implicit_dereference` of an access-to-subprogram value.

Replace paragraph 12: [AI95-00231-01]

A `function_call` denotes a constant, as defined in 6.5; the nominal subtype of the constant is given by the result subtype of the function.

by:

A `function_call` denotes a constant, as defined in 6.5; the nominal subtype of the constant is given by the nominal subtype of the function result.

## 6.5 Return Statements

Replace paragraph 2: [AI95-00318-02]

`return_statement ::= return [expression];`

by:

`return_statement ::= simple_return_statement | extended_return_statement`

`simple_return_statement ::= return [expression];`

`extended_return_statement ::=`

`return identifier : [aliased] return_subtype_indication [:= expression] [do`  
`handled_sequence_of_statements`  
`end return];`

`return_subtype_indication ::= subtype_indication | access_definition`

Replace paragraph 3: [AI95-00318-02]

The expression, if any, of a `return_statement` is called the *return expression*. The *result subtype* of a function is the subtype denoted by the `subtype_mark` after the reserved word **return** in the profile of the function. The expected type for a return expression is the result type of the corresponding function.

by:

The *result subtype* of a function is the subtype denoted by the `subtype_mark`, or defined by the `access_definition`, after the reserved word **return** in the profile of the function. The expression, if any, of a `simple_return_statement` or `extended_return_statement` is called the *return expression*. The expected type for a return expression is the result type of the corresponding function.

**Replace paragraph 4: [AI95-00318-02]**

A `return_statement` shall be within a callable construct, and it *applies to* the innermost one. A `return_statement` shall not be within a body that is within the construct to which the `return_statement` applies.

**by:**

A `return_statement` shall be within a callable construct, and it *applies to* the innermost callable construct or `extended_return_statement` that contains it. A `return_statement` shall not be within a body that is within the construct to which the `return_statement` applies.

**Replace paragraph 5: [AI95-00318-02]**

A function body shall contain at least one `return_statement` that applies to the function body, unless the function contains `code_statements`. A `return_statement` shall include a return expression if and only if it applies to a function body.

**by:**

A function body shall contain at least one `return_statement` that applies to the function body, unless the function contains `code_statements`. A `simple_return_statement` shall include a return expression if and only if it applies to a function body. An `extended_return_statement` shall apply to a function body.

If the result subtype of a function is defined by a `subtype_mark`, the `return_subtype_indication` of an `extended_return_statement` that applies to the function body shall be a `subtype_indication`. The type of the `subtype_indication` shall be the result type of the function. If the result subtype of the function is constrained, then the subtype defined by the `subtype_indication` shall also be constrained and shall statically match this result subtype. If the result subtype of the function is unconstrained, then the subtype defined by the `subtype_indication` shall be a definite subtype, or there shall be a return expression.

If the result subtype of the function is defined by an `access_definition`, the `return_subtype_indication` shall be an `access_definition`. The subtype defined by the `access_definition` shall statically match the result subtype of the function. The accessibility level of this anonymous access subtype is that of the result subtype.

If the type of the return expression is limited, then the return expression shall be an aggregate, a function call (or equivalent use of an operator), or a `qualified_expression` or parenthesized expression whose operand is one of these.

*Static Semantics*

Within an `extended_return_statement`, the *return object* is declared with the given identifier, with nominal subtype defined by the `return_subtype_indication`.

**Replace paragraph 6: [AI95-00318-02]**

For the execution of a `return_statement`, the expression (if any) is first evaluated and converted to the result subtype.

**by:**

For the execution of an `extended_return_statement`, the `subtype_indication` or `access_definition` is elaborated. This creates the nominal subtype of the return object. If there is a return expression, it is evaluated and converted to the nominal subtype (which might raise `Constraint_Error` -- see 4.6) and becomes the initial value of the return object; otherwise, the return object is initialized by default as for a stand-alone object of its nominal subtype (see 3.3.1). If the nominal subtype is indefinite, the return object is constrained by its initial value. The `handled_sequence_of_statements`, if any, is then executed.

For the execution of a `simple_return_statement`, the expression (if any) is first evaluated and converted to the result subtype to become the value of the anonymous *return object*.

**Delete paragraph 7: [AI95-00318-02]**

If the result type is class-wide, then the tag of the result is the tag of the value of the expression.

**Replace paragraph 8: [AI95-00318-02]**

If the result type is a specific tagged type:

**by:**

If the result type of a function is a specific tagged type, the tag of the return object is that of the result type.

**Delete paragraph 9: [AI95-00318-02]**

- If it is limited, then a check is made that the tag of the value of the return expression identifies the result type. `Constraint_Error` is raised if this check fails.

**Delete paragraph 10: [AI95-00318-02]**

- If it is nonlimited, then the tag of the result is that of the result type.

**Delete paragraph 11: [AI95-00318-02]**

A type is a *return-by-reference* type if it is a descendant of one of the following:

**Delete paragraph 12: [AI95-00318-02]**

- a tagged limited type;

**Delete paragraph 13: [AI95-00318-02]**

- a task or protected type;

**Delete paragraph 14: [AI95-00318-02]**

- a nonprivate type with the reserved word **limited** in its declaration;

**Delete paragraph 15: [AI95-00318-02]**

- a composite type with a subcomponent of a return-by-reference type;

**Delete paragraph 16: [AI95-00318-02]**

- a private type whose full type is a return-by-reference type.

**Delete paragraph 17: [AI95-00318-02]**

If the result type is a return-by-reference type, then a check is made that the return expression is one of the following:

**Delete paragraph 18: [AI95-00162-01; AI95-00316-01; AI95-00318-02]**

- a name that denotes an object view whose accessibility level is not deeper than that of the master that elaborated the function body; or

**Delete paragraph 19: [AI95-00318-02]**

- a parenthesized expression or `qualified_expression` whose operand is one of these kinds of expressions.

**Replace paragraph 20: [AI95-00318-02; AI95-00344-01]**

The exception `Program_Error` is raised if this check fails.

**by:**

If the result type is class-wide, a check is made that the accessibility level of the type identified by the tag of the result is not deeper than that of the master that elaborated the function body. If this check fails, `Program_Error` is raised.



**Delete paragraph 21: [AI95-00318-02]**

For a function with a return-by-reference result type the result is returned by reference; that is, the function call denotes a constant view of the object associated with the value of the return expression. For any other function, the result is returned by copy; that is, the converted value is assigned into an anonymous constant created at the point of the `return_statement`, and the function call denotes that object.

**Replace paragraph 22: [AI95-00318-02]**

Finally, a transfer of control is performed which completes the execution of the construct to which the `return_statement` applies, and returns to the caller.

**by:**

Finally, a transfer of control is performed which completes the execution of the construct to which the `return_statement` applies, and returns to the caller. In the case of a function, the `function_call` denotes a constant view of the return object.

**Replace paragraph 24: [AI95-00318-02]**

```
return;                -- in a procedure body, entry_body, or accept_statement
return Key_Value(Last_Index); -- in a function body
```

**by:**

```
return;                -- in a procedure body, entry_body,
                        -- accept_statement, or extended_return_statement

return Key_Value(Last_Index); -- in a function body

return Node : Cell do   -- in a function body, see 3.10.1 for Cell
  Node.Value := Result;
  Node.Succ := Next_Node;
end return;
```

**6.5.1 Pragma No\_Return****Insert new clause: [AI95-00329-01]**

A pragma `No_Return` indicates that a procedure can return only by propagating an exception.

*Syntax*

The form of a pragma `No_Return`, which is a program unit pragma (see 10.1.5), is as follows:

```
pragma No_Return(local_name{, local_name});
```

*Legality Rules*

The pragma shall apply to one or more procedures or generic procedures.

If a pragma `No_Return` applies to a procedure or a generic procedure, there shall be no `return_statements` that apply to that procedure.

*Static Semantics*

If a pragma `No_Return` applies to a generic procedure, pragma `No_Return` applies to all instances of that generic procedure.

*Dynamic Semantics*

If a pragma `No_Return` applies to a procedure, then the exception `Program_Error` is raised at the point of the call of the procedure if the procedure body completes normally.

## 6.7 Null Procedures

### Insert new clause: [AI95-00348-01]

A `null_procedure_declaration` provides a shorthand to declare a procedure with an empty body.

#### *Syntax*

```
    null_procedure_declaration ::= procedure_specification is null;
```

#### *Static Semantics*

A `null_procedure_declaration` declares a *null procedure*. A completion is not allowed for a `null_procedure_declaration`.

#### *Dynamic Semantics*

The execution of a null procedure is invoked by a subprogram call. For the execution of a subprogram call on a null procedure, the execution of the `subprogram_body` has no effect.

## Section 7: Packages

### 7.3 Private Types and Private Extensions

Replace paragraph 2: [AI95-00251-01]

```
private_extension_declaration ::=
  type defining_identifier [discriminant_part] is
    [abstract] new ancestor_subtype_indication with private;
```

by:

```
private_extension_declaration ::=
  type defining_identifier [discriminant_part] is
    [abstract] new ancestor_subtype_indication [and interface_list] with private;
```

#### 7.3.1 Private Operations

Replace paragraph 12: [AI95-00287-01]

9 Partial views provide assignment (unless the view is limited), membership tests, selected components for the selection of discriminants and inherited components, qualification, and explicit conversion.

9 Partial views provide initialization, membership tests, selected components for the selection of discriminants and inherited components, qualification, and explicit conversion. Nonlimited partial views also provide assignment\_statements.

### 7.4 Deferred Constants

Replace paragraph 9: [AI95-00256-01]

The completion of a deferred constant declaration shall occur before the constant is frozen (see 7.4).

by:

The completion of a deferred constant declaration shall occur before the constant is frozen (see 13.14).

### 7.5 Limited Types

Replace paragraph 1: [AI95-00287-01]

A limited type is (a view of) a type for which the assignment operation is not allowed. A nonlimited type is a (view of a) type for which the assignment operation is allowed.

by:

A limited type is (a view of) a type for which copying (such as for an assignment\_statement) is not allowed. A nonlimited type is a (view of a) type for which copying is allowed.

Insert before paragraph 2: [AI95-00287-01; AI95-00318-02]

If a tagged record type has any limited components, then the reserved word **limited** shall appear in its record\_type\_definition.

the new paragraph:

In the following contexts, an expression of a limited type is not permitted unless it is an aggregate, a function\_call, or a parenthesized expression or qualified\_expression whose operand is permitted by this rule:

- the initialization expression of an object\_declaration (see 3.3.1)

- the `default_expression` of a `component_declaration` (see 3.8)
- the expression of a `record_component_association` (see 4.3.1)
- the expression for an `ancestor_part` of an `extension_aggregate` (see 4.3.2)
- an expression of a `positional_array_aggregate` or the expression of an `array_component_association` (see 4.3.3)
- the `qualified_expression` of an initialized allocator (see 4.8)
- the expression of a `return_statement` (see 6.5)
- the `default_expression` or actual parameter for a formal object of mode **in** (see 12.4)

**Insert after paragraph 8: [AI95-00287-01; AI95-00318-02]**

There are no predefined equality operators for a limited type.

**the new paragraph:**

*Implementation Requirements*

For an `aggregate` of a limited type used to initialize an object as allowed above, the implementation shall not create a separate anonymous object for the `aggregate`. For a `function_call` of a type with a part that is of a task, protected, or limited record type that is used to initialize an object as allowed above, the implementation shall not create a separate return object (see 6.5) for the `function_call`. The `aggregate` or `function_call` shall be constructed directly in the new object.

**Replace paragraph 9: [AI95-00287-01; AI95-00318-02]**

13 The following are consequences of the rules for limited types:

**by:**

13 While it is allowed to write initializations of limited objects, such initializations never copy a limited object. The source of such an assignment operation must be an `aggregate` or `function_call`, and such `aggregates` and `function_calls` must be built directly in the target object.

**Delete paragraph 10: [AI95-00287-01]**

- An initialization expression is not allowed in an `object_declaration` if the type of the object is limited.

**Delete paragraph 11: [AI95-00287-01]**

- A default expression is not allowed in a `component_declaration` if the type of the record component is limited.

**Delete paragraph 12: [AI95-00287-01]**

- An initialized allocator is not allowed if the designated type is limited.

**Delete paragraph 13: [AI95-00287-01]**

- A generic formal parameter of mode **in** must not be of a limited type.

**Delete paragraph 14: [AI95-00287-01]**

14 `Aggregates` are not available for a limited composite type. Concatenation is not available for a limited array type.

**Delete paragraph 15: [AI95-00287-01]**

15 The rules do not exclude a `default_expression` for a formal parameter of a limited type; they do not exclude a deferred constant of a limited type if the full declaration of the constant is of a nonlimited type.

## 7.6 User-Defined Assignment and Finalization

Replace paragraph 5: [AI95-00161-01]

```
type Controlled is abstract tagged private;
```

by:

```
type Controlled is abstract tagged private;
pragma Preelaborable_Initialization(Controlled);
```

Replace paragraph 6: [AI95-00348-01]

```
procedure Initialize (Object : in out Controlled);
procedure Adjust    (Object : in out Controlled);
procedure Finalize  (Object : in out Controlled);
```

by:

```
procedure Initialize (Object : in out Controlled) is null;
procedure Adjust    (Object : in out Controlled) is null;
procedure Finalize  (Object : in out Controlled) is null;
```

Replace paragraph 7: [AI95-00161-01]

```
type Limited_Controlled is abstract tagged limited private;
```

by:

```
type Limited_Controlled is abstract tagged limited private;
pragma Preelaborable_Initialization(Limited_Controlled);
```

Replace paragraph 8: [AI95-00348-01]

```
procedure Initialize (Object : in out Limited_Controlled);
procedure Finalize  (Object : in out Limited_Controlled);
private
  ... -- not specified by the language
end Ada.Finalization;
```

by:

```
procedure Initialize (Object : in out Limited_Controlled) is null;
procedure Finalize  (Object : in out Limited_Controlled) is null;
private
  ... -- not specified by the language
end Ada.Finalization;
```

Replace paragraph 9: [AI95-00348-01; AI95-00360-01]

A controlled type is a descendant of Controlled or Limited\_Controlled. The (default) implementations of Initialize, Adjust, and Finalize have no effect. The predefined "=" operator of type Controlled always returns True, since this operator is incorporated into the implementation of the predefined equality operator of types derived from Controlled, as explained in 4.5.2. The type Limited\_Controlled is like Controlled, except that it is limited and it lacks the primitive subprogram Adjust.

by:

A controlled type is a descendant of Controlled or Limited\_Controlled. The predefined "=" operator of type Controlled always returns True, since this operator is incorporated into the implementation of the predefined equality operator of types derived from Controlled, as explained in 4.5.2. The type Limited\_Controlled is like Controlled, except that it is limited and it lacks the primitive subprogram Adjust.

A type is said to *need finalization* if:

- it is a controlled type, a task type or a protected type; or
- it has a component that needs finalization; or

- it is a limited type that has an access discriminant whose designated type needs finalization; or
- it is one of a number of language-defined types that are explicitly defined to need finalization.

**Replace paragraph 21: [AI95-00147-01]**

- For an **aggregate** or function call whose value is assigned into a target object, the implementation need not create a separate anonymous object if it can safely create the value of the **aggregate** or function call directly in the target object. Similarly, for an **assignment\_statement**, the implementation need not create an anonymous object if the value being assigned is the result of evaluating a name denoting an object (the source object) whose storage cannot overlap with the target. If the source object might overlap with the target object, then the implementation can avoid the need for an intermediary anonymous object by exercising one of the above permissions and perform the assignment one component at a time (for an overlapping array assignment), or not at all (for an assignment where the target and the source of the assignment are the same object). Even if an anonymous object is created, the implementation may move its value to the target object as part of the assignment without re-adjusting so long as the anonymous object has no aliased subcomponents.

**by:**

- For an **aggregate** or function call whose value is assigned into a target object, the implementation need not create a separate anonymous object if it can safely create the value of the **aggregate** or function call directly in the target object. Similarly, for an **assignment\_statement**, the implementation need not create an anonymous object if the value being assigned is the result of evaluating a name denoting an object (the source object) whose storage cannot overlap with the target. If the source object might overlap with the target object, then the implementation can avoid the need for an intermediary anonymous object by exercising one of the above permissions and perform the assignment one component at a time (for an overlapping array assignment), or not at all (for an assignment where the target and the source of the assignment are the same object).

Furthermore, an implementation is permitted to omit implicit Initialize, Adjust, and Finalize calls and associated assignment operations on an object of nonlimited controlled type provided that:

- any omitted Initialize call is not a call on a user-defined Initialize procedure, and
- any usage of the value of the object after the implicit Initialize or Adjust call and before any subsequent Finalize call on the object does not change the external effect of the program, and
- after the omission of such calls and operations, any execution of the program that executes an Initialize or Adjust call on an object or initializes an object by an **aggregate** will also later execute a Finalize call on the object and will always do so prior to assigning a new value to the object, and
- the assignment operations associated with omitted Adjust calls are also omitted.

This permission applies to Adjust and Finalize calls even if the implicit calls have additional external effects.

## 7.6.1 Completion and Finalization

**Replace paragraph 3: [AI95-00162-01]**

After execution of a construct or entity is complete, it is *left*, meaning that execution continues with the next action, as defined for the execution that is taking place. Leaving an execution happens immediately after its completion, except in the case of a master: the execution of a **task\_body**, a **block\_statement**, a **subprogram\_body**, an **entry\_body**, or an **accept\_statement**. A master is finalized after it is complete, and before it is left.

**by:**

After execution of a construct or entity is complete, it is *left*, meaning that execution continues with the next action, as defined for the execution that is taking place. Leaving an execution happens immediately after its completion, except in the case of a master: the execution of a body other than a **package\_body**; the

elaboration of a declaration other than the declaration of a package; the execution of an `accept_statement`, a `block_statement`, or a `simple_statement`; or the evaluation of an `expression` or `range` that is not part of an enclosing `expression`, `range`, or `simple_statement`. A master is finalized after it is complete, and before it is left.

**Replace paragraph 11: [AI95-00280-01]**

The order in which the finalization of a master performs finalization of objects is as follows: Objects created by declarations in the master are finalized in the reverse order of their creation. For objects that were created by `allocators` for an access type whose ultimate ancestor is declared in the master, this rule is applied as though each such object that still exists had been created in an arbitrary order at the first freezing point (see 13.14) of the ultimate ancestor type.

**by:**

The order in which the finalization of a master performs finalization of objects is as follows: Objects created by declarations in the master are finalized in the reverse order of their creation. For objects that were created by `allocators` for an access type whose ultimate ancestor is declared in the master, this rule is applied as though each such object that still exists had been created in an arbitrary order at the first freezing point (see 13.14) of the ultimate ancestor type; the finalization of these objects is called the *finalization of the collection*.

**Replace paragraph 12: [AI95-00256-01]**

The target of an assignment statement is finalized before copying in the new value, as explained in 7.6.

**by:**

The target of an `assignment_statement` is finalized before copying in the new value, as explained in 7.6.

**Replace paragraph 13: [AI95-00162-01]**

If the `object_name` in an `object_renaming_declaration`, or the actual parameter for a generic formal **in out** parameter in a `generic_instantiation`, denotes any part of an anonymous object created by a function call, the anonymous object is not finalized until after it is no longer accessible via any name. Otherwise, an anonymous object created by a function call or by an `aggregate` is finalized no later than the end of the innermost enclosing `declarative_item` or `statement`; if that is a `compound_statement`, the object is finalized before starting the execution of any `statement` within the `compound_statement`.

**by:**

The master of an object is the master enclosing its creation whose accessibility level (see 3.10.2) is equal to that of the object.

**Replace paragraph 13.1: [AI95-00162-01]**

If a transfer of control or raising of an exception occurs prior to performing a finalization of an anonymous object, the anonymous object is finalized as part of the finalizations due to be performed for the object's innermost enclosing master.

**by:**

In the case of a potentially blocking operation which is a master, finalization of an (anonymous) object occurs before blocking if the last use of the object occurs before blocking. In particular, for a `delay_statement`, any finalization occurs before delaying the task. In the case of an `expression` which is a master, finalization of any (anonymous) objects occurs as the final part of evaluation of the `expression`.

**Replace paragraph 16: [AI95-00256-01]**

- For an `Adjust` invoked as part of the initialization of a controlled object, other adjustments due to be performed might or might not be performed, and then `Program_Error` is raised. During its propagation, finalization might or might not be applied to objects whose `Adjust` failed. For an `Adjust` invoked as part of an assignment statement, any other adjustments due to be performed are performed, and then `Program_Error` is raised.

**by:**

- For an Adjust invoked as part of assignment operations other than those invoked as part of an `assignment_statement`, other adjustments due to be performed might or might not be performed, and then `Program_Error` is raised. During its propagation, finalization might or might not be applied to objects whose Adjust failed. For an Adjust invoked as part of an `assignment_statement`, any other adjustments due to be performed are performed, and then `Program_Error` is raised.



## Section 8: Visibility Rules

### 8.1 Declarative Region

Insert after paragraph 4: [AI95-00318-02]

- a loop\_statement;

the new paragraph:

- an extended\_return\_statement;

### 8.3 Visibility

Insert after paragraph 12: [AI95-00251-01]

- An implicit declaration of an inherited subprogram overrides a previous implicit declaration of an inherited subprogram.

the new paragraphs:

- If two or more homographs are implicitly declared at the same place:
  - If one is a non-null non-abstract subprogram, then it overrides all which are null or abstract subprograms.
  - If all are null procedures or abstract subprograms, then any null procedure overrides all abstract subprograms; if more than one homograph remains that is not thus overridden, then one is chosen arbitrarily to override the others.

Replace paragraph 20: [AI95-00217-06]

- The declaration of a library unit (including a library\_unit\_renaming\_declaration) is hidden from all visibility except at places that are within its declarative region or within the scope of a with\_clause that mentions it. For each declaration or renaming of a generic unit as a child of some parent generic package, there is a corresponding declaration nested immediately within each instance of the parent. Such a nested declaration is hidden from all visibility except at places that are within the scope of a with\_clause that mentions the child.

by:

- The declaration of a library unit (including a library\_unit\_renaming\_declaration) is hidden from all visibility at places outside its declarative region that are not within the scope of a nonlimited\_with\_clause that mentions it. The limited view of a library package is hidden from all visibility at places that are not within the scope of a limited\_with\_clause that mentions it; in addition, the limited view is hidden from all visibility within the declarative region of the package, as well as within the scope of any nonlimited\_with\_clause that mentions it. For each declaration or renaming of a generic unit as a child of some parent generic package, there is a corresponding declaration nested immediately within each instance of the parent. Such a nested declaration is hidden from all visibility except at places that are within the scope of a with\_clause that mentions the child.

Insert after paragraph 23: [AI95-00195-01]

- A declaration is also hidden from direct visibility where hidden from all visibility.

the new paragraph:

An attribute\_definition\_clause is *visible* at a place if a declaration at the point of the attribute\_definition\_clause would be immediately visible at the place.

**Replace paragraph 26: [AI95-00218-03; AI95-00251-01; AI95-00377-01]**

A non-overridable declaration is illegal if there is a homograph occurring immediately within the same declarative region that is visible at the place of the declaration, and is not hidden from all visibility by the non-overridable declaration. In addition, a type extension is illegal if somewhere within its immediate scope it has two visible components with the same name. Similarly, the `context_clause` for a subunit is illegal if it mentions (in a `with_clause`) some library unit, and there is a homograph of the library unit that is visible at the place of the corresponding stub, and the homograph and the mentioned library unit are both declared immediately within the same declarative region. These rules also apply to dispatching operations declared in the visible part of an instance of a generic unit. However, they do not apply to other overloadable declarations in an instance; such declarations may have type conformant profiles in the instance, so long as the corresponding declarations in the generic were not type conformant.

**by:**

A non-overridable declaration is illegal if there is a homograph occurring immediately within the same declarative region that is visible at the place of the declaration, and is not hidden from all visibility by the non-overridable declaration. In addition, a type extension is illegal if somewhere within its immediate scope it has two visible components with the same name. Similarly, the `context_clause` for a compilation unit is illegal if it mentions (in a `with_clause`) some library unit, and there is a homograph of the library unit that is visible at the place of the compilation unit, and the homograph and the mentioned library unit are both declared immediately within the same declarative region.

If two or more homographs are implicitly declared at the same place (and not overridden by a non-overridable declaration) then at most one shall be a non-null non-abstract subprogram. If all are null or abstract, then all of the null subprograms shall be fully conformant with one another. If all are abstract, then all of the subprograms shall be fully conformant with one another.

All of these rules also apply to dispatching operations declared in the visible part of an instance of a generic unit. However, they do not apply to other overloadable declarations in an instance; such declarations may have type conformant profiles in the instance, so long as the corresponding declarations in the generic were not type conformant.

If a `subprogram_declaration`, `abstract_subprogram_declaration`, `subprogram_body`, `subprogram_body_stub`, `subprogram_renaming_declaration`, or `generic_instantiation` of a subprogram has an `overriding_indicator`, then:

- the operation shall be a primitive operation for some type;
- if the `overriding_indicator` is **overriding**, then the operation shall override a homograph at the point of the declaration or body;
- if the `overriding_indicator` is **not overriding**, then the operation shall not override any homograph (at any point).

In addition to the places where Legality Rules normally apply, these rules also apply in the private part of an instance of a generic unit.

## 8.4 Use Clauses

**Replace paragraph 5: [AI95-00217-06]**

A `package_name` of a `use_package_clause` shall denote a package.

**by:**

A `package_name` of a `use_package_clause` shall denote a nonlimited view of a package.

**Insert after paragraph 7: [AI95-00217-06]**

For a `use_clause` immediately within a declarative region, the scope is the portion of the declarative region starting just after the `use_clause` and extending to the end of the declarative region. However, the scope of a

`use_clause` in the private part of a library unit does not include the visible part of any public descendant of that library unit.

**the new paragraph:**

A package is *named* in a `use_package_clause` if it is denoted by a `package_name` of that clause. A type is *named* in a `use_type_clause` if it is determined by a `subtype_mark` of that clause.

**Replace paragraph 8: [AI95-00217-06]**

For each package denoted by a `package_name` of a `use_package_clause` whose scope encloses a place, each declaration that occurs immediately within the declarative region of the package is *potentially use-visible* at this place if the declaration is visible at this place. For each type *T* or *TClass* determined by a `subtype_mark` of a `use_type_clause` whose scope encloses a place, the declaration of each primitive operator of type *T* is *potentially use-visible* at this place if its declaration is visible at this place.

**by:**

For each package named in a `use_package_clause` whose scope encloses a place, each declaration that occurs immediately within the declarative region of the package is *potentially use-visible* at this place if the declaration is visible at this place. For each type *T* or *TClass* named in a `use_type_clause` whose scope encloses a place, the declaration of each primitive operator of type *T* is *potentially use-visible* at this place if its declaration is visible at this place.

## 8.5.1 Object Renaming Declarations

**Replace paragraph 2: [AI95-00230-01]**

```
object_renaming_declaration ::=
    defining_identifier : subtype_mark renames object_name;
```

**by:**

```
object_renaming_declaration ::=
    defining_identifier : subtype_mark renames object_name;
| defining_identifier : access_definition renames object_name;
```

**Replace paragraph 3: [AI95-00230-01; AI95-00254-01]**

The type of the `object_name` shall resolve to the type determined by the `subtype_mark`.

**by:**

The type of the `object_name` shall resolve to the type determined by the `subtype_mark`, or in the case where the type is defined by an `access_definition`, to a specific anonymous access type which in the case of an access-to-object type shall have the same designated type as that of the `access_definition` and in the case of an access-to-subprogram type shall have a designated profile which is subtype conformant with that of the `access_definition`.

**Replace paragraph 4: [AI95-00231-01; AI95-00254-01]**

The renamed entity shall be an object.

**by:**

The renamed entity shall be an object. In the case where the type is defined by an `access_definition` of an access-to-object type, the renamed entity shall be of an access-to-constant type if and only if the `access_definition` defines an access-to-constant type.

**Replace paragraph 5: [AI95-00363-01]**

The renamed entity shall not be a subcomponent that depends on discriminants of a variable whose nominal subtype is unconstrained, unless this subtype is indefinite, or the variable is aliased. A `Slice` of an array shall not be renamed if this restriction disallows renaming of the array. In addition to the places where Legality Rules normally apply, these rules apply also in the private part of an instance of a generic unit. These rules

also apply for a renaming that appears in the body of a generic unit, with the additional requirement that even if the nominal subtype of the variable is indefinite, its type shall not be a descendant of an untagged generic formal derived type.

by:

The renamed entity shall not be a subcomponent that depends on discriminants of a variable whose nominal subtype is unconstrained, unless this subtype is indefinite, or the variable is constrained by its initial value. A slice of an array shall not be renamed if this restriction disallows renaming of the array. In addition to the places where Legality Rules normally apply, these rules apply also in the private part of an instance of a generic unit. These rules also apply for a renaming that appears in the body of a generic unit, with the additional requirement that even if the nominal subtype of the variable is indefinite, its type shall not be a descendant of an untagged generic formal derived type.

**Replace paragraph 6: [AI95-00230-01]**

An `object_renaming_declaration` declares a new view of the renamed object whose properties are identical to those of the renamed view. Thus, the properties of the renamed object are not affected by the `renaming_declaration`. In particular, its value and whether or not it is a constant are unaffected; similarly, the constraints that apply to an object are not affected by renaming (any constraint implied by the `subtype_mark` of the `object_renaming_declaration` is ignored).

by:

An `object_renaming_declaration` declares a new view of the renamed object whose properties are identical to those of the renamed view. Thus, the properties of the renamed object are not affected by the `renaming_declaration`. In particular, its value and whether or not it is a constant are unaffected; similarly, the constraints that apply to an object are not affected by renaming (any constraint implied by the `subtype_mark` or `access_definition` of the `object_renaming_declaration` is ignored).

### 8.5.3 Package Renaming Declarations

**Replace paragraph 3: [AI95-00217-06]**

The renamed entity shall be a package.

by:

The renamed entity shall be a nonlimited view of a package.

### 8.5.4 Subprogram Renaming Declarations

**Replace paragraph 2: [AI95-00218-03]**

`subprogram_renaming_declaration ::= subprogram_specification renames callable_entity_name;`

by:

`subprogram_renaming_declaration ::=`  
`[overriding_indicator]`  
`subprogram_specification renames callable_entity_name;`

**Insert after paragraph 5: [AI95-00228-01]**

The profile of a renaming-as-body shall be subtype-conformant with that of the renamed callable entity, and shall conform fully to that of the declaration it completes. If the renaming-as-body completes that declaration before the subprogram it declares is frozen, the profile shall be mode-conformant with that of the renamed callable entity and the subprogram it declares takes its convention from the renamed subprogram; otherwise, the profile shall be subtype-conformant with that of the renamed callable entity and the convention of the renamed subprogram shall not be intrinsic. A renaming-as-body is illegal if the declaration occurs before the subprogram whose declaration it completes is frozen, and the renaming renames the subprogram itself, through one or more subprogram renaming declarations, none of whose subprograms has been frozen.

the new paragraph:

If the *callable\_entity\_name* of a renaming denotes a subprogram which shall be overridden (see 3.9.3), then the renaming is illegal.

## 8.6 The Context of Overload Resolution

### Replace paragraph 17: [AI95-00382-01]

If a usage name appears within the declarative region of a *type\_declaration* and denotes that same *type\_declaration*, then it denotes the *current instance* of the type (rather than the type itself). The current instance of a type is the object or value of the type that is associated with the execution that evaluates the usage name.

by:

If a usage name appears within the declarative region of a *type\_declaration* and denotes that same *type\_declaration*, then it denotes the *current instance* of the type (rather than the type itself); the current instance of a type is the object or value of the type that is associated with the execution that evaluates the usage name. This rule does not apply if the usage name appears within the *subtype\_mark* of an *access\_definition* for an access-to-object type, or within the subtype of a parameter or result of an access-to-subprogram type.

### Replace paragraph 20: [AI95-00231-01]

The *expected type* for a given *expression*, *name*, or other construct determines, according to the *type resolution rules* given below, the types considered for the construct during overload resolution. The type resolution rules provide support for class-wide programming, universal numeric literals, dispatching operations, and anonymous access types:

by:

The *expected type* for a given *expression*, *name*, or other construct determines, according to the *type resolution rules* given below, the types considered for the construct during overload resolution. The type resolution rules provide support for class-wide programming, universal literals, dispatching operations, and anonymous access types:

### Replace paragraph 25: [AI95-00230-01; AI95-00231-01; AI95-00254-01]

- when *T* is an anonymous access type (see 3.10) with designated type *D*, to an access-to-variable type whose designated type is *D*'Class or is covered by *D*.

by:

- when *T* is a specific anonymous access-to-object type (see 3.10) with designated type *D*, to an access-to-object type whose designated type is *D*'Class or is covered by *D*, and that is access-to-constant only if *T* is access-to-constant; or
- when *T* is an anonymous access-to-subprogram type (see 3.10), to an access-to-subprogram type whose designated profile is subtype-conformant with that of *T*.

### Replace paragraph 27: [AI95-00332-01]

When the expected type for a construct is required to be a *single* type in a given class, the type expected for the construct shall be determinable solely from the context in which the construct appears, excluding the construct itself, but using the requirement that it be in the given class; the type of the construct is then this single expected type. Furthermore, the context shall not be one that expects any type in some class that contains types of the given class; in particular, the construct shall not be the operand of a *type\_conversion*.

by:

When a construct is one that requires that its expected type be a *single* type in a given class, the type of the construct shall be determinable solely from the context in which the construct appears, excluding the

construct itself, but using the requirement that it be in the given class. Furthermore, the context shall not be one that expects any type in some class that contains types of the given class; in particular, the construct shall not be the operand of a `type_conversion`.

## Section 9: Tasks and Synchronization

### 9.1 Task Units and Task Objects

**Replace paragraph 2: [AI95-00345-01]**

```
task_type_declaration ::=
    task type defining_identifier [known_discriminant_part] [is task_definition];
```

**by:**

```
task_type_declaration ::=
    task type defining_identifier [known_discriminant_part] [is
        [new interface_list with]
        task_definition];
```

**Delete paragraph 8: [AI95-00345-01]**

*Legality Rules*

A task declaration requires a completion, which shall be a `task_body`, and every `task_body` shall be the completion of some task declaration.

**Insert after paragraph 9.1: [AI95-00345-01]**

For a task declaration without a `task_definition`, a `task_definition` without `task_items` is assumed.

**the new paragraphs:**

If a `task_type_declaration` includes an `interface_list`, the task type is derived from each interface named in the `interface_list`.

For a `task_type_declaration`, if the first parameter of a primitive inherited subprogram is of the task type or an access parameter designating the task type, and there is an `entry_declaration` for a single entry with the same identifier within the `task_type_declaration`, having a profile that is type conformant with that of the inherited subprogram after omitting this first parameter, the inherited subprogram is said to be *implemented* by the conforming task entry.

*Legality Rules*

A task declaration requires a completion, which shall be a `task_body`, and every `task_body` shall be the completion of some task declaration.

Each `interface_subtype_mark` of an `interface_list` appearing within a `task_type_declaration` shall denote a limited interface type that is not a protected interface.

For each primitive subprogram inherited by the type declared by a `task_type_declaration`, at most one of the following shall apply:

- the inherited subprogram shall be overridden with a primitive subprogram of the task type, in which case the overriding subprogram shall be subtype conformant with the inherited subprogram and not abstract; or
- the inherited subprogram is implemented by a single entry of the task type; in which case its profile after omitting the first parameter shall be subtype conformant with that of the task entry.

If neither applies, the inherited subprogram shall be a null procedure.

**Replace paragraph 21: [AI95-00287-01]**

4 A task type is a limited type (see 7.5), and hence has neither an assignment operation nor predefined equality operators. If an application needs to store and exchange task identities, it can do so by defining an access type designating the corresponding task objects and by using access values for identification purposes. Assignment is available for such an access type as for any access type. Alternatively, if the implementation supports the Systems Programming Annex, the Identity attribute can be used for task identification (see C.7).

by:

4 A task type is a limited type (see 7.5), and hence has neither `assignment_statements` nor predefined equality operators. If an application needs to store and exchange task identities, it can do so by defining an access type designating the corresponding task objects and by using access values for identification purposes. Assignment is available for such an access type as for any access type. Alternatively, if the implementation supports the Systems Programming Annex, the Identity attribute can be used for task identification (see C.7).

### 9.3 Task Dependence - Termination of Tasks

Replace paragraph 2: [AI95-00162-01]

- If the task is created by the evaluation of an `allocator` for a given access type, it depends on each master that includes the elaboration of the declaration of the ultimate ancestor of the given access type.

by:

- If the task is created by the evaluation of an `allocator` for a given access type, it depends on each master that includes the elaboration of the declaration of the ultimate ancestor of the given access type other than the declaration itself.

Replace paragraph 3: [AI95-00162-01]

- If the task is created by the elaboration of an `object_declaration`, it depends on each master that includes this elaboration.

by:

- If the task is created by the elaboration of an `object_declaration`, it depends on each master that includes this elaboration other than the declaration itself.

### 9.4 Protected Units and Protected Objects

Replace paragraph 2: [AI95-00345-01]

`protected_type_declaration ::=`  
`protected type` `defining_identifier` [`known_discriminant_part`] [`is protected_definition`];

by:

`protected_type_declaration ::=`  
`protected type` `defining_identifier` [`known_discriminant_part`] [`is`  
[`new interface_list with`  
`protected_definition`];

Delete paragraph 10: [AI95-00345-01]

*Legality Rules*

A protected declaration requires a completion, which shall be a `protected_body`, and every `protected_body` shall be the completion of some protected declaration.

Replace paragraph 11: [AI95-00345-01]

A `protected_definition` defines a protected type and its first subtype. The list of `protected_operation_declarations` of a `protected_definition`, together with the `known_discriminant_part`, if any, is called the visible part of the protected unit. The optional list of `protected_element_declarations` after the reserved word **private** is called the private part of the protected unit.



by:

A `protected_definition` defines a protected type and its first subtype. The list of `protected_operation_declarations` of a `protected_definition`, together with the `known_discriminant_part`, if any, is called the visible part of the protected unit. The optional list of `protected_element_declarations` after the reserved word **private** is called the private part of the protected unit. If a `protected_type_declaration` includes an `interface_list`, the protected type is derived from each interface named in the `interface_list`.

For a `protected_type_declaration`, the first parameter of a primitive inherited subprogram is of the protected type or an access parameter designating the protected type, and there is a `protected_operation_declaration` for a protected subprogram or single entry with the same identifier within the `protected_type_declaration`, having a profile that is type conformant with that of the inherited subprogram after omitting this first parameter, the inherited subprogram is said to be *implemented* by the conforming protected subprogram or entry.

#### *Legality Rules*

A protected declaration requires a completion, which shall be a `protected_body`, and every `protected_body` shall be the completion of some protected declaration.

Each `interface_subtype_mark` of an `interface_list` appearing within a `protected_type_declaration` shall denote a limited interface type that is not a task interface.

For each primitive subprogram inherited by the type declared by a `protected_type_declaration`, at most one of the following shall apply:

- the inherited subprogram is overridden with a primitive subprogram of the protected type, in which case the overriding subprogram shall be subtype conformant with the inherited subprogram and not abstract; or
- the inherited subprogram is implemented by a protected subprogram or single entry of the protected type, in which case its profile after omitting the first parameter shall be subtype conformant with that of the protected subprogram or entry.

If neither applies, the inherited subprogram is a null procedure.

If an inherited subprogram is implemented by a protected procedure or an entry, then the first parameter of the inherited subprogram shall be of mode **out** or **in out**, or an access-to-variable parameter.

#### **Insert after paragraph 20: [AI95-00280-01]**

As the first step of the *finalization* of a protected object, each call remaining on any entry queue of the object is removed from its queue and `Program_Error` is raised at the place of the corresponding `entry_call_statement`.

#### **the new paragraph:**

##### *Bounded (Run-Time) Errors*

It is a bounded error to call an entry or subprogram of a protected object after that object is finalized. If the error is detected, `Program_Error` is raised. Otherwise, the call proceeds normally, which may leave a task queued forever.

#### **Replace paragraph 23: [AI95-00287-01]**

15 A protected type is a limited type (see 7.5), and hence has neither an assignment operation nor predefined equality operators.

by:

15 A protected type is a limited type (see 7.5), and hence has neither `assignment_statements` nor predefined equality operators.

## 9.6 Delay Statements, Duration, and Time

Replace paragraph 11: [AI95-00351-01]

```
subtype Year_Number is Integer range 1901 .. 2099;
subtype Month_Number is Integer range 1 .. 12;
subtype Day_Number is Integer range 1 .. 31;
subtype Day_Duration is Duration range 0.0 .. 86_400.0;
```

by:

```
subtype Year_Number is Integer range 1901 .. 2399;
subtype Month_Number is Integer range 1 .. 12;
subtype Day_Number is Integer range 1 .. 31;
subtype Day_Duration is Duration range 0.0 .. 86_400.0;
```

Replace paragraph 24: [AI95-00351-01]

The functions Year, Month, Day, and Seconds return the corresponding values for a given value of the type Time, as appropriate to an implementation-defined timezone; the procedure Split returns all four corresponding values. Conversely, the function Time\_Of combines a year number, a month number, a day number, and a duration, into a value of type Time. The operators "+" and "-" for addition and subtraction of times and durations, and the relational operators for times, have the conventional meaning.

by:

The functions Year, Month, Day, and Seconds return the corresponding values for a given value of the type Time, as appropriate to an implementation-defined time zone; the procedure Split returns all four corresponding values. Conversely, the function Time\_Of combines a year number, a month number, a day number, and a duration, into a value of type Time. The operators "+" and "-" for addition and subtraction of times and durations, and the relational operators for times, have the conventional meaning.

### 9.6.1 Formatting, Time Zones, and other operations for Time

Insert new clause: [AI95-00351-01]

*Static Semantics*

The following language-defined library packages exist:

```
package Ada.Calendar.Time_Zones is

    -- Time zone manipulation:

    type Time_Offset is range -1440 .. 1440;

    Unknown_Zone_Error : exception;

    function UTC_Time_Offset (Date : Time := Clock) return Time_Offset;

end Ada.Calendar.Time_Zones;

package Ada.Calendar.Arithmetic is

    -- Arithmetic on days:

    type Day_Count is range
        -366*(1+Year_Number'Last - Year_Number'First)
        ..
        366*(1+Year_Number'Last - Year_Number'First);

    subtype Leap_Seconds_Count is Integer range -999 .. 999;

    procedure Difference (Left, Right : in Time;
                        Days : out Day_Count;
```

```

        Seconds : out Duration;
        Leap_Seconds : out Leap_Seconds_Count);

function "+" (Left : Time; Right : Day_Count) return Time;

function "+" (Left : Day_Count; Right : Time) return Time;

function "-" (Left : Time; Right : Day_Count) return Time;

function "-" (Left, Right : Time) return Day_Count;

end Ada.Calendar.Arithmetic;

with Ada.Calendar.Time_Zones;
package Ada.Calendar.Formatting is

    -- Day of the week:

    type Day_Name is (Monday, Tuesday, Wednesday, Thursday,
        Friday, Saturday, Sunday);

    function Day_of_Week (Date : Time) return Day_Name;

    -- Hours:Minutes:Seconds access:

    subtype Hour_Number          is Natural range 0 .. 23;
    subtype Minute_Number       is Natural range 0 .. 59;
    subtype Second_Number       is Natural range 0 .. 59;
    subtype Second_Duration     is Day_Duration range 0.0 .. 1.0;

    function Hour                (Date : Time;
        Time_Zone : Time_Zones.Time_Offset := 0)
        return Hour_Number;

    function Minute              (Date : Time;
        Time_Zone : Time_Zones.Time_Offset := 0)
        return Minute_Number;

    function Second              (Date : Time;
        Time_Zone : Time_Zones.Time_Offset := 0)
        return Second_Number;

    function Sub_Second          (Date : Time;
        Time_Zone : Time_Zones.Time_Offset := 0)
        return Second_Duration;

    function Seconds_Of (Hour    : Hour_Number;
        Minute : Minute_Number;
        Second  : Second_Number := 0;
        Sub_Second : Second_Duration := 0.0)
        return Day_Duration;

    procedure Split (Seconds    : in Day_Duration;
        Hour      : out Hour_Number;
        Minute    : out Minute_Number;
        Second    : out Second_Number;
        Sub_Second : out Second_Duration);

    procedure Split (Date      : in Time;
        Time_Zone : in Time_Zones.Time_Offset := 0;
        Year      : out Year_Number;
        Month     : out Month_Number;
        Day       : out Day_Number;
        Hour      : out Hour_Number;
        Minute    : out Minute_Number;
        Second    : out Second_Number;

```

```

        Sub_Second : out Second_Duration);

function Time_Of (Year      : Year_Number;
                  Month     : Month_Number;
                  Day       : Day_Number;
                  Hour      : Hour_Number;
                  Minute    : Minute_Number;
                  Second     : Second_Number;
                  Sub_Second : Second_Duration := 0.0;
                  Leap_Second: Boolean := False;
                  Time_Zone  : Time_Zones.Time_Offset := 0)
    return Time;

function Time_Of (Year      : Year_Number;
                  Month     : Month_Number;
                  Day       : Day_Number;
                  Seconds    : Day_Duration;
                  Leap_Second: Boolean := False;
                  Time_Zone  : Time_Zones.Time_Offset := 0)
    return Time;

procedure Split (Date      : in Time;
                 Time_Zone  : in Time_Zones.Time_Offset := 0;
                 Year      : out Year_Number;
                 Month     : out Month_Number;
                 Day       : out Day_Number;
                 Hour      : out Hour_Number;
                 Minute    : out Minute_Number;
                 Second     : out Second_Number;
                 Sub_Second : out Second_Duration;
                 Leap_Second: out Boolean);

procedure Split (Date      : in Time;
                 Time_Zone  : in Time_Zones.Time_Offset := 0;
                 Year      : out Year_Number;
                 Month     : out Month_Number;
                 Day       : out Day_Number;
                 Seconds    : out Day_Duration;
                 Leap_Second: out Boolean);

-- Simple image and value:
function Image (Date : Time;
               Include_Time_Fraction : Boolean := False;
               Time_Zone : Time_Zones.Time_Offset := 0) return String;

function Value (Date : String;
               Time_Zone : Time_Zones.Time_Offset := 0) return Time;

function Image (Elapsed_Time : Duration;
               Include_Time_Fraction : Boolean := False) return String;

function Value (Elapsed_Time : String) return Duration;

end Ada.Calendar.Formatting;

```

Type Time\_Offset represents the number of minutes difference between the implementation-defined time zone used by Ada.Calendar and another time zone.

```
function UTC_Time_Offset (Date : Time := Clock) return Time_Offset;
```

Returns, as a number of minutes, the difference between the implementation-defined time zone of Calendar, and UTC time, at the time Date. If the time zone of the Calendar implementation is unknown, then Unknown\_Zone\_Error is raised.

```
procedure Difference (Left, Right : in Time;
                    Days : out Day_Count;
                    Seconds : out Duration;
```

```
Leap_Seconds : out Leap_Seconds_Count);
```

Returns the difference between Left and Right. Days is the number of days of difference, Seconds is the remainder seconds of difference, and Leap\_Seconds is the number of leap seconds. If Left < Right, then Seconds <= 0.0, Days <= 0, and Leap\_Seconds <= 0. Otherwise, all values are non-negative. For the returned values, if Days = 0, then Seconds + Duration(Leap\_Seconds) = Calendar."-" (Left, Right).

```
function "+" (Left : Time; Right : Day_Count) return Time;
function "+" (Left : Day_Count; Right : Time) return Time;
```

Adds a number of days to a time value. Time\_Error is raised if the result is not representable as a value of type Time.

```
function "-" (Left : Time; Right : Day_Count) return Time;
```

Subtracts a number of days from a time value. Time\_Error is raised if the result is not representable as a value of type Time.

```
function "-" (Left, Right : Time) return Day_Count;
```

Subtracts two time values, and returns the number of days between them. This is the same value that Difference would return in Days.

```
function Day_of_Week (Date : Time) return Day_Name;
```

Returns the day of the week for Time. This is based on the Year, Month, and Day values of Time.

```
function Hour (Date : Time;
               Time_Zone : Time_Zones.Time_Offset := 0)
  return Hour_Number;
```

Returns the hour for Date, as appropriate for the specified time zone offset.

```
function Minute (Date : Time;
                 Time_Zone : Time_Zones.Time_Offset := 0)
  return Minute_Number;
```

Returns the minute within the hour for Date, as appropriate for the specified time zone offset.

```
function Second (Date : Time;
                 Time_Zone : Time_Zones.Time_Offset := 0)
  return Second_Number;
```

Returns the second within the hour and minute for Date, as appropriate for the specified time zone offset.

```
function Sub_Second (Date : Time;
                     Time_Zone : Time_Zones.Time_Offset := 0)
  return Second_Duration;
```

Returns the fraction of second for Date (this has the same accuracy as Day\_Duration), as appropriate for the specified time zone offset.

```
function Seconds_Of (Hour : Hour_Number;
                    Minute : Minute_Number;
                    Second : Second_Number := 0;
                    Sub_Second : Second_Duration := 0.0)
  return Day_Duration;
```

Returns a Day\_Duration value for the Hour:Minute:Second.Sub\_Second. This value can be used in Calendar.Time\_Of as well as the argument to Calendar."+" and Calendar."-".

```
procedure Split (Seconds : in Day_Duration;
                Hour : out Hour_Number;
                Minute : out Minute_Number;
                Second : out Second_Number;
                Sub_Second : out Second_Duration);
```

Splits Seconds into Hour:Minute:Second.Sub\_Second.

```

procedure Split (Date      : in Time;
                  Time_Zone : in Time_Zones.Time_Offset := 0;
                  Year       : out Year_Number;
                  Month      : out Month_Number;
                  Day        : out Day_Number;
                  Hour       : out Hour_Number;
                  Minute     : out Minute_Number;
                  Second     : out Second_Number;
                  Sub_Second : out Second_Duration);

```

Splits Date into its constituent parts (Year, Month, Day, Hour, Minute, Second, Sub\_Second), relative to the specified time zone offset.

```

function Time_Of (Year      : Year_Number;
                  Month      : Month_Number;
                  Day        : Day_Number;
                  Hour       : Hour_Number;
                  Minute     : Minute_Number;
                  Second     : Second_Number;
                  Sub_Second : Second_Duration := 0.0;
                  Leap_Second: Boolean := False;
                  Time_Zone  : Time_Zones.Time_Offset := 0)
return Time;

```

Returns a Time built from the date and time values, relative to the specified time zone offset. Time\_Error is raised if Leap\_Second is True, and Hour, Minute, and Second are not appropriate for a Leap\_Second.

```

function Time_Of (Year      : Year_Number;
                  Month      : Month_Number;
                  Day        : Day_Number;
                  Seconds    : Day_Duration;
                  Leap_Second: Boolean := False;
                  Time_Zone  : Time_Zones.Time_Offset := 0)
return Time;

```

Returns a Time built from the date and time values, relative to the specified time zone offset. Time\_Error is raised if Leap\_Second is True, and Seconds is not appropriate for a Leap\_Second.

```

procedure Split (Date      : in Time;
                  Time_Zone : in Time_Zones.Time_Offset := 0;
                  Year       : out Year_Number;
                  Month      : out Month_Number;
                  Day        : out Day_Number;
                  Hour       : out Hour_Number;
                  Minute     : out Minute_Number;
                  Second     : out Second_Number;
                  Sub_Second : out Second_Duration;
                  Leap_Second: out Boolean);

```

Split Date into its constituent parts (Year, Month, Day, Hour, Minute, Second, Sub\_Second), relative to the specified time zone offset. Leap\_Second is True if Date identifies a leap second.

```

procedure Split (Date      : in Time;
                  Time_Zone : in Time_Zones.Time_Offset := 0;
                  Year       : out Year_Number;
                  Month      : out Month_Number;
                  Day        : out Day_Number;
                  Seconds    : out Day_Duration;
                  Leap_Second: out Boolean);

```

Split Date into its constituent parts (Year, Month, Day, Seconds), relative to the specified time zone offset. Leap\_Second is True if Date identifies a leap second.

```

function Image (Date : Time;
                Include_Time_Fraction : Boolean := False;
                Time_Zone : Time_Zones.Time_Offset := 0) return String;

```

Returns a string form of the Date relative to the given Time\_Zone. The format is "Year-Month-Day Hour:Minute:Second", where each value other than Year is a 2-digit form of the value of the functions defined in Calendar and Calendar.Formatting, including a leading '0', if needed. Year is a 4-digit value. If Include\_Time\_Fraction is True, Sub\_Seconds\*100 is suffixed to the string as a 2-digit value following a '.'.

```
function Value (Date : String)
    Time_Zone : Time_Zones.Time_Offset := 0) return Time;
```

Returns a Time value for the image given as Date, relative to the given time zone. Constraint\_Error is raised if the string is not formatted as described for Image, or the function cannot interpret the given string as a Time value.

```
function Image (Elapsed_Time : Duration;
    Include_Time_Fraction : Boolean := False) return String;
```

Returns a string form of the Elapsed\_Time. The format is "Hour:Minute:Second", where each value is a 2-digit form of the value, including a leading '0', if needed. If Include\_Time\_Fraction is True, Sub\_Seconds\*100 is suffixed to the string as a 2-digit value following a '.'. If Elapsed\_Time < 0.0, the result is Image (**abs** Elapsed\_Time, Include\_Time\_Fraction) prefixed with "-". If **abs** Elapsed\_Time represents 100 hours or more, the result is implementation-defined.

```
function Value (Elapsed_Time : String) return Duration;
```

Returns a Duration value for the image given as Elapsed\_Time. Constraint\_Error is raised if the string is not formatted as described for Image, or the function cannot interpret the given string as a Duration value.

#### *Implementation Advice*

An implementation should support leap seconds if the target system supports them. If leap seconds are not supported, Difference should return zero for Leap\_Seconds, Split should return False for Leap\_Second, and Time\_Of should raise Time\_Error if Leap\_Second is True.

#### NOTES

36 The time in the time zone known as Greenwich Mean Time (GMT) is generally equivalent to UTC time.

37 The implementation-defined time zone of package Calendar may, but need not, be the local time zone. UTC\_Time\_Offset always returns the difference relative to the implementation-defined time zone of package Calendar. If UTC\_Time\_Offset does not raise Unknown\_Zone\_Error, UTC time can be safely calculated (within the accuracy of the underlying time-base).

38 Calling Split on the results of subtracting Duration(UTC\_Time\_Offset\*60) from Clock provides the components (hours, minutes, and so on) of the UTC time. In the United States, for example, UTC\_Time\_Offset will generally be negative.

## 9.7.2 Timed Entry Calls

### Replace paragraph 1: [AI95-00345-01]

A timed\_entry\_call issues an entry call that is cancelled if the call (or a requeue-with-abort of the call) is not selected before the expiration time is reached.

**by:**

A timed\_entry\_call issues an entry call that is cancelled if the call (or a requeue-with-abort of the call) is not selected before the expiration time is reached. A procedure call may appear rather than an entry call for cases where the procedure might be implemented by an entry.

### Replace paragraph 3: [AI95-00345-01]

```
entry_call_alternative ::=
    entry_call_statement [sequence_of_statements]
```

by:

```
entry_call_alternative ::=
    procedure_or_entry_call [sequence_of_statements]

procedure_or_entry_call ::=
    procedure_call_statement | entry_call_statement
```

*Legality Rules*

If a `procedure_call_statement` is used for a `procedure_or_entry_call`, the *procedure\_name* or *procedure\_prefix* of the `procedure_call_statement` shall denote an entry renamed as a procedure, a formal subprogram, or (a view of) a primitive subprogram of a limited interface whose first parameter is a controlling parameter (see 3.9.2).

*Static Semantics*

If a `procedure_call_statement` is used for a `procedure_or_entry_call`, and the procedure is implemented by an entry, then the *procedure\_name*, or *procedure\_prefix* and possibly the first parameter of the `procedure_call_statement`, determine the target object of the call and the entry to be called.

**Replace paragraph 4: [AI95-00345-01]**

For the execution of a `timed_entry_call`, the *entry\_name* and the actual parameters are evaluated, as for a simple entry call (see 9.5.3). The expiration time (see 9.6) for the call is determined by evaluating the *delay\_expression* of the `delay_alternative`; the entry call is then issued.

by:

For the execution of a `timed_entry_call`, the *entry\_name*, *procedure\_name*, or *procedure\_prefix*, and any actual parameters are evaluated, as for a simple entry call (see 9.5.3) or procedure call (see 6.4). The expiration time (see 9.6) for the call is determined by evaluating the *delay\_expression* of the `delay_alternative`. If the call is an entry call or a call on a procedure implemented by an entry, the entry call is then issued. Otherwise, the call proceeds as described in 6.4 for a procedure call, followed by the *sequence\_of\_statements* of the `entry_call_alternative`, and the `delay_alternative` *sequence\_of\_statements* is ignored.

## 9.7.4 Asynchronous Transfer of Control

**Replace paragraph 4: [AI95-00345-01]**

```
triggering_statement ::= entry_call_statement | delay_statement
```

by:

```
triggering_statement ::= procedure_or_entry_call | delay_statement
```

**Replace paragraph 6: [AI95-00345-01]**

For the execution of an `asynchronous_select` whose *triggering\_statement* is an `entry_call_statement`, the *entry\_name* and actual parameters are evaluated as for a simple entry call (see 9.5.3), and the entry call is issued. If the entry call is queued (or requeued-with-abort), then the *abortable\_part* is executed. If the entry call is selected immediately, and never requeued-with-abort, then the *abortable\_part* is never started.

by:

For the execution of an `asynchronous_select` whose *triggering\_statement* is a `procedure_or_entry_call`, the *entry\_name*, *procedure\_name*, or *procedure\_prefix*, and actual parameters are evaluated as for a simple entry call (see 9.5.3) or procedure call (see 6.4). If the call is an entry call or a call on a procedure implemented by an entry, the entry call is issued. If the entry call is queued (or requeued-with-abort), then the *abortable\_part* is executed. If the entry call is selected immediately, and never requeued-with-abort, then the *abortable\_part* is never started. If the call is on a procedure that is not implemented by an entry, the call proceeds as described in 6.4, followed by the *sequence\_of\_statements* of the *triggering\_alternative*, and the *abortable\_part* is never started.



## 9.8 Abort of a Task - Abort of a Sequence of Statements

Replace paragraph 3: [AI95-00345-01]

Each *task\_name* is expected to be of any task type; they need not all be of the same task type.

by:

Each *task\_name* is expected to be of any task type or task interface type; they need not all be of the same type.

## 9.9 Task and Entry Attributes

Replace paragraph 1: [AI95-00345-01]

For a prefix T that is of a task type (after any implicit dereference), the following attributes are defined:

by:

For a prefix T that is of a task type or task interface type (after any implicit dereference), the following attributes are defined:

## Section 10: Program Structure and Compilation Issues

### 10.1.1 Compilation Units - Library Units

**Insert after paragraph 12: [AI95-00217-06; AI95-00326-01]**

A `library_unit_declaration` or a `library_unit_renaming_declaration` is *private* if the declaration is immediately preceded by the reserved word **private**; it is otherwise *public*. A library unit is private or public according to its declaration. The *public descendants* of a library unit are the library unit itself, and the public descendants of its public children. Its other descendants are *private descendants*.

**the new paragraphs:**

For each library `package_declaration` in the environment, there is an implicit declaration of a *limited view* of that library package. The limited view of a package contains:

- For each nested `package_declaration`, a declaration of the limited view of that package, with the same `defining_program_unit_name`.
- For each `type_declaration` in the visible part, an incomplete view of the type is declared. If the `type_declaration` is tagged, then the view is a tagged incomplete view.

The limited view of a library `package_declaration` is private if that library `package_declaration` is immediately preceded by the reserved word **private**.

There is no syntax for declaring limited views of packages, because they are always implicit. The implicit declaration of a limited view of a package is *not* the declaration of a library unit (the library `package_declaration` is); nonetheless, it is a `library_item`.

A library `package_declaration` is the completion of the declaration of its limited view.

**Replace paragraph 19: [AI95-00331-01]**

For each declaration or renaming of a generic unit as a child of some parent generic package, there is a corresponding declaration nested immediately within each instance of the parent. This declaration is visible only within the scope of a `with_clause` that mentions the child generic unit.

**by:**

For each child *C* of some parent generic package *P*, there is a corresponding declaration *C* nested immediately within each instance of *P*. For the purposes of this rule, if a child *C* itself has a child *D*, each corresponding declaration for *C* has a corresponding child *D*. The corresponding declaration for a child within an instance is visible only within the scope of a `with_clause` that mentions the (original) child generic unit.

**Replace paragraph 26: [AI95-00217-06]**

A `library_item` depends semantically upon its parent declaration. A subunit depends semantically upon its parent body. A `library_unit_body` depends semantically upon the corresponding `library_unit_declaration`, if any. A compilation unit depends semantically upon each `library_item` mentioned in a `with_clause` of the compilation unit. In addition, if a given compilation unit contains an `attribute_reference` of a type defined in another compilation unit, then the given compilation unit depends semantically upon the other compilation unit. The semantic dependence relationship is transitive.

**by:**

A `library_item` depends semantically upon its parent declaration. A subunit depends semantically upon its parent body. A `library_unit_body` depends semantically upon the corresponding `library_unit_declaration`, if any. The implicit declaration of the limited view of a library package depends semantically upon the implicit declaration of the limited view of its parent. The declaration of a library package depends semantically upon the implicit declaration of its limited view. A compilation unit depends semantically upon each `library_item` mentioned in a `with_clause` of the compilation unit. In addition, if a given compilation

unit contains an **attribute\_reference** of a type defined in another compilation unit, then the given compilation unit depends semantically upon the other compilation unit. The semantic dependence relationship is transitive.

*Dynamic Semantics*

The elaboration of the limited view of a package has no effect.

### 10.1.2 Context Clauses - With Clauses

**Replace paragraph 4: [AI95-00217-06; AI95-00326-01]**

`with_clause ::= with library_unit_name {, library_unit_name};`

**by:**

`with_clause ::= limited_with_clause | nonlimited_with_clause`  
`limited_with_clause ::= limited [private] with library_unit_name {, library_unit_name};`  
`nonlimited_with_clause ::= [private] with library_unit_name {, library_unit_name};`

**Replace paragraph 6: [AI95-00217-06]**

A *library\_item* is *mentioned* in a *with\_clause* if it is denoted by a *library\_unit\_name* or a prefix in the *with\_clause*.

**by:**

A *library\_item* is *named* in a *with\_clause* if it is denoted by a *library\_unit\_name* in the *with\_clause*. A *library\_item* is *mentioned* in a *with\_clause* if it is named in the *with\_clause* or if it is denoted by a prefix in the *with\_clause*.

**Replace paragraph 8: [AI95-00217-06; AI95-00220-01; AI95-00262-01]**

If a *with\_clause* of a given *compilation\_unit* mentions a private child of some library unit, then the given *compilation\_unit* shall be either the declaration of a private descendant of that library unit or the body or a subunit of a (public or private) descendant of that library unit.

**by:**

If a *with\_clause* of a given *compilation\_unit* mentions a private child of some library unit, then the given *compilation\_unit* shall be one of:

- the declaration, body, or subunit of a private descendant of that library unit;
- the body or subunit of a public descendant of that library unit, but not a subprogram body acting as a subprogram declaration (see 10.1.4); or
- the declaration of a public descendant of that library unit, and the *with\_clause* shall include the reserved word **private**.

A name denoting a library item that is visible only due to being mentioned in *with\_clauses* that include the reserved word **private** shall appear only within

- a private part,
- a body, but not within the *subprogram\_specification* of a library subprogram body,
- a private descendant of the unit on which one of these *with\_clauses* appear, or
- a pragma within a context clause.

A *library\_item* mentioned in a *limited\_with\_clause* shall be a *package\_declaration*[, not a *subprogram\_declaration*, *generic\_declaration*, *generic\_instantiation*, or *package\_renaming\_declaration*].

A *limited\_with\_clause* shall not appear on a *library\_unit\_body* or subunit.

A `limited_with_clause` which names a `library_item` shall not appear:

- in the same `context_clause` as a `nonlimited_with_clause` which mentions the same `library_item`; or
- in the same `context_clause` as a `use_clause` which names an entity declared within the declarative region of the `library_item`; or
- in the scope of a `nonlimited_with_clause` which mentions the same `library_item`; or
- in the scope of a `use_clause` which names an entity declared within the declarative region of the `library_item`.

### 10.1.3 Subunits of Compilation Units

**Replace paragraph 3: [AI95-00218-03]**

`subprogram_body_stub ::= subprogram_specification is separate;`

**by:**

`subprogram_body_stub ::=`  
`[overriding_indicator]`  
`subprogram_specification is separate;`

**Replace paragraph 8: [AI95-00243-01]**

The *parent body* of a subunit is the body of the program unit denoted by its `parent_unit_name`. The term *subunit* is used to refer to a subunit and also to the `proper_body` of a subunit.

**by:**

The *parent body* of a subunit is the body of the program unit denoted by its `parent_unit_name`. The term *subunit* is used to refer to a subunit and also to the `proper_body` of a subunit. A *subunit of a program unit* includes subunits declared directly in the program unit as well as any subunits declared in those subunits (recursively).

### 10.1.4 The Compilation Process

**Replace paragraph 3: [AI95-00217-06]**

The mechanisms for creating an environment and for adding and replacing compilation units within an environment are implementation defined.

**by:**

The mechanisms for creating an environment and for adding and replacing compilation units within an environment are implementation defined. The mechanisms for adding a unit mentioned in a `limited_with_clause` to an environment are implementation defined.

**Replace paragraph 6: [AI95-00217-06]**

The implementation may require that a compilation unit be legal before inserting it into the environment.

**by:**

The implementation may require that a compilation unit be legal before it can be mentioned in a `limited_with_clause` or it can be inserted into the environment.

**Replace paragraph 7: [AI95-00214-01]**

When a compilation unit that declares or renames a library unit is added to the environment, the implementation may remove from the environment any preexisting `library_item` with the same `defining_program_unit_name`. When a compilation unit that is a subunit or the body of a library unit is

added to the environment, the implementation may remove from the environment any preexisting version of the same compilation unit. When a given compilation unit is removed from the environment, the implementation may also remove any compilation unit that depends semantically upon the given one. If the given compilation unit contains the body of a subprogram to which a **pragma Inline** applies, the implementation may also remove any compilation unit containing a call to that subprogram.

**by:**

When a compilation unit that declares or renames a library unit is added to the environment, the implementation may remove from the environment any preexisting **library\_item** or **subunit** with the same full expanded name. When a compilation unit that is a subunit or the body of a library unit is added to the environment, the implementation may remove from the environment any preexisting version of the same compilation unit. When a compilation unit that contains a **body\_stub** is added to the environment, the implementation may remove any preexisting **library\_item** or **subunit** with the same full expanded name as the **body\_stub**. When a given compilation unit is removed from the environment, the implementation may also remove any compilation unit that depends semantically upon the given one. If the given compilation unit contains the body of a subprogram to which a **pragma Inline** applies, the implementation may also remove any compilation unit containing a call to that subprogram.

### 10.1.5 Pragmas and Program Units

**Replace paragraph 9: [AI95-00212-01]**

An implementation may place restrictions on configuration pragmas, so long as it allows them when the environment contains no **library\_items** other than those of the predefined environment.

**by:**

An implementation may require that configuration pragmas that select partition-wide or system-wide options be compiled when the environment contains no **library\_items** other than those of the predefined environment. In this case, the implementation shall still accept configuration pragmas in individual compilations that confirm the initially selected partition-wide or system-wide options.

### 10.1.6 Environment-Level Visibility Rules

**Replace paragraph 2: [AI95-00312-01]**

Within the **parent\_unit\_name** at the beginning of a **library\_item**, and within a **with\_clause**, the only declarations that are visible are those that are **library\_items** of the environment, and the only declarations that are directly visible are those that are root **library\_items** of the environment. {notwithstanding} Notwithstanding the rules of 4.1.3, an expanded name in a **with\_clause** may consist of a **prefix** that denotes a generic package and a **selector\_name** that denotes a child of that generic package. [(The child is necessarily a generic unit; see 10.1.1.)]

**by:**

Within the **parent\_unit\_name** at the beginning of a **library\_item**, and within a **with\_clause**, the only declarations that are visible are those that are **library\_items** of the environment, and the only declarations that are directly visible are those that are root **library\_items** of the environment.

**Insert after paragraph 5: [AI95-00312-01]**

Within a **pragma** that appears at the place of a compilation unit, the immediately preceding **library\_item** and each of its ancestors is visible. The ancestor root **library\_item** is directly visible.

**the new paragraph:**

Notwithstanding the rules of 4.1.3, an expanded name in a **with\_clause**, a **pragma** in a **context\_clause**, or a **pragma** that appears at the place of a compilation unit may consist of a **prefix** that denotes a generic package and a **selector\_name** that denotes a child of that generic package. (The child is necessarily a generic unit; see 10.1.1.)

## 10.2 Program Execution

### Replace paragraph 6: [AI95-00217-06]

- If a compilation unit with stubs is needed, then so are any corresponding subunits.

by:

- If a compilation unit with stubs is needed, then so are any corresponding subunits;
- If the limited view of a unit is needed, then the full view of the unit is needed.

### Replace paragraph 9: [AI95-00256-01]

The order of elaboration of library units is determined primarily by the *elaboration dependences*. There is an elaboration dependence of a given `library_item` upon another if the given `library_item` or any of its subunits depends semantically on the other `library_item`. In addition, if a given `library_item` or any of its subunits has a pragma `Elaborate` or `Elaborate_All` that mentions another library unit, then there is an elaboration dependence of the given `library_item` upon the body of the other library unit, and, for `Elaborate_All` only, upon each `library_item` needed by the declaration of the other library unit.

by:

The order of elaboration of library units is determined primarily by the *elaboration dependences*. There is an elaboration dependence of a given `library_item` upon another if the given `library_item` or any of its subunits depends semantically on the other `library_item`. In addition, if a given `library_item` or any of its subunits has a pragma `Elaborate` or `Elaborate_All` that names another library unit, then there is an elaboration dependence of the given `library_item` upon the body of the other library unit, and, for `Elaborate_All` only, upon each `library_item` needed by the declaration of the other library unit.

### 10.2.1 Elaboration Control

#### Insert after paragraph 4: [AI95-00161-01]

A pragma `Preelaborate` is a library unit pragma.

the new paragraphs:

The form of pragma `Preelaborable_Initialization` is as follows:

```
pragma Preelaborable_Initialization (direct_name);
```

#### Replace paragraph 9: [AI95-00161-01]

- The creation of a default-initialized object (including a component) of a descendant of a private type, private extension, controlled type, task type, or protected type with `entry_declarations`; similarly the evaluation of an `extension_aggregate` with an ancestor `subtype_mark` denoting a subtype of such a type.

by:

- The creation of an object (including a component) of a type which does not have preelaborable initialization. Similarly the evaluation of an `extension_aggregate` with an ancestor `subtype_mark` denoting a subtype of such a type.

#### Insert after paragraph 11: [AI95-00161-01]

If a pragma `Preelaborate` (or pragma `Pure` -- see below) applies to a library unit, then it is *preelaborated*. If a library unit is preelaborated, then its declaration, if any, and body, if any, are elaborated prior to all non-preelaborated `library_items` of the partition. The declaration and body of a preelaborated library unit, and all subunits that are elaborated as part of elaborating the library unit, shall be preelaborable. In addition to the places where Legality Rules normally apply (see 12.3), this rule applies also in the private part of an instance

of a generic unit. In addition, all compilation units of a preelaborated library unit shall depend semantically only on compilation units of other preelaborated library units.

**the new paragraphs:**

The following rules specify which entities have preelaborable initialization:

- The partial view of a private type or private extension, a protected type without `entry_declarations`, a generic formal private type, or a generic formal derived type, have preelaborable initialization if and only if the `pragma Preelaborable_Initialization` has been applied to them.
- A component (including a discriminant) of a record or protected type has preelaborable initialization if its declaration includes a `default_expression` whose execution does not perform any actions prohibited in preelaborable constructs as described above, or if its declaration does not include a default expression and its type has preelaborable initialization.
- A derived type has preelaborable initialization if its parent type has preelaborable initialization and (in the case of a derived record or protected type) if the non-inherited components all have preelaborable initialization. Moreover, a user-defined controlled type with an overriding `Initialize` procedure does not have preelaborable initialization.
- A view of a type has preelaborable initialization if it is an elementary type, an array type whose component type has preelaborable initialization, or a record type whose components all have preelaborable initialization.

A `pragma Preelaborable_Initialization` specifies that a type has preelaborable initialization. This pragma shall appear in the visible part of a package or generic package.

If the pragma appears in the first list of `declarative_items` of a `package_specification`, then the `direct_name` shall denote the first subtype of a private type, private extension, or protected type without `entry_declarations`, and the type shall be declared within the same package as the pragma. If the pragma is applied to a private type or a private extension, the full view of the type shall have preelaborable initialization. If the pragma is applied to a protected type, each component of the protected type shall have preelaborable initialization. In addition to the places where Legality Rules normally apply, these rules apply also in the private part of an instance of a generic unit.

If the pragma appears in a `generic_formal_part`, then the `direct_name` shall denote a generic formal private type or a generic formal derived type declared in the same `generic_formal_part` as the pragma. In a `generic_instantiation` the corresponding actual type shall have preelaborable initialization.

**Replace paragraph 16: [AI95-00366-01]**

A pure `library_item` is a preelaborable `library_item` that does not contain the declaration of any variable or named access type, except within a subprogram, generic subprogram, task unit, or protected unit.

**by:**

A pure `library_item` is a preelaborable `library_item` that does not contain the declaration of any variable, or named access-to-object type for which the `Storage_Size` has not been specified by a static expression with value zero (0) and is not defined to be zero (0), excepting declarations within a subprogram, generic subprogram, generic formal part, task unit, or protected unit.

**Replace paragraph 17: [AI95-00366-01]**

A `pragma Pure` is used to declare that a library unit is pure. If a `pragma Pure` applies to a library unit, then its compilation units shall be pure, and they shall depend semantically only on compilation units of other library units that are declared pure.

**by:**

A `pragma Pure` is used to declare that a library unit is pure. If a `pragma Pure` applies to a library unit, then its compilation units shall be pure, and they shall depend semantically only on compilation units of other library units that are declared pure. Furthermore, the full view of any private type declared in the visible part of the library unit shall support external streaming (see 13.13.2).

**Replace paragraph 18: [AI95-00366-01]**

If a library unit is declared pure, then the implementation is permitted to omit a call on a library-level subprogram of the library unit if the results are not needed after the call. Similarly, it may omit such a call and simply reuse the results produced by an earlier call on the same subprogram, provided that none of the parameters are of a limited type, and the addresses and values of all by-reference actual parameters, and the values of all by-copy-in actual parameters, are the same as they were at the earlier call. This permission applies even if the subprogram produces other side effects when called.

**by:**

If a library unit is declared pure, then the implementation is permitted to omit a call on a library-level subprogram of the library unit if the results are not needed after the call. In addition, the implementation may omit a call on such a subprogram and simply reuse the results produced by an earlier call on the same subprogram, provided that none of the parameters nor any object accessible via access values from the parameters are of a limited type, and the addresses and values of all by-reference actual parameters, the values of all by-copy-in actual parameters, and the values of all objects accessible via access values from the parameters, are the same as they were at the earlier call. This permission applies even if the subprogram produces other side effects when called.



## Section 11: Exceptions

### 11.3 Raise Statements

Replace paragraph 2: [AI95-00361-01]

`raise_statement ::= raise [exception_name];`

by:

`raise_statement ::= raise; |  
raise exception_name [with string_expression];`

Insert after paragraph 3: [AI95-00361-01]

The name, if any, in a `raise_statement` shall denote an exception. A `raise_statement` with no *exception\_name* (that is, a *re-raise statement*) shall be within a handler, but not within a body enclosed by that handler.

the new paragraph:

*Name Resolution Rules*

The expression, if any, in a `raise_statement`, is expected to be of type `String`.

Replace paragraph 4: [AI95-00361-01]

To *raise an exception* is to raise a new occurrence of that exception, as explained in 11.4. For the execution of a `raise_statement` with an *exception\_name*, the named exception is raised. For the execution of a re-raise statement, the exception occurrence that caused transfer of control to the innermost enclosing handler is raised again.

by:

To *raise an exception* is to raise a new occurrence of that exception, as explained in 11.4. For the execution of a `raise_statement` with an *exception\_name*, the named exception is raised. If a *string\_expression* is present, a call of `Ada.Exceptions.Exception_Message` returns that string. For the execution of a re-raise statement, the exception occurrence that caused transfer of control to the innermost enclosing handler is raised again.

### 11.4.1 The Package Exceptions

Replace paragraph 2: [AI95-00362-01]

```
package Ada.Exceptions is
  type Exception_Id is private;
  Null_Id : constant Exception_Id;
  function Exception_Name(Id : Exception_Id) return String;
```

by:

```
package Ada.Exceptions is
  pragma Preelaborate(Exceptions);
  type Exception_Id is private;
  pragma Preelaborable_Initialization (Exception_Id);
  Null_Id : constant Exception_Id;
  function Exception_Name(Id : Exception_Id) return String;
```

Replace paragraph 3: [AI95-00362-01]

```
type Exception_Occurrence is limited private;
type Exception_Occurrence_Access is access all Exception_Occurrence;
Null_Occurrence : constant Exception_Occurrence;
```

by:

```
type Exception_Occurrence is limited private;
pragma Preelaborable_Initialization (Exception_Occurrence);
type Exception_Occurrence_Access is access all Exception_Occurrence;
Null_Occurrence : constant Exception_Occurrence;
```

**Replace paragraph 4: [AI95-00329-01]**

```
procedure Raise_Exception(E : in Exception_Id;
                        Message : in String := "");
function Exception_Message(X : Exception_Occurrence) return String;
procedure Reraise_Occurrence(X : in Exception_Occurrence);
```

by:

```
procedure Raise_Exception(E : in Exception_Id;
                        Message : in String := "");
    pragma No_Return(Raise_Exception);
function Exception_Message(X : Exception_Occurrence) return String;
procedure Reraise_Occurrence(X : in Exception_Occurrence);
```

**Replace paragraph 10: [AI95-00361-01; AI95-00378-01]**

Raise\_Exception raises a new occurrence of the identified exception. In this case, Exception\_Message returns the Message parameter of Raise\_Exception. For a *raise\_statement* with an *exception\_name*, Exception\_Message returns implementation-defined information about the exception occurrence. Reraise\_Occurrence reraises the specified exception occurrence.

by:

Raise\_Exception raises a new occurrence of the identified exception. In this case, Exception\_Message returns the Message parameter of Raise\_Exception. For a *raise\_statement* with an *exception\_name* and a *string\_expression*, Exception\_Message returns that string. For a *raise\_statement* with an *exception\_name* but without a *string\_expression*, Exception\_Message returns implementation-defined information about the exception occurrence. In all cases, Exception\_Message returns a string with lower bound 1. Reraise\_Occurrence reraises the specified exception occurrence.

**Replace paragraph 12: [AI95-00378-01]**

The Exception\_Name functions return the full expanded name of the exception, in upper case, starting with a root library unit. For an exception declared immediately within package Standard, the *defining\_identifier* is returned. The result is implementation defined if the exception is declared within an unnamed *block\_statement*.

by:

The Exception\_Name functions return the full expanded name of the exception, in upper case, starting with a root library unit. The returned string has lower bound 1. For an exception declared immediately within package Standard, the *defining\_identifier* is returned. The result is implementation defined if the exception is declared within an unnamed *block\_statement*.

**Replace paragraph 13: [AI95-00378-01]**

Exception\_Information returns implementation-defined information about the exception occurrence.

by:

Exception\_Information returns implementation-defined information about the exception occurrence. The returned string has lower bound 1.

**Replace paragraph 14: [AI95-00241-01; AI95-00329-01]**

Raise\_Exception and Reraise\_Occurrence have no effect in the case of Null\_Id or Null\_Occurrence. Exception\_Message, Exception\_Identity, Exception\_Name, and Exception\_Information raise Constraint\_Error for a Null\_Id or Null\_Occurrence.

by:

Reraise\_Occurrence has no effect in the case of Null\_Occurrence. Raise\_Exception and Exception\_Name raise Constraint\_Error for a Null\_Id. Exception\_Message, Exception\_Name, and Exception\_Information raise Constraint\_Error for a Null\_Occurrence. Exception\_Identity applied to Null\_Occurrence returns Null\_Id.

## 11.4.2 Pragmas Assert and Assertion\_Policy

**Insert new clause: [AI95-00286-01]**

Pragma Assert is used to assert the truth of a Boolean expression at any point within a sequence of declarations or statements. Pragma Assertion\_Policy is used to control whether such assertions are to be ignored by the implementation, checked at run-time, or handled in some implementation-defined manner.

*Syntax*

The form of a **pragma** Assert is as follows:

```
pragma Assert([Check =>] Boolean_expression [, [Message =>] string_expression]);
```

A **pragma** Assert is allowed at the place where a **declarative\_item** or a **statement** is allowed.

The form of a **pragma** Assertion\_Policy is as follows:

```
pragma Assertion_Policy(policy_identifier);
```

A **pragma** Assertion\_Policy is a configuration pragma.

*Legality Rules*

The *policy\_identifier* of an Assertion\_Policy pragma shall be either Check, Ignore, or an implementation-defined identifier.

*Static Semantics*

A **pragma** Assertion\_Policy is a configuration pragma that specifies the assertion policy in effect for the compilation units to which it applies. Different policies may apply to different compilation units within the same partition. The default assertion policy is implementation-defined.

The following language-defined library package exists:

```
package Ada.Assertions is
  pragma Pure (Assertions);

  Assertion_Error : exception;

  procedure Assert (Check : in Boolean);
  procedure Assert (Check : in Boolean; Message : in String);

end Ada.Assertions;
```

A compilation unit containing a **pragma** Assert has a semantic dependence on the Ada.Assertions library unit.

The assertion policy that applies within an instance is the policy that applies within the generic unit.

*Dynamic Semantics*

An assertion policy specifies how a **pragma** Assert is interpreted by the implementation. If the assertion policy is Ignore at the point of a **pragma** Assert, the pragma is ignored. If the assertion policy is Check at the point of a **pragma** Assert, the elaboration of the pragma consists of evaluating the Boolean expression, and if it evaluates to False, evaluating the Message string, if any, and raising the exception Ada.Assertions.Assertion\_Error, with a message if the Message argument is provided.

Calling the procedure Ada.Assertions.Assert without a Message parameter is equivalent to:

```
if Check = False then
```

```
    raise Ada.Assertions.Assertion_Error;  
end if;
```

Calling the procedure `Ada.Assertions.Assert` with a `Message` parameter is equivalent to:

```
if Check = False then  
    raise Ada.Assertions.Assertion_Error with Message;  
end if;
```

The procedures `Assertions.Assert` have these effects independently of the assertion policy in effect.

*Implementation Permissions*

`Assertion_Error` may be declared by renaming an implementation-defined exception from another package.

Implementations may define their own assertion policies.

NOTES

Normally, the Boolean expression in an `Assert` pragma should not call functions that have significant side-effects when the result of the expression is `True`, so that the particular assertion policy in effect will not affect normal operation of the program.

## 11.5 Suppressing Checks

### Replace paragraph 1: [AI95-00224-01]

A pragma `Suppress` gives permission to an implementation to omit certain language-defined checks.

by:

*Checking pragmas* give instructions to an implementation on handling language-defined checks. A pragma `Suppress` gives permission to an implementation to omit certain language-defined checks, while a pragma `Unsuppress` revokes the permission to omit checks.

### Replace paragraph 3: [AI95-00224-01]

The form of a pragma `Suppress` is as follows:

by:

The forms of checking pragmas are as follows:

### Replace paragraph 4: [AI95-00224-01]

```
pragma Suppress(identifier [, [On =>] name]);
```

by:

```
pragma Suppress(identifier);  
pragma Unsuppress(identifier);
```

### Replace paragraph 5: [AI95-00224-01]

A pragma `Suppress` is allowed only immediately within a `declarative_part`, immediately within a `package_specification`, or as a configuration pragma.

by:

A checking pragma is allowed only immediately within a `declarative_part`, immediately within a `package_specification`, or as a configuration pragma.

### Replace paragraph 6: [AI95-00224-01]

The identifier shall be the name of a check. The `name` (if present) shall statically denote some entity.

by:

The identifier shall be the name of a check.

**Delete paragraph 7: [AI95-00224-01]**

For a pragma Suppress that is immediately within a `package_specification` and includes a `name`, the `name` shall denote an entity (or several overloaded subprograms) declared immediately within the `package_specification`.

**Replace paragraph 8: [AI95-00224-01]**

A pragma Suppress gives permission to an implementation to omit the named check from the place of the pragma to the end of the innermost enclosing declarative region, or, if the pragma is given in a `package_specification` and includes a `name`, to the end of the scope of the named entity. If the pragma includes a `name`, the permission applies only to checks performed on the named entity, or, for a subtype, on objects and values of its type. Otherwise, the permission applies to all entities. If permission has been given to suppress a given check, the check is said to be *suppressed*.

**by:**

A checking pragma applies to the named check in a specific region (see below), and applies to all entities in that region. A checking pragma given in a `declarative_part` or immediately within a `package_specification` applies from the place of the pragma to the end of the innermost enclosing declarative region. The region for a checking pragma given as a configuration pragma is the declarative region for the entire compilation unit (or units) to which it applies.

If a checking pragma applies to a generic instantiation, then the checking pragma also applies to the instance. If a checking pragma applies to a call to a subprogram that has a pragma Inline applied to it, then the checking pragma also applies to the inlined subprogram body.

A pragma Suppress gives permission to an implementation to omit the named check (or every check in the case of `All_Checks`) for any entities to which it applies. If permission has been given to suppress a given check, the check is said to be *suppressed*.

A pragma Unsuppress revokes the permission to omit the named check (or every check in the case of `All_Checks`) given by any pragma Suppress that applies at the point of the pragma Unsuppress. The permission is revoked for the region to which the pragma Unsuppress applies. If there is no such permission at the point of a pragma Unsuppress, then the pragma has no effect. A later pragma Suppress can renew the permission.

**Replace paragraph 11: [AI95-00231-01]**

When evaluating a dereference (explicit or implicit), check that the value of the `name` is not **null**. When passing an actual parameter to a formal access parameter, check that the value of the actual parameter is not **null**. When evaluating a `discriminant_association` for an access discriminant, check that the value of the discriminant is not **null**.

**by:**

When evaluating a dereference (explicit or implicit), check that the value of the `name` is not **null**. When converting to a null-excluding subtype, check that the converted value is not **null**.

**Insert before paragraph 20: [AI95-00280-01]****Elaboration\_Check**

When a subprogram or protected entry is called, a task activation is accomplished, or a generic instantiation is elaborated, check that the body of the corresponding unit has already been elaborated.

**the new paragraphs:****Accessibility\_Check**

Check the accessibility level of an entity or view.

**Allocation\_Check**

For an **allocator**, check that the master of any tasks has not yet finished waiting for dependents, and that the finalization of the collection has not started.

**Replace paragraph 27: [AI95-00224-01]**

An implementation is allowed to place restrictions on Suppress pragmas. An implementation is allowed to add additional check names, with implementation-defined semantics. When Overflow\_Check has been suppressed, an implementation may also suppress an unspecified subset of the Range\_Checks.

**by:**

An implementation is allowed to place restrictions on checking pragmas, subject only to the requirement that pragma Unsuppress shall allow any check names supported by pragma Suppress. An implementation is allowed to add additional check names, with implementation-defined semantics. When Overflow\_Check has been suppressed, an implementation may also suppress an unspecified subset of the Range\_Checks.

An implementation may support an additional parameter on pragma Unsuppress similar to the one allowed for pragma Suppress (see J.10). The meaning of such a parameter is implementation-defined.

**Insert after paragraph 29: [AI95-00224-01]**

2 There is no guarantee that a suppressed check is actually removed; hence a pragma Suppress should be used only for efficiency reasons.

**the new paragraph:**

3 It is possible to give both a pragma Suppress and Unsuppress for the same check immediately within the same declarative\_part. In that case, the last pragma given determines whether or not the check is suppressed. Similarly, it is possible to resuppress a check which has been unsuppressed by giving a pragma Suppress in an inner declarative region.

**Replace paragraph 32: [AI95-00224-01]**

```
pragma Suppress(Range_Check);  
pragma Suppress(Index_Check, On => Table);
```

**by:**

```
pragma Suppress(Index_Check);  
pragma Unsuppress(Overflow_Check);
```

## Section 12: Generic Units

### 12.3 Generic Instantiation

Replace paragraph 2: [AI95-00218-03]

```
generic_instantiation ::=
  package defining_program_unit_name is
    new generic_package_name [generic_actual_part];
  | procedure defining_program_unit_name is
    new generic_procedure_name [generic_actual_part];
  | function defining_designator is
    new generic_function_name [generic_actual_part];
```

by:

```
generic_instantiation ::=
  package defining_program_unit_name is
    new generic_package_name [generic_actual_part];
  | [overriding_indicator]
  procedure defining_program_unit_name is
    new generic_procedure_name [generic_actual_part];
  | [overriding_indicator]
  function defining_designator is
    new generic_function_name [generic_actual_part];
```

### 12.4 Formal Objects

Delete paragraph 8: [AI95-00287-01]

The type of a generic formal object of mode **in** shall be nonlimited.

Replace paragraph 9: [AI95-00255-01]

A `formal_object_declaration` declares a generic formal object. The default mode is **in**. For a formal object of mode **in**, the nominal subtype is the one denoted by the `subtype_mark` in the declaration of the formal. For a formal object of mode **in out**, its type is determined by the `subtype_mark` in the declaration; its nominal subtype is nonstatic, even if the `subtype_mark` denotes a static subtype.

by:

A `formal_object_declaration` declares a generic formal object. The default mode is **in**. For a formal object of mode **in**, the nominal subtype is the one denoted by the `subtype_mark` in the declaration of the formal. For a formal object of mode **in out**, its type is determined by the `subtype_mark` in the declaration; its nominal subtype is nonstatic, even if the `subtype_mark` denotes a static subtype; for a composite type, its nominal subtype is unconstrained if the first subtype of the type is unconstrained, even if the `subtype_mark` denotes a constrained subtype.

Replace paragraph 10: [AI95-00269-01]

In an instance, a `formal_object_declaration` of mode **in** declares a new stand-alone constant object whose initialization expression is the actual, whereas a `formal_object_declaration` of mode **in out** declares a view whose properties are identical to those of the actual.

by:

In an instance, a `formal_object_declaration` of mode **in** is a *full constant declaration* and declares a new stand-alone constant object whose initialization expression is the actual, whereas a `formal_object_declaration` of mode **in out** declares a view whose properties are identical to those of the actual.

## 12.5 Formal Types

**Replace paragraph 3: [AI95-00251-01]**

```
formal_type_definition ::=
    formal_private_type_definition
  | formal_derived_type_definition
  | formal_discrete_type_definition
  | formal_signed_integer_type_definition
  | formal_modular_type_definition
  | formal_floating_point_definition
  | formal_ordinary_fixed_point_definition
  | formal_decimal_fixed_point_definition
  | formal_array_type_definition
  | formal_access_type_definition
```

**by:**

```
formal_type_definition ::=
    formal_private_type_definition
  | formal_derived_type_definition
  | formal_discrete_type_definition
  | formal_signed_integer_type_definition
  | formal_modular_type_definition
  | formal_floating_point_definition
  | formal_ordinary_fixed_point_definition
  | formal_decimal_fixed_point_definition
  | formal_array_type_definition
  | formal_access_type_definition
  | formal_interface_type_definition
```

**Replace paragraph 8: [AI95-00233-01]**

The formal type also belongs to each class that contains the determined class. The primitive subprograms of the type are as for any type in the determined class. For a formal type other than a formal derived type, these are the predefined operators of the type. For an elementary formal type, the predefined operators are implicitly declared immediately after the declaration of the formal type. For a composite formal type, the predefined operators are implicitly declared either immediately after the declaration of the formal type, or later in its immediate scope according to the rules of 7.3.1. In an instance, the copy of such an implicit declaration declares a view of the predefined operator of the actual type, even if this operator has been overridden for the actual type. The rules specific to formal derived types are given in 12.5.1.

**by:**

The formal type also belongs to each class that contains the determined class. The primitive subprograms of the type are as for any type in the determined class. For a formal type other than a formal derived type, these are the predefined operators of the type. For an elementary formal type, the predefined operators are implicitly declared immediately after the declaration of the formal type. For a composite formal type, the predefined operators are implicitly declared either immediately after the declaration of the formal type, or later immediately within the declarative region in which the type is declared according to the rules of 7.3.1. In an instance, the copy of such an implicit declaration declares a view of the predefined operator of the actual type, even if this operator has been overridden for the actual type. The rules specific to formal derived types are given in 12.5.1.

### 12.5.1 Formal Private and Derived Types

**Replace paragraph 3: [AI95-00251-01]**

```
formal_derived_type_definition ::= [abstract] new subtype_mark [with private]
```

**by:**

```
formal_derived_type_definition ::=
```



[abstract] new subtype\_mark [[and interface\_list] with private]

**Insert after paragraph 10: [AI95-00231-01]**

- If the ancestor subtype is an unconstrained discriminated subtype, then the actual shall have the same number of discriminants, and each discriminant of the actual shall correspond to a discriminant of the ancestor, in the sense of 3.7.

**the new paragraph:**

- If the ancestor subtype is an access subtype, the actual subtype shall exclude null if and only if the ancestor subtype excludes null.

**Insert after paragraph 15: [AI95-00251-01]**

For a generic formal type with an unknown\_discriminant\_part, the actual may, but need not, have discriminants, and may be definite or indefinite.

**the new paragraph:**

The actual type for a generic formal derived type shall be a descendant of every ancestor of the formal type.

**Replace paragraph 20: [AI95-00233-01]**

If the ancestor type is a composite type that is not an array type, the formal type inherits components from the ancestor type (including discriminants if a new discriminant\_part is not specified), as for a derived type defined by a derived\_type\_definition (see 3.4).

**by:**

If the ancestor type is a composite type that is not an array type, the formal type inherits components from the ancestor type (including discriminants if a new discriminant\_part is not specified), as for a derived type defined by a derived\_type\_definition (see 3.4 and 7.3.1).

**Replace paragraph 21: [AI95-00233-01]**

For a formal derived type, the predefined operators and inherited user-defined subprograms are determined by the ancestor type, and are implicitly declared at the earliest place, if any, within the immediate scope of the formal type, where the corresponding primitive subprogram of the ancestor is visible (see 7.3.1). In an instance, the copy of such an implicit declaration declares a view of the corresponding primitive subprogram of the ancestor of the formal derived type, even if this primitive has been overridden for the actual type. When the ancestor of the formal derived type is itself a formal type, the copy of the implicit declaration declares a view of the corresponding copied operation of the ancestor. In the case of a formal private extension, however, the tag of the formal type is that of the actual type, so if the tag in a call is statically determined to be that of the formal type, the body executed will be that corresponding to the actual type.

**by:**

For a formal derived type, the predefined operators and inherited user-defined subprograms are determined by the ancestor type, and are implicitly declared at the earliest place, if any, immediately within the declarative region in which the formal type is declared, where the corresponding primitive subprogram of the ancestor is visible (see 7.3.1). In an instance, the copy of such an implicit declaration declares a view of the corresponding primitive subprogram of the ancestor of the formal derived type, even if this primitive has been overridden for the actual type. When the ancestor of the formal derived type is itself a formal type, the copy of the implicit declaration declares a view of the corresponding copied operation of the ancestor. In the case of a formal private extension, however, the tag of the formal type is that of the actual type, so if the tag in a call is statically determined to be that of the formal type, the body executed will be that corresponding to the actual type.

**Insert after paragraph 23: [AI95-00158-01]**

S'Definite

S'Definite yields True if the actual subtype corresponding to S is definite; otherwise it yields False. The value of this attribute is of the predefined type Boolean.

**the new paragraphs:**

*Dynamic Semantics*

In the case where a formal type is tagged with unknown discriminants, and the actual type is a class-wide type *T*Class, each of the primitive operations of the actual type is considered to be a subprogram (with an intrinsic calling convention -- see 6.3.1) whose body consists of a dispatching call upon the corresponding operation of *T*, with its formal parameters as the actual parameters. If it is a function, the result of the dispatching call is returned.

If the corresponding operation of *T* has no controlling formal parameters, then the controlling tag value is determined by the context of the call, according to the rules for tag-indeterminate calls (see 3.9.2 and 5.2). In the case where the tag would be statically determined to be that of the actual type, the call raises Program\_Error. If such a function is renamed, any call on the renaming raises Program\_Error.

## 12.5.4 Formal Access Types

**Replace paragraph 4: [AI95-00231-01]**

If and only if the `general_access_modifier` **constant** applies to the formal, the actual shall be an access-to-constant type. If the `general_access_modifier` **all** applies to the formal, then the actual shall be a general access-to-variable type (see 3.10).

**by:**

If and only if the `general_access_modifier` **constant** applies to the formal, the actual shall be an access-to-constant type. If the `general_access_modifier` **all** applies to the formal, then the actual shall be a general access-to-variable type (see 3.10). If and only if the formal subtype excludes null, the actual subtype shall exclude null.

## 12.5.5 Formal Interface Types

**Insert new clause: [AI95-00251-01; AI95-00345-01]**

The class determined for a formal interface type is the class of all interface types.

*Syntax*

`formal_interface_type_definition ::= interface_type_definition`

*Legality Rules*

The actual type shall be an interface type.

The actual type shall be a descendant of every ancestor of the formal type.

The actual type shall be a limited, task, protected, or synchronized interface if and only if the formal type is also, respectively, a limited, task, protected, or synchronized interface.

## 12.6 Formal Subprograms

**Replace paragraph 2: [AI95-00260-02]**

`formal_subprogram_declaration ::= with subprogram_specification [is subprogram_default];`

**by:**

```
formal_subprogram_declaration ::= formal_abstract_subprogram_declaration
| formal_concrete_subprogram_declaration
formal_concrete_subprogram_declaration ::=
    with subprogram_specification [is subprogram_default];
formal_abstract_subprogram_declaration ::=
    with subprogram_specification is abstract [subprogram_default];
```

**Replace paragraph 3: [AI95-00348-01]**

subprogram\_default ::= default\_name | <>

by:

subprogram\_default ::= default\_name | <> | null

**Insert after paragraph 4: [AI95-00260-01; AI95-00348-01]**

default\_name ::= name

**the new paragraph:**

A subprogram\_default of **null** shall not be specified for a formal function or for a formal\_abstract\_subprogram\_declaration.

**Insert after paragraph 8: [AI95-00260-02]**

The profiles of the formal and actual shall be mode-conformant.

**the new paragraphs:**

If a formal parameter of an formal\_abstract\_subprogram\_declaration is of a specific tagged type T or of an anonymous access designating a specific tagged type T, T is called a *controlling type* of the formal\_abstract\_subprogram\_declaration. Similarly, if the result of an formal\_abstract\_subprogram\_declaration for a function is of a specific tagged type T or of an anonymous access designating a specific tagged type T, T is called a *controlling type* of the formal\_abstract\_subprogram\_declaration. A formal\_abstract\_subprogram\_declaration shall have exactly one controlling type.

The actual subprogram for a formal\_abstract\_subprogram\_declaration shall be a dispatching operation of the controlling type or of the actual type corresponding to the controlling type.

**Replace paragraph 9: [AI95-00345-01]**

A formal\_subprogram\_declaration declares a generic formal subprogram. The types of the formal parameters and result, if any, of the formal subprogram are those determined by the subtype\_marks given in the formal\_subprogram\_declaration; however, independent of the particular subtypes that are denoted by the subtype\_marks, the nominal subtypes of the formal parameters and result, if any, are defined to be nonstatic, and unconstrained if of an array type (no applicable index constraint is provided in a call on a formal subprogram). In an instance, a formal\_subprogram\_declaration declares a view of the actual. The profile of this view takes its subtypes and calling convention from the original profile of the actual entity, while taking the formal parameter names and default\_expressions from the profile given in the formal\_subprogram\_declaration. The view is a function or procedure, never an entry.

by:

A formal\_subprogram\_declaration declares a generic formal subprogram. The types of the formal parameters and result, if any, of the formal subprogram are those determined by the subtype\_marks given in the formal\_subprogram\_declaration; however, independent of the particular subtypes that are denoted by the subtype\_marks, the nominal subtypes of the formal parameters and result, if any, are defined to be nonstatic, and unconstrained if of an array type (no applicable index constraint is provided in a call on a formal subprogram). In an instance, a formal\_subprogram\_declaration declares a view of the actual. The profile of this view takes its subtypes and calling convention from the original profile of the actual entity, while taking the formal parameter names and default\_expressions from the profile given in the formal\_subprogram\_declaration.

**Insert after paragraph 10: [AI95-00260-01; AI95-00348-01]**

If a generic unit has a subprogram\_default specified by a box, and the corresponding actual parameter is omitted, then it is equivalent to an explicit actual parameter that is a usage name identical to the defining name of the formal.

**the new paragraphs:**

If a generic unit has a `subprogram_default` specified by the reserved word **null**, and the corresponding actual parameter is omitted, then it is equivalent to an explicit actual parameter that is a null procedure having the profile given in the `formal_subprogram_declaration`.

The subprogram declared by a `formal_abstract_subprogram_declaration` with a controlling type T is a dispatching operation of type T.

**Replace paragraph 16: [AI95-00260-01; AI95-00348-01]**

18 The actual subprogram cannot be abstract (see 3.9.3).

**by:**

18 The actual subprogram cannot be abstract unless the formal subprogram is a `formal_abstract_subprogram_declaration` (see 3.9.3).

19 The subprogram declared by a `formal_abstract_subprogram_declaration` is an abstract subprogram. All calls on a subprogram declared by a `formal_abstract_subprogram_declaration` must be dispatching calls. See 3.9.3.

20 A null procedure as a subprogram default has convention Intrinsic (see 6.3.1).

## 12.7 Formal Packages

**Replace paragraph 3: [AI95-00317-01]**

```
formal_package_actual_part ::=
    (<>) | [generic_actual_part]
```

**by:**

```
formal_package_actual_part ::=
    ([others =>] <>)
    | [generic_actual_part]
    | (formal_package_association {, formal_package_association}, others => <>)

formal_package_association ::=
    generic_association
    | generic_formal_parameter_selector_name => <>
```

Any positional `formal_package_associations` shall precede any named `formal_package_associations`.

**Replace paragraph 5: [AI95-00317-01]**

The actual shall be an instance of the template. If the `formal_package_actual_part` is (<>), then the actual may be any instance of the template; otherwise, each actual parameter of the actual instance shall match the corresponding actual parameter of the formal package (whether the actual parameter is given explicitly or by default), as follows:

**by:**

The actual shall be an instance of the template. If the `formal_package_actual_part` is (<>) or (**others** => <>), then the actual may be any instance of the template; otherwise, certain of the actual parameters of the actual instance shall match the corresponding actual parameter of the formal package, determined as follows:

- If the `formal_package_actual_part` includes `generic_associations` as well as associations with <>, then only the actual parameters specified explicitly with `generic_associations` are required to match;
- Otherwise, all actual parameters shall match, whether the actual parameter is given explicitly or by default.

The rules for matching of actual parameters between the actual instance and the formal package are as follows:

**Replace paragraph 10: [AI95-00317-01]**

The visible part of a formal package includes the first list of `basic_declarative_items` of the `package_specification`. In addition, if the `formal_package_actual_part` is ( $\langle \rangle$ ), it also includes the `generic_formal_part` of the template for the formal package.

**by:**

The visible part of a formal package includes the first list of `basic_declarative_items` of the `package_specification`. In addition, for each actual parameter that is not required to match, a copy of the declaration of the corresponding formal parameter of the template is included in the visible part of the formal package. If the copied declaration is for a formal type, copies of the implicit declarations of the primitive subprograms of the formal type are also included in the visible part of the formal package.

For the purposes of matching, if the actual instance *A* is itself a formal package, then the actual parameters of *A* are those specified explicitly or implicitly in the `formal_package_actual_part` for *A*, plus, for those not specified, the copies of the formal parameters of the template included in the visible part of *A*.

## Section 13: Representation Issues

### 13.1 Representation Items

**Replace paragraph 11: [AI95-00326-01]**

Operational and representation aspects of a generic formal parameter are the same as those of the actual.  
Operational and representation aspects of a partial view are the same as those of the full view. A type-related representation item is not allowed for a descendant of a generic formal untagged type.

**by:**

Operational and representation aspects of a generic formal parameter are the same as those of the actual.  
Operational and representation aspects are the same for all views of a type. A type-related representation item is not allowed for a descendant of a generic formal untagged type.

### 13.3 Representation Attributes

**Insert after paragraph 8: [AI95-00133-01]**

A *storage element* is an addressable element of storage in the machine. A *word* is the largest amount of storage that can be conveniently and efficiently manipulated by the hardware, given the implementation's run-time model. A word consists of an integral number of storage elements.

**the new paragraph:**

A *machine scalar* is an amount of storage that can be conveniently and efficiently loaded, stored, or operated upon by the hardware. Machine scalars consist of an integral number of storage elements. The set of machine scalars is implementation defined, but must include at least the storage element and the word. Machine scalars are used to interpret `component_clauses` when the nondefault bit ordering applies.

**Replace paragraph 25: [AI95-00051-01]**

Alignment may be specified for first subtypes and stand-alone objects via an `attribute_definition_clause`; the expression of such a clause shall be static, and its value nonnegative. If the Alignment of a subtype is specified, then the Alignment of an object of the subtype is at least as strict, unless the object's Alignment is also specified. The Alignment of an object created by an allocator is that of the designated subtype.

**by:**

Alignment may be specified for first subtypes and stand-alone objects via an `attribute_definition_clause`; the expression of such a clause shall be static, and its value nonnegative. The Alignment of an object is at least as strict as the Alignment of its subtype, unless the object's Alignment is specified. The Alignment of an object created by an allocator is that of the designated subtype.

**Delete paragraph 26: [AI95-00247-01]**

If an Alignment is specified for a composite subtype or object, this Alignment shall be equal to the least common multiple of any specified Alignments of the subcomponent subtypes, or an integer multiple thereof.

**Replace paragraph 28: [AI95-00051-01]**

If the Alignment is specified for an object that is not allocated under control of the implementation, execution is erroneous if the object is not aligned according to the Alignment.

**by:**

Program execution is erroneous if an object that is not allocated under control of the implementation is not aligned according to its Alignment.

**Replace paragraph 30: [AI95-00051-01]**

- An implementation should support specified Alignments that are factors and multiples of the number of storage elements per word, subject to the following:

**by:**

- An implementation should support a confirming Alignment clause for any kind of type.
- An implementation should support a nonconfirming Alignment clause for a discrete type, fixed point type, record type, or array type, specifying an Alignment value that is zero or a power of two, subject to the following:

**Replace paragraph 31: [AI95-00051-01]**

- An implementation need not support specified Alignments for combinations of Sizes and Alignments that cannot be easily loaded and stored by available machine instructions.

**by:**

- An implementation need not support an Alignment clause for a signed integer type specifying an Alignment greater than the largest Alignment value that is ever chosen by default by the implementation for any signed integer type. A corresponding limitation may be imposed for modular integer types, fixed point types, enumeration types, record types, and array types.

**Replace paragraph 32: [AI95-00051-01]**

- An implementation need not support specified Alignments that are greater than the maximum Alignment the implementation ever returns by default.

**by:**

- An implementation need not support a nonconfirming Alignment clause which could enable the creation of an object of an elementary type which cannot be easily loaded and stored by available machine instructions.

**Replace paragraph 42: [AI95-00051-01]**

The recommended level of support for the Size attribute of objects is:

**by:**

The recommended level of support for the Size attribute of objects is the same as for subtypes (see below).

**Delete paragraph 43: [AI95-00051-01]**

- A Size clause should be supported for an object if the specified Size is at least as large as its subtype's Size, and corresponds to a size in storage elements that is a multiple of the object's Alignment (if the Alignment is nonzero).

**Replace paragraph 50: [AI95-00051-01]**

If the Size of a subtype is specified, and allows for efficient independent addressability (see 9.10) on the target architecture, then the Size of the following objects of the subtype should equal the Size of the subtype:

**by:**

If the Size of a subtype allows for efficient independent addressability (see 9.10) on the target architecture, then the Size of the following objects of the subtype should equal the Size of the subtype:

**Insert after paragraph 56: [AI95-00051-01]**

- For a subtype implemented with levels of indirection, the Size should include the size of the pointers, but not the size of what they point at.

**the new paragraphs:**

- An implementation should support a confirming Size clause for any kind of type.
- An implementation should support a nonconfirming Size clause for a discrete type or a fixed point type, subject to the following:
- An implementation need not support a Size clause for a signed integer type specifying a Size greater than that of the largest signed integer type supported by the implementation in the absence of a size clause (that is, when the size is chosen by default). A corresponding limitation may be imposed for modular integer types, fixed point types, and enumeration types.

### 13.5.1 Record Representation Clauses

**Insert after paragraph 10: [AI95-00133-01]**

The position, first\_bit, and last\_bit shall be static expressions. The value of position and first\_bit shall be nonnegative. The value of last\_bit shall be no less than first\_bit - 1.

**the new paragraphs:**

If the nondefault bit ordering applies to the type, then either:

- the value of last\_bit shall be less than the size of the largest machine scalar; or
- the value of first\_bit shall be zero and the value of last\_bit + 1 shall be a multiple of System.Storage\_Unit.

**Replace paragraph 13: [AI95-00133-01]**

A record\_representation\_clause (without the mod\_clause) specifies the layout. The storage place attributes (see 13.5.2) are taken from the values of the position, first\_bit, and last\_bit expressions after normalizing those values so that first\_bit is less than Storage\_Unit.

**by:**

A record\_representation\_clause (without the mod\_clause) specifies the layout.

If the default bit ordering applies to the type, the position, first\_bit, and last\_bit of each component\_clause directly specify the position and size of the corresponding component.

If the nondefault bit ordering applies to the type then the layout is determined as follows:

- the component\_clauses for which the value of last\_bit is greater than or equal to the size of the largest machine scalar directly specify the position and size of the corresponding component;
- for other component\_clauses, all the components having the same value of position are considered to be part of a single machine scalar, located at that position; this machine scalar has a size which is the smallest machine scalar size larger than the largest last\_bit for all component\_clauses at that position; the first\_bit and last\_bit of each component\_clause are then interpreted as bit offsets in this machine scalar.

**Insert after paragraph 17: [AI95-00133-01]**

The recommended level of support for record\_representation\_clauses is:

**the new paragraph:**

- An implementation should support machine scalars that correspond to all the integer, floating point, and address formats supported by the machine.



### 13.5.2 Storage Place Attributes

#### Replace paragraph 2: [AI95-00133-01]

R.C'Position

Denotes the same value as R.C'Address - R'Address. The value of this attribute is of the type *universal\_integer*.

by:

R.C'Position

If the nondefault bit ordering applies to the composite type, and if a *component\_clause* specifies the placement of C, denotes the value given for the *position* of the *component\_clause*; otherwise, denotes the same value as R.C'Address - R'Address. The value of this attribute is of the type *universal\_integer*.

#### Replace paragraph 3: [AI95-00133-01]

R.C'First\_Bit

Denotes the offset, from the start of the first of the storage elements occupied by C, of the first bit occupied by C. This offset is measured in bits. The first bit of a storage element is numbered zero. The value of this attribute is of the type *universal\_integer*.

by:

R.C'First\_Bit

If the nondefault bit ordering applies to the composite type, and if a *component\_clause* specifies the placement of C, denotes the value given for the *first\_bit* of the *component\_clause*; otherwise, denotes the offset, from the start of the first of the storage elements occupied by C, of the first bit occupied by C. This offset is measured in bits. The first bit of a storage element is numbered zero. The value of this attribute is of the type *universal\_integer*.

#### Replace paragraph 4: [AI95-00133-01]

R.C'Last\_Bit

Denotes the offset, from the start of the first of the storage elements occupied by C, of the last bit occupied by C. This offset is measured in bits. The value of this attribute is of the type *universal\_integer*.

by:

R.C'Last\_Bit

If the nondefault bit ordering applies to the composite type, and if a *component\_clause* specifies the placement of C, denotes the value given for the *last\_bit* of the *component\_clause*; otherwise, denotes the offset, from the start of the first of the storage elements occupied by C, of the last bit occupied by C. This offset is measured in bits. The value of this attribute is of the type *universal\_integer*.

### 13.5.3 Bit Ordering

#### Replace paragraph 8: [AI95-00133-01]

- If *Word\_Size* = *Storage\_Unit*, then the implementation should support the nondefault bit ordering in addition to the default bit ordering.

by:

- The implementation should support the nondefault bit ordering in addition to the default bit ordering.

NOTES

13 Bit\_Order clauses make it possible to write `record_representation_clauses` that can be ported between machines having different bit ordering. They do not guarantee transparent exchange of data between such machines.

## 13.7 The Package System

Replace paragraph 3: [AI95-00362-01]

```
package System is
  pragma Preelaborate(System);
```

by:

```
package System is
  pragma Pure(System);
```

Replace paragraph 12: [AI95-00161-01]

```
type Address is implementation-defined;
Null_Address : constant Address;
```

by:

```
type Address is implementation-defined;
pragma Preelaborable_Initialization(Address);
Null_Address : constant Address;
```

In paragraph 15 replace: [AI95-00221-01]

```
Default_Bit_Order : constant Bit_Order;
```

by:

```
Default_Bit_Order : constant Bit_Order := implementation-defined;
```

Replace paragraph 35: [AI95-00221-01]

See 13.5.3 for an explanation of `Bit_Order` and `Default_Bit_Order`.

by:

See 13.5.3 for an explanation of `Bit_Order` and `Default_Bit_Order`. `Default_Bit_Order` shall be a static constant.

Replace paragraph 36: [AI95-00362-01]

An implementation may add additional implementation-defined declarations to package `System` and its children. However, it is usually better for the implementation to provide additional functionality via implementation-defined children of `System`. Package `System` may be declared pure.

by:

An implementation may add additional implementation-defined declarations to package `System` and its children. However, it is usually better for the implementation to provide additional functionality via implementation-defined children of `System`.

### 13.7.1 The Package System.Storage\_Elements

Replace paragraph 2: [AI95-00362-01]

```
package System.Storage_Elements is
  pragma Preelaborate(System.Storage_Elements);
```

by:

```
package System.Storage_Elements is
  pragma Pure(System.Storage_Elements);
```

**Delete paragraph 15: [AI95-00362-01]**

Package System.Storage\_Elements may be declared pure.

**13.9.1 Data Validity****Replace paragraph 12: [AI95-00167-01]**

A call to an imported function or an instance of Unchecked\_Conversion is erroneous if the result is scalar, and the result object has an invalid representation.

by:

A call to an imported function or an instance of Unchecked\_Conversion is erroneous if the result is scalar, the result object has an invalid representation, and the result is used other than as the **expression** of an **assignment\_statement** or an **object\_declaration**, or as the prefix of a Valid attribute. If such a result object is used as the source of an assignment, and the assigned value is an invalid representation for the target of the assignment, then any use of the target object prior to a further assignment to the target object, other than as the prefix of a Valid attribute reference, is erroneous.

**13.11 Storage Management****Replace paragraph 6: [AI95-00161-01]**

```
type Root_Storage_Pool is
  abstract new Ada.Controlled.Limited_Controlled with private;
```

by:

```
type Root_Storage_Pool is
  abstract new Ada.Controlled.Limited_Controlled with private;
pragma Preelaborable_Initialization(Root_Storage_Pool);
```

**Replace paragraph 25: [AI95-00230-01]**

A storage pool for an anonymous access type should be created at the point of an allocator for the type, and be reclaimed when the designated object becomes inaccessible.

by:

The storage pool used for an allocator of an anonymous access type should be determined as follows:

- If the **allocator** is initializing an access discriminant of an object of a limited type, and the discriminant is itself a subcomponent of an object being created by an outer **allocator**, then the storage pool used for the outer **allocator** should also be used for the **allocator** initializing the access discriminant;
- Otherwise, the storage pool should be created at the point of the **allocator**, and be reclaimed when the allocated object becomes inaccessible.

**13.11.1 The Max\_Size\_In\_Storage\_Elements Attribute****Replace paragraph 3: [AI95-00256-01]**

Denotes the maximum value for Size\_In\_Storage\_Elements that will be requested via Allocate for an access type whose designated subtype is S. The value of this attribute is of type *universal\_integer*.

by:

Denotes the maximum value for Size\_In\_Storage\_Elements that could be requested by the implementation via Allocate for an access type whose designated subtype is S. The value of this attribute is of type *universal\_integer*.

### 13.11.2 Unchecked Storage Deallocation

**Replace paragraph 17: [AI95-00162-01]**

For a standard storage pool, Free should actually reclaim the storage.

**by:**

For a standard storage pool, Free should actually reclaim the storage. If the object being reclaimed has an access discriminant which designates an object which was created by an allocator of the (anonymous) type of the access discriminant, then the designated object should also be reclaimed.

### 13.12 Pragma Restrictions

**Replace paragraph 4: [AI95-00381-01]**

`restriction ::= restriction_identifier  
| restriction_parameter_identifier => expression`

**by:**

`restriction ::= restriction_identifier  
| restriction_parameter_identifier => restriction_parameter_argument`

`restriction_parameter_argument ::= name | expression`

**Insert after paragraph 7: [AI95-00257-01; AI95-00368-01]**

The set of restrictions is implementation defined.

**the new paragraphs:**

The following *restriction\_identifiers* are language-defined (additional restrictions are defined in the Specialized Needs Annexes):

**No\_Implementation\_Attributes**

There are no implementation-defined attributes. This restriction applies only to the current compilation or environment, not the entire partition.

**No\_Implementation\_Pragmas**

There are no implementation-defined pragmas or pragma arguments. This restriction applies only to the current compilation or environment, not the entire partition.

**No\_Obsolescent\_Features**

There is no use of language features defined in Annex J. It is implementation-defined if uses of the renamings of J.1 are detected by this restriction. This restriction applies only to the current compilation or environment, not the entire partition.

#### 13.12.1 Restriction No\_Dependence

**Insert new clause: [AI95-00381-01]**

*Static Semantics*

The following *restriction\_parameter\_identifier* is language defined:

**No\_Dependence**

Specifies a language-defined library unit on which there are no semantic dependences.

*Name Resolution Rules*

The *restriction\_parameter\_argument* of a No\_Dependence restriction shall be a name that corresponds to the full expanded name of a language-defined library unit.

*Post-Compilation Rules*

No compilation unit included in the partition shall depend semantically on the library unit identified by the name.

### 13.13.1 The Package Streams

**Replace paragraph 3: [AI95-00161-01]**

```
type Root_Stream_Type is abstract tagged limited private;
```

**by:**

```
type Root_Stream_Type is abstract tagged limited private;
pragma Preelaborable_Initialization(Root_Stream_Type);
```

**Replace paragraph 8: [AI95-00227-01]**

The Read operation transfers Item'Length stream elements from the specified stream to fill the array Item. The index of the last stream element transferred is returned in Last. Last is less than Item'Last only if the end of the stream is reached.

**by:**

The Read operation transfers stream elements from the specified stream to fill the array Item. Elements are transferred until Item'Length elements have been transferred, or until the end of the stream is reached. If any elements are transferred, the index of the last stream element transferred is returned in Last. Otherwise, Item'First - 1 is returned in Last. Last is less than Item'Last only if the end of the stream is reached.

**Insert after paragraph 10: [AI95-00227-01]**

See A.12.1, ``The Package Streams.Stream\_IO'' for an example of extending type Root\_Stream\_Type.

**the new paragraph:**

If the end of stream has been reached, and Item'First is Stream\_Element\_Offset'First, Read will raise Constraint\_Error.

### 13.13.2 Stream-Oriented Attributes

**Insert after paragraph 1: [AI95-00366-01]**

The operational attributes Write, Read, Output, and Input convert values to a stream of elements and reconstruct values from a stream.

**the new paragraphs:**

A type is said to *support external streaming* if Read and Write attributes are available that provide for sending values of such a type between active partitions, with Write marshalling the representation, and Read unmarshalling the representation.

A limited type supports external streaming only if it has available Read and Write attributes. A type with a part that is of an access type supports external streaming only if that access type or the type of some part that includes the access type component, has Read and Write attributes that have been specified via an `attribute_definition_clause`, and that `attribute_definition_clause` is visible. An anonymous access type does not support external streaming. All other types support external streaming.

**Insert before paragraph 2: [AI95-00270-01]**

For every subtype S of a specific type T, the following attributes are defined.

**the new paragraphs:**

For every subtype S of an elementary type T, the following operational attribute is defined:

S'Stream\_Size

Denotes the number of bits occupied in a stream by items of subtype *S*. Hence, the number of stream elements required per item of elementary type *T* is:

$$T\_Stream\_Size / Ada.Streams.Stream\_Element'Size$$

The value of this attribute is of type `universal_integer` and is a multiple of `Stream_Element'Size`.

`Stream_Size` may be specified for first subtypes via an `attribute_definition_clause`; the expression of such a clause shall be static, non-negative, and a multiple of `Stream_Element'Size`.

*Implementation Advice*

The recommended level of support for the `Stream_Size` attribute is: A `Stream_Size` clause should be supported for an elementary type *T* if the specified `Stream_Size` is a multiple of `Stream_Element'Size` and is no less than the size of the first subtype of *T*, and no greater than the size of the largest type of the same elementary class (signed integer, modular integer, floating point, ordinary fixed point, decimal fixed point, or access).

**Replace paragraph 9: [AI95-00195-01; AI95-00270-01]**

For elementary types, the representation in terms of stream elements is implementation defined. For composite types, the Write or Read attribute for each component is called in canonical order, which is last dimension varying fastest for an array, and positional aggregate order for a record. Bounds are not included in the stream if *T* is an array type. If *T* is a discriminated type, discriminants are included only if they have defaults. If *T* is a tagged type, the tag is not included. For type extensions, the Write or Read attribute for the parent type is called, followed by the Write or Read attribute of each component of the extension part, in canonical order. For a limited type extension, if the attribute of any ancestor type of *T* has been directly specified and the attribute of any ancestor type of the type of any of the extension components which are of a limited type has not been specified, the attribute of *T* shall be directly specified.

**by:**

For elementary types, the representation in terms of stream elements is implementation defined. For composite types, the Write or Read attribute for each component is called in canonical order, which is last dimension varying fastest for an array, and positional aggregate order for a record. Bounds are not included in the stream if *T* is an array type. If *T* is a discriminated type, discriminants are included only if they have defaults. If *T* is a tagged type, the tag is not included. For type extensions, the Write or Read attribute for the parent type is called, followed by the Write or Read attribute of each component of the extension part, in canonical order. For a limited type extension, if the attribute of the parent type of *T* is available anywhere within the immediate scope of *T*, and the attribute of the type of any of the extension components which are of a limited type, *L*, is not available at the freezing point of *T*, then the attribute of *T* shall be directly specified.

`Constraint_Error` is raised by the predefined Write attribute if the value of the elementary item is outside the range of values representable using `Stream_Size` bits. For a signed integer type, an enumeration type, or a fixed-point type, the range is unsigned only if the integer code for the first subtype low bound is non-negative, and a (symmetric) signed range that covers all values of the first subtype would require more than `Stream_Size` bits; otherwise the range is signed.

**Replace paragraph 17: [AI95-00270-01]**

If a stream element is the same size as a storage element, then the normal in-memory representation should be used by Read and Write for scalar objects. Otherwise, Read and Write should use the smallest number of stream elements needed to represent all values in the base range of the scalar type.

**by:**

By default, the predefined stream-oriented attributes for an elementary type should only read or write the minimum number of stream elements required by the first subtype of the type, rounded up to the nearest factor or multiple of the word size that is also a multiple of the stream element size.

**Replace paragraph 27: [AI95-00195-01]**

S'Output then calls S'Write to write the value of *Item* to the stream. S'Input then creates an object (with the bounds or discriminants, if any, taken from the stream), initializes it with S'Read, and returns the value of the object.

**by:**

S'Output then calls S'Write to write the value of *Item* to the stream. S'Input then creates an object (with the bounds or discriminants, if any, taken from the stream), passes it to S'Read, and returns the value of the object. Normal default initialization and finalization take place for this object (see 3.3.1, 7.6, 7.6.1).

**Replace paragraph 31: [AI95-00344-01]**

First writes the external tag of *Item* to *Stream* (by calling `String'Output(Tags.External_Tag(Item'Tag) -- see 3.9)` and then dispatches to the subprogram denoted by the *Output* attribute of the specific type identified by the tag.

**by:**

First writes the external tag of *Item* to *Stream* (by calling `String'Output(Stream, Tags.External_Tag(Item'Tag) -- see 3.9)` and then dispatches to the subprogram denoted by the *Output* attribute of the specific type identified by the tag. *Tag\_Error* is raised if the tag of *Item* identifies a type declared at an accessibility level deeper than that of *S*.

**Replace paragraph 34: [AI95-00279-01; AI95-00344-01]**

First reads the external tag from *Stream* and determines the corresponding internal tag (by calling `Tags.Internal_Tag(String'Input(Stream)) -- see 3.9)` and then dispatches to the subprogram denoted by the *Input* attribute of the specific type identified by the internal tag; returns that result.

**by:**

First reads the external tag from *Stream* and determines the corresponding internal tag (by calling `Tags.Descendant_Tag(String'Input(Stream), S'Tag)` which might raise *Tag\_Error* -- see 3.9) and then dispatches to the subprogram denoted by the *Input* attribute of the specific type identified by the internal tag; returns that result. If the specific type identified by the internal tag is not covered by *T*'Class or is abstract, *Constraint\_Error* is raised.

**Replace paragraph 35: [AI95-00195-01]**

In the default implementation of *Read* and *Input* for a composite type, for each scalar component that is a discriminant or whose *component\_declaration* includes a *default\_expression*, a check is made that the value returned by *Read* for the component belongs to its subtype. *Constraint\_Error* is raised if this check fails. For other scalar components, no check is made. For each component that is of an access type, if the implementation can detect that the value returned by *Read* for the component is not a value of its subtype, *Constraint\_Error* is raised. If the value is not a value of its subtype and this error is not detected, the component has an abnormal value, and erroneous execution can result (see 13.9.1).

**by:**

In the default implementation of *Read* and *Input* for a composite type, for each scalar component that is a discriminant or whose *component\_declaration* includes a *default\_expression*, a check is made that the value returned by *Read* for the component belongs to its subtype. *Constraint\_Error* is raised if this check fails. For other scalar components, no check is made. For each component that is of an access type, if the implementation can detect that the value returned by *Read* for the component is not a value of its subtype, *Constraint\_Error* is raised. If the value is not a value of its subtype and this error is not detected, the component has an abnormal value, and erroneous execution can result (see 13.9.1). In the default implementation of *Read* for a composite type with defaulted discriminants, if the actual parameter of *Read* is constrained, a check is made that the discriminants read from the stream are equal to those of the actual parameter. *Constraint\_Error* is raised if this check fails.

It is unspecified at which point and in which order these checks are performed. In particular, if Constraint\_Error is raised due to the failure of one of these checks, it is unspecified how many stream elements have been read from the stream.

**Insert after paragraph 36: [AI95-00279-01; AI95-00344-01]**

The stream-oriented attributes may be specified for any type via an `attribute_definition_clause`. All nonlimited types have default implementations for these operations. An `attribute_reference` for one of these attributes is illegal if the type is limited, unless the attribute has been specified by an `attribute_definition_clause` or (for a type extension) the attribute has been specified for an ancestor type. For an `attribute_definition_clause` specifying one of these attributes, the subtype of the Item parameter shall be the base subtype if scalar, and the first subtype otherwise. The same rule applies to the result of the Input function.

**the new paragraph:**

*Erroneous Execution*

If the internal tag returned by Descendant\_Tag to T'Class'Input identifies a specific type whose tag has not been created, or does not exist in the partition at the time of the call, execution is erroneous.

**Insert after paragraph 36.1: [AI95-00195-01]**

For every subtype *S* of a language-defined nonlimited specific type *T*, the output generated by S'Output or S'Write shall be readable by S'Input or S'Read, respectively. This rule applies across partitions if the implementation conforms to the Distributed Systems Annex.

**the new paragraphs:**

If Constraint\_Error is raised during a call to Read because of failure of one the above checks, the implementation must ensure that the discriminants of the actual parameter of Read are not modified.

*Implementation Permissions*

The number of calls performed by the predefined implementation of the stream-oriented attributes on the Read and Write operations of the stream type is unspecified. An implementation may take advantage of this permission to perform internal buffering. However, all the calls on the Read and Write operations of the stream type needed to implement an explicit invocation of a stream-oriented attribute must take place before this invocation returns. An explicit invocation is one appearing explicitly in the program text, possibly through a generic instantiation (see 12.3).

**Insert after paragraph 38: [AI95-00279-01]**

32 User-specified attributes of S'Class are not inherited by other class-wide types descended from S.

**the new paragraph:**

33 If the prefix subtype *S* of function S'Class'Input is a library-level subtype, then reading a value of a type which has not yet been frozen with the S'Class'Input function will always raise Tag\_Error; execution cannot be erroneous.

## 13.14 Freezing Rules

**Insert after paragraph 7: [AI95-00251-01]**

- The declaration of a record extension causes freezing of the parent subtype.

**the new paragraph:**

- The declaration of a specific descendant of an interface type freezes the interface type.

**Insert after paragraph 15: [AI95-00341-01]**

- At the place where a subtype is frozen, its type is frozen. At the place where a type is frozen, any expressions or names within the full type definition cause freezing; the first subtype, and any



component subtypes, index subtypes, and parent subtype of the type are frozen as well. For a specific tagged type, the corresponding class-wide type is frozen as well. For a class-wide type, the corresponding specific type is frozen as well.

**the new paragraph:**

- At the place where a specific tagged type is frozen, the primitive subprograms of the type are frozen.

**Insert after paragraph 19: [AI95-00279-01]**

An operational or representation item that directly specifies an aspect of an entity shall appear before the entity is frozen (see 13.1).

**the new paragraph:**

*Dynamic Semantics*

The tag (see 3.9) of a tagged type T is created at the point where T is frozen.

## Annex A: Predefined Language Environment

### A.1 The Package Standard

#### Replace paragraph 36: [AI95-00285-01]

```
-- The predefined operators for the type Character are the same as for
-- any enumeration type.

-- The declaration of type Wide_Character is based on the standard ISO 10646 BMP character set.
-- The first 256 positions have the same contents as type Character. See 3.5.2.
```

```
type Wide_Character is (nul, soh ... FFFE, FFFF);
```

```
package ASCII is ... end ASCII; --Obsolescent; see J.5
```

by:

```
-- The predefined operators for the type Character are the same as for
-- any enumeration type.

-- The declaration of type Wide_Character is based on the standard ISO/IEC 10646:2003 BMP character
set.
-- The first 256 positions have the same contents as type Character. See 3.5.2.
```

```
type Wide_Character is (nul, soh ... FFFE, FFFF);
```

```
-- The declaration of type Wide_Wide_Character is based on the full
-- ISO/IEC 10646:2003 character set. The first 65536 positions have the
-- same contents as type Wide_Character. See 3.5.2.
```

```
type Wide_Wide_Character is (nul, soh ... FFFE, FFFF, ...);
```

```
package ASCII is ... end ASCII; --Obsolescent; see J.5
```

#### Replace paragraph 42: [AI95-00285-01]

```
-- The predefined operators for this type correspond to those for String
```

by:

```
-- The predefined operators for this type correspond to those for String.
```

```
type Wide_Wide_String is array (Positive range <>) of
Wide_Wide_Character;
pragma Pack (Wide_Wide_String);
```

```
-- The predefined operators for this type correspond to those for String.
```

#### Replace paragraph 49: [AI95-00285-01]

In each of the types Character and Wide\_Character, the character literals for the space character (position 32) and the non-breaking space character (position 160) correspond to different values. Unless indicated otherwise, each occurrence of the character literal ' ' in this International Standard refers to the space character. Similarly, the character literals for hyphen (position 45) and soft hyphen (position 173) correspond to different values. Unless indicated otherwise, each occurrence of the character literal '-' in this International Standard refers to the hyphen character.

by:

In each of the types Character, Wide\_Character, and Wide\_Wide\_Character, the character literals for the space character (position 32) and the non-breaking space character (position 160) correspond to different values. Unless indicated otherwise, each occurrence of the character literal ' ' in this International Standard

refers to the space character. Similarly, the character literals for hyphen (position 45) and soft hyphen (position 173) correspond to different values. Unless indicated otherwise, each occurrence of the character literal '-' in this International Standard refers to the hyphen character.

### A.3 Character Handling

#### Replace paragraph 1: [AI95-00285-01]

This clause presents the packages related to character processing: an empty pure package Characters and child packages Characters.Handling and Characters.Latin\_1. The package Characters.Handling provides classification and conversion functions for Character data, and some simple functions for dealing with Wide\_Character data. The child package Characters.Latin\_1 declares a set of constants initialized to values of type Character.

by:

This clause presents the packages related to character processing: an empty pure package Characters and child packages Characters.Handling and Characters.Latin\_1. The package Characters.Handling provides classification and conversion functions for Character data, and some simple functions for dealing with Wide\_Character and Wide\_Wide\_Character data. The child package Characters.Latin\_1 declares a set of constants initialized to values of type Character.

#### A.3.2 The Package Characters.Handling

##### Replace paragraph 2: [AI95-00362-01]

```
package Ada.Characters.Handling is
  pragma Preelaborate(Handling);
```

by:

```
package Ada.Characters.Handling is
  pragma Pure(Handling);
```

##### Replace paragraph 13: [AI95-00285-01]

--Classifications of and conversions between Wide\_Character and Character.

by:

--Classifications of and conversions between Wide\_Wide\_Character, Wide\_Character, and Character.

##### Insert after paragraph 14: [AI95-00285-01]

```
function Is_Character (Item : in Wide_Character) return Boolean;
function Is_String    (Item : in Wide_String)    return Boolean;
```

the new paragraph:

```
function Is_Character (Item : in Wide_Wide_Character) return Boolean;
function Is_String    (Item : in Wide_Wide_String)    return Boolean;
function Is_Wide_Character (Item : in Wide_Wide_Character) return Boolean;
function Is_Wide_String  (Item : in Wide_Wide_String)  return Boolean;
```

##### Insert after paragraph 16: [AI95-00285-01]

```
function To_String      (Item          : in Wide_String;
                        Substitute : in Character := ' ')
  return String;
```

the new paragraph:

```
function To_Character (Item :          in Wide_Wide_Character;
                      Substitute : in Character := ' ') return Character;
function To_String    (Item :          in Wide_Wide_String;
                      Substitute : in Character := ' ') return String;
```

**Insert after paragraph 18: [AI95-00285-01]**

```
function To_Wide_String (Item : in String) return Wide_String;
```

**the new paragraphs:**

```
function To_Wide_Character (Item : in Wide_Wide_Character;  
                           Substitute : in Wide_Character := ' ')  
return Wide_Character;
```

```
function To_Wide_String (Item : in Wide_Wide_String;  
                        Substitute : in Wide_Character := ' ')  
return Wide_String;
```

```
function To_Wide_Wide_Character (Item : in Character)  
return Wide_Wide_Character;
```

```
function To_Wide_Wide_String (Item : in String)  
return Wide_Wide_String;
```

```
function To_Wide_Wide_Character (Item : in Wide_Character)  
return Wide_Wide_Character;
```

```
function To_Wide_Wide_String (Item : in Wide_String)  
return Wide_Wide_String;
```

**Replace paragraph 42: [AI95-00285-01]**

The following set of functions test Wide\_Character values for membership in Character, or convert between corresponding characters of Wide\_Character and Character.

**by:**

The following functions test Wide\_Wide\_Character or Wide\_Character values for membership in Wide\_Character or Character, or convert between corresponding characters of Wide\_Wide\_Character, Wide\_Character, and Character.

**Delete paragraph 43: [AI95-00285-01]**

Is\_Character  
Returns True if Wide\_Character'Pos(Item) <= Character'Pos(Character'Last).

**Delete paragraph 44: [AI95-00285-01]**

Is\_String  
Returns True if Is\_Character(Item(I)) is True for each I in Item'Range.

**Delete paragraph 45: [AI95-00285-01]**

To\_Character  
Returns the Character corresponding to Item if Is\_Character(Item), and returns the Substitute Character otherwise.

**Delete paragraph 46: [AI95-00285-01]**

To\_String  
Returns the String whose range is 1..Item'Length and each of whose elements is given by To\_Character of the corresponding element in Item.

**Delete paragraph 47: [AI95-00285-01]**

To\_Wide\_Character  
Returns the Wide\_Character X such that Character'Pos(Item) = Wide\_Character'Pos(X).

**Replace paragraph 48: [AI95-00285-01]**

To\_Wide\_String Returns the Wide\_String whose range is 1..Item'Length and each of whose elements is given by To\_Wide\_Character of the corresponding element in Item.

by:

```
function Is_Character (Item : in Wide_Character) return Boolean;

  Returns True if Wide_Character'Pos(Item) <= Character'Pos(Character'Last).

function Is_Character (Item : in Wide_Wide_Character) return Boolean;

  Returns True if Wide_Wide_Character'Pos(Item) <= Character'Pos(Character'Last).

function Is_Wide_Character (Item : in Wide_Wide_Character) return Boolean;

  Returns True if Wide_Wide_Character'Pos(Item) <= Wide_Character'Pos(Wide_Character'Last).

function Is_String (Item : in Wide_String)      return Boolean;
function Is_String (Item : in Wide_Wide_String) return Boolean;

  Returns True if Is_Character(Item(I)) is True for each I in Item'Range.

function Is_Wide_String (Item : in Wide_Wide_String) return Boolean;

  Returns True if Is_Wide_Character(Item(I)) is True for each I in Item'Range.

function To_Character (Item :      in Wide_Character;
                      Substitute : in Character := ' ') return Character;
function To_Character (Item :      in Wide_Wide_Character;
                      Substitute : in Character := ' ') return Character;

  Returns the Character corresponding to Item if Is_Character(Item), and returns the Substitute
  Character otherwise.

function To_Wide_Character (Item : in Character) return Wide_Character;

  Returns the Wide_Character X such that Character'Pos(Item) = Wide_Character'Pos (X).

function To_Wide_Character (Item :      in Wide_Wide_Character;
                      Substitute : in Wide_Character := ' ')
                      return Wide_Character;

  Returns the Wide_Character corresponding to Item if Is_Wide_Character(Item), and returns the
  Substitute Wide_Character otherwise.

function To_Wide_Wide_Character (Item : in Character) return
  Wide_Wide_Character;

  Returns the Wide_Wide_Character X such that Character'Pos(Item) = Wide_Wide_Character'Pos
  (X).

function To_Wide_Wide_Character (Item : in Wide_Character)
                      return Wide_Wide_Character;

  Returns the Wide_Wide_Character X such that Wide_Character'Pos(Item) =
  Wide_Wide_Character'Pos (X).

function To_String (Item :      in Wide_String;
                    Substitute : in Character := ' ') return String;
function To_String (Item :      in Wide_Wide_String;
                    Substitute : in Character := ' ') return String;

  Returns the String whose range is 1..Item'Length and each of whose elements is given by
  To_Character of the corresponding element in Item.

function To_Wide_String (Item : in String) return Wide_String;

  Returns the Wide_String whose range is 1..Item'Length and each of whose elements is given by
  To_Wide_Character of the corresponding element in Item.
```

```

function To_Wide_String (Item : in Wide_Wide_String;
                        Substitute : in Wide_Character := ' ')
return Wide_String;

```

Returns the Wide\_String whose range is 1..Item'Length and each of whose elements is given by To\_Wide\_Character of the corresponding element in Item with the given Substitute Wide\_Character.

```

function To_Wide_Wide_String (Item : in String) return Wide_Wide_String;
function To_Wide_Wide_String (Item : in Wide_String) return Wide_Wide_String;

```

Returns the Wide\_Wide\_String whose range is 1..Item'Length and each of whose elements is given by To\_Wide\_Wide\_Character of the corresponding element in Item.

#### Delete paragraph 49: [AI95-00285-01]

If an implementation provides a localized definition of Character or Wide\_Character, then the effects of the subprograms in Characters.Handling should reflect the localizations. See also 3.5.2.

## A.4 String Handling

#### Replace paragraph 1: [AI95-00285-01]

This clause presents the specifications of the package Strings and several child packages, which provide facilities for dealing with string data. Fixed-length, bounded-length, and unbounded-length strings are supported, for both String and Wide\_String. The string-handling subprograms include searches for pattern strings and for characters in program-specified sets, translation (via a character-to-character mapping), and transformation (replacing, inserting, overwriting, and deleting of substrings).

by:

This clause presents the specifications of the package Strings and several child packages, which provide facilities for dealing with string data. Fixed-length, bounded-length, and unbounded-length strings are supported, for String, Wide\_String, and Wide\_Wide\_String. The string-handling subprograms include searches for pattern strings and for characters in program-specified sets, translation (via a character-to-character mapping), and transformation (replacing, inserting, overwriting, and deleting of substrings).

### A.4.1 The Package Strings

#### Replace paragraph 4: [AI95-00285-01]

```

Space      : constant Character      := ' ';
Wide_Space : constant Wide_Character := ' ';

```

by:

```

Space      : constant Character      := ' ';
Wide_Space : constant Wide_Character := ' ';
Wide_Wide_Space : constant Wide_Wide_Character := ' ';

```

### A.4.2 The Package Strings.Maps

#### Replace paragraph 3: [AI95-00362-01]

```

package Ada.Strings.Maps is
  pragma Preelaborate(Maps);

```

by:

```

package Ada.Strings.Maps is
  pragma Pure(Maps);

```

**Replace paragraph 4: [AI95-00161-01]**

```
-- Representation for a set of character values:
type Character_Set is private;
```

by:

```
-- Representation for a set of character values:
type Character_Set is private;
pragma Preelaborable_Initialization(Character_Set);
```

**Replace paragraph 20: [AI95-00161-01]**

```
-- Representation for a character to character mapping:
type Character_Mapping is private;
```

by:

```
-- Representation for a character to character mapping:
type Character_Mapping is private;
pragma Preelaborable_Initialization(Character_Mapping);
```

**A.4.3 Fixed-Length String Handling****Insert after paragraph 8: [AI95-00301-01]**

```
-- Search subprograms
```

the new paragraphs:

```
function Index (Source  : in String;
                Pattern : in String;
                From    : in Positive;
                Going   : in Direction := Forward;
                Mapping  : in Maps.Character_Mapping := Maps.Identity)
return Natural;

function Index (Source  : in String;
                Pattern : in String;
                From    : in Positive;
                Going   : in Direction := Forward;
                Mapping  : in Maps.Character_Mapping_Function)
return Natural;

function Index (Source  : in String;
                Set      : in Maps.Character_Set;
                From     : in Positive;
                Test     : in Membership := Inside;
                Going    : in Direction := Forward)
return Natural;

function Index_Non_Blank (Source : in String;
                        From      : in Positive;
                        Going     : in Direction := Forward)
return Natural;
```

**Insert after paragraph 56: [AI95-00301-01]**

- Otherwise, Length\_Error is propagated.

the new paragraphs:

```
function Index (Source  : in String;
                Pattern : in String;
                From    : in Positive;
                Going   : in Direction := Forward;
                Mapping  : in Maps.Character_Mapping := Maps.Identity)
return Natural;
```

```

function Index (Source : in String;
                Pattern : in String;
                From    : in Positive;
                Going    : in Direction := Forward;
                Mapping  : in Maps.Character_Mapping_Function)
return Natural;

```

Each Index function searches, starting from From, for a slice of Source, with length Pattern'Length, that matches Pattern with respect to Mapping; the parameter Going indicates the direction of the lookup. If From < Source'First, then Index\_Error is propagated. If Going = Forward, then Index returns the smallest index I which is greater than or equal to From such that the slice of Source starting at I matches Pattern. If Going = Backward, then Index returns the largest index I such that the slice of Source starting at I matches Pattern and has an upper bound less than or equal to From. If there is no such slice, then 0 is returned. If Pattern is the null string then Pattern\_Error is propagated.

**Replace paragraph 58: [AI95-00301-01]**

Each Index function searches for a slice of Source, with length Pattern'Length, that matches Pattern with respect to Mapping; the parameter Going indicates the direction of the lookup. If Going = Forward, then Index returns the smallest index I such that the slice of Source starting at I matches Pattern. If Going = Backward, then Index returns the largest index I such that the slice of Source starting at I matches Pattern. If there is no such slice, then 0 is returned. If Pattern is the null string then Pattern\_Error is propagated.

**by:**

If Going = Forward, returns

```
Index (Source, Pattern, Source'First, Forward, Mapping);
```

otherwise returns

```
Index (Source, Pattern, Source'Last, Backward, Mapping);
```

```

function Index (Source : in String;
                Set      : in Maps.Character_Set;
                From     : in Positive;
                Test      : in Membership := Inside;
                Going     : in Direction := Forward)
return Natural;

```

Index searches for the first or last occurrence of any of a set of characters (when Test=Inside), or any of the complement of a set of characters (when Test=Outside). If From < Source'First, then Index\_Error is propagated. Otherwise, it returns the smallest index I >= From (if Going=Forward) or the largest index I <= From (if Going=Backward) such that Source(I) satisfies the Test condition with respect to Set; it returns 0 if there is no such Character in Source.

**Replace paragraph 60: [AI95-00301-01]**

Index searches for the first or last occurrence of any of a set of characters (when Test=Inside), or any of the complement of a set of characters (when Test=Outside). It returns the smallest index I (if Going=Forward) or the largest index I (if Going=Backward) such that Source(I) satisfies the Test condition with respect to Set; it returns 0 if there is no such Character in Source.

**by:**

If Going = Forward, returns

```
Index (Source, Set, Source'First, Test, Forward);
```

otherwise returns

```
Index (Source, Set, Source'Last, Test, Backward);
```

```

function Index_Non_Blank (Source : in String;

```



```

                                From    : in Positive;
                                Going   : in Direction := Forward)
return Natural;

Returns Index (Source, Maps.To_Set(Space), From, Outside, Going);

```

#### A.4.4 Bounded-Length String Handling

Insert after paragraph 12: [AI95-00301-01]

```
function To_String (Source : in Bounded_String) return String;
```

the new paragraphs:

```

procedure Set_Bounded_String
  (Target : out Bounded_String;
   Source : in String;
   Drop   : in Truncation := Error);

```

Insert after paragraph 28: [AI95-00301-01]

```

function Slice (Source : in Bounded_String;
               Low     : in Positive;
               High    : in Natural)
return String;

```

the new paragraphs:

```

function Bounded_Slice
  (Source : in Bounded_String;
   Low    : in Positive;
   High   : in Natural)
return Bounded_String;

procedure Bounded_Slice
  (Source : in Bounded_String;
   Target : out Bounded_String;
   Low    : in Positive;
   High   : in Natural);

```

Replace paragraph 43: [AI95-00301-01]

-- Search functions

by:

-- Search subprograms

```

function Index (Source : in Bounded_String;
               Pattern : in String;
               From    : in Positive;
               Going   : in Direction := Forward;
               Mapping  : in Maps.Character_Mapping := Maps.Identity)
return Natural;

function Index (Source : in Bounded_String;
               Pattern : in String;
               From    : in Positive;
               Going   : in Direction := Forward;
               Mapping  : in Maps.Character_Mapping_Function)
return Natural;

function Index (Source : in Bounded_String;
               Set     : in Maps.Character_Set;
               From    : in Positive;
               Test     : in Membership := Inside;
               Going   : in Direction := Forward)

```

```

    return Natural;

    function Index_Non_Blank (Source : in Bounded_String;
                             From   : in Positive;
                             Going  : in Direction := Forward)
    return Natural;

```

**Insert after paragraph 92: [AI95-00301-01]**

To\_String returns the String value with lower bound 1 represented by Source. If B is a Bounded\_String, then B = To\_Bounded\_String(To\_String(B)).

**the new paragraphs:**

```

procedure Set_Bounded_String
(Target : out Bounded_String;
 Source : in String;
 Drop   : in Truncation := Error);

Equivalent to Target := To_Bounded_String (Source, Drop);

```

**Replace paragraph 101: [AI95-00238-01; AI95-00301-01]**

Returns the slice at positions Low through High in the string represented by Source; propagates Index\_Error if Low > Length(Source)+1 or High > Length(Source).

**by:**

Returns the slice at positions Low through High in the string represented by Source; propagates Index\_Error if Low > Length(Source)+1 or High > Length(Source). The bounds of the returned string are Low and High.

```

function Bounded_Slice
(Source : in Bounded_String;
 Low    : in Positive;
 High   : in Natural;
 Drop   : in Truncation := Error)
return Bounded_String;

```

Returns the slice at positions Low through High in the string represented by Source as a bounded string; propagates Index\_Error if Low > Length(Source)+1 or High > Length(Source).

```

procedure Bounded_Slice
(Source : in Bounded_String;
 Target : out Bounded_String;
 Low    : in Positive;
 High   : in Natural;
 Drop   : in Truncation := Error);

```

Equivalent to Target := Bounded\_Slice (Source, Low, High, Drop);

## A.4.5 Unbounded-Length String Handling

**Replace paragraph 4: [AI95-00161-01]**

```

type Unbounded_String is private;

```

**by:**

```

type Unbounded_String is private;
pragma Preelaborable_Initialization(Unbounded_String);

```

**Insert after paragraph 11: [AI95-00301-01]**

```

function To_String (Source : in Unbounded_String) return String;

```

**the new paragraphs:**

```

procedure Set_Unbounded_String

```

```

(Target : out Unbounded_String;
Source : in String);

```

**Insert after paragraph 22: [AI95-00301-01]**

```

function Slice (Source : in Unbounded_String;
               Low    : in Positive;
               High   : in Natural)
return String;

```

**the new paragraphs:**

```

function Unbounded_Slice
(Source : in Unbounded_String;
 Low    : in Positive;
 High   : in Natural)
return Unbounded_String;

procedure Unbounded_Slice
(Source : in Unbounded_String;
 Target : out Unbounded_String;
 Low    : in Positive;
 High   : in Natural);

```

**Insert after paragraph 38: [AI95-00301-01]**

*-- Search subprograms*

**the new paragraphs:**

```

function Index (Source : in Unbounded_String;
               Pattern : in String;
               From    : in Positive;
               Going    : in Direction := Forward;
               Mapping  : in Maps.Character_Mapping := Maps.Identity)
return Natural;

function Index (Source : in Unbounded_String;
               Pattern : in String;
               From    : in Positive;
               Going    : in Direction := Forward;
               Mapping  : in Maps.Character_Mapping_Function)
return Natural;

function Index (Source : in Unbounded_String;
               Set      : in Maps.Character_Set;
               From     : in Positive;
               Test      : in Membership := Inside;
               Going     : in Direction := Forward)
return Natural;

function Index_Non_Blank (Source : in Unbounded_String;
                        From      : in Positive;
                        Going      : in Direction := Forward)
return Natural;

```

**Insert after paragraph 72: [AI95-00360-01]**

```

private
... -- not specified by the language
end Ada.Strings.Unbounded;

```

**the new paragraph:**

The type Unbounded\_String needs finalization (see 7.6).

**Insert after paragraph 79: [AI95-00301-01]**

- If U is an Unbounded\_String, then To\_Unbounded\_String(To\_String(U)) = U.

**the new paragraph:**

The procedure Set\_Unbounded\_String sets Target to an Unbounded\_String that represents Source.

**Insert after paragraph 82: [AI95-00301-01]**

The Element, Replace\_Element, and Slice subprograms have the same effect as the corresponding bounded-length string subprograms.

**the new paragraph:**

The function Unbounded\_Slice returns the slice at positions Low through High in the string represented by Source as an Unbounded\_String. The procedure Unbounded\_Slice sets Target to the Unbounded\_String representing the slice at positions Low through High in the string represented by Source. Both routines propagate Index\_Error if Low > Length(Source)+1 or High > Length(Source).

## A.4.6 String-Handling Sets and Mappings

**Replace paragraph 3: [AI95-00362-01]**

```
package Ada.Strings.Maps.Constants is
  pragma Preelaborate(Constants);
```

**by:**

```
package Ada.Strings.Maps.Constants is
  pragma Pure(Constants);
```

## A.4.7 Wide\_String Handling

**Replace paragraph 1: [AI95-00302-03]**

Facilities for handling strings of Wide\_Character elements are found in the packages Strings.Wide\_Maps, Strings.Wide\_Fixed, Strings.Wide\_Bounded, Strings.Wide\_Unbounded, and Strings.Wide\_Maps.Wide\_Constants. They provide the same string-handling operations as the corresponding packages for strings of Character elements.

**by:**

Facilities for handling strings of Wide\_Character elements are found in the packages Strings.Wide\_Maps, Strings.Wide\_Fixed, Strings.Wide\_Bounded, Strings.Wide\_Unbounded, and Strings.Wide\_Maps.Wide\_Constants, and in the functions Strings.Wide\_Hash and Strings.Wide\_Unbounded.Wide\_Hash. They provide the same string-handling operations as the corresponding packages and functions for strings of Character elements.

**Replace paragraph 4: [AI95-00161-01]**

```
-- Representation for a set of Wide_Character values:
type Wide_Character_Set is private;
```

**by:**

```
-- Representation for a set of Wide_Character values:
type Wide_Character_Set is private;
pragma Preelaborable_Initialization(Wide_Character_Set);
```

**Replace paragraph 20: [AI95-00161-01]**

```
-- Representation for a Wide_Character to Wide_Character mapping:
type Wide_Character_Mapping is private;
```

by:

```
-- Representation for a Wide_Character to Wide_Character mapping:
type Wide_Character_Mapping is private;
pragma Preelaborable_Initialization(Wide_Character_Mapping);
```

#### Replace paragraph 29: [AI95-00302-03]

For each of the packages Strings.Fixed, Strings.Bounded, Strings.Unbounded, and Strings.Maps.Constants the corresponding wide string package has the same contents except that

by:

For each of the packages Strings.Fixed, Strings.Bounded, Strings.Unbounded, and Strings.Maps.Constants, and for functions Strings.Hash and Strings.Unbounded.Hash, the corresponding wide string package has the same contents except that

#### Replace paragraph 46: [AI95-00285-01; AI95-00362-01]

```
Character_Set : constant Wide_Maps.Wide_Character_Set;
-- Contains each Wide_Character value WC such that Characters.Is_Character(WC) is True
```

by:

```
Character_Set : constant Wide_Maps.Wide_Character_Set;
-- Contains each Wide_Character value WC such that
-- Characters.Handling.Is_Character(WC) is True
```

Pragma Pure is replaced by pragma Preelaborate in Strings.Wide\_Maps.Wide\_Constants.

## A.4.8 Wide\_Wide\_String Handling

#### Insert new clause: [AI95-00285-01]

Facilities for handling strings of Wide\_Wide\_Character elements are found in the packages Strings.Wide\_Wide\_Maps, Strings.Wide\_Wide\_Fixed, Strings.Wide\_Wide\_Bounded, Strings.Wide\_Wide\_Unbounded, and Strings.Wide\_Wide\_Maps.Wide\_Wide\_Constants. They provide the same string-handling operations as the corresponding packages for strings of Character elements.

*Static Semantics*

The library package Strings.Wide\_Wide\_Maps has the following declaration.

```
package Ada.Strings.Wide_Wide_Maps is
  pragma Preelaborate(Wide_Wide_Maps);

  -- Representation for a set of Wide_Wide_Character values:
  type Wide_Wide_Character_Set is private;
  pragma Preelaborable_Initialization(Wide_Wide_Character_Set);

  Null_Set : constant Wide_Wide_Character_Set;

  type Wide_Wide_Character_Range is
    record
      Low : Wide_Wide_Character;
      High : Wide_Wide_Character;
    end record;
  -- Represents Wide_Wide_Character range Low..High

  type Wide_Wide_Character_Ranges is array (Positive range <>)
    of Wide_Wide_Character_Range;

  function To_Set (Ranges : in Wide_Wide_Character_Ranges)
    return Wide_Wide_Character_Set;

  function To_Set (Span : in Wide_Wide_Character_Range)
```

```

    return Wide_Wide_Character_Set;

function To_Ranges (Set : in Wide_Wide_Character_Set)
    return Wide_Wide_Character_Ranges;

function "=" (Left, Right : in Wide_Wide_Character_Set) return Boolean;

function "not" (Right : in Wide_Wide_Character_Set)
    return Wide_Wide_Character_Set;
function "and" (Left, Right : in Wide_Wide_Character_Set)
    return Wide_Wide_Character_Set;
function "or" (Left, Right : in Wide_Wide_Character_Set)
    return Wide_Wide_Character_Set;
function "xor" (Left, Right : in Wide_Wide_Character_Set)
    return Wide_Wide_Character_Set;
function "-" (Left, Right : in Wide_Wide_Character_Set)
    return Wide_Wide_Character_Set;

function Is_In (Element : in Wide_Wide_Character;
                Set : in Wide_Wide_Character_Set)
    return Boolean;

function Is_Subset (Elements : in Wide_Wide_Character_Set;
                   Set : in Wide_Wide_Character_Set)
    return Boolean;

function "<=" (Left : in Wide_Wide_Character_Set;
              Right : in Wide_Wide_Character_Set)
    return Boolean renames Is_Subset;

-- Alternative representation for a set of Wide_Wide_Character values:
subtype Wide_Wide_Character_Sequence is Wide_Wide_String;

function To_Set (Sequence : in Wide_Wide_Character_Sequence)
    return Wide_Wide_Character_Set;

function To_Set (Singleton : in Wide_Wide_Character)
    return Wide_Wide_Character_Set;

function To_Sequence (Set : in Wide_Wide_Character_Set)
    return Wide_Wide_Character_Sequence;

-- Representation for a Wide_Wide_Character to Wide_Wide_Character
-- mapping:
type Wide_Wide_Character_Mapping is private;
pragma Preelaborable_Initialization(Wide_Wide_Character_Mapping);

function Value (Map : in Wide_Wide_Character_Mapping;
               Element : in Wide_Wide_Character)
    return Wide_Wide_Character;

Identity : constant Wide_Wide_Character_Mapping;

function To_Mapping (From, To : in Wide_Wide_Character_Sequence)
    return Wide_Wide_Character_Mapping;

function To_Domain (Map : in Wide_Wide_Character_Mapping)
    return Wide_Wide_Character_Sequence;

function To_Range (Map : in Wide_Wide_Character_Mapping)
    return Wide_Wide_Character_Sequence;

type Wide_Wide_Character_Mapping_Function is
    access function (From : in Wide_Wide_Character)
        return Wide_Wide_Character;

```

```

private
  ... -- not specified by the language
end Ada.Strings.Wide_Wide_Maps;

```

The context clause for each of the packages Strings.Wide\_Wide\_Fixed, Strings.Wide\_Wide\_Bounded, and Strings.Wide\_Wide\_Unbounded identifies Strings.Wide\_Wide\_Maps instead of Strings.Maps.

For each of the packages Strings.Fixed, Strings.Bounded, Strings.Unbounded, and Strings.Maps.Constants the corresponding wide wide string package has the same contents except that

- Wide\_Wide\_Space replaces Space
- Wide\_Wide\_Character replaces Character
- Wide\_Wide\_String replaces String
- Wide\_Wide\_Character\_Set replaces Character\_Set
- Wide\_Wide\_Character\_Mapping replaces Character\_Mapping
- Wide\_Wide\_Character\_Mapping\_Function replaces Character\_Mapping\_Function
- Wide\_Wide\_Maps replaces Maps
- Bounded\_Wide\_Wide\_String replaces Bounded\_String
- Null\_Bounded\_Wide\_Wide\_String replaces Null\_Bounded\_String
- To\_Bounded\_Wide\_Wide\_String replaces To\_Bounded\_String
- To\_Wide\_Wide\_String replaces To\_String
- Unbounded\_Wide\_Wide\_String replaces Unbounded\_String
- Null\_Unbounded\_Wide\_Wide\_String replaces Null\_Unbounded\_String
- Wide\_Wide\_String\_Access replaces String\_Access
- To\_Unbounded\_Wide\_Wide\_String replaces To\_Unbounded\_String

The following additional declarations are present in Strings.Wide\_Wide\_Maps.Wide\_Wide\_Constants:

```

Character_Set : constant Wide_Wide_Maps.Wide_Wide_Character_Set;
-- Contains each Wide_Wide_Character value WWC such that
-- Characters.Handling.Is_Character(WWC) is True
Wide_Character_Set : constant Wide_Wide_Maps.Wide_Wide_Character_Set;
-- Contains each Wide_Wide_Character value WWC such that
-- Characters.Handling.Is_Wide_Character(WWC) is True

```

#### NOTES

14 If a null Wide\_Wide\_Character\_Mapping\_Function is passed to any of the Wide\_Wide\_String handling subprograms, Constraint\_Error is propagated.

## A.4.9 String Hashing

### Insert new clause: [AI95-00302-03]

#### Static Semantics

The library function Strings.Hash has the following declaration:

```

with Ada.Containers;
function Ada.Strings.Hash (Key : String) return Containers.Hash_Type;
pragma Pure (Ada.Strings.Hash);

```

Return an implementation-defined value which is a function of the value of Key. If A and B are strings such that A equals B, Hash(A) equals Hash(B).

The library function Strings.Unbounded.Hash has the following declaration:

```
with Ada.Containers;  
function Ada.Strings.Unbounded.Hash (Key : Unbounded_String) return  
    Containers.Hash_Type;  
pragma Preelaborate (Ada.Strings.Unbounded.Hash);
```

Return an implementation-defined value which is a function of the value of Key. If A and B are unbounded strings such that A equals B, Hash(A) equals Hash(B).

*Implementation Advice*

The various Hash functions should be good hash functions, returning a wide spread of values for different string values. It should be unlikely for similar strings to return the same value.

## A.5 The Numerics Packages

Replace paragraph 3: [AI95-00388-01]

```
package Ada.Numerics is  
  pragma Pure (Numerics);  
  Argument_Error : exception;  
  Pi : constant :=  
      3.14159_26535_89793_23846_26433_83279_50288_41971_69399_37511;  
  e : constant :=  
      2.71828_18284_59045_23536_02874_71352_66249_77572_47093_69996;  
end Ada.Numerics;
```

by:

```
package Ada.Numerics is  
  pragma Pure (Numerics);  
  Argument_Error : exception;  
  Pi : constant :=  
      3.14159_26535_89793_23846_26433_83279_50288_41971_69399_37511;  
   $\pi$  : constant := Pi;  
  e : constant :=  
      2.71828_18284_59045_23536_02874_71352_66249_77572_47093_69996;  
end Ada.Numerics;
```

### A.5.2 Random Number Generation

Insert after paragraph 15: [AI95-00360-01]

```
private  
  ... -- not specified by the language  
end Ada.Numerics.Float_Random;
```

the new paragraph:

The type Generator needs finalization (see 7.6).

Insert after paragraph 27: [AI95-00360-01]

```
private  
  ... -- not specified by the language  
end Ada.Numerics.Discrete_Random;
```

the new paragraph:

The type Generator needs finalization (see 7.6) in every instantiation of Numerics.Discrete\_Random.



### A.5.3 Attributes of Floating Point Types

**Insert after paragraph 41: [AI95-00267-01]**

The function yields the integral value nearest to  $X$ , rounding toward the even integer if  $X$  lies exactly halfway between two integers. A zero result has the sign of  $X$  when `S'Signed_Zeros` is `True`.

**the new paragraphs:**

`S'Machine_Rounding`

`S'Machine_Rounding` denotes a function with the following specification:

```
function S'Machine_Rounding ( $X$  : T)
return T
```

The function yields the integral value nearest to  $X$ . If  $X$  lies exactly halfway between two integers, one of those integers is returned, but which of them is returned is unspecified. A zero result has the sign of  $X$  when `S'Signed_Zeros` is `True`. This function provides access to the rounding behavior which is most efficient on the target processor.

### A.6 Input-Output

**Replace paragraph 1: [AI95-00285-01]**

Input-output is provided through language-defined packages, each of which is a child of the root package `Ada`. The generic packages `Sequential_IO` and `Direct_IO` define input-output operations applicable to files containing elements of a given type. The generic package `Storage_IO` supports reading from and writing to an in-memory buffer. Additional operations for text input-output are supplied in the packages `Text_IO` and `Wide_Text_IO`. Heterogeneous input-output is provided through the child packages `Streams.Stream_IO` and `Text_IO.Text_Streams` (see also 13.13). The package `IO_Exceptions` defines the exceptions needed by the predefined input-output packages.

**by:**

Input-output is provided through language-defined packages, each of which is a child of the root package `Ada`. The generic packages `Sequential_IO` and `Direct_IO` define input-output operations applicable to files containing elements of a given type. The generic package `Storage_IO` supports reading from and writing to an in-memory buffer. Additional operations for text input-output are supplied in the packages `Text_IO`, `Wide_Text_IO`, and `Wide_Wide_Text_IO`. Heterogeneous input-output is provided through the child packages `Streams.Stream_IO` and `Text_IO.Text_Streams` (see also 13.13). The package `IO_Exceptions` defines the exceptions needed by the predefined input-output packages.

### A.7 External Files and File Objects

**Replace paragraph 4: [AI95-00285-01]**

Input-output for direct access files is likewise defined by a generic package called `Direct_IO`. Input-output in human-readable form is defined by the (nongeneric) packages `Text_IO` for `Character` and `String` data, and `Wide_Text_IO` for `Wide_Character` and `Wide_String` data. Input-output for files containing streams of elements representing values of possibly different types is defined by means of the (nongeneric) package `Streams.Stream_IO`.

**by:**

Input-output for direct access files is likewise defined by a generic package called `Direct_IO`. Input-output in human-readable form is defined by the (nongeneric) packages `Text_IO` for `Character` and `String` data, `Wide_Text_IO` for `Wide_Character` and `Wide_String` data, and `Wide_Wide_Text_IO` for `Wide_Wide_Character` and `Wide_Wide_String` data. Input-output for files containing streams of elements representing values of possibly different types is defined by means of the (nongeneric) package `Streams.Stream_IO`.

**Replace paragraph 10: [AI95-00285-01]**

```
type File_Mode is (In_File, Out_File, Append_File);  
-- for Sequential_IO, Text_IO, Wide_Text_IO, and Stream_IO
```

by:

```
type File_Mode is (In_File, Out_File, Append_File);  
-- for Sequential_IO, Text_IO, Wide_Text_IO, Wide_Wide_Text_IO, and Stream_IO
```

**Replace paragraph 13: [AI95-00285-01]**

Several file management operations are common to Sequential\_IO, Direct\_IO, Text\_IO, and Wide\_Text\_IO. These operations are described in subclause A.8.2 for sequential and direct files. Any additional effects concerning text input-output are described in subclause A.10.2.

by:

Several file management operations are common to Sequential\_IO, Direct\_IO, Text\_IO, Wide\_Text\_IO, and Wide\_Wide\_Text\_IO. These operations are described in subclause A.8.2 for sequential and direct files. Any additional effects concerning text input-output are described in subclause A.10.2.

**Replace paragraph 15: [AI95-00285-01]**

18 Each instantiation of the generic packages Sequential\_IO and Direct\_IO declares a different type File\_Type. In the case of Text\_IO, Wide\_Text\_IO, and Streams.Stream\_IO, the corresponding type File\_Type is unique.

**Replace paragraph 15: [AI95-00285-01]**

18 Each instantiation of the generic packages Sequential\_IO and Direct\_IO declares a different type File\_Type. In the case of Text\_IO, Wide\_Text\_IO, Wide\_Wide\_Text\_IO, and Streams.Stream\_IO, the corresponding type File\_Type is unique.

## A.8 Sequential and Direct Files

**Replace paragraph 1: [AI95-00283-01]**

Two kinds of access to external files are defined in this subclause: *sequential access* and *direct access*. The corresponding file types and the associated operations are provided by the generic packages Sequential\_IO and Direct\_IO. A file object to be used for sequential access is called a *sequential file*, and one to be used for direct access is called a *direct file*. Access to stream files is described in A.12.1.

by:

Two kinds of access to external files are defined in this subclause: *sequential access* and *direct access*. The corresponding file types and the associated operations are provided by the generic packages Sequential\_IO and Direct\_IO. A file object to be used for sequential access is called a *sequential file*, and one to be used for direct access is called a *direct file*. Access to *stream files* is described in A.12.1.

### A.8.1 The Generic Package Sequential\_IO

**Insert after paragraph 16: [AI95-00360-01]**

```
private  
... -- not specified by the language  
end Ada.Sequential_IO;
```

**the new paragraph:**

The type File\_Type needs finalization (see 7.6) in every instantiation of Sequential\_IO.

## A.8.2 File Management

### Replace paragraph 3: [AI95-00283-01]

Establishes a new external file, with the given name and form, and associates this external file with the given file. The given file is left open. The current mode of the given file is set to the given access mode. The default access mode is the mode `Out_File` for sequential and text input-output; it is the mode `Inout_File` for direct input-output. For direct access, the size of the created file is implementation defined.

by:

Establishes a new external file, with the given name and form, and associates this external file with the given file. The given file is left open. The current mode of the given file is set to the given access mode. The default access mode is the mode `Out_File` for sequential, stream, and text input-output; it is the mode `Inout_File` for direct input-output. For direct access, the size of the created file is implementation defined.

### Replace paragraph 16: [AI95-00085-01]

Resets the given file so that reading from its elements can be restarted from the beginning of the file (for modes `In_File` and `Inout_File`), and so that writing to its elements can be restarted at the beginning of the file (for modes `Out_File` and `Inout_File`) or after the last element of the file (for mode `Append_File`). In particular, for direct access this means that the current index is set to one. If a `Mode` parameter is supplied, the current mode of the given file is set to the given mode. In addition, for sequential files, if the given file has mode `Out_File` or `Append_File` when `Reset` is called, the last element written since the most recent open or reset is the last element that can be read from the file. If no elements have been written and the file mode is `Out_File`, the reset file is empty. If no elements have been written and the file mode is `Append_File`, then the reset file is unchanged.

by:

Resets the given file so that reading from its elements can be restarted from the beginning of the external file (for modes `In_File` and `Inout_File`), and so that writing to its elements can be restarted at the beginning of the external file (for modes `Out_File` and `Inout_File`) or after the last element of the external file (for mode `Append_File`). In particular, for direct access this means that the current index is set to one. If a `Mode` parameter is supplied, the current mode of the given file is set to the given mode. In addition, for sequential files, if the given file has mode `Out_File` or `Append_File` when `Reset` is called, the last element written since the most recent open or reset is the last element that can be read from the external file. If no elements have been written and the file mode is `Out_File`, the reset file is empty. If no elements have been written and the file mode is `Append_File`, then the reset file is unchanged.

### Replace paragraph 22: [AI95-00248-01]

Returns a string which uniquely identifies the external file currently associated with the given file (and may thus be used in an `Open` operation). If an external environment allows alternative specifications of the name (for example, abbreviations), the string returned by the function should correspond to a full specification of the name.

by:

Returns a string which uniquely identifies the external file currently associated with the given file (and may thus be used in an `Open` operation).

## A.8.4 The Generic Package `Direct_IO`

### Insert after paragraph 19: [AI95-00360-01]

```
private
  ... -- not specified by the language
end Ada.Direct_IO;
```

the new paragraph:

The type `File_Type` needs finalization (see 7.6) in every instantiation of `Direct_IO`.

### A.10.1 The Package `Text_IO`

Insert after paragraph 48: [AI95-00301-01]

```
procedure Put(File : in File_Type; Item : in String);
procedure Put(Item : in String);
```

the new paragraphs:

```
function Get_Line(File : in File_Type) return String;
function Get_Line return String;
```

Insert after paragraph 85: [AI95-00360-01]

```
Status_Error : exception renames IO_Exceptions.Status_Error;
Mode_Error   : exception renames IO_Exceptions.Mode_Error;
Name_Error   : exception renames IO_Exceptions.Name_Error;
Use_Error    : exception renames IO_Exceptions.Use_Error;
Device_Error : exception renames IO_Exceptions.Device_Error;
End_Error    : exception renames IO_Exceptions.End_Error;
Data_Error   : exception renames IO_Exceptions.Data_Error;
Layout_Error : exception renames IO_Exceptions.Layout_Error;
private
  ... -- not specified by the language
end Ada.Text_IO;
```

the new paragraph:

The type `File_Type` needs finalization (see 7.6).

### A.10.6 Get and Put Procedures

In paragraph 5 replace: [AI95-00223-01]

Input-output of enumeration values uses the syntax of the corresponding lexical elements. Any `Get` procedure for an enumeration type begins by skipping any leading blanks, or line or page terminators. `Get` procedures for numeric or enumeration types start by skipping leading blanks, where a *blank* is defined as a space or a horizontal tabulation character. Next, characters are input only so long as the sequence input is an initial sequence of an identifier or of a character literal (in particular, input ceases when a line terminator is encountered). The character or line terminator that causes input to cease remains available for subsequent input.

by:

Input-output of enumeration values uses the syntax of the corresponding lexical elements. Any `Get` procedure for an enumeration type begins by skipping any leading blanks, or line or page terminators. A *blank* is defined as a space or a horizontal tabulation character. Next, characters are input only so long as the sequence input is an initial sequence of an identifier or of a character literal (in particular, input ceases when a line terminator is encountered). The character or line terminator that causes input to cease remains available for subsequent input.

### A.10.7 Input-Output of Characters and Strings

Replace paragraph 13: [AI95-00301-01]

For an item of type `String`, the following procedures are provided:

by:

For an item of type String, the following subprograms are provided:

**Insert after paragraph 17: [AI95-00301-01]**

Determines the length of the given string and attempts that number of Put operations for successive characters of the string (in particular, no operation is performed if the string is null).

**the new paragraphs:**

```
function Get_Line(File : in File_Type) return String;
function Get_Line return String;
```

Returns a result string constructed by reading successive characters from the specified input file, and assigning them to successive characters of the result string. The result string has a lower bound of 1 and an upper bound of the number of characters read. Reading stops when the end of the line is met; Skip\_Line is then (in effect) called with a spacing of 1.

The exception End\_Error is propagated if an attempt is made to skip a file terminator.

## A.10.11 Input-Output for Unbounded Strings

**Insert new clause: [AI95-00301-01]**

The package Text\_IO.Unbounded\_IO provides input-output in human-readable form for Unbounded\_Strings.

*Static Semantics*

The library package Text\_IO.Unbounded\_IO has the following declaration:

```
with Ada.Strings.Unbounded;
package Ada.Text_IO.Unbounded_IO is

  procedure Put
    (File : in File_Type;
     Item : in Strings.Unbounded.Unbounded_String);

  procedure Put
    (Item : in Strings.Unbounded.Unbounded_String);

  procedure Put_Line
    (File : in Text_IO.File_Type;
     Item : in Strings.Unbounded.Unbounded_String);

  procedure Put_Line
    (Item : in Strings.Unbounded.Unbounded_String);

  function Get_Line
    (File : in File_Type)
    return Strings.Unbounded.Unbounded_String;

  function Get_Line
    return Strings.Unbounded.Unbounded_String;

  procedure Get_Line
    (File : in File_Type; Item : out Strings.Unbounded.Unbounded_String);

  procedure Get_Line
    (Item : out Strings.Unbounded.Unbounded_String);

end Ada.Text_IO.Unbounded_IO;
```

For an item of type Unbounded\_String, the following subprograms are provided:

```
procedure Put
```

```
(File : in File_Type;
Item : in Strings.Unbounded.Unbounded_String);

Equivalent to Text_IO.Put (File, Strings.Unbounded.To_String(Item));

procedure Put
(Item : in Strings.Unbounded.Unbounded_String);

Equivalent to Text_IO.Put (Strings.Unbounded.To_String(Item));

procedure Put_Line
(File : in Text_IO.File_Type;
Item : in Strings.Unbounded.Unbounded_String);

Equivalent to Text_IO.Put_Line (File, Strings.Unbounded.To_String(Item));

procedure Put_Line
(Item : in Strings.Unbounded.Unbounded_String);

Equivalent to Text_IO.Put_Line (Strings.Unbounded.To_String(Item));

function Get_Line
(File : in File_Type)
return Strings.Unbounded.Unbounded_String;

Returns Strings.Unbounded.To_Unbounded_String(Text_IO.Get_Line(File));

function Get_Line
return Strings.Unbounded.Unbounded_String;

Returns Strings.Unbounded.To_Unbounded_String(Text_IO.Get_Line);

procedure Get_Line
(File : in File_Type; Item : out Strings.Unbounded.Unbounded_String);

Equivalent to Item := Get_Line (File);

procedure Get_Line
(Item : out Strings.Unbounded.Unbounded_String);

Equivalent to Item := Get_Line;
```

## A.11 Wide Text Input-Output and Wide Wide Text Input-Output

### Replace the title: [AI95-00285-01]

Wide Text Input-Output

by:

Wide Text Input-Output and Wide Wide Text Input-Output

### Replace paragraph 1: [AI95-00285-01]

The package Wide\_Text\_IO provides facilities for input and output in human-readable form. Each file is read or written sequentially, as a sequence of wide characters grouped into lines, and as a sequence of lines grouped into pages.

by:

The packages Wide\_Text\_IO and Wide\_Wide\_Text\_IO provide facilities for input and output in human-readable form. Each file is read or written sequentially, as a sequence of wide characters (or wide wide characters) grouped into lines, and as a sequence of lines grouped into pages.

### Replace paragraph 2: [AI95-00285-01]

The specification of package Wide\_Text\_IO is the same as that for Text\_IO, except that in each Get, Look\_Ahead, Get\_Immediate, Get\_Line, Put, and Put\_Line procedure, any occurrence of Character is replaced by Wide\_Character, and any occurrence of String is replaced by Wide\_String.

by:

The specification of package `Wide_Text_IO` is the same as that for `Text_IO`, except that in each `Get`, `Look_Ahead`, `Get_Immediate`, `Get_Line`, `Put`, and `Put_Line` procedure, any occurrence of `Character` is replaced by `Wide_Character`, and any occurrence of `String` is replaced by `Wide_String`. Nongeneric equivalents of `Wide_Text_IO.Integer_IO` and `Wide_Text_IO.Float_IO` are provided (as for `Text_IO`) for each predefined numeric type, with names such as `Ada.Integer_Wide_Text_IO`, `Ada.Long_Integer_Wide_Text_IO`, `Ada.Float_Wide_Text_IO`, `Ada.Long_Float_Wide_Text_IO`.

**Replace paragraph 3: [AI95-00285-01; AI95-00301-01]**

Nongeneric equivalents of `Wide_Text_IO.Integer_IO` and `Wide_Text_IO.Float_IO` are provided (as for `Text_IO`) for each predefined numeric type, with names such as `Ada.Integer_Wide_Text_IO`, `Ada.Long_Integer_Wide_Text_IO`, `Ada.Float_Wide_Text_IO`, `Ada.Long_Float_Wide_Text_IO`.

by:

The specification of package `Wide_Wide_Text_IO` is the same as that for `Text_IO`, except that in each `Get`, `Look_Ahead`, `Get_Immediate`, `Get_Line`, `Put`, and `Put_Line` procedure, any occurrence of `Character` is replaced by `Wide_Wide_Character`, and any occurrence of `String` is replaced by `Wide_Wide_String`. Nongeneric equivalents of `Wide_Wide_Text_IO.Integer_IO` and `Wide_Wide_Text_IO.Float_IO` are provided (as for `Text_IO`) for each predefined numeric type, with names such as `Ada.Integer_Wide_Wide_Text_IO`, `Ada.Long_Integer_Wide_Wide_Text_IO`, `Ada.Float_Wide_Wide_Text_IO`, `Ada.Long_Float_Wide_Wide_Text_IO`.

The specification of package `Wide_Text_IO.Wide_Unbounded_IO` is the same as that for `Text_IO.Unbounded_IO`, except that any occurrence of `Unbounded_String` is replaced by `Wide_Unbounded_String`, and any occurrence of package `Unbounded` is replaced by `Wide_Unbounded`. The specification of package `Wide_Wide_Text_IO.Wide_Unbounded_IO` is the same as that for `Text_IO.Unbounded_IO`, except that any occurrence of `Unbounded_String` is replaced by `Wide_Wide_Unbounded_String`, and any occurrence of package `Unbounded` is replaced by `Wide_Wide_Unbounded`.

## A.12 Stream Input-Output

**Replace paragraph 1: [AI95-00285-01]**

The packages `Streams.Stream_IO`, `Text_IO.Text_Streams`, and `Wide_Text_IO.Text_Streams` provide stream-oriented operations on files.

by:

The packages `Streams.Stream_IO`, `Text_IO.Text_Streams`, `Wide_Text_IO.Text_Streams`, and `Wide_Wide_Text_IO.Text_Streams` provide stream-oriented operations on files.

### A.12.1 The Package `Streams.Stream_IO`

**Insert after paragraph 27: [AI95-00360-01]**

```
private
    ... -- not specified by the language
end Ada.Streams.Stream_IO;
```

the new paragraph:

The type `File_Type` needs finalization (see 7.6).

**Replace paragraph 28: [AI95-00283-01]**

The subprograms `Create`, `Open`, `Close`, `Delete`, `Reset`, `Mode`, `Name`, `Form`, `Is_Open`, and `End_of_File` have the same effect as the corresponding subprograms in `Sequential_IO` (see A.8.2).

**by:**

The subprograms given in subclause A.8.2 for the control of external files (Create, Open, Close, Delete, Reset, Mode, Name, Form, and Is\_Open) are available for stream files.

The End\_of\_File function:

- Propagates Mode\_Error if the mode of the file is not In\_File;
- If positioning is supported for the given external file, the function returns True if the current index exceeds the size of the external file; otherwise it returns False;
- If positioning is not supported for the given external file, the function returns True if no more elements can be read from the given file; otherwise it returns False.

**Replace paragraph 28.1: [AI95-00085-01]**

The Set\_Mode procedure changes the mode of the file. If the new mode is Append\_File, the file is positioned to its end; otherwise, the position in the file is unchanged.

**by:**

The Set\_Mode procedure sets the mode of the file. If the new mode is Append\_File, the file is positioned to its end; otherwise, the position in the file is unchanged.

**Replace paragraph 30: [AI95-00256-01]**

The procedures Read and Write are equivalent to the corresponding operations in the package Streams. Read propagates Mode\_Error if the mode of File is not In\_File. Write propagates Mode\_Error if the mode of File is not Out\_File or Append\_File. The Read procedure with a Positive\_Count parameter starts reading at the specified index. The Write procedure with a Positive\_Count parameter starts writing at the specified index.

**by:**

The procedures Read and Write are equivalent to the corresponding operations in the package Streams. Read propagates Mode\_Error if the mode of File is not In\_File. Write propagates Mode\_Error if the mode of File is not Out\_File or Append\_File. The Read procedure with a Positive\_Count parameter starts reading at the specified index. The Write procedure with a Positive\_Count parameter starts writing at the specified index. For a file that supports positioning, Read without a Positive\_Count parameter starts reading at the current index, and Write without a Positive\_Count parameter starts writing at the current index.

## **A.12.4 The Package Wide\_Wide\_Text\_IO.Text\_Streams**

**Insert new clause: [AI95-00285-01]**

The package Wide\_Wide\_Text\_IO.Text\_Streams provides a function for treating a wide wide text file as a stream.

*Static Semantics*

The library package Wide\_Wide\_Text\_IO.Text\_Streams has the following declaration:

```
with Ada.Streams;  
package Ada.Wide_Wide_Text_IO.Text_Streams is  
  type Stream_Access is access all Streams.Root_Stream_Type'Class;  
  function Stream (File : in File_Type) return Stream_Access;  
end Ada.Wide_Wide_Text_IO.Text_Streams;
```

The Stream function has the same effect as the corresponding function in Streams.Stream\_IO.

## **A.16 The Package Directories**

**Insert new clause: [AI95-00248-01]**

The package Directories provides operations for manipulating files and directories, and their names.



*Static Semantics*

The library package Directories has the following declaration:

```

with Ada.IO_Exceptions;
with Ada.Calendar;
package Ada.Directories is

    -- Directory and file operations:

    function Current_Directory return String;
    procedure Set_Directory (Directory : in String);

    procedure Create_Directory (New_Directory : in String;
                               Form : in String := "");

    procedure Delete_Directory (Directory : in String);

    procedure Create_Path (New_Directory : in String;
                           Form : in String := "");

    procedure Delete_Tree (Directory : in String);

    procedure Delete_File (Name : in String);

    procedure Rename (Old_Name, New_Name : in String);

    procedure Copy_File (Source_Name, Target_Name : in String;
                         Form : in String := "");

    -- File and directory name operations:

    function Full_Name (Name : in String) return String;

    function Simple_Name (Name : in String) return String;

    function Containing_Directory (Name : in String) return String;

    function Extension (Name : in String) return String;

    function Base_Name (Name : in String) return String;

    function Compose (Containing_Directory : in String := "";
                     Name : in String;
                     Extension : in String := "") return String;

    -- File and directory queries:

    type File_Kind is (Directory, Ordinary_File, Special_File);

    type File_Size is range 0 .. implementation-defined;

    function Exists (Name : in String) return Boolean;

    function Kind (Name : in String) return File_Kind;

    function Size (Name : in String) return File_Size;

    function Modification_Time (Name : in String) return Ada.Calendar.Time;

    -- Directory searching:

    type Directory_Entry_Type is limited private;

    type Filter_Type is array (File_Kind) of Boolean;

    type Search_Type is limited private;

```

```

procedure Start_Search (Search : in out Search_Type;
    Directory : in String;
    Pattern : in String;
    Filter : in Filter_Type := (others => True));

procedure End_Search (Search : in out Search_Type);

function More_Entries (Search : in Search_Type) return Boolean;

procedure Get_Next_Entry (Search : in out Search_Type;
    Directory_Entry : out Directory_Entry_Type);

procedure Search (
    Directory : in String;
    Pattern : in String;
    Filter : in Filter_Type := (others => True);
    Process : not null access procedure (Directory_Entry : in
Directory_Entry_Type));

-- Operations on Directory Entries:

function Simple_Name (Directory_Entry : in Directory_Entry_Type)
    return String;

function Full_Name (Directory_Entry : in Directory_Entry_Type)
    return String;

function Kind (Directory_Entry : in Directory_Entry_Type)
    return File_Kind;

function Size (Directory_Entry : in Directory_Entry_Type)
    return File_Size;

function Modification_Time (Directory_Entry : in Directory_Entry_Type)
    return Ada.Calendar.Time;

Status_Error : exception renames Ada.IO_Exceptions.Status_Error;
Name_Error : exception renames Ada.IO_Exceptions.Name_Error;
Use_Error : exception renames Ada.IO_Exceptions.Use_Error;
Device_Error : exception renames Ada.IO_Exceptions.Device_Error;

private
    -- Not specified by the language.
end Ada.Directories;

```

External files may be classified as directories, special files, or ordinary files. A *directory* is an external file that is a container for files on the target system. A *special file* is an external file that cannot be created or read by a predefined Ada Input-Output package. External files that are not special files or directories are called *ordinary files*.

A *file name* is a string identifying an external file. Similarly, a *directory name* is a string identifying a directory. The interpretation of file names and directory names is implementation-defined.

The *full name* of an external file is a full specification of the name of the file. If the external environment allows alternative specifications of the name (for example, abbreviations), the full name should not use such alternatives. A full name typically will include the names of all of directories that contain the item. The *simple name* of an external file is the name of the item, not including any containing directory names. Unless otherwise specified, a file name or directory name parameter to a predefined Ada input-output subprogram can be a full name, a simple name, or any other form of name supported by the implementation.

The *default directory* is the directory that is used if a directory or file name is not a full name (that is, when the name does not fully identify all of the containing directories).

A *directory entry* is a single item in a directory, identifying a single external file (including directories and special files).

For each function that returns a string, the lower bound of the returned value is 1.

The following file and directory operations are provided:

**function** Current\_Directory **return** String;

Returns the full directory name for the current default directory. The name returned shall be suitable for a future call to Set\_Directory. The exception Use\_Error is propagated if a default directory is not supported by the external environment.

**procedure** Set\_Directory (Directory : **in** String);

Sets the current default directory. The exception Name\_Error is propagated if the string given as Directory does not identify an existing directory. The exception Use\_Error is propagated if the external environment does not support making Directory (in the absence of Name\_Error) a default directory.

**procedure** Create\_Directory (New\_Directory : **in** String;  
Form : **in** String := "");

Creates a directory with name New\_Directory. The Form parameter can be used to give system-dependent characteristics of the directory; the interpretation of the Form parameter is implementation-defined. A null string for Form specifies the use of the default options of the implementation of the new directory. The exception Name\_Error is propagated if the string given as New\_Directory does not allow the identification of a directory. The exception Use\_Error is propagated if the external environment does not support the creation of a directory with the given name (in the absence of Name\_Error) and form.

**procedure** Delete\_Directory (Directory : **in** String);

Deletes an existing empty directory with name Directory. The exception Name\_Error is propagated if the string given as Directory does not identify an existing directory. The exception Use\_Error is propagated if the external environment does not support the deletion of the directory (or some portion of its contents) with the given name (in the absence of Name\_Error).

**procedure** Create\_Path (New\_Directory : **in** String;  
Form : **in** String := "");

Creates zero or more directories with name New\_Directory. Each non-existent directory named by New\_Directory is created. For example, on a typical Unix system, Create\_Path ("/usr/me/my"); would create directory "me" in directory "usr", then create directory "my" in directory "me". The Form can be used to give system-dependent characteristics of the directory; the interpretation of the Form parameter is implementation-defined. A null string for Form specifies the use of the default options of the implementation of the new directory. The exception Name\_Error is propagated if the string given as New\_Directory does not allow the identification of any directory. The exception Use\_Error is propagated if the external environment does not support the creation of any directories with the given name (in the absence of Name\_Error) and form.

**procedure** Delete\_Tree (Directory : **in** String);

Deletes an existing directory with name Directory. The directory and all of its contents (possibly including other directories) are deleted. The exception Name\_Error is propagated if the string given as Directory does not identify an existing directory. The exception Use\_Error is propagated if the external environment does not support the deletion of the directory or some portion of its contents with the given name (in the absence of Name\_Error). If Use\_Error is propagated, it is unspecified if a portion of the contents of the directory are deleted.

**procedure** Delete\_File (Name : **in** String);

Deletes an existing ordinary or special file with Name. The exception Name\_Error is propagated if the string given as Name does not identify an existing ordinary or special external file. The

exception `Use_Error` is propagated if the external environment does not support the deletion of the file with the given name (in the absence of `Name_Error`).

**procedure** `Rename` (`Old_Name`, `New_Name` : **in** `String`);

Renames an existing external file (including directories) with `Old_Name` to `New_Name`. The exception `Name_Error` is propagated if the string given as `Old_Name` does not identify an existing external file. The exception `Use_Error` is propagated if the external environment does not support the renaming of the file with the given name (in the absence of `Name_Error`). In particular, `Use_Error` is propagated if a file or directory already exists with `New_Name`.

**procedure** `Copy_File` (`Source_Name`, `Target_Name` : **in** `String`;  
                          `Form` : **in** `String`);

Copies the contents of the existing external file with `Source_Name` to `Target_Name`. The resulting external file is a duplicate of the source external file. The `Form` can be used to give system-dependent characteristics of the resulting external file; the interpretation of the `Form` parameter is implementation-defined. Exception `Name_Error` is propagated if the string given as `Source_Name` does not identify an existing external ordinary or special file or if the string given as `Target_Name` does not allow the identification of an external file. The exception `Use_Error` is propagated if the external environment does not support the creating of the file with the name given by `Target_Name` and form given by `Form`, or copying of the file with the name given by `Source_Name` (in the absence of `Name_Error`).

The following file and directory name operations are provided:

**function** `Full_Name` (`Name` : **in** `String`) **return** `String`;

Returns the full name corresponding to the file name specified by `Name`. The exception `Name_Error` is propagated if the string given as `Name` does not allow the identification of an external file (including directories and special files).

**function** `Simple_Name` (`Name` : **in** `String`) **return** `String`;

Returns the simple name portion of the file name specified by `Name`. The exception `Name_Error` is propagated if the string given as `Name` does not allow the identification of an external file (including directories and special files).

**function** `Containing_Directory` (`Name` : **in** `String`) **return** `String`;

Returns the name of the containing directory of the external file (including directories) identified by `Name`. (If more than one directory can contain `Name`, the directory name returned is implementation-defined.) The exception `Name_Error` is propagated if the string given as `Name` does not allow the identification of an external file. The exception `Use_Error` is propagated if the external file does not have a containing directory.

**function** `Extension` (`Name` : **in** `String`) **return** `String`;

Returns the extension name corresponding to `Name`. The extension name is a portion of a simple name (not including any separator characters), typically used to identify the file class. If the external environment does not have extension names, then the null string is returned. The exception `Name_Error` is propagated if the string given as `Name` does not allow the identification of an external file.

**function** `Base_Name` (`Name` : **in** `String`) **return** `String`;

Returns the base name corresponding to `Name`. The base name is the remainder of a simple name after removing any extension and extension separators. The exception `Name_Error` is propagated if the string given as `Name` does not allow the identification of an external file (including directories and special files).

**function** `Compose` (`Containing_Directory` : **in** `String` := "";  
                  `Name` : **in** `String`;  
                  `Extension` : **in** `String` := "") **return** `String`;

Returns the name of the external file with the specified `Containing_Directory`, `Name`, and `Extension`. If `Extension` is the null string, then `Name` is interpreted as a simple name; otherwise `Name` is interpreted as a base name. The exception `Name_Error` is propagated if the string given as `Containing_Directory` is not null and does not allow the identification of a directory, or if the string given as `Extension` is not null and is not a possible extension, or if the string given as `Name` is not a possible simple name (if `Extension` is null) or base name (if `Extension` is non-null).

The following file and directory queries and types are provided:

```
type File_Kind is (Directory, Ordinary_File, Special_File);
```

The type `File_Kind` represents the kind of file represented by an external file or directory.

```
type File_Size is range 0 .. implementation-defined;
```

The type `File_Size` represents the size of an external file.

```
function Exists (Name : in String) return Boolean;
```

Returns True if external file represented by `Name` exists, and False otherwise. The exception `Name_Error` is propagated if the string given as `Name` does not allow the identification of an external file (including directories and special files).

```
function Kind (Name : in String) return File_Kind;
```

Returns the kind of external file represented by `Name`. The exception `Name_Error` is propagated if the string given as `Name` does not allow the identification of an existing external file.

```
function Size (Name : in String) return File_Size;
```

Returns the size of the external file represented by `Name`. The size of an external file is the number of stream elements contained in the file. If the external file is discontinuous (not all elements exist), the result is implementation-defined. If the external file is not an ordinary file, the result is implementation-defined. The exception `Name_Error` is propagated if the string given as `Name` does not allow the identification of an existing external file. The exception `Constraint_Error` is propagated if the file size is not a value of type `File_Size`.

```
function Modification_Time (Name : in String) return Ada.Calendar.Time;
```

Returns the time that the external file represented by `Name` was most recently modified. If the external file is not an ordinary file, the result is implementation-defined. The exception `Name_Error` is propagated if the string given as `Name` does not allow the identification of an existing external file. The exception `Use_Error` is propagated if the external environment does not support the reading the modification time of the file with the name given by `Name` (in the absence of `Name_Error`).

The following directory searching operations and types are provided:

```
type Directory_Entry_Type is limited private;
```

The type `Directory_Entry_Type` represents a single item in a directory. These items can only be created by the `Get_Next_Entry` procedure in this package. Information about the item can be obtained from the functions declared in this package. A default initialized object of this type is invalid; objects returned from `Get_Next_Entry` are valid.

```
type Filter_Type is array (File_Kind) of Boolean;
```

The type `Filter_Type` specifies which directory entries are provided from a search operation. If the `Directory` component is True, directory entries representing directories are provided. If the `Ordinary_File` component is True, directory entries representing ordinary files are provided. If the `Special_File` component is True, directory entries representing special files are provided.

```
type Search_Type is limited private;
```

The type `Search_Type` contains the state of a directory search. A default-initialized `Search_Type` object has no entries available (`More_Entries` returns False).

```

procedure Start_Search (Search : in out Search_Type;
                        Directory : in String;
                        Pattern : in String;
                        Filter : in Filter_Type := (others => True));

```

Starts a search in the directory entry in the directory named by Directory for entries matching Pattern. Pattern represents a file name matching pattern. If Pattern is null, all items in the directory are matched; otherwise, the interpretation of Pattern is implementation-defined. Only items which match Filter will be returned. After a successful call on Start\_Search, the object Search may have entries available, but it may have no entries available if no files or directories match Pattern and Filter. The exception Name\_Error is propagated if the string given by Directory does not identify an existing directory, or if Pattern does not allow the identification of any possible external file or directory. The exception Use\_Error is propagated if the external environment does not support the searching of the directory with the given name (in the absence of Name\_Error).

```

procedure End_Search (Search : in out Search_Type);

```

Ends the search represented by Search. After a successful call on End\_Search, the object Search will have no entries available.

```

function More_Entries (Search : in Search_Type) return Boolean;

```

Returns True if more entries are available to be returned by a call to Get\_Next\_Entry for the specified search object, and False otherwise.

```

procedure Get_Next_Entry (Search : in out Search_Type;
                        Directory_Entry : out Directory_Entry_Type);

```

Returns the next Directory\_Entry for the search described by Search that matches the pattern and filter. If no further matches are available, Status\_Error is raised. It is implementation-defined as to whether the results returned by this routine are altered if the contents of the directory are altered while the Search object is valid (for example, by another program). The exception Use\_Error is propagated if the external environment does not support continued searching of the directory represented by Search.

```

procedure Search (
    Directory : in String;
    Pattern : in String;
    Filter : in Filter_Type := (others => True);
    Process : not null access procedure
        (Directory_Entry : in Directory_Entry_Type));

```

Searches in the directory entry in the directory named by Directory, calling the subprogram designated by Process passing each entry matching Pattern. Pattern represents a file name matching pattern. If Pattern is null, all items in the directory are matched; otherwise, the interpretation of Pattern is implementation-defined. Only items which match Filter will be returned. The exception Name\_Error is propagated if the string given by Directory does not identify an existing directory, or if Pattern does not allow the identification of any possible external file or directory. The exception Use\_Error is propagated if the external environment does not support the searching of the directory with the given name (in the absence of Name\_Error).

```

function Simple_Name (Directory_Entry : in Directory_Entry_Type)
    return String;

```

Returns the simple external name of the external file (including directories) represented by Directory\_Entry. The format of the name returned is implementation-defined. The exception Status\_Error is propagated if Directory\_Entry is invalid.

```

function Full_Name (Directory_Entry : in Directory_Entry_Type)
    return String;

```

Returns the full external name of the external file (including directories) represented by Directory\_Entry. The format of the name returned is implementation-defined. The exception Status\_Error is propagated if Directory\_Entry is invalid.

```
function Kind (Directory_Entry : in Directory_Entry_Type)
  return File_Kind;
```

Returns the kind of external file represented by Directory\_Entry. The exception Status\_Error is propagated if Directory\_Entry is invalid.

```
function Size (Directory_Entry : in Directory_Entry_Type)
  return File_Size;
```

Returns the size of the external file represented by Directory\_Entry. The size of an external file is the number of stream elements contained in the file. If the external file is discontinuous (not all elements exist), the result is implementation-defined. If the external file represented by Directory\_Entry is not an ordinary file, the result is implementation-defined. The exception Status\_Error is propagated if Directory\_Entry is invalid. The exception Constraint\_Error is propagated if the file size is not a value of type File\_Size.

```
function Modification_Time (Directory_Entry : in Directory_Entry_Type)
  return Ada.Calendar.Time;
```

Returns the time that the external file represented by Directory\_Entry was most recently modified. If the external file represented by Directory\_Entry is not an ordinary file, the result is implementation-defined. The exception Status\_Error is propagated if Directory\_Entry is invalid. The exception Use\_Error is propagated if the external environment does not support the reading the modification time of the file represented by Directory\_Entry.

#### *Implementation Requirements*

For Copy\_File, if Source\_Name identifies an existing external ordinary file created by a predefined Ada Input-Output package, and Target\_Name and Form can be used in the Create operation of that Input-Output package with mode Out\_File without raising an exception, then Copy\_File shall not propagate Use\_Error.

#### *Implementation Advice*

If other information about a file is available (such as the owner or creation date) in a directory entry, the implementation should provide functions in a child package Directories.Information to retrieve it.

Start\_Search and Search should raise Use\_Error if Pattern is malformed, but not if it could represent a file in the directory but does not actually do so.

For Rename, if both New\_Name and Old\_Name are simple names, then Rename should not propagate Use\_Error.

#### NOTES

37 The file name operations Containing\_Directory, Full\_Name, Simple\_Name, Base\_Name, Extension, and Compose operate on file names, not external files. The files identified by these operations do not need to exist. Name\_Error is raised only if the file name is malformed and cannot possibly identify a file.

38 Using access types, values of Search\_Type and Directory\_Entry\_Type can be saved and queried later. However, another task or application can modify or delete the file represented by a Directory\_Entry\_Type value or the directory represented by a Search\_Type value; such a value can only give the information valid at the time it is created. Therefore, long-term storage of these values is not recommended.

39 If the target system does not support directories inside of directories, Is\_Directory will always return False, and Containing\_Directory will always raise Use\_Error.

40 If the target system does not support creation or deletion of directories, Create\_Directory, Create\_Path, Delete\_Directory, and Delete\_Tree will always propagate Use\_Error.

## A.17 The Package Environment\_Variables

The package Environment\_Variables allows a program to read or modify the environment variables. Environment variables are name-value pairs, where both the name and value are strings. The definition of what constitutes an "environment variable", and the meaning of the name and value, are implementation defined.

*Static Semantics*

The library package Environment\_Variables has the following declaration:

```
package Ada.Environment_Variables is
  pragma Preelaborate(Environment_Variables);

  function Value (Name : in String) return String;

  function Exists (Name : in String) return Boolean;

  procedure Set (Name : in String; Value : in String);

  procedure Clear (Name : in String);
  procedure Clear;

  procedure Iterate (
    Process : not null access procedure (Name, Value : in String));

end Ada.Environment_Variables;

function Value (Name : in String) return String;
```

If the external execution environment supports environment variables, then Value returns the value of the environment variable with the given name. If no environment variable with the given name exists, then Constraint\_Error is propagated. If the execution environment does not support environment variables, then Program\_Error is propagated.

```
function Exists (Name : in String) return Boolean;
```

If the external execution environment supports environment variables and an environment variable with the given name currently exists, then Exists returns True; otherwise it returns False.

```
procedure Set (Name : in String; Value : in String);
```

If the external execution environment supports environment variables, then Set first clears any existing environment variable with the given name, and then defines a single new environment variable with the given name and value. Otherwise Program\_Error is propagated.

If implementation-defined circumstances prohibit the definition of an environment variable with the given name and value, then Constraint\_Error is propagated.

It is implementation defined whether there exist values for which the call Set(Name, Value) has the same effect as Clear (Name).

```
procedure Clear (Name : in String);
```

If the external execution environment supports environment variables, then Clear deletes all existing environment variable with the given name. Otherwise Program\_Error is propagated.

```
procedure Clear;
```

If the external execution environment supports environment variables, then Clear deletes all existing environment variables. Otherwise Program\_Error is propagated.

```
procedure Iterate (
  Process : not null access procedure (Name, Value : in String));
```

If the external execution environment supports environment variables, then Iterate calls the subprogram designated by Process for each existing environment variable, passing the name and value of that environment variable. Otherwise Program\_Error is propagated.

If several environment variables exist which have the same name, Process is called once for each such variable.

*Bounded (Run-Time) Errors*

It is a bounded error to call Value if more than one environment variable exists with the given name; the possible outcomes are that:



- one of the values is returned, and that same value is returned in subsequent calls in the absence of changes to the environment; or
- Program\_Error is propagated.

#### *Erroneous Execution*

Making calls to the procedures Set or Clear concurrently with calls to any subprogram of package Environment\_Variables, or to any instantiation of Iterate, results in erroneous execution.

Making calls to the procedures Set or Clear in the actual subprogram corresponding to the Process parameter of Iterate results in erroneous execution.

#### *Documentation Requirements*

An implementation shall document how the operations of this package behave if environment variables are changed by external mechanisms (for instance, calling operating system services).

#### *Implementation Permissions*

An implementation running on a system which does not support environment variables is permitted to define the operations of package Environment\_Variables with the semantics corresponding to the case where the external execution environment does support environment variables. In this case, it shall provide a mechanism to initialize a nonempty set of environment variables prior to the execution of a partition.

#### *Implementation Advice*

If the execution environment supports subprocesses, the currently defined environment variables should be used to initialize the environment variables of the subprocess.

Changes to the environment variables made outside the control of this package should be reflected immediately in the effect of the operations of this package. Changes to the environment variables made using this package should be reflected immediately in the external execution environment. This package should not perform any buffering of the environment variables.

## A.18 Containers

### **Insert new clause: [AI95-00302-03]**

This clause presents the specifications of the package Containers and several child packages, which provide facilities for storing collections of elements.

A variety of sequence and associative containers are provided. Each container includes a *cursor* type. A cursor is a reference to an element within a container. Many operations on cursors are common to all of the containers.

Within this clause we provide Implementation Advice for the desired average or worst case time complexity of certain operations on a container. This advice is expressed using a big-O notation. A complexity of  $O(f(N))$ , presuming  $f$  is some function of a length parameter  $N$  and  $t(N)$  is the time the operation takes (on average or worst case, as specified) for the length  $N$ , means that there exists a finite  $A$  such that for any  $N$ ,  $t(N)/f(N) < A$ .

If the advice suggests that the complexity should be less than  $O(f(N))$ , then for any arbitrarily small positive real  $D$ , there should exist a positive integer  $M$  such that for all  $N > M$ ,  $t(N)/f(N) < D$ .

### A.18.1 The Package Containers

#### **Insert new clause: [AI95-00302-03]**

The package Containers is the root of the containers subsystem.

#### *Static Semantics*

The library package Containers has the following declaration:

```

package Ada.Containers is
  pragma Pure(Containers);

  type Hash_Type is mod implementation-defined;

  type Count_Type is range 0 .. implementation-defined;

end Ada.Containers;

```

Hash\_Type represents the range of the result of a hash function. Count\_Type represents the (potential or actual) number of elements of a container.

*Implementation Advice*

Hash\_Type'Modulus should be at least  $2^{32}$ . Count\_Type'Last should be at least  $2^{31}-1$ .

## A.18.2 The Package Containers.Vectors

**Insert new clause: [AI95-00302-03]**

The language-defined generic package Containers.Vectors provides private types Vector and Cursor, and a set of operations for each type. A vector container allows insertion and deletion at any position, but it is specifically optimized for insertion and deletion at the high end (the end with the higher index) of the container. A vector container also provides random access to its elements.

A vector container behaves conceptually as an array that expands as necessary as items are inserted. The *length* of a vector is the number of elements that the vector contains. The *capacity* of a vector is the maximum number of elements that can be inserted into the vector prior to it being automatically expanded.

A vector container may contain *empty elements*. Empty elements do not have a specified value.

*Static Semantics*

The generic library package Containers.Vectors has the following declaration:

```

generic
  type Index_Type is range <>;
  type Element_Type is private;
  with function "=" (Left, Right : Element_Type)
    return Boolean is <>;
package Ada.Containers.Vectors is
  pragma Preelaborate(Vectors);

  subtype Extended_Index is
    Index_Type'Base range
      Index_Type'First-1 ..
      Index_Type'Min (Index_Type'Base'Last - 1, Index_Type'Last) + 1;
  No_Index : constant Extended_Index := Extended_Index'First;

  subtype Index_Subtype is Index_Type;

  type Vector is tagged private;

  type Cursor is private;

  Empty_Vector : constant Vector;

  No_Element : constant Cursor;

  function To_Vector (Length : Count_Type) return Vector;

  function To_Vector
    (New_Item : Element_Type;
     Length   : Count_Type) return Vector;

  function "&" (Left, Right : Vector) return Vector;

```

```

function "&" (Left  : Vector;
               Right : Element_Type) return Vector;

function "&" (Left  : Element_Type;
               Right : Vector) return Vector;

function "&" (Left, Right  : Element_Type) return Vector;

function "=" (Left, Right : Vector) return Boolean;

function Capacity (Container : Vector) return Count_Type;

procedure Reserve_Capacity (Container : in out Vector;
                           Capacity  : in      Count_Type);

function Length (Container : Vector) return Count_Type;

function Is_Empty (Container : Vector) return Boolean;

procedure Clear (Container : in out Vector);

function To_Cursor (Container : Vector;
                   Index      : Extended_Index) return Cursor;

function To_Index (Position  : Cursor) return Extended_Index;

function Element (Container : Vector;
                  Index      : Index_Type)
return Element_Type;

function Element (Position : Cursor) return Element_Type;

procedure Query_Element
(Container : in Vector;
 Index    : in Index_Type;
 Process  : not null access procedure (Element : in Element_Type));

procedure Query_Element
(Position : in Cursor;
 Process  : not null access procedure (Element : in Element_Type));

procedure Update_Element
(Container : in Vector;
 Index    : in Index_Type;
 Process  : not null access procedure (Element : in out Element_Type));

procedure Update_Element
(Position : in Cursor;
 Process  : not null access procedure (Element : in out Element_Type));

procedure Replace_Element (Container : in Vector;
                           Index     : in Index_Type;
                           By        : in Element_Type);

procedure Replace_Element (Position : in Cursor;
                           By        : in Element_Type);

procedure Assign (Target : in out Vector;
                  Source : in      Vector);

procedure Move (Target : in out Vector;
                Source : in out Vector);

procedure Insert (Container : in out Vector;
                  Before    : in      Extended_Index;

```

```

        New_Item : in      Vector);

procedure Insert (Container : in out Vector;
        Before    : in      Cursor;
        New_Item   : in      Vector);

procedure Insert (Container : in out Vector;
        Before    : in      Cursor;
        New_Item   : in      Vector;
        Position   : out Cursor);

procedure Insert (Container : in out Vector;
        Before    : in      Extended_Index;
        New_Item   : in      Element_Type;
        Count      : in      Count_Type := 1);

procedure Insert (Container : in out Vector;
        Before    : in      Cursor;
        New_Item   : in      Element_Type;
        Count      : in      Count_Type := 1);

procedure Insert (Container : in out Vector;
        Before    : in      Cursor;
        New_Item   : in      Element_Type;
        Position   : out Cursor;
        Count      : in      Count_Type := 1);

procedure Prepend (Container : in out Vector;
        New_Item   : in      Vector);

procedure Prepend (Container : in out Vector;
        New_Item   : in      Element_Type;
        Count      : in      Count_Type := 1);

procedure Append (Container : in out Vector;
        New_Item   : in      Vector);

procedure Append (Container : in out Vector;
        New_Item   : in      Element_Type;
        Count      : in      Count_Type := 1);

procedure Insert_Space (Container : in out Vector;
        Before     : in      Extended_Index;
        Count      : in      Count_Type := 1);

procedure Insert_Space (Container : in out Vector;
        Before     : in      Cursor;
        Position    : out Cursor;
        Count      : in      Count_Type := 1);

procedure Set_Length (Container : in out Vector;
        Length      : in      Count_Type);

procedure Delete (Container : in out Vector;
        Index       : in      Extended_Index;
        Count       : in      Count_Type := 1);

procedure Delete (Container : in out Vector;
        Position    : in out Cursor;
        Count       : in      Count_Type := 1);

procedure Delete_First (Container : in out Vector;
        Count       : in      Count_Type := 1);

procedure Delete_Last (Container : in out Vector;

```

```

        Count      : in      Count_Type := 1);

function First_Index (Container : Vector) return Index_Type;

function First (Container : Vector) return Cursor;

function First_Element (Container : Vector)
    return Element_Type;

function Last_Index (Container : Vector) return Extended_Index;

function Last (Container : Vector) return Cursor;

function Last_Element (Container : Vector)
    return Element_Type;

procedure Swap (Container : in Vector;
                I, J      : in Index_Type);

procedure Swap (I, J      : in      Cursor);

generic
    with function "<" (Left, Right : Element_Type)
        return Boolean is <>;
procedure Generic_Sort (Container : in Vector);

function Find_Index (Container : Vector;
                    Item      : Element_Type;
                    Index     : Index_Type := Index_Type'First)
    return Extended_Index;

function Find (Container : Vector;
              Item      : Element_Type;
              Position  : Cursor := No_Element)
    return Cursor;

function Reverse_Find_Index (Container : Vector;
                            Item      : Element_Type;
                            Index     : Index_Type := Index_Type'Last)
    return Extended_Index;

function Reverse_Find (Container : Vector;
                      Item      : Element_Type;
                      Position  : Cursor := No_Element)
    return Cursor;

function Contains (Container : Vector;
                  Item      : Element_Type) return Boolean;

function Next (Position : Cursor) return Cursor;

function Previous (Position : Cursor) return Cursor;

procedure Next (Position : in out Cursor);

procedure Previous (Position : in out Cursor);

function Has_Element (Position : Cursor) return Boolean;

procedure Iterate
    (Container : in Vector;
     Process   : not null access procedure (Position : in Cursor));

procedure Reverse_Iterate
    (Container : in Vector;

```

```

    Process      : not null access procedure (Position : in Cursor));

private

    ... -- not specified by the language

end Ada.Containers.Vectors;

```

The type Vector is used to represent vectors. The type Vector needs finalization (see 7.6).

Empty\_Vector represents the empty vector object. It has a length of 0. If an object of type Vector is not otherwise initialized, it is initialized to the same value as Empty\_Vector.

No\_Element represents a cursor that designates no element. If an object of type Cursor is not otherwise initialized, it is initialized to the same value as No\_Element.

No\_Index represents a position that does not correspond to any element. The subtype Extended\_Index includes the indices covered by Index\_Type plus the value No\_Index and, if it exists, the successor to the Index\_Type'Last.

Some operations are assumed to work on a constant set of elements. For such an operation, a subprogram is said to *tamper with cursors* of a vector object *V* if:

- it inserts or deletes elements of *V*, that is, it calls the Insert, Insert\_Space, Clear, Delete, or Set\_Length procedures with *V* as a parameter; or
- it finalizes *V*; or
- it calls the Move procedure with *V* as a parameter.

Some operations are assumed to not change elements. For such an operation, a subprogram is said to *tamper with elements* of a vector object *V* if:

- it tampers with cursors of *V*; or
- it modifies one or more elements of *V*, that is, it calls the Replace\_Element, Update\_Element, or Swap procedures or an instance of Generic\_Sort with *V* as a parameter.

```
function To_Vector (Length : Count_Type) return Vector;
```

Returns a vector with a length of Length, filled with empty elements.

```
function To_Vector
(New_Item : Element_Type;
Length    : Count_Type) return Vector;
```

Returns a vector with a length of Length, filled with elements initialized to the value New\_Item.

```
function "&" (Left, Right : Vector) return Vector;
```

Returns a vector comprising the elements of Left followed by the elements of Right.

```
function "&" (Left  : Vector;
             Right : Element_Type) return Vector;
```

Returns a vector comprising the elements of Left followed by the element Right.

```
function "&" (Left  : Element_Type;
             Right : Vector) return Vector;
```

Returns a vector comprising the element Left followed by the elements of Right.

```
function "&" (Left, Right : Element_Type) return Vector;
```

Returns a vector comprising the element Left followed by the element Right.

```
function "=" (Left, Right : Vector) return Boolean;
```

If Left and Right denote the same vector object, then the function returns True. If Left and Right have different lengths, then the function returns False. Otherwise, it compares each element in Left

to the corresponding element in Right using the generic formal equality operator; if element equality returns False, then the function returns False. If the function has not returned a result after checking all of the elements, it returns True. Any exception raised during evaluation of element equality is propagated.

**function** Capacity (Container : Vector) **return** Count\_Type;

Returns the capacity of Container.

**procedure** Reserve\_Capacity (Container : **in out** Vector;  
Capacity : **in** Count\_Type);

Reserve\_Capacity allocates new internal data structures such that the length of the resulting vector can become at least the value Capacity without requiring an additional call to Reserve\_Capacity, and is large enough to hold the current length of Container. Reserve\_Capacity then copies the elements into the new data structures and deallocates the old data structures. Any exception raised during allocation is propagated and Container is not modified.

**function** Length (Container : Vector) **return** Count\_Type;

Returns the number of elements in Container.

**function** Is\_Empty (Container : Vector) **return** Boolean;

Equivalent to Length (Container) = 0.

**procedure** Clear (Container : **in out** Vector);

Removes all the elements from Container. The capacity of Container does not change.

**function** To\_Cursor (Container : Vector;  
Index : Extended\_Index) **return** Cursor;

If Index is not in the range First\_Index (Container) .. Last\_Index (Container), then No\_Element is returned. Otherwise, a cursor designating the element at position Index in Container is returned.

**function** To\_Index (Position : Cursor) **return** Extended\_Index;

If Position is No\_Element, No\_Index is returned. Otherwise, the index (within its containing vector) of the element designated by Cursor is returned.

**function** Element (Container : Vector;  
Index : Index\_Type)  
**return** Element\_Type;

If Index is not in the range First\_Index (Container) .. Last\_Index (Container), then Constraint\_Error is propagated. Otherwise, Element returns the element at position Index.

**function** Element (Position : Cursor) **return** Element\_Type;

If Position equals No\_Element, then Constraint\_Error is propagated. Otherwise, Element returns the element designated by Position.

**procedure** Query\_Element  
(Container : **in** Vector;  
Index : **in** Index\_Type;  
Process : **not null access procedure** (Element : **in** Element\_Type));

If Index is not in the range First\_Index (Container) .. Last\_Index (Container), then Constraint\_Error is propagated. Otherwise, Query\_Element calls Process.all with the element at position Index as the argument. Program\_Error is propagated if Process.all tampers with the elements of Container. Any exception raised by Process.all is propagated.

**procedure** Query\_Element  
(Position : **in** Cursor;  
Process : **not null access procedure** (Element : **in** Element\_Type));

If Position equals No\_Element, then Constraint\_Error is propagated. Otherwise, Query\_Element calls Process.all with the element designated by Position as the argument. Program\_Error is

propagated if Process.all tampers with the elements of Container. Any exception raised by Process.all is propagated.

```
procedure Update_Element
(Container : in Vector;
 Index    : in Index_Type;
 Process  : not null access procedure (Element : in out Element_Type));
```

If Index is not in the range First\_Index (Container) .. Last\_Index (Container), then Constraint\_Error is propagated. Otherwise, Update\_Element calls Process.all with the element at position Index as the argument. Program\_Error is propagated if Process.all tampers with the elements of Container. Any exception raised by Process.all is propagated.

If Element\_Type is unconstrained and definite, then the Element parameter of Process.all shall be unconstrained.

The element at position Index is not an empty element after successful completion of this operation.

```
procedure Update_Element
(Position : in Cursor;
 Process  : not null access procedure (Element : in out Element_Type));
```

If Position equals No\_Element, then Constraint\_Error is propagated. Otherwise, Update\_Element calls Process.all with the element designated by Position as the argument. Program\_Error is propagated if Process.all tampers with the elements of Container. Any exception raised by Process.all is propagated.

If Element\_Type is unconstrained and definite, then the Element parameter of Process.all shall be unconstrained.

The element designated by Position is not an empty element after successful completion of this operation.

```
procedure Replace_Element (Container : in Vector;
                           Index     : in Index_Type;
                           By        : in Element_Type);
```

If Index is not in the range First\_Index (Container) .. Last\_Index (Container), then Constraint\_Error is propagated. Otherwise Replace\_Element assigns the value By to the element at position Index. Any exception raised during the assignment is propagated. The element at position Index is not an empty element after successful call to Replace\_Element.

```
procedure Replace_Element (Position : in Cursor;
                           By        : in Element_Type);
```

If Position equals No\_Element, then Constraint\_Error is propagated. Otherwise Replace\_Element assigns By to the element designated by Position. Any exception raised during the assignment is propagated. The element at Position is not an empty element after successful call to Replace\_Element.

```
procedure Assign (Target : in out Vector;
                  Source : in      Vector);
```

If Target denotes the same object as Source, then the operation has no effect. Otherwise, Assign first calls Clear (Target), then Reserve\_Capacity (Target, Length (Source)). It then assigns the elements of Source to the corresponding positions in Target, and sets the length of Target to the length of Source. Any exception raised during element assignment is propagated.

```
procedure Move (Target : in out Vector;
                Source : in out Vector);
```

If Target denotes the same object as Source, then Move has no effect. Otherwise, Move first calls Clear (Target); then, each element from Source is removed from Source and inserted into Target in the original order. The length of Source is 0 after a successful call to Move.

```
procedure Insert (Container : in out Vector;
```



```

Before      : in      Extended_Index;
New_Item    : in      Vector);

```

If Before is not in the range First\_Index (Container) .. Last\_Index (Container) + 1, then Constraint\_Error is propagated. If Length(New\_Item) is 0, then Insert does nothing. Otherwise, it computes the new length *NL* as the sum of the current length and Length (New\_Item); if the value of Last appropriate for length *NL* would be greater than Index\_Type'Last then Constraint\_Error is propagated.

If the current vector capacity is less than or equal to *NL*, Reserve\_Capacity (Container, *NL*) is called to increase the vector capacity. Then Insert slides the elements in the range Before .. Last\_Index (Container) up by Length(New\_Item) positions, and then copies the elements of New\_Item to the positions starting at Before. Any exception raised during the copying is propagated.

```

procedure Insert (Container : in out Vector;
                  Before     : in      Cursor;
                  New_Item    : in      Vector);

```

Program\_Error is propagated unless Before is equal to No\_Element or designated an element in Target. Otherwise, if Length(New\_Item) is 0, then Insert does nothing. If Before is No\_Element, then the call is equivalent to Insert (Container, Last\_Index (Container) + 1, New\_Item); otherwise the call is equivalent to Insert (Container, To\_Index (Before), New\_Item);

```

procedure Insert (Container : in out Vector;
                  Before     : in      Cursor;
                  New_Item    : in      Vector;
                  Position    : out Cursor);

```

Program\_Error is propagated unless Before is equal to No\_Element or designated an element in Target. If Before equals No\_Element, then let *T* be Last\_Index (Container) + 1; otherwise, let *T* be To\_Index (Before). Insert (Container, *T*, New\_Item) is called, and then Position is set to To\_Cursor (Container, *T*).

```

procedure Insert (Container : in out Vector;
                  Before     : in      Extended_Index;
                  New_Item    : in      Element_Type;
                  Count       : in      Count_Type := 1);

```

Equivalent to Insert (Container, Before, To\_Vector (New\_Item, Count));

```

procedure Insert (Container : in out Vector;
                  Before     : in      Cursor;
                  New_Item    : in      Element_Type;
                  Count       : in      Count_Type := 1);

```

Equivalent to Insert (Container, Before, To\_Vector (New\_Item, Count));

```

procedure Insert (Container : in out Vector;
                  Before     : in      Cursor;
                  New_Item    : in      Element_Type;
                  Position    : out Cursor;
                  Count       : in      Count_Type := 1);

```

Equivalent to Insert (Container, Before, To\_Vector (New\_Item, Count), Position);

```

procedure Prepend (Container : in out Vector;
                  New_Item    : in      Vector;
                  Count       : in      Count_Type := 1);

```

Equivalent to Insert (Container, Index\_Type'First, New\_Item).

```

procedure Prepend (Container : in out Vector;
                  New_Item    : in      Element_Type;
                  Count       : in      Count_Type := 1);

```

Equivalent to Insert (Container, Index\_Type'First, New\_Item, Count).

```

procedure Append (Container : in out Vector;

```

```
New_Item : in Vector);
```

Equivalent to Insert (Container, Last\_Index (Container) + 1, New\_Item).

```
procedure Append (Container : in out Vector;
                  New_Item  : in Element_Type;
                  Count      : in Count_Type := 1);
```

Equivalent to Insert (Container, Last\_Index (Container) + 1, New\_Item, Count).

```
procedure Insert_Space (Container : in out Vector;
                       Before     : in Extended_Index;
                       Count      : in Count_Type := 1);
```

If Before is not in the range First\_Index (Container) .. Last\_Index (Container) + 1, then Constraint\_Error is propagated. If Count is 0, then Insert\_Space does nothing. Otherwise, it computes the new length *NL* as the sum of the current length and Count; if the value of Last appropriate for length *NL* would be greater than Index\_Type'Last then Constraint\_Error is propagated.

If the current vector capacity is less than or equal to *NL*, Reserve\_Capacity (Container, *NL*) is called to increase the vector capacity. Then Insert\_Space slides the elements in the range Before .. Last\_Index (Container) up by Count positions, and then inserts empty elements in the positions starting at Before.

```
procedure Insert_Space (Container : in out Vector;
                       Before     : in Cursor;
                       Position   : out Cursor;
                       Count      : in Count_Type := 1);
```

Program\_Error is propagated unless Before is equal to No\_Element or designated an element in Target. If Before equals No\_Element, then let *T* be Last\_Index (Container) + 1; otherwise, let *T* be To\_Index (Before). Insert\_Space (Container, *T*, Count) is called, and then Position is set to To\_Cursor (Container, *T*).

```
procedure Set_Length (Container : in out Vector;
                     Length     : in Count_Type);
```

If Length is larger than the capacity of Container, Set\_Length calls Reserve\_Capacity (Container, Length), then sets the length of the Container to Length. If Length is greater than the original length of Container, empty elements are added to Container; otherwise elements are removed from Container.

```
procedure Delete (Container : in out Vector;
                 Index      : in Extended_Index;
                 Count      : in Count_Type := 1);
```

If Index is not in the range First\_Index (Container) .. Last\_Index (Container), then Constraint\_Error is propagated. If Count is 0, Delete has no effect. Otherwise Delete slides the elements (if any) starting at position Index + Count down to Index. Any exception raised during element assignment is propagated.

```
procedure Delete (Container : in out Vector;
                 Position    : in out Cursor;
                 Count      : in Count_Type := 1);
```

If Position equals No\_Element, then Constraint\_Error is propagated. If Position does not designate an element in Container, then Program\_Error is propagated. Otherwise, Delete (Container, To\_Index (Position), Count) is called.

```
procedure Delete_First (Container : in out Vector;
                       Count      : in Count_Type := 1);
```

Equivalent to Delete (Container, Index\_Type'First, Count).

```
procedure Delete_Last (Container : in out Vector;
                      Count      : in Count_Type := 1);
```

If Length (Container) <= Count then Delete\_Last is equivalent to Clear (Container). Otherwise it is equivalent to Delete (Container, Index\_Type'Val(Index\_Type'Pos(Last\_Index(Container)) - Count + 1), Count).

**function** First\_Index (Container : Vector) **return** Index\_Type;

Returns the value Index\_Type'First.

**function** First (Container : Vector) **return** Cursor;

If Container is empty, First returns No\_Element. Otherwise, it returns a cursor that designates the first element in Container.

**function** First\_Element (Container : Vector) **return** Element\_Type;

Equivalent to Element (Container, First\_Index (Container)).

**function** Last\_Index (Container : Vector) **return** Extended\_Index;

If Container is empty, Last\_Index returns No\_Index. Otherwise, it returns the position of the last element in Container.

**function** Last (Container : Vector) **return** Cursor;

If Container is empty, Last returns No\_Element. Otherwise, it returns a cursor that designates the last element in Container.

**function** Last\_Element (Container : Vector) **return** Element\_Type;

Equivalent to Element (Container, Last\_Index (Container)).

**procedure** Swap (Container : **in** Vector;  
                  I, J : **in** Index\_Type);

If I or J is not in the range First\_Index (Container) .. Last\_Index (Container), then Constraint\_Error is propagated. Otherwise, Swap exchanges the values of the elements at positions I and J.

**procedure** Swap (I, J : **in** Cursor);

If either I or J is No\_Element, then Constraint\_Error is propagated. If I and J designate elements in different containers, then Program\_Error is propagated. Otherwise Swap exchanges the values of the elements designated by I and J.

**generic**

**with function** "<" (Left, Right : Element\_Type) **return** Boolean is <>;

**procedure** Generic\_Sort (Container : **in** Vector);

Reorders the elements of Container such that the elements are sorted smallest first as determined by the generic formal "<" operator provided. Any exception raised during evaluation of "<" is propagated.

**function** Find\_Index (Container : Vector;  
                      Item : Element\_Type;  
                      Index : Index\_Type := Index\_Type'First)  
**return** Extended\_Index;

Searches the elements of Container for an element equal to Item (in the sense of the generic formal equality operator). The search starts at position Index and proceeds towards Last\_Index (Container). If no equal element is found, then Find\_Index returns No\_Index. Otherwise, it returns the index of the first equal element encountered.

**function** Find (Container : Vector;  
              Item : Element\_Type;  
              Position : Cursor := No\_Element)  
**return** Cursor;

If Position is not No\_Element, and does not designate an element in Container, then Program\_Error is propagated. Otherwise Find searches the elements of Container for an element equal to Item (in the sense of the generic formal equality operator). The search starts at the first element if Cursor

equals No\_Element, and at the element designated by Cursor otherwise. It proceeds towards the last element of Container. If no equal element is found, then Find returns No\_Cursor. Otherwise, it returns a cursor designating the first equal element encountered.

```
function Reverse_Find_Index (Container : Vector;
                             Item      : Element_Type;
                             Index     : Index_Type := Index_Type'Last)
return Extended_Index;
```

Searches the elements of Container for an element equal to Item (in the sense of the generic formal equality operator). The search starts at position Index or, if Index is greater than Last\_Index (Container), at position Last\_Index (Container). It proceeds towards First\_Index (Container). If no equal element is found, then Reverse\_Find\_Index returns No\_Index. Otherwise, it returns the index of the first equal element encountered.

```
function Reverse_Find (Container : Vector;
                       Item      : Element_Type;
                       Position   : Cursor := No_Element)
return Cursor;
```

If Position is not No\_Element, and does not designate an element in Container, then Program\_Error is propagated. Otherwise Reverse\_Find searches the elements of Container for an element equal to Item (in the sense of the generic formal equality operator). The search starts at the last element if Cursor equals No\_Element, and at the element designated by Cursor otherwise. It proceeds towards the first element of Container. If no equal element is found, then Reverse\_Find returns No\_Cursor. Otherwise, it returns a cursor designating the first equal element encountered.

```
function Contains (Container : Vector;
                  Item      : Element_Type) return Boolean;
```

Equivalent to Has\_Element (Find (Container, Item)).

```
function Next (Position : Cursor) return Cursor;
```

If Position equals No\_Element or designates the last element of the container, then Next returns the value No\_Element. Otherwise, returns a cursor that designates the element with index To\_Index (Position) + 1 in the same vector as Position.

```
function Previous (Position : Cursor) return Cursor;
```

If Position equals No\_Element or designates the first element of the container, then Previous returns the value No\_Element. Otherwise, returns a cursor that designates the element with index (To\_Index (Position) - 1) in the same vector as Position.

```
procedure Next (Position : in out Cursor);
```

Equivalent to Position := Next (Position).

```
procedure Previous (Position : in out Cursor);
```

Equivalent to Position := Previous (Position).

```
function Has_Element (Position : Cursor) return Boolean;
```

Returns True if Position designates an element, and returns False otherwise.

```
procedure Iterate
(Container : in Vector;
 Process  : not null access procedure (Position : in Cursor));
```

Invokes Process.all with a cursor that designates each element in Container, in index order. Program\_Error is propagated if Process.all tampers with the cursors of Container. Any exception raised by Process is propagated.

```
procedure Reverse_Iterate
(Container : in Vector;
 Process  : not null access procedure (Position : in Cursor));
```

Iterates over the nodes in Container as per Iterate, except that elements are traversed in reverse index order.

#### *Bounded (Run-Time) Errors*

Reading the value of an empty element by calling Element, Query\_Element, Update\_Element, Generic\_Sort, "=", Find, or Reverse\_Find is a bounded error. The implementation may treat the element as having any valid value of the element type, or raise Constraint\_Error or Program\_Error before modifying the vector.

A Cursor value is *ambiguous* if any of the following have occurred since it was created:

- Insert, Insert\_Space, or Delete has been called on the vector that contains the element the cursor designates with an index value (or a cursor designating an element at such an index value) less than or equal to the index value of the element designated by the cursor; or
- The vector that contains the element it designates has been passed to an instance of Generic\_Sort.

It is a bounded error to call any subprogram other than "=" or Has\_Element declared in Containers.Vectors with an ambiguous (but not invalid, see below) cursor parameter. Possible results are:

- The cursor may be treated as if it was No\_Element;
- The cursor may designate some element in the vector (but not necessarily the element that it originally designated);
- Constraint\_Error may be raised; or
- Program\_Error may be raised.

#### *Erroneous Execution*

A Cursor value is *invalid* if any of the following have occurred since it was created:

- The vector that contains the element it designates has been finalized;
- The vector that contains the element it designates has been used as the Source or Target of a call to Move; or
- The element it designates has been deleted.

The result of "=" or Has\_Element is unspecified if it is called with an invalid cursor parameter. Execution is erroneous if any other subprogram declared in Containers.Vectors is called with an invalid cursor parameter.

#### *Implementation Requirements*

No storage associated with a vector object shall be lost upon assignment or scope exit.

#### *Implementation Advice*

Containers.Vectors should be implemented similarly to an array. In particular, if the length of a vector is  $N$ , then

- the worst-case time complexity of Append with Count=1 and Element should be  $O(\log N)$ ; and
- the worst-case time complexity of Prepend with Count=1 and Delete\_First with Count=1 should be  $O(N \log N)$ .

The worst-case time complexity of a call on an instantiation of Containers.Vectors.Generic\_Sort should be  $O(N^2)$ , and the average time complexity should be better than  $O(N^2)$ .

Containers.Vectors.Generic\_Sort should minimize copying of elements.

Move should not copy elements, and should minimize copying of internal data structures.

#### NOTES:

41 All elements of a vector occupy locations in the internal array. If a sparse container is required, a Hashed\_Map should be used rather than a vector.

42 If Index\_Type'BaseFirst = Index\_Type'First an instantiation of Ada.Containers.Vectors will raise Constraint\_Error. A value below Index\_Type'First is required so that an empty vector has a meaningful value of Last\_Index.

### A.18.3 The Package Containers.Doubly\_Linked\_Lists

#### Insert new clause: [AI95-00302-03]

The language-defined generic package Containers.Doubly\_Linked\_Lists provides private types List and Cursor, and a set of operations for each type. A list container is optimized for insertion and deletion at any position.

A doubly-linked list container object manages a linked list of internal *nodes*, each of which contains an element and pointers to the next (successor) and previous (predecessor) internal nodes. A cursor designates a particular node within a list (and by extension the element contained in that node). A cursor keeps designating the same node (and element) as long as the node is part of the container, even if the node is moved in the container.

The *length* of a list is the number of elements it contains.

#### Static Semantics

The generic library package Containers.Doubly\_Linked\_Lists has the following declaration:

```
generic
  type Element_Type is private;
  with function "=" (Left, Right : Element_Type) return Boolean is <>;
package Ada.Containers.Doubly_Linked_Lists is
  pragma Preelaborate (Doubly_Linked_Lists);

  type List is tagged private;

  type Cursor is private;

  Empty_List : constant List;

  No_Element : constant Cursor;

  function "=" (Left, Right : List) return Boolean;

  function Length (Container : List) return Natural;

  function Is_Empty (Container : List) return Boolean;

  procedure Clear (Container : in out List);

  function Element (Position : Cursor)
    return Element_Type;

  procedure Query_Element
    (Position : in Cursor;
     Process : not null access procedure (Element : in Element_Type));

  procedure Update_Element
    (Position : in Cursor;
     Process : not null access procedure (Element : in out Element_Type));

  procedure Replace_Element (Position : in Cursor;
                             By       : in Element_Type);

  procedure Move (Target : in out List;
                  Source : in out List);

  procedure Prepend (Container : in out List;
                    New_Item  : in   Element_Type);
```

```

        Count      : in      Count_Type := 1);

procedure Append (Container : in out List;
        New_Item  : in      Element_Type;
        Count     : in      Count_Type := 1);

procedure Insert (Container : in out List;
        Before    : in      Cursor;
        New_Item  : in      Element_Type;
        Count     : in      Count_Type := 1);

procedure Insert (Container : in out List;
        Before    : in      Cursor;
        New_Item  : in      Element_Type;
        Position  : out     Cursor;
        Count     : in      Count_Type := 1);

procedure Insert (Container : in out List;
        Before    : in      Cursor;
        Position  : out     Cursor;
        Count     : in      Count_Type := 1);

procedure Delete (Container : in out List;
        Position  : in out   Cursor;
        Count     : in      Count_Type := 1);

procedure Delete_First (Container : in out List;
        Count     : in      Count_Type := 1);

procedure Delete_Last (Container : in out List;
        Count     : in      Count_Type := 1);

generic
    with function "<" (Left, Right : Element_Type)
        return Boolean is <>;
procedure Generic_Sort (Container : in out List);

generic
    with function "<" (Left, Right : Element_Type)
        return Boolean is <>;
procedure Generic_Merge (Target  : in out List;
        Source  : in out List);

procedure Reverse_List (Container : in out List);

procedure Swap (I, J : in Cursor);

procedure Swap_Links (Container : in out List;
        I, J           : in      Cursor);

procedure Splice (Target  : in out List;
        Before  : in      Cursor;
        Source  : in out List);

procedure Splice (Target  : in out List;
        Before  : in      Cursor;
        Position : in      Cursor);

procedure Splice (Target  : in out List;
        Before  : in      Cursor;
        Source  : in out List;
        Position : in      Cursor);

function First (Container : List) return Cursor;

function First_Element (Container : List)

```

```

    return Element_Type;

function Last (Container : List) return Cursor;

function Last_Element (Container : List)
    return Element_Type;

function Contains (Container : List;
                  Item      : Element_Type) return Boolean;

function Find (Container : List;
              Item      : Element_Type;
              Position  : Cursor := No_Element)
    return Cursor;

function Reverse_Find (Container : List;
                     Item      : Element_Type;
                     Position  : Cursor := No_Element)
    return Cursor;

function Next (Position : Cursor) return Cursor;

function Previous (Position : Cursor) return Cursor;

procedure Next (Position : in out Cursor);

procedure Previous (Position : in out Cursor);

function Has_Element (Position : Cursor) return Boolean;

procedure Iterate
    (Container : in List;
     Process   : not null access procedure (Position : in Cursor));

procedure Reverse_Iterate
    (Container : in List;
     Process   : not null access procedure (Position : in Cursor));

private

    ... -- not specified by the language

end Ada.Containers.Doubly_Linked_Lists;

```

The type List is used to represent lists. The type List needs finalization (see 7.6).

Empty\_List represents the empty List object. It has a length of 0. If an object of type List is not otherwise initialized, it is initialized to the same value as Empty\_List.

No\_Element represents a cursor that designates no element. If an object of type Cursor is not otherwise initialized, it is initialized to the same value as No\_Element.

Some operations are assumed to work on a constant set of elements. For such an operation, a subprogram is said to *tamper with cursors* of a list object *L* if:

- it inserts or deletes elements of *L*, that is, it calls the Insert, Clear, Delete, or Delete\_Last procedures with *L* as a parameter; or
- it reorders the elements of *L*, that is, it calls the Splice, Swap\_Links, or Reverse\_List procedures or an instance of Generic\_Sort or Generic\_Merge with *C* as a parameter; or
- it finalizes *L*; or
- it calls the Move procedure with *L* as a parameter.

Some operations are assumed to not change elements. For such an operation, a subprogram is said to *tamper with elements* of a list object *L* if:



- it tampers with cursors of  $L$ ; or
- it modifies one or more elements of  $L$ , that is, it calls the `Replace_Element`, `Update_Element`, or `Swap` procedures with  $L$  as a parameter.

**function** "=" (Left, Right : List) **return** Boolean;

If Left and Right denote the same list object, then the function returns True. If Left and Right have different lengths, then the function returns False. Otherwise, it compares each element in Left to the corresponding element in Right using the generic formal equality operator; if element equality returns False, then the function returns False. If the function has not returned a result after checking all of the elements, it returns True. Any exception raised during evaluation of element equality is propagated.

**function** Length (Container : List) **return** Count\_Type;

Returns the number of elements in Container.

**function** Is\_Empty (Container : List) **return** Boolean;

Equivalent to `Length (Container) = 0`.

**procedure** Clear (Container : **in out** List);

Removes all the elements from Container.

**function** Element (Position : Cursor) **return** Element\_Type;

If Position equals `No_Element`, then `Constraint_Error` is propagated. Otherwise, Element returns the element designated by Position.

**procedure** Query\_Element  
(Position : **in** Cursor;  
Process : **not null access procedure** (Element : **in** Element\_Type));

If Position equals `No_Element`, then `Constraint_Error` is propagated. Otherwise, Query\_Element calls `Process.all` with the element on node designated by Position as the argument. `Program_Error` is propagated if `Process.all` tampers with the elements of Container. Any exception raised by `Process.all` is propagated.

**procedure** Update\_Element  
(Position : **in** Cursor;  
Process : **not null access procedure** (Element : **in out** Element\_Type));

If Position equals `No_Element`, then `Constraint_Error` is propagated. Otherwise, Update\_Element calls `Process.all` with the element on node designated by Position as the argument. `Program_Error` is propagated if `Process.all` tampers with the elements of Container. Any exceptions raised by `Process.all` are propagated.

If Element\_Type is unconstrained and definite, then the Element parameter of `Process.all` shall be unconstrained.

**procedure** Replace\_Element (Position : Cursor;  
By : Element\_Type);

If Position equals `No_Element`, then `Constraint_Error` is propagated. Otherwise Replace\_Element assigns the value By to the element designated by Position.

**procedure** Move (Target : **in out** List;  
Source : **in out** List);

If Target denotes the same object as Source, then Move has no effect. Otherwise, Move first calls `Clear (Target)`. Then, the nodes in Source are moved to Target (in the original order). The length of Target is set to the length of Source, and the length of Source is set to 0.

**procedure** Prepend (Container : **in out** List;  
New\_Item : **in** Element\_Type;  
Count : **in** Count\_Type := 1);

Equivalent to Insert (Container, First (Container), New\_Item, Count).

```
procedure Append (Container : in out List;
                  New_Item  : in      Element_Type;
                  Count      : in      Count_Type := 1);
```

Equivalent to Insert (Container, No\_Element, New\_Item, Count).

```
procedure Insert (Container : in out List;
                  Before     : in      Cursor;
                  New_Item   : in      Element_Type;
                  Count      : in      Count_Type := 1);
```

Program\_Error is propagated unless Before is equal to No\_Element or designated an element in Container. Otherwise, Insert inserts Count copies of New\_Item prior to the element designated by Before. If Before equals No\_Element, the new elements are inserted after the last node (if any). Any exception raised during allocation of internal storage is propagated, and Container is not modified.

```
procedure Insert (Container : in out List;
                  Before     : in      Cursor;
                  New_Item   : in      Element_Type;
                  Position    : out     Cursor;
                  Count      : in      Count_Type := 1);
```

Program\_Error is propagated unless Before is equal to No\_Element or designated an element in Container. Otherwise, Insert allocates Count copies of New\_Item, and inserts them prior to the element designated by Before. If Before equals No\_Element, the new elements are inserted after the last element (if any). Position designates the first newly-inserted element. Any exception raised during allocation of internal storage is propagated, and Container is not modified.

```
procedure Insert (Container : in out List;
                  Before     : in      Cursor;
                  Position    : out     Cursor;
                  Count      : in      Count_Type := 1);
```

Program\_Error is propagated unless Before is equal to No\_Element or designated an element in Container. Otherwise, Insert inserts Count new elements prior to the element designated by Before. If Before equals No\_Element, the new elements are inserted after the last node (if any). The new elements are initialized with any implicit initial value for any part (as for an object\_declaration with no initialization expression - see 3.3.1). Any exception raised during allocation of internal storage is propagated, and Container is not modified.

```
procedure Delete (Container : in out List;
                  Position    : in out Cursor;
                  Count      : in      Count_Type := 1);
```

If Position equals No\_Element, then Constraint\_Error is propagated. If Position does not designate an element in Container, then Program\_Error is propagated. Otherwise Delete removes (from Container) Count elements starting at the element designated by Position (or all of the elements if there are less than Count elements starting at Position).

```
procedure Delete_First (Container : in out List;
                       Count      : in      Count_Type := 1);
```

Equivalent to Delete (Container, First (Container), Count).

```
procedure Delete_Last (Container : in out List;
                      Count      : in      Count_Type := 1);
```

If Length (Container) <= Count then Delete\_Last is equivalent to Clear (Container). Otherwise it removes the last Count nodes from Container.

```
generic
  with function "<" (Left, Right : Element_Type) return Boolean is <>;
procedure Generic_Sort (Container : in out List);
```

Reorders the nodes of Container such that the elements are sorted smallest first as determined by the generic formal "<" operator provided. The sort must be stable. Any exception raised during evaluation of "<" is propagated.

```
generic
  with function "<" (Left, Right : Element_Type) return Boolean is <>;
procedure Generic_Merge (Target  : in out List;
                        Source   : in out List);
```

Generic\_Merge removes elements from Source and inserts them into Target so that Target be sorted smallest first as determined by the generic formal "<" operator.

Any exception raised during evaluation of "<" is propagated. If Target and Source are not sorted smallest first, then Program\_Error is propagated. In these cases, Target is left in an unspecified order, but contains the union of the elements that were initially in Source and Target; Source is left empty.

```
procedure Reverse_List (Container : in out List);
```

Reorders the elements of Container in reverse order.

```
procedure Swap (I, J : in Cursor);
```

If either I or J is No\_Element, then Constraint\_Error is propagated. If I and J designate elements in different containers, then Program\_Error is propagated. Otherwise Swap exchanges the values of the elements designated by I and J.

```
procedure Swap_Links (Container : in out List;
                      I, J      : in      Cursor);
```

If either I or J is No\_Element, then Constraint\_Error is propagated. If I or J do not designate an element in Container, then Program\_Error is propagated. Otherwise, Swap\_Links exchanges the nodes designated by I and J.

```
procedure Splice (Target  : in out List;
                  Before   : in      Cursor;
                  Source    : in out List);
```

Program\_Error is propagated unless Before is equal to No\_Element or designated an element in Target. Otherwise, if Source denotes the same object as Target, the operation has no effect. Otherwise, Splice reorders elements such that they are removed from Source and moved to Target, immediately prior to Before. If Before equals No\_Element, the nodes of Source are spliced after the last node of Target. The length of Target is incremented by the number of nodes in Source, and the length of Source is set to 0.

```
procedure Splice (Target  : in out List;
                  Before   : in      Cursor;
                  Position  : in      Cursor);
```

If either of Before or Position is not No\_Element, and does not designate an element in Target, then Program\_Error is propagated. If Position equals No\_Element, or if Position equals Before, or if the successor of Position equals Before, the operation has no effect. Otherwise the element designated by Position is moved immediately prior to Before, or, if Before equals No\_Element, after the last element.

```
procedure Splice (Target  : in out List;
                  Before   : in      Cursor;
                  Source    : in out List;
                  Position  : in      Cursor);
```

If Position is No\_Element then Constraint\_Error is propagated. If Before does not equal No\_Element, and does not designate an element in Target, then Program\_Error is propagated. If Position does not equal No\_Element, and does not designate a node in Source, then Program\_Error is propagated. If Source denotes the same object as Target, then Splice is equivalent to Splice (Target, Before, Position). Otherwise the element designated by Position is removed from Source

and moved to Target, immediately prior to Before, or, if Before equals No\_Element, after the last element of Target. The length of Target is incremented, and the length of Source is decremented.

**function** First (Container : List) **return** Cursor;

If Container is empty, First returns the value No\_Element. Otherwise it returns a cursor that designates the first node in Container.

**function** First\_Element (Container : List) **return** Element\_Type;

Equivalent to Element (First (Container)).

**function** Last (Container : List) **return** Cursor;

If Container is empty, Last returns the value No\_Element. Otherwise it returns a cursor that designates the last node in Container.

**function** Last\_Element (Container : List) **return** Element\_Type;

Equivalent to Element (Last (Container)).

**function** Contains (Container : List;  
Item : Element\_Type) **return** Boolean;

Equivalent to Find (Container, Item) /= No\_Element.

**function** Find (Container : List;  
Item : Element\_Type;  
Position : Cursor := No\_Element)  
**return** Cursor;

If Position is not No\_Element, and does not designate an element in Container, then Program\_Error is propagated. Find searches the elements of Container for an element equal to Item (in the sense of the generic formal equality operator). The search starts at the element designated by Position, or at the first element if Position equals No\_Element. It proceeds towards Last (Container). If no equal element is found, then Find returns No\_Element. Otherwise, it returns a cursor designating the first equal element encountered.

**function** Reverse\_Find (Container : List;  
Item : Element\_Type;  
Position : Cursor := No\_Element)  
**return** Cursor;

If Position is not No\_Element, and does not designate an element in Container, then Program\_Error is propagated. Find searches the elements of Container for an element equal to Item (in the sense of the generic formal equality operator). The search starts at the element designated by Position, or at the last element if Position equals No\_Element. It proceeds towards First (Container). If no equal element is found, then Reverse\_Find returns No\_Element. Otherwise, it returns a cursor designating the first equal element encountered.

**function** Next (Position : Cursor) **return** Cursor;

If Position equals No\_Element or designates the last element of the container, then Next returns the value No\_Element. Otherwise, it returns a cursor that designates the successor of the element designated by Position.

**function** Previous (Position : Cursor) **return** Cursor;

If Position equals No\_Element or designates the first element of the container, then Previous returns the value No\_Element. Otherwise, it returns a cursor that designates the predecessor of the element designated by Position.

**procedure** Next (Position : **in out** Cursor);

Equivalent to Position := Next (Position).

**procedure** Previous (Position : **in out** Cursor);

Equivalent to Position := Previous (Position).

```
function Has_Element (Position : Cursor) return Boolean;
```

Returns True if Position designates an element, and returns False otherwise.

```
procedure Iterate
```

```
(Container : in List;
```

```
Process : not null access procedure (Position : in Cursor));
```

Iterate calls Process.all with a cursor that designates each node in Container, starting with the first node and moving the cursor as per the Next function. Program\_Error is propagated if Process.all tampers with the cursors of Container. Any exception raised by Process.all is propagated.

```
procedure Reverse_Iterate
```

```
(Container : in List;
```

```
Process : not null access procedure (Position : in Cursor));
```

Iterates over the nodes in Container as per Iterate, except that elements are traversed in reverse order, starting with the last node and moving the cursor as per the Previous function.

#### *Erroneous Execution*

A Cursor value is *invalid* if any of the following have occurred since it was created:

- The list that contains the element it designates has been finalized;
- The list that contains the element it designates has been used as the Source or Target of a call to Move; or
- The element it designates has been deleted.

The result of "=" or Has\_Element is unspecified if it is called with an invalid cursor parameter. Execution is erroneous if any other subprogram declared in Containers.Doubly\_Linked\_Lists is called with an invalid cursor parameter.

#### *Implementation Requirements*

No storage associated with a doubly-linked List object shall be lost upon assignment or scope exit.

#### *Implementation Advice*

Containers.Doubly\_Linked\_Lists should be implemented similarly to a linked list. In particular, if  $N$  is the length of a list, then the worst-case time complexity of Element, Insert with Count=1, and Delete with Count=1 should be  $O(\log N)$ .

The worst-case time complexity of a call on an instantiation of Containers.Doubly\_Linked\_Lists.Generic\_Sort should be  $O(N^2)$ , and the average time complexity should be better than  $O(N^2)$ .

Move should not copy elements, and should minimize copying of internal data structures.

#### NOTES:

43 Sorting a list never copies elements, and is a stable sort (equal elements remain in the original order). This is different than sorting an array or vector, which may need to copy elements, and is probably not a stable sort.

## A.18.4 Maps

### Insert new clause: [AI95-00302-03]

The language-defined generic packages Containers.Hashing\_Maps and Containers.Ordered\_Maps provide private types Map and Cursor, and a set of operations for each type. A map container allows an arbitrary type to be used as a key to find the element associated with that key. A hashed map uses a hash function to organize the keys, while an ordered map orders the keys per a specified relation.

This section describes the declarations that are common to both kinds of maps. See A.18.5 for a description of the semantics specific to Containers.Hashing\_Maps and A.18.6 for a description of the semantics specific to Containers.Ordered\_Maps.

*Static Semantics*

The type Map is used to represent maps. The type Map needs finalization (see 7.6).

A map contains pairs of keys and elements, called *nodes*. Map cursors designate nodes, but also can be thought of as designating an element (the element contained in the node) for consistency with the other containers. There exists an equivalence relation on keys, whose definition is different for hashed maps and ordered maps. A map never contains two or more nodes with equivalent keys. The *length* of a map is the number of nodes it contains.

Each nonempty map has two particular nodes called the *first node* and the *last node* (which may be the same). Each node except for the last node has a *successor node*. If there are no other intervening operations, starting with the first node and repeatedly going to the successor node will visit each node in the map exactly once until the last node is reached. The exact definition of these terms is different for hashed maps and ordered maps.

Some operations are assumed to work on a constant set of elements. For such an operation, a subprogram is said to *tamper with cursors* of a map object *M* if:

- it inserts or deletes elements of *M*, that is, it calls the Insert, Include, Clear, Delete, or Exclude procedures with *M* as a parameter; or
- it finalizes *M*; or
- it calls the Move procedure with *M* as a parameter; or
- it calls one of the operations defined to tamper with the cursors of *M*.

Some operations are assumed to not change elements. For such an operation, a subprogram is said to *tamper with elements* of a map object *M* if:

- it tampers with cursors of *M*; or
- it modifies one or more elements of *M*, that is, it calls the Replace, Replace\_Element, or Update\_Element procedures with *M* as a parameter.

Empty\_Map represents the empty Map object. It has a length of 0. If an object of type Map is not otherwise initialized, it is initialized to the same value as Empty\_Map.

No\_Element represents a cursor that designates no node. If an object of type Cursor is not otherwise initialized, it is initialized to the same value as No\_Element.

**function** "=" (Left, Right : Map) **return** Boolean;

If Left and Right denote the same map object, then the function returns True. If Left and Right have different lengths, then the function returns False. Otherwise, for each key *K* in Left, the function returns False if:

- a key equivalent to *K* is not present in Right; or
- the element associated with *K* in Left is not equal to the element associated with *K* in Right (using the generic formal equality operator for elements).

If the function has not returned a result after checking all of the keys, it returns True. Any exception raised during evaluation of key equivalence or element equality is propagated.

**function** Length (Container : Map) **return** Count\_Type;

Returns the number of nodes in Container.

**function** Is\_Empty (Container : Map) **return** Boolean;

Equivalent to Length (Container) = 0.

**procedure** Clear (Container : **in out** Map);

Removes all the nodes from Container.

**function** Key (Position : Cursor) **return** Key\_Type;

If Position equals No\_Element, then Constraint\_Error is propagated. Otherwise, Key returns the key component of the node designated by Position.

**function** Element (Position : Cursor) **return** Element\_Type;

If Position equals No\_Element, then Constraint\_Error is propagated. Otherwise, Element returns the element component of the node designated by Position.

**procedure** Query\_Element  
 (Position : **in** Cursor;  
   Process : **not null access procedure** (Key : **in** Key\_Type;  
   Element : **in** Element\_Type));

If Position equals No\_Element, then Constraint\_Error is propagated. Otherwise, Query\_Element calls Process.all with the key and element from the node designated by Position as the arguments. Program\_Error is propagated if Process.all tampers with the elements of Container. Any exceptions raised by Process.all are propagated.

**procedure** Update\_Element  
 (Position : **in** Cursor;  
   Process : **not null access procedure** (Key : **in** Key\_Type;  
   Element : **in out** Element\_Type));

If Position equals No\_Element, then Constraint\_Error is propagated. Otherwise, Update\_Element calls Process.all with the key and element from the node designated by Position as the arguments. Program\_Error is propagated if Process.all tampers with the elements of Container. Any exceptions raised by Process.all are propagated.

If Element\_Type is unconstrained and definite, then the Element parameter of Process.all shall be unconstrained.

**procedure** Replace\_Element (Position : **in** Cursor;  
                           By : **in** Element\_Type);

If Position equals No\_Element, then Constraint\_Error is propagated. Otherwise Replace\_Element assigns By to the element of the node designated by Position.

**procedure** Move (Target : **in out** Map;  
               Source : **in out** Map);

If Target denotes the same object as Source, then Move has no effect. Otherwise, Move first calls Clear (Target). Then, each node from Source is removed from Source and inserted into Target. The length of Source is 0 after a successful call to Move.

**procedure** Insert (Container : **in out** Map;  
                   Key : **in** Key\_Type;  
                   New\_Item : **in** Element\_Type;  
                   Position : **out** Cursor;  
                   Inserted : **out** Boolean);

Insert checks if a node with a key equivalent to Key is already present in Container. If a match is found, Inserted is set to False and Position designates the element with the matching key. Otherwise, Insert allocates a new node, initializes it to Key and New\_Item, and adds it to Container; Inserted is set to True and Position designates the newly-inserted node. Any exception raised during allocation is propagated and Container is not modified.

**procedure** Insert (Container : **in out** Map;  
                   Key : **in** Key\_Type;  
                   Position : **out** Cursor;  
                   Inserted : **out** Boolean);

Insert inserts Key into Container as per the five-parameter Insert, with the difference that an element initialized with any implicit initial values for any part (as for an object\_declaration with no initialization expression - see 3.3.1) is inserted.

```

procedure Insert (Container : in out Map;
                  Key       : in      Key_Type;
                  New_Item  : in      Element_Type);

```

Insert inserts Key and New\_Item into Container as per the five-parameter Insert, with the difference that if a node with a key equivalent to Key is already in the map, then Constraint\_Error is propagated.

```

procedure Include (Container : in out Map;
                  Key       : in      Key_Type;
                  New_Item  : in      Element_Type);

```

Include inserts Key and New\_Item into Container as per the five-parameter Insert, with the difference that if a node with a key equivalent to Key is already in the map, then this operation assigns Key and New\_Item to the matching node. Any exception raised during assignment is propagated.

```

procedure Replace (Container : in out Map;
                  Key       : in      Key_Type;
                  New_Item  : in      Element_Type);

```

Replace checks if a node with a key equivalent to Key is present in Container. If a match is found, Replace assigns Key and New\_Item to the matching node; otherwise, Constraint\_Error is propagated.

```

procedure Delete (Container : in out Map;
                  Key       : in      Key_Type);

```

Delete checks if a node with a key equivalent to Key is present in Container. If a match is found, Delete removes the node from the map; otherwise, Constraint\_Error is propagated.

```

procedure Delete (Container : in out Map;
                  Position  : in out Cursor);

```

If Position equals No\_Element, then Constraint\_Error is propagated. If Position does not designate an element in Container, then Program\_Error is propagated. Otherwise, Delete removes the node designated by Position from the map. Position is set to No\_Element on return.

```

procedure Exclude (Container : in out Map;
                  Key       : in      Key_Type);

```

Exclude checks if a node with a key equivalent to Key is present in Container. If a match is found, Exclude removes the node from the map and then deallocates the node.

```

function Contains (Container : Map;
                  Key       : Key_Type) return Boolean;

```

Equivalent to Find (Container, Key) /= No\_Element.

```

function Find (Container : Map;
               Key       : Key_Type) return Cursor;

```

If Length (Container) equals 0, then Find returns No\_Element. Otherwise, Find checks if a node with a key equivalent to Key is present in Container. If a match is found, a cursor designating the matching node is returned; otherwise, No\_Element is returned.

```

function Element (Container : Map;
                  Key       : Key_Type) return Element_Type;

```

Equivalent to Element (Find (Container, Key)).

```

function First (Container : Map) return Cursor;

```

If Length (Container) = 0, then First returns No\_Element. Otherwise, First returns a cursor that designates the first node in Container.

```

function Next (Position : Cursor) return Cursor;

```



Returns a cursor that designates the successor of the node designated by Position. If Position designates the last node, then No\_Element is returned. If Position equals No\_Element, then No\_Element is returned.

```
procedure Next (Position : in out Cursor);
```

Equivalent to Position := Next (Position).

```
function Has_Element (Position : Cursor) return Boolean;
```

Returns True if Position designates a node, and returns False otherwise.

```
procedure Iterate
```

```
(Container : in Map;
```

```
Process : not null access procedure (Position : in Cursor));
```

Iterate calls Process.all with a cursor that designates each node in Container, starting with the first node and moving the cursor according to the successor relation. Program\_Error is propagated if Process.all tampers with the elements of Container. Any exception raised by Process.all is propagated.

#### *Erroneous Execution*

A Cursor value is *invalid* if any of the following have occurred since it was created:

- The map that contains the node it designates has been finalized;
- The map that contains the node it designates has been used as the Source or Target of a call to Move; or
- The node it designates has been deleted from the map.

The result of "=" or Has\_Element is unspecified if these functions are called with an invalid cursor parameter. Execution is erroneous if any other subprogram declared in Containers.Hashed\_Maps or Containers.Ordered\_Maps is called with an invalid cursor parameter.

#### *Implementation Requirements*

No storage associated with a Map object shall be lost upon assignment or scope exit.

#### *Implementation Advice*

Move should not copy elements, and should minimize copying of internal data structures.

## A.18.5 The Package Containers.Hashed\_Maps

**Insert new clause: [AI95-00302-03]**

#### *Static Semantics*

The generic library package Containers.Hashed\_Maps has the following declaration:

```
generic
  type Key_Type is private;
  type Element_Type is private;
  with function Hash (Key : Key_Type) return Hash_Type;
  with function Equivalent_Keys (Left, Right : Key_Type)
    return Boolean;
  with function "=" (Left, Right : Element_Type)
    return Boolean is <>;
package Ada.Containers.Hashed_Maps is
  pragma Preelaborate (Hashed_Maps);

  type Map is tagged private;

  type Cursor is private;

  Empty_Map : constant Map;
```

```

No_Element : constant Cursor;

function "=" (Left, Right : Map) return Boolean;

function Length (Container : Map) return Count_Type;

function Is_Empty (Container : Map) return Boolean;

procedure Clear (Container : in out Map);

function Key (Position : Cursor) return Key_Type;

function Element (Position : Cursor) return Element_Type;

procedure Query_Element
(Position : in Cursor;
 Process  : not null access procedure (Key      : in Key_Type;
                                       Element : in Element_Type));

procedure Update_Element
(Position : in Cursor;
 Process  : not null access procedure (Key      : in Key_Type;
                                       Element : in out Element_Type));

procedure Replace_Element (Position : in Cursor;
                           By       : in Element_Type);

procedure Move (Target : in out Map;
                Source : in out Map);

procedure Insert (Container : in out Map;
                  Key       : in      Key_Type;
                  New_Item  : in      Element_Type;
                  Position  :          out Cursor;
                  Inserted  :          out Boolean);

procedure Insert (Container : in out Map;
                  Key       : in      Key_Type;
                  Position  :          out Cursor;
                  Inserted  :          out Boolean);

procedure Insert (Container : in out Map;
                  Key       : in      Key_Type;
                  New_Item  : in      Element_Type);

procedure Include (Container : in out Map;
                  Key       : in      Key_Type;
                  New_Item  : in      Element_Type);

procedure Replace (Container : in out Map;
                  Key       : in      Key_Type;
                  New_Item  : in      Element_Type);

procedure Delete (Container : in out Map;
                  Key       : in      Key_Type);

procedure Delete (Container : in out Map;
                  Position  : in out Cursor);

procedure Exclude (Container : in out Map;
                  Key       : in      Key_Type);

function Contains (Container : Map;
                  Key       : Key_Type) return Boolean;

```

```

function Find (Container : Map;
               Key       : Key_Type)
  return Cursor;

function Element (Container : Map;
                  Key       : Key_Type)
  return Element_Type;

function First (Container : Map)
  return Cursor;

function Next (Position : Cursor) return Cursor;

procedure Next (Position : in out Cursor);

function Has_Element (Position : Cursor) return Boolean;

function Equivalent_Keys (Left, Right : Cursor)
  return Boolean;

function Equivalent_Keys (Left  : Cursor;
                          Right : Key_Type)
  return Boolean;

function Equivalent_Keys (Left  : Key_Type;
                          Right : Cursor)
  return Boolean;

procedure Iterate
  (Container : in Map;
   Process   : not null access procedure (Position : in Cursor));

function Capacity (Container : Map) return Count_Type;

procedure Reserve_Capacity (Container : in out Map;
                           Capacity   : in      Count_Type);

private

  ... -- not specified by the language

end Ada.Containers.Hashed_Maps;

```

An object of type Map contains an expandable hash table, which is used to provide direct access to nodes. The *capacity* of an object of type Map is the maximum number of nodes that can be inserted into the hash table prior to it being automatically expanded.

Two keys *K1* and *K2* are defined to be *equivalent* if Equivalent\_Keys (*K1*, *K2*) returns True.

Function Hash is expected to return the same value each time it is called with a particular key value. For any two equivalent key values, Hash is expected to return the same value. If Hash behaves in some other manner, the behavior of this package is unspecified. Which subprograms of this package call Hash, and how many times they call it, is unspecified.

Function Equivalent\_Keys is expected to return the same value each time it is called with a particular pair of key values. For any two keys *K1* and *K2*, the boolean values Equivalent\_Keys (*K1*, *K2*) and Equivalent\_Key (*K2*, *K1*) are expected to be equal. If Equivalent\_Keys behaves in some other manner, the behavior of this package is unspecified. Which subprograms of this package call Equivalent\_Keys, and how many times they call it, is unspecified.

If the value of a key stored in a node of a map is changed other than by an operation in this package such that at least one of Hash or Equivalent\_Keys give different results, the behavior of this package is unspecified.

Which nodes are the first node and the last node of a map, and which node is the successor of a given node, are unspecified, other than the general semantics described in A.18.4.

```
procedure Clear (Container : in out Map);
```

In addition to the semantics described in A.18.4, Clear does not affect the capacity of Container.

```
procedure Insert (Container : in out Map;
                  Key       : in      Key_Type;
                  New_Item  : in      Element_Type;
                  Position  : out      Cursor;
                  Inserted  : out      Boolean);
```

In addition to the semantics described in A.18.4, if Length (Container) equals Capacity (Container), then Insert first calls Reserve\_Capacity to increase the capacity of Container to some larger value.

```
function Equivalent_Keys (Left, Right : Cursor)
return Boolean;
```

Equivalent to Equivalent\_Keys (Key (Left), Key (Right)).

```
function Equivalent_Keys (Left  : Cursor;
                          Right : Key_Type) return Boolean;
```

Equivalent to Equivalent\_Keys (Key (Left), Right).

```
function Equivalent_Keys (Left  : Key_Type;
                          Right : Cursor) return Boolean;
```

Equivalent to Equivalent\_Keys (Left, Key (Right)).

```
function Capacity (Container : Map) return Count_Type;
```

Returns the capacity of Container.

```
procedure Reserve_Capacity (Container : in out Map;
                           Capacity  : in      Count_Type);
```

Reserve\_Capacity allocates a new hash table such that the length of the resulting map can become at least the value Capacity without requiring an additional call to Reserve\_Capacity, and is large enough to hold the current length of Container. Reserve\_Capacity then rehashes the nodes in Container onto the new hash table. It replaces the old hash table with the new hash table, and then deallocates the old hash table. Any exception raised during allocation is propagated and Container is not modified.

Reserve\_Capacity tampers with the cursors of Container.

#### *Implementation Advice*

If  $N$  is the length of a map, the average time complexity of the subprograms Element, Insert, Include, Replace, Delete, Exclude and Find that take a key parameter should be  $O(\log N)$ . The average time complexity of the subprograms that take a cursor parameter should be  $O(1)$ . The average time complexity of Reserve\_Capacity should be  $O(N)$ .

## A.18.6 The Package Containers.Ordered\_Maps

**Insert new clause: [AI95-00302-03]**

#### *Static Semantics*

The generic library package Containers.Ordered\_Maps has the following declaration:

```
generic
  type Key_Type is private;
  type Element_Type is private;
  with function "<" (Left, Right : Key_Type) return Boolean is <>;
  with function "=" (Left, Right : Element_Type) return Boolean is <>;
package Ada.Containers.Ordered_Maps is
```

```

pragma Preelaborate (Ordered_Maps);

type Map is tagged private;

type Cursor is private;

Empty_Map : constant Map;

No_Element : constant Cursor;

function "=" (Left, Right : Map) return Boolean;

function Length (Container : Map) return Count_Type;

function Is_Empty (Container : Map) return Boolean;

procedure Clear (Container : in out Map);

function Key (Position : Cursor) return Key_Type;

function Element (Position : Cursor) return Element_Type;

procedure Query_Element
  (Position : in Cursor;
   Process  : not null access procedure (Key      : in Key_Type;
                                           Element : in Element_Type));

procedure Update_Element
  (Position : in Cursor;
   Process  : not null access procedure (Key      : in      Key_Type;
                                           Element : in out Element_Type));

procedure Replace_Element (Position : in Cursor;
                           By       : in Element_Type);

procedure Move (Target : in out Map;
                Source : in out Map);

procedure Insert (Container : in out Map;
                  Key       : in      Key_Type;
                  New_Item  : in      Element_Type;
                  Position  : out Cursor;
                  Inserted  : out Boolean);

procedure Insert (Container : in out Map;
                  Key       : in      Key_Type;
                  Position  : out Cursor;
                  Inserted  : out Boolean);

procedure Insert (Container : in out Map;
                  Key       : in      Key_Type;
                  New_Item  : in      Element_Type);

procedure Include (Container : in out Map;
                  Key       : in      Key_Type;
                  New_Item  : in      Element_Type);

procedure Replace (Container : in out Map;
                  Key       : in      Key_Type;
                  New_Item  : in      Element_Type);

procedure Delete (Container : in out Map;
                  Key       : in      Key_Type);

procedure Delete (Container : in out Map;
                  Position  : in out Cursor);

```

```

procedure Delete_First (Container : in out Map);

procedure Delete_Last (Container : in out Map);

procedure Exclude (Container : in out Map;
                  Key       : in      Key_Type);

function Contains (Container : Map;
                  Key       : Key_Type) return Boolean;

function Find (Container : Map;
               Key       : Key_Type) return Cursor;

function Element (Container : Map;
                  Key       : Key_Type) return Element_Type;

function Floor (Container : Map;
                Key       : Key_Type) return Cursor;

function Ceiling (Container : Map;
                  Key       : Key_Type) return Cursor;

function First (Container : Map) return Cursor;

function First_Key (Container : Map) return Key_Type;

function First_Element (Container : Map) return Element_Type;

function Last (Container : Map) return Cursor;

function Last_Key (Container : Map) return Key_Type;

function Last_Element (Container : Map) return Element_Type;

function Next (Position : Cursor) return Cursor;

procedure Next (Position : in out Cursor);

function Previous (Position : Cursor) return Cursor;

procedure Previous (Position : in out Cursor);

function Has_Element (Position : Cursor) return Boolean;

function "<" (Left, Right : Cursor) return Boolean;

function ">" (Left, Right : Cursor) return Boolean;

function "<" (Left : Cursor; Right : Key_Type) return Boolean;

function ">" (Left : Cursor; Right : Key_Type) return Boolean;

function "<" (Left : Key_Type; Right : Cursor) return Boolean;

function ">" (Left : Key_Type; Right : Cursor) return Boolean;

procedure Iterate
  (Container : in Map;
   Process   : not null access procedure (Position : in Cursor));

procedure Reverse_Iterate
  (Container : in Map;
   Process   : not null access procedure (Position : in Cursor));

private

```

... -- *not specified by the language*

**end** Ada.Containers.Ordered\_Maps;

Two keys  $K1$  and  $K2$  are *equivalent* if both  $K1 < K2$  and  $K2 < K1$  return False, using the generic formal "<" operator for keys.

Functions "<" and "=" on Key\_Type values are expected to return the same result value each time they are called with a particular pair of key values. If  $A = B$  returns True, then  $B = A$  is expected to also return True. If  $A < B$  returns True, then  $B < A$  is expected to return False. For any two equivalent elements, "=" is expected to return True. If "<" or "=" behaves in some other manner, the behavior of this package is unspecified. Which subprograms of this package call "<" and "=", and how many times these functions are called, is unspecified.

If the value of a key stored in a map is changed other than by an operation in this package such that at least one of "<" or "=" give different results, the behavior of this package is unspecified.

The first node of a nonempty map is the one whose key is less than the key of all the other nodes in the map. The last node of a nonempty map is the one whose key is greater than the key of all the other elements in the map. The successor of a node is the node with the smallest key that is larger than the key of the given node. The predecessor of a node is the node with the largest key that is smaller than the key of the given node. All comparisons are done using the generic formal "<" operator for keys.

**procedure** Delete\_First (Container : **in out** Map);

If Container is empty, Delete\_First has no effect. Otherwise the node designated by First (Container) is removed from Container. Delete\_First tampers with the cursors of Container.

**procedure** Delete\_Last (Container : **in out** Map);

If Container is empty, Delete\_Last has no effect. Otherwise the node designated by Last (Container) is removed from Container. Delete\_Last tampers with the cursors of Container.

**function** Floor (Container : Map;  
Key : Key\_Type) **return** Cursor;

Floor searches for the last node whose key is not greater than Key. If such a node is found, a cursor that designates it is returned. Otherwise No\_Element is returned.

**function** Ceiling (Container : Map;  
Key : Key\_Type) **return** Cursor;

Ceiling searches for the first node whose key is not less than Key, using the generic formal "<" operator for keys. If such a node is found, a cursor that designates it is returned. Otherwise No\_Element is returned.

**function** First\_Key (Container : Map) **return** Key\_Type;

Equivalent to Key (First (Container)).

**function** First\_Element (Container : Map) **return** Element\_Type;

Equivalent to Element (First (Container)).

**function** Last (Container : Map) **return** Cursor;

Returns a cursor that designates the last node in Container. If Container is empty, returns No\_Element.

**function** Last\_Key (Container : Map) **return** Key\_Type;

Equivalent to Key (Last (Container)).

**function** Last\_Element (Container : Map) **return** Element\_Type;

Equivalent to Element (Last (Container)).

**function** Previous (Position : Cursor) **return** Cursor;

If Position equals No\_Element, then Previous returns No\_Element. Otherwise Previous returns the a cursor designating the node that precedes the one designated by Position. If Position designates the first element, then Previous returns No\_Element.

**procedure** Previous (Position : **in out** Cursor);

Equivalent to Position := Previous (Position).

**function** "<" (Left, Right : Cursor) **return** Boolean;

Equivalent to Key (Left) < Key (Right).

**function** ">" (Left, Right : Cursor) **return** Boolean;

Equivalent to Key (Right) < Key (Left).

**function** "<" (Left : Cursor; Right : Key\_Type) **return** Boolean;

Equivalent to Key (Left) < Right.

**function** ">" (Left : Cursor; Right : Key\_Type) **return** Boolean;

Equivalent to Right < Key (Left).

**function** "<" (Left : Key\_Type; Right : Cursor) **return** Boolean;

Equivalent to Left < Key (Right).

**function** ">" (Left : Key\_Type; Right : Cursor) **return** Boolean;

Equivalent to Key (Right) < Left.

**procedure** Reverse\_Iterate

(Container : **in** Map;

Process : **not null access procedure** (Position : **in** Cursor));

Iterates over the nodes in Container as per Iterate, with the difference that the nodes are traversed in predecessor order, starting with the last node.

#### *Implementation Advice*

If  $N$  is the length of a map, then the worst-case time complexity of the Element, Insert, Include, Replace, Delete, Exclude and Find operations that take a key parameter should be  $O((\log N)^2)$  or better. The worst-case time complexity of the subprograms that take a cursor parameter should be  $O(1)$ .

## A.18.7 Sets

### **Insert new clause: [AI95-00302-03]**

The language-defined generic packages Containers.Hash\_Sets and Containers.Ordered\_Sets provide private types Set and Cursor, and a set of operations for each type. A set container allows elements of an arbitrary type to be stored without duplication. A hashed set uses a hash function to organize elements, while an ordered set orders its element per a specified relation.

This section describes the declarations that are common to both kinds of sets. See A.18.8 for a description of the semantics specific to Containers.Hash\_Sets and A.18.9 for a description of the semantics specific to Containers.Ordered\_Sets.

#### *Static Semantics*

The type Set is used to represent sets. The type Set needs finalization (see 7.6).

A set contains elements. Set cursors designate elements. There exists an equivalence relation on elements, whose definition is different for hashed sets and ordered sets. A set never contains two or more equivalent elements. The *length* of a set is the number of elements it contains.

Each nonempty set has two particular elements called the *first element* and the *last element* (which may be the same). Each element except for the last element has a *successor element*. If there are no other intervening operations, starting with the first element and repeatedly going to the successor element will visit



each element in the map exactly once until the last element is reached. The exact definition of these terms is different for hashed sets and ordered sets.

Some operations are assumed to work on a constant set of elements. For such an operation, a subprogram is said to *tamper with cursors* of a set object *S* if:

- it inserts or deletes elements of *S*, that is, it calls the Insert, Include, Clear, Delete, Exclude, or Replace\_Element procedures with *S* as a parameter; or
- it finalizes *S*; or
- it calls the Move procedure with *S* as a parameter; or
- it calls one of the operations defined to tamper with cursors of *S*.

Some operations are assumed to not change elements. For such an operation, a subprogram is said to *tamper with elements* of a set object *S* if:

- it tampers with cursors of *S*; or
- it modifies one or more elements of *S*, that is, it calls the Replace or Update\_Element\_Preserving\_Key procedures with *S* as a parameter.

Empty\_Set represents the empty Set object. It has a length of 0. If an object of type Set is not otherwise initialized, it is initialized to the same value as Empty\_Set.

No\_Element represents a cursor that designates no element. If an object of type Cursor is not otherwise initialized, it is initialized to the same value as No\_Element.

**function** "=" (Left, Right : Set) **return** Boolean;

If Left and Right denote the same set object, then the function returns True. If Left and Right have different lengths, then the function returns False. Otherwise, for each element *E* in Left, the function returns False if an element equal to *E* (in the sense of the generic formal equality operator) is not present in Right. If the function has not returned a result after checking all of the elements, it returns True. Any exception raised during evaluation of element equality is propagated.

**function** Equivalent\_Sets (Left, Right : Set) **return** Boolean;

If Left and Right denote the same set object, then the function returns True. If Left and Right have different lengths, then the function returns False. Otherwise, for each element *E* in Left, the function returns False if an element equivalent to *E* is not present in Right. If the function has not returned a result after checking all of the elements, it returns True. Any exception raised during evaluation of element equivalence is propagated.

**function** Length (Container : Set) **return** Count\_Type;

Returns the number of elements in Container.

**function** Is\_Empty (Container : Set) **return** Boolean;

Equivalent to Length (Container) = 0.

**procedure** Clear (Container : **in out** Set);

Removes all the elements from Container.

**function** Element (Position : Cursor) **return** Element\_Type;

If Position equals No\_Element, then Constraint\_Error is propagated. Otherwise, Element returns the element designated by Position.

**procedure** Query\_Element

(Position : **in** Cursor;

Process : **not null access procedure** (Element : **in** Element\_Type));

If Position equals No\_Element, then Constraint\_Error is propagated. Otherwise, Query\_Element calls Process.all with the element designated by Position as the argument. Program\_Error is

propagated if Process.all tampers with the elements of Container. Any exceptions raised by Process.all are propagated.

```
procedure Replace_Element (Container : in Set;
                           Position  : in Cursor;
                           By        : in Element_Type);
```

If Position equals No\_Element, then Constraint\_Error is propagated. If Position does not designate an element in Container, then Program\_Error is propagated. Otherwise, the element designated by Position is tested for equivalence to By; if they are found to be equivalent, Replace\_Element assigns By to the element designated by Position. Otherwise, the element designated by Position is removed from the container, then By is inserted into the container. If the insertion fails, Program\_Error is propagated.

```
procedure Move (Target : in out Set;
                Source  : in out Set);
```

If Target denotes the same object as Source, then Move has no effect. Otherwise, Move first clears Target. Then, each element from Source is removed from Source and inserted into Target. The length of Source is 0 after a successful call to Move.

```
procedure Insert (Container : in out Set;
                  New_Item  : in Element_Type;
                  Position  : out Cursor;
                  Inserted  : out Boolean);
```

Insert checks if an element equivalent to New\_Item is already present in Container. If a match is found, Inserted is set to False and Position designates the matching element. Otherwise, Insert adds New\_Item to Container; Inserted is set to True and Position designates the newly-inserted element. Any exception raised during allocation is propagated and Container is not modified.

```
procedure Insert (Container : in out Set;
                  New_Item  : in Element_Type);
```

Insert inserts New\_Item into Container as per the four-parameter Insert, with the difference that if an element equivalent to New\_Item is already in the set, then Constraint\_Error is propagated.

```
procedure Include (Container : in out Set;
                  New_Item  : in Element_Type);
```

Include inserts New\_Item into Container as per the four-parameter Insert, with the difference that if an element equivalent to New\_Item is already in the set, then it is replaced. Any exception raised during assignment is propagated.

```
procedure Replace (Container : in out Set;
                  New_Item  : in Element_Type);
```

Replace checks if an element equivalent to New\_Item is already in the set. If a match is found, that element is replaced with New\_Item; otherwise, Constraint\_Error is propagated.

```
procedure Delete (Container : in out Set;
                  Item      : in Element_Type);
```

Delete checks if an element equivalent to Item is present in Container. If a match is found, Delete removes the element from the set; otherwise, Constraint\_Error is propagated.

```
procedure Delete (Container : in out Set;
                  Position  : in out Cursor);
```

If Position equals No\_Element, Delete has no effect. If Position does not designate an element in Container, then Program\_Error is propagated. Otherwise, Delete removes the node designated by Position from the set. Position is set to No\_Element on return.

```
procedure Exclude (Container : in out Set;
                  Item      : in Element_Type);
```

Exclude checks if an element equivalent to Item is present in Container. If a match is found, Exclude removes the element from the set.

```
function Contains (Container : Set;
                  Item      : Element_Type) return Boolean;
```

Equivalent to Find (Container, Item) /= No\_Element.

```
function Find (Container : Set;
              Item      : Element_Type) return Cursor;
```

If Length (Container) equals 0, then Find returns No\_Element. Otherwise, Find checks if an element equivalent to Item is present in Container. If a match is found, a cursor designating the matching element is returned; otherwise, No\_Element is returned.

```
function First (Container : Set) return Cursor;
```

If Length (Container) = 0, then First returns No\_Element. Otherwise, First returns a cursor that designates the first node in Container.

```
function Next (Position : Cursor) return Cursor;
```

Returns a cursor that designates the successor of the element designated by Position. If Position designates the last element, then No\_Element is returned. If Position equals No\_Element, then No\_Element is returned.

```
procedure Next (Position : in out Cursor);
```

Equivalent to Position := Next (Position).

```
function Has_Element (Position : Cursor) return Boolean;
```

Returns True if Position designates an element, and returns False otherwise.

```
procedure Iterate
(Container : in Set;
 Process   : not null access procedure (Position : in Cursor));
```

Iterate calls Process.all with a cursor that designates each element in Container, starting with the first node and moving the cursor according to the successor relation. Program\_Error is propagated if Process.all tampers with the elements of Container. Any exception raised by Process.all is propagated.

```
procedure Union (Target : in out Set;
                Source  : in      Set);
```

Union inserts into Target the elements of Source that are not equivalent to some element already in Target.

```
function Union (Left, Right : Set) return Set;
```

Returns a set comprising all of the elements of Left, and the elements of Right that are not equivalent to some element of Left.

```
procedure Intersection (Target : in out Set;
                      Source  : in      Set);
```

Intersection deletes from Target the elements of Target that are not equivalent to some element of Source.

```
function Intersection (Left, Right : Set) return Set;
```

Returns a set comprising all the elements of Left that are equivalent to the some element of Right.

```
procedure Difference (Target : in out Set;
                    Source  : in      Set);
```

If Target denotes the same object as Source, then Difference clears Target. Otherwise, it deletes from Target the elements that are equivalent to some element of Source.

```
function Difference (Left, Right : Set) return Set;
```

Returns a set comprising the elements of Left that are not equivalent to some element of Right.

```
procedure Symmetric_Difference (Target : in out Set;  
                               Source : in      Set);
```

If Target denotes the same object as Source, then Symmetric\_Difference clears Target. Otherwise, it deletes from Target the elements that are equivalent to some element of Source, and inserts into Target the elements of Source that are not equivalent to some element of Target.

```
function Symmetric_Difference (Left, Right : Set) return Set;
```

Returns a set comprising the elements of Left that are not equivalent to some element of Right, and the elements of Right that are not equivalent to some element of Left.

```
function Overlap (Left, Right : Set) return Boolean;
```

If an element of Left is equivalent to some element of Right, then Overlap returns True. Otherwise it returns False.

```
function Is_Subset (Subset : Set;  
                   Of_Set : Set) return Boolean;
```

If an element of Subset is not equivalent to some element of Of\_Set, then Is\_Subset returns False. Otherwise it returns True.

Both Containers.Hash\_Set and Containers.Ordered\_Set declare a nested generic package Generic\_Keys, which provides operations that allow set manipulation in terms of a key (typically, a portion of an element) instead of a complete element. The formal function Key of Generic\_Keys extracts a key value from an element. It is expected to return the same value each time it is called with a particular element. The behavior of Generic\_Keys is unspecified if Key behaves in some other manner.

A key is expected to unambiguously determine one equivalence class for elements. The behavior of Generic\_Keys is unspecified if the formal parameters of this package behave in some other manner.

The subprograms in package Generic\_Keys named Contains, Find, Element, Delete, and Exclude, are equivalent to the corresponding subprograms in the parent package, with the difference that the Key parameter is used locate an element in the set.

```
procedure Replace (Container : in out Set;  
                  Key       : in      Key_Type;  
                  New_Item  : in      Element_Type);
```

Equivalent to Replace\_Element (Container, Find (Container, Key), New\_Item).

```
function Key (Position : Cursor) return Key_Type;
```

Equivalent to Key (Element (Position)).

```
procedure Update_Element_Preserving_Key  
(Container : in out Set;  
 Position  : in      Cursor;  
 Process   : not null access procedure  
              (Element : in out Element_Type));
```

If Position equals No\_Element, then Constraint\_Error is propagated. If Position does not designate an element in Container, then Program\_Error is propagated. Otherwise, Update\_Element\_Preserving\_Key uses Key to save the key value *K* of the element designated by Position. Update\_Element\_Preserving\_Key then calls Process.all with that element as the argument. Program\_Error is propagated if Process.all tampers with the elements of Container. Any exception raised by Process.all is propagated. After Process.all returns, Update\_Element\_Preserving\_Key checks if *K* determines the same equivalence class as that for the new element; if not, the element is removed from the set and Program\_Error is propagated.

If Element\_Type is unconstrained and definite, then the Element parameter of Process.all shall be unconstrained.

*Erroneous Execution*

A Cursor value is *invalid* if any of the following have occurred since it was created:

- The set that contains the element it designates has been finalized;
- The set that contains the element it designates has been used as the Source or Target of a call to Move; or
- The element it designates has been deleted from the set.

The result of "=" or Has\_Element is unspecified if these functions are called with an invalid cursor parameter. Execution is erroneous if any other subprogram declared in Containers.Hash\_Sets or Containers.Ordered\_Sets is called with an invalid cursor parameter.

#### *Implementation Requirements*

No storage associated with a Set object shall be lost upon assignment or scope exit.

#### *Implementation Advice*

Move should not copy elements, and should minimize copying of internal data structures.

## A.18.8 The Package Containers.Hash\_Sets

**Insert new clause: [AI95-00302-03]**

#### *Static Semantics*

The generic library package Containers.Hash\_Sets has the following declaration:

```

generic
  type Element_Type is private;
  with function Hash (Element : Element_Type) return Hash_Type;
  with function Equivalent_Elements (Left, Right : Element_Type)
    return Boolean;
  with function "=" (Left, Right : Element_Type) return Boolean is <>;
package Ada.Containers.Hash_Sets is
  pragma Preelaborate (Hash_Sets);

  type Set is tagged private;

  type Cursor is private;

  Empty_Set : constant Set;

  No_Element : constant Cursor;

  function "=" (Left, Right : Set) return Boolean;

  function Equivalent_Sets (Left, Right : Set) return Boolean;

  function Length (Container : Set) return Count_Type;

  function Is_Empty (Container : Set) return Boolean;

  procedure Clear (Container : in out Set);

  function Element (Position : Cursor) return Element_Type;

  procedure Query_Element
    (Position : in Cursor;
     Process  : not null access procedure (Element : in Element_Type));

  procedure Replace_Element (Container : in Set;
                           Position  : in Cursor;
                           By        : in Element_Type);

  procedure Move (Target : in out Set;

```

```

        Source : in out Set);

procedure Insert (Container : in out Set;
                  New_Item  : in    Element_Type;
                  Position   :      out Cursor;
                  Inserted   :      out Boolean);

procedure Insert (Container : in out Set;
                  New_Item  : in    Element_Type);

procedure Include (Container : in out Set;
                  New_Item  : in    Element_Type);

procedure Replace (Container : in out Set;
                  New_Item  : in    Element_Type);

procedure Delete (Container : in out Set;
                  Item       : in    Element_Type);

procedure Delete (Container : in out Set;
                  Position   : in out Cursor);

procedure Exclude (Container : in out Set;
                  Item       : in    Element_Type);

function Contains (Container : Set;
                  Item       : Element_Type) return Boolean;

function Find (Container : Set;
               Item       : Element_Type) return Cursor;

function First (Container : Set) return Cursor;

function Next (Position : Cursor) return Cursor;

procedure Next (Position : in out Cursor);

function Has_Element (Position : Cursor) return Boolean;

function Equivalent_Elements (Left, Right : Cursor)
    return Boolean;

function Equivalent_Elements (Left  : Cursor;
                              Right : Element_Type)
    return Boolean;

function Equivalent_Elements (Left  : Element_Type;
                              Right : Cursor)
    return Boolean;

procedure Iterate
    (Container : in Set;
     Process   : not null access procedure (Position : in Cursor));

procedure Union (Target : in out Set;
                 Source  : in    Set);

function Union (Left, Right : Set) return Set;

function "or" (Left, Right : Set) return Set renames Union;

procedure Intersection (Target : in out Set;
                       Source  : in    Set);

function Intersection (Left, Right : Set) return Set;

```

```

function "and" (Left, Right : Set) return Set renames Intersection;

procedure Difference (Target : in out Set;
                     Source : in Set);

function Difference (Left, Right : Set) return Set;

function "-" (Left, Right : Set) return Set renames Difference;

procedure Symmetric_Difference (Target : in out Set;
                               Source : in Set);

function Symmetric_Difference (Left, Right : Set) return Set;

function "xor" (Left, Right : Set) return Set
renames Symmetric_Difference;

function Overlap (Left, Right : Set) return Boolean;

function Is_Subset (Subset : Set;
                  Of_Set : Set) return Boolean;

function Capacity (Container : Set) return Count_Type;

procedure Reserve_Capacity (Container : in out Set;
                           Capacity : in Count_Type);

generic
  type Key_Type (<>) is limited private;
  with function Key (Element : in Element_Type) return Key_Type;
  with function Hash (Key : Key_Type) return Hash_Type;
  with function Equivalent_Keys (Left : Key_Type; Right : Element_Type)
                                return Boolean;

package Generic_Keys is

  function Contains (Container : Set;
                   Key : Key_Type)
    return Boolean;

  function Find (Container : Set;
               Key : Key_Type)
    return Cursor;

  function Key (Position : Cursor) return Key_Type;

  function Element (Container : Set;
                  Key : Key_Type)
    return Element_Type;

  procedure Replace (Container : in out Set;
                   Key : in Key_Type;
                   New_Item : in Element_Type);

  procedure Delete (Container : in out Set;
                  Key : in Key_Type);

  procedure Exclude (Container : in out Set;
                   Key : in Key_Type);

  procedure Update_Element_Preserving_Key
    (Container : in out Set;
     Position : in Cursor;
     Process : not null access procedure
              (Element : in out Element_Type));

  function Equivalent_Keys (Left : Cursor;

```

```

                                Right : Key_Type)
    return Boolean;

    function Equivalent_Keys (Left  : Key_Type;
                               Right : Cursor)
    return Boolean;

end Generic_Keys;

private

    ... -- not specified by the language

end Ada.Containers.Hashed_Sets;

```

An object of type Set contains an expandable hash table, which is used to provide direct access to elements. The *capacity* of an object of type Set is the maximum number of elements that can be inserted into the hash table prior to it being automatically expanded.

Two elements *E1* and *E2* are defined to be *equivalent* if Equivalent\_Elements (*E1*, *E2*) returns True.

Function Hash is expected to return the same value each time it is called with a particular element value. For any two equivalent elements, Hash is expected to return the same value. If Hash behaves in some other manner, the behavior of this package is unspecified. Which subprograms of this package call Hash, and how many times they call it, is unspecified.

Function Equivalent\_Elements is expected to return the same value each time it is called with a particular pair of element values. For any two elements *E1* and *E2*, the boolean values Equivalent\_Elements (*E1*, *E2*) and Equivalent\_Elements (*E2*, *E1*) are expected to be equal. If Equivalent\_Elements behaves in some other manner, the behavior of this package is unspecified. Which subprograms of this package call Equivalent\_Elements, and how many times they call it, is unspecified.

If the value of an element stored in a set is changed other than by an operation in this package such that at least one of Hash or Equivalent\_Elements give different results, the behavior of this package is unspecified.

Which elements are the first element and the last element of a set, and which element is the successor of a given element, are unspecified, other than the general semantics described in A.18.7.

```

procedure Clear (Container : in out Set);

```

In addition to the semantics described in A.18.7, Clear does not affect the capacity of Container.

```

procedure Insert (Container : in out Set;
                  New_Item  : in   Element_Type;
                  Position  : out  Cursor;
                  Inserted  : out  Boolean);

```

In addition to the semantics described in A.18.7, if Length (Container) equals Capacity (Container), then Insert first calls Reserve\_Capacity to increase the capacity of Container to some larger value.

```

function First (Container : Set) return Cursor;

```

If Length (Container) = 0, then First returns No\_Element. Otherwise, First returns a cursor that designates the first hashed element in Container.

```

function Equivalent_Elements (Left, Right : Cursor)
    return Boolean;

```

Equivalent to Equivalent\_Elements (Element (Left), Element (Right)).

```

function Equivalent_Elements (Left  : Cursor;
                               Right : Element_Type) return Boolean;

```

Equivalent to Equivalent\_Elements (Element (Left), Right).

```

function Equivalent_Elements (Left  : Element_Type;
                               Right : Cursor) return Boolean;

```



Equivalent to Equivalent\_Elements (Left, Element (Right)).

```
function Capacity (Container : Set) return Count_Type;
```

Returns the capacity of Container.

```
procedure Reserve_Capacity (Container : in out Set;  
                           Capacity  : in      Count_Type);
```

Reserve\_Capacity allocates a new hash table such that the length of the resulting set can become at least the value Capacity without requiring an additional call to Reserve\_Capacity, and is large enough to hold the current length of Container. Reserve\_Capacity then rehashes the elements in Container onto the new hash table. It replaces the old hash table with the new hash table, and then deallocates the old hash table. Any exception raised during allocation is propagated and Container is not modified.

Reserve\_Capacity tampers with the cursors of Container.

For any element  $E$ , the function Generic\_Keys.Hash must be such that  $\text{Hash}(E) = \text{Generic\_Keys.Hash}(\text{Key}(E))$ . If Key or Generic\_Keys.Hash behave in some other manner, the behavior of Generic\_Keys is unspecified. Which subprograms of Generic\_Keys call Generic\_Keys.Hash, and how many times they call it, is unspecified.

For any two elements  $E1$  and  $E2$ , the boolean values Equivalent\_Element( $E1$ ,  $E2$ ), Equivalent\_Keys(Key( $E1$ ),  $E2$ ), and Equivalent\_Keys(Key( $E2$ ),  $E1$ ) are all expected to be equal. If Key or Equivalent behave in some other manner, the behavior of Generic\_Keys is unspecified. Which subprograms of Generic\_Keys call Equivalent, and how many times they call it, is unspecified.

```
function Equivalent_Keys (Left   : Cursor;  
                         Right  : Key_Type) return Boolean;
```

Equivalent to Equivalent\_Keys (Key (Left), Right).

```
function Equivalent_Keys (Left   : Key_Type;  
                         Right  : Cursor) return Boolean;
```

Equivalent to Equivalent\_Keys (Left, Key (Right)).

#### *Implementation Advice*

If  $N$  is the length of a set, the average time complexity of the subprograms Insert, Include, Replace, Delete, Exclude and Find that take an element parameter should be  $O(\log N)$ . The average time complexity of the subprograms that take a cursor parameter should be  $O(1)$ . The average time complexity of Reserve\_Capacity should be  $O(N)$ .

## A.18.9 The Package Containers.Ordered\_Sets

**Insert new clause: [AI95-00302-03]**

#### *Static Semantics*

The generic library package Containers.Ordered\_Sets has the following declaration:

```
generic  
  type Element_Type is private;  
  with function "<" (Left, Right : Element_Type) return Boolean is <>;  
  with function "=" (Left, Right : Element_Type) return Boolean is <>;  
package Ada.Containers.Ordered_Sets is  
  pragma Preelaborate (Ordered_Sets);  
  
  type Set is tagged private;  
  
  type Cursor is private;  
  
  Empty_Set : constant Set;
```

```

No_Element : constant Cursor;

function "=" (Left, Right : Set) return Boolean;

function Equivalent_Sets (Left, Right : Set) return Boolean;

function Length (Container : Set) return Count_Type;

function Is_Empty (Container : Set) return Boolean;

procedure Clear (Container : in out Set);

function Element (Position : Cursor) return Element_Type;

procedure Query_Element
(Position : in Cursor;
 Process  : not null access procedure (Element : in Element_Type));

procedure Replace_Element (Container : in Set;
                           Position  : in Cursor;
                           By         : in Element_Type);

procedure Move (Target : in out Set;
                 Source : in out Set);

procedure Insert (Container : in out Set;
                  New_Item   : in Element_Type;
                  Position   : out Cursor;
                  Inserted   : out Boolean);

procedure Insert (Container : in out Set;
                  New_Item   : in Element_Type);

procedure Include (Container : in out Set;
                  New_Item   : in Element_Type);

procedure Replace (Container : in out Set;
                  New_Item   : in Element_Type);

procedure Delete (Container : in out Set;
                  Item       : in Element_Type);

procedure Exclude (Container : in out Set;
                  Item       : in Element_Type);

procedure Delete (Container : in out Set;
                  Position   : in out Cursor);

procedure Delete_First (Container : in out Set);

procedure Delete_Last (Container : in out Set);

procedure Union (Target : in out Set;
                 Source  : in Set);

function Union (Left, Right : Set) return Set;

function "or" (Left, Right : Set) return Set renames Union;

procedure Intersection (Target : in out Set;
                       Source  : in Set);

function Intersection (Left, Right : Set) return Set;

function "and" (Left, Right : Set) return Set renames Intersection;

```

```

procedure Difference (Target : in out Set;
                      Source : in      Set);

function Difference (Left, Right : Set) return Set;

function "-" (Left, Right : Set) return Set renames Difference;

procedure Symmetric_Difference (Target : in out Set;
                                Source : in      Set);

function Symmetric_Difference (Left, Right : Set) return Set;

function "xor" (Left, Right : Set) return Set renames
    Symmetric_Difference;

function Overlap (Left, Right : Set) return Boolean;

function Is_Subset (Subset : Set;
                   Of_Set  : Set) return Boolean;

function Contains (Container : Set;
                   Item       : Element_Type) return Boolean;

function Find (Container : Set;
               Item       : Element_Type)
    return Cursor;

function Floor (Container : Set;
                Item       : Element_Type)
    return Cursor;

function Ceiling (Container : Set;
                  Item       : Element_Type)
    return Cursor;

function First (Container : Set) return Cursor;

function First_Element (Container : Set) return Element_Type;

function Last (Container : Set) return Cursor;

function Last_Element (Container : Set) return Element_Type;

function Next (Position : Cursor) return Cursor;

procedure Next (Position : in out Cursor);

function Previous (Position : Cursor) return Cursor;

procedure Previous (Position : in out Cursor);

function Has_Element (Position : Cursor) return Boolean;

function "<" (Left, Right : Cursor) return Boolean;

function ">" (Left, Right : Cursor) return Boolean;

function "<" (Left : Cursor; Right : Element_Type)
    return Boolean;

function ">" (Left : Cursor; Right : Element_Type)
    return Boolean;

function "<" (Left : Element_Type; Right : Cursor)
    return Boolean;

```

```

function ">" (Left : Element_Type; Right : Cursor)
    return Boolean;

procedure Iterate
    (Container : in Set;
     Process   : not null access procedure (Position : in Cursor));

procedure Reverse_Iterate
    (Container : in Set;
     Process   : not null access procedure (Position : in Cursor));

generic
    type Key_Type (<>) is limited private;
    with function Key (Element : Element_Type) return Key_Type;
    with function "<" (Left : Key_Type; Right : Element_Type)
        return Boolean is <>;
    with function ">" (Left : Key_Type; Right : Element_Type)
        return Boolean is <>;
package Generic_Keys is

    function Contains (Container : Set;
                     Key       : Key_Type) return Boolean;

    function Find (Container : Set;
                 Key       : Key_Type)
        return Cursor;

    function Floor (Container : Set;
                  Item      : Key_Type)
        return Cursor;

    function Ceiling (Container : Set;
                    Item      : Key_Type)
        return Cursor;

    function Key (Position : Cursor) return Key_Type;

    function Element (Container : Set;
                    Key       : Key_Type)
        return Element_Type;

    procedure Replace (Container : in out Set;
                     Key       : in Key_Type;
                     New_Item  : in Element_Type);

    procedure Delete (Container : in out Set;
                     Key       : in Key_Type);

    procedure Exclude (Container : in out Set;
                     Key       : in Key_Type);

    function "<" (Left : Cursor; Right : Key_Type)
        return Boolean;

    function ">" (Left : Cursor; Right : Key_Type)
        return Boolean;

    function "<" (Left : Key_Type; Right : Cursor)
        return Boolean;

    function ">" (Left : Key_Type; Right : Cursor)
        return Boolean;

    procedure Update_Element_Preserving_Key
        (Container : in out Set;
         Position  : in Cursor;

```

```

        Process      : not null access procedure
                        (Element : in out Element_Type));

    end Generic_Keys;

private

    ... -- not specified by the language

end Ada.Containers.Ordered_Sets;

```

Two elements  $E1$  and  $E2$  are *equivalent* if both  $E1 < E2$  and  $E2 < E1$  return False, using the generic formal "<" operator for elements.

Functions "<" and "=" on Element\_Type values are expected to return the same result value each time they are called with a particular pair of element values. If  $A = B$  returns True, then  $B = A$  is expected to also return True. If  $A < B$  returns True, then  $B < A$  is expected to return False. For any two equivalent elements, "=" is expected to return True. If "<" or "=" behaves in some other manner, the behavior of this package is unspecified. Which subprograms of this package call "<" and "=", and how many times these functions are called, is unspecified.

If the value of an element stored in a set is changed other than by an operation in this package such that at least one of "<" or "=" give different results, the behavior of this package is unspecified.

The first element of a nonempty set is the one which is less than all the other elements in the set. The last element of a nonempty set is the one which is greater than all the other elements in the set. The successor of an element is the smallest element that is larger than the given element. The predecessor of an element is the largest element that is smaller than the given element. All comparisons are done using the generic formal "<" operator for elements.

```

procedure Delete_First (Container : in out Set);

    If Container is empty, Delete_First has no effect. Otherwise the element designated by First
    (Container) is removed from Container. Delete_First tampers with the cursors of Container.

```

```

procedure Delete_Last (Container : in out Set);

    If Container is empty, Delete_Last has no effect. Otherwise the element designated by Last
    (Container) is removed from Container. Delete_Last tampers with the cursors of Container.

```

```

function Floor (Container : Set;
                Item       : Element_Type) return Cursor;

```

Floor searches for the last element which is not greater than Item. If such an element is found, a cursor that designates it is returned. Otherwise No\_Element is returned.

```

function Ceiling (Container : Set;
                  Item       : Element_Type) return Cursor;

```

Ceiling searches for the first element which is not less than Item. If such an element is found, a cursor that designates it is returned. Otherwise No\_Element is returned.

```

function First_Element (Container : Set) return Element_Type;

```

Equivalent to Element (First (Container)).

```

function Last (Container : Set) return Cursor;

```

Returns a cursor that designates the last node in Container. If Container is empty, returns No\_Element.

```

function Last_Element (Container : Set) return Element_Type;

```

Equivalent to Element (Last (Container)).

```

function Previous (Position : Cursor) return Cursor;

```

If Position equals No\_Element, then Previous returns No\_Element. Otherwise Previous returns a cursor designating the element that precedes the one designated by Position. If Position designates the first element, then Previous returns No\_Element.

**procedure** Previous (Position : **in out** Cursor);

Equivalent to Position := Previous (Position).

**function** "<" (Left, Right : Cursor) **return** Boolean;

Equivalent to Element (Left) < Element (Right).

**function** ">" (Left, Right : Cursor) **return** Boolean;

Equivalent to Element (Right) < Element (Left).

**function** "<" (Left : Cursor; Right : Element\_Type) **return** Boolean;

Equivalent to Element (Left) < Right.

**function** ">" (Left : Cursor; Right : Element\_Type) **return** Boolean;

Equivalent to Right < Element (Left).

**function** "<" (Left : Element\_Type; Right : Cursor) **return** Boolean;

Equivalent to Left < Element (Right).

**function** ">" (Left : Element\_Type; Right : Cursor) **return** Boolean;

Equivalent to Element (Right) < Left.

**procedure** Reverse\_Iterate

(Container : **in** Set;

Process : **not null access procedure** (Position : **in** Cursor));

Iterates over the elements in Container as per Iterate, with the difference that the elements are traversed in predecessor order, starting with the last node.

For any two elements  $E1$  and  $E2$ , the boolean values  $(E1 < E2)$ ,  $(\text{Key}(E1) < E2)$ , and  $(\text{Key}(E2) > E1)$  are all expected to be equal. If Key, Generic\_Keys."<", or Generic\_Keys.">" behave in some other manner, the behavior of this package is unspecified. Which subprograms of this package call Key, Generic\_Keys."<" and Generic\_Keys.">", and how many times the functions are called, is unspecified.

In addition to the semantics described in A.18.7, the subprograms in package Generic\_Keys named Floor, Ceiling, "<", and ">", are equivalent to the corresponding subprograms in the parent package, with the difference that the Key subprogram parameter is compared to elements in the container using the Generic\_Keys generic formal relational operators.

#### *Implementation Advice*

If  $N$  is the length of a set, then the worst-case time complexity of the Insert, Include, Replace, Delete, Exclude and Find operations that take an element parameter should be  $O((\log N)^2)$  or better. The worst-case time complexity of the subprograms that take a cursor parameter should be  $O(1)$ .

## A.18.10 The Package Containers.Indefinite\_Vectors

### **Insert new clause: [AI95-00302-03]**

The language-defined generic package Containers.Indefinite\_Vectors provides a private type Vector and a set of operations. It provides the same operations as the package Containers.Vectors (see A.18.2) does, with the difference that the generic formal Element\_Type is indefinite.

#### *Static Semantics*

The declaration of the generic library package Containers.Indefinite\_Vectors has the same contents as Containers.Vectors except:

- The generic formal Element\_Type is indefinite.

- The Element parameter of access subprogram Process of Update\_Element may be constrained even if Element\_Type is unconstrained.

### A.18.11 The Package Containers.Indefinite\_Doubly\_Linked\_Lists

#### Insert new clause: [AI95-00302-03]

The language-defined generic package Containers.Indefinite\_Doubly\_Linked\_Lists provides private types List and Cursor, and a set of operations for each type. It provides the same operations as the package Containers.Doubly\_Linked\_Lists (see A.18.3) does, with the difference that the generic formal Element\_Type is indefinite.

#### *Static Semantics*

The declaration of the generic library package Containers.Indefinite\_Doubly\_Linked\_Lists has the same contents as Containers.Doubly\_Linked\_Lists except:

- The generic formal Element\_Type is indefinite.
- The procedure with the profile:

```

procedure Insert (Container : in out List;
                  Before    : in      Cursor;
                  Position   :      out Cursor;
                  Count      : in      Count_Type := 1);

```

is omitted.

- The Element parameter of access subprogram Process of Update\_Element may be constrained even if Element\_Type is unconstrained.

### A.18.12 The Package Containers.Indefinite\_Hashed\_Maps

#### Insert new clause: [AI95-00302-03]

The language-defined generic package Containers.Indefinite\_Hashed\_Maps provides a map with the same operations as the package Containers.Hashed\_Maps (see A.18.5), with the difference that the generic formal types Key\_Type and Element\_Type are indefinite.

#### *Static Semantics*

The declaration of the generic library package Containers.Indefinite\_Hashed\_Maps has the same contents as Containers.Hashed\_Maps except:

- The generic formal Key\_Type is indefinite.
- The generic formal Element\_Type is indefinite.
- The procedure with the profile:

```

procedure Insert (Container : in out Map;
                  Key        : in      Key_Type;
                  Position   :      out Cursor;
                  Inserted   :      out Boolean);

```

is omitted.

- The Element parameter of access subprogram Process of Update\_Element may be constrained even if Element\_Type is unconstrained.

### A.18.13 The Package Containers.Indefinite\_Ordered\_Maps

**Insert new clause: [AI95-00302-03]**

The language-defined generic package Containers.Indefinite\_Ordered\_Maps provides a map with the same operations as the package Containers.Ordered\_Maps (see A.18.6), with the difference that the generic formal types Key\_Type and Element\_Type are indefinite.

*Static Semantics*

The declaration of the generic library package Containers.Indefinite\_Ordered\_Maps has the same contents as Containers.Ordered\_Maps except:

- The generic formal Key\_Type is indefinite.
- The generic formal Element\_Type is indefinite.
- The procedure with the profile:

```

procedure Insert (Container : in out Map;
                  Key       : in      Key_Type;
                  Position  :      out Cursor;
                  Inserted  :      out Boolean);

```

is omitted.

- The Element parameter of access subprogram Process of Update\_Element may be constrained even if Element\_Type is unconstrained.

### A.18.14 The Package Containers.Indefinite\_Hashed\_Sets

**Insert new clause: [AI95-00302-03]**

The language-defined generic package Containers.Indefinite\_Hashed\_Sets provides a set with the same operations as the package Containers.Hashed\_Sets (see A.18.8), with the difference that the generic formal type Element\_Type is indefinite.

*Static Semantics*

The declaration of the generic library package Containers.Indefinite\_Hashed\_Sets has the same contents as Containers.Hashed\_Sets except:

- The generic formal Element\_Type is indefinite.
- The Element parameter of access subprogram Process of Update\_Element\_Preserving\_Key may be constrained even if Element\_Type is unconstrained.

### A.18.15 The Package Containers.Indefinite\_Ordered\_Sets

**Insert new clause: [AI95-00302-03]**

The language-defined generic package Containers.Indefinite\_Ordered\_Sets provides a set with the same operations as the package Containers.Ordered\_Sets (see A.18.9), with the difference that the generic formal type Element\_Type is indefinite.

*Static Semantics*

The declaration of the generic library package Containers.Indefinite\_Ordered\_Sets has the same contents as Containers.Ordered\_Sets except:

- The generic formal Element\_Type is indefinite.
- The Element parameter of access subprogram Process of Update\_Element\_Preserving\_Key may be constrained even if Element\_Type is unconstrained.



## A.18.16 Array Sorting

### Insert new clause: [AI95-00302-03]

The language-defined generic procedures Containers.Generic\_Array\_Sort and Containers.Generic\_Constrained\_Array\_Sort provide sorting on arbitrary array types.

#### *Static Semantics*

The generic library procedure Containers.Generic\_Array\_Sort has the following declaration:

```
generic
  type Index_Type is (<>);
  type Element_Type is private;
  type Array_Type is array (Index_Type range <>) of Element_Type;
  with function "<" (Left, Right : Element_Type)
    return Boolean is <>;
procedure Ada.Containers.Generic_Array_Sort (Container : in out Array_Type);
pragma Pure (Ada.Containers.Generic_Array_Sort);
```

Reorders the elements of Container such that the elements are sorted smallest first as determined by the generic formal "<" operator provided. Any exception raised during evaluation of "<" is propagated.

The generic library procedure Containers.Generic\_Constrained\_Array\_Sort has the following declaration:

```
generic
  type Index_Type is (<>);
  type Element_Type is private;
  type Array_Type is array (Index_Type) of Element_Type;
  with function "<" (Left, Right : Element_Type)
    return Boolean is <>;
procedure Ada.Containers.Generic_Constrained_Array_Sort
  (Container : in out Array_Type);
pragma Pure (Ada.Containers.Generic_Constrained_Array_Sort);
```

Reorders the elements of Container such that the elements are sorted smallest first as determined by the generic formal "<" operator provided. Any exception raised during evaluation of "<" is propagated.

#### *Implementation Advice*

The worst-case time complexity of a call on an instantiation of Containers.Generic\_Array\_Sort or Containers.Generic\_Constrained\_Array\_Sort should be  $O(N^2)$  or better, and the average time complexity should be better than  $O(N^2)$ , where  $N$  is the length of the Container parameter.

Containers.Generic\_Array\_Sort and Containers.Generic\_Constrained\_Array\_Sort should minimize copying of elements.

## Annex B: Interface to Other Languages

### B.1 Interfacing Pragmas

**Insert after paragraph 38: [AI95-00320-01]**

Notwithstanding what this International Standard says elsewhere, the elaboration of a declaration denoted by the `local_name` of a `pragma Import` does not create the entity. Such an elaboration has no other effect than to allow the defining name to denote the external entity.

**the new paragraph:**

*Erroneous Execution*

It is the programmer's responsibility to ensure that the use of interfacing pragmas does not violate Ada semantics; otherwise, program execution is erroneous.

### B.2 The Package Interfaces

**Insert after paragraph 10: [AI95-00204-01]**

- Floating point types corresponding to each floating point format fully supported by the hardware.

**the new paragraph:**

Support for interfacing to any foreign language is optional. However, an implementation shall not provide any attribute, library unit, or pragma having the same name as an attribute, library unit, or pragma (respectively) specified in the following clauses of this Annex unless the provided construct is either as specified in those clauses or is more limited in capability than that required by those clauses. A program that attempts to use an unsupported capability of this Annex shall either be identified by the implementation before run time or shall raise an exception at run time.

**Insert after paragraph 11: [AI95-00204-01]**

An implementation may provide implementation-defined library units that are children of Interfaces, and may add declarations to the visible part of Interfaces in addition to the ones defined above.

**the new paragraph:**

A child package of package Interfaces with the name of a convention may be provided independently of whether the convention is supported by the pragma Convention and vice versa. Such a child package should contain any declarations that would be useful for interfacing to the language (implementation) represented by the convention. Any declarations useful for interfacing to any language on the given hardware architecture should be provided directly in Interfaces.

**Delete paragraph 12: [AI95-00204-01]**

For each implementation-defined convention identifier, there should be a child package of package Interfaces with the corresponding name. This package should contain any declarations that would be useful for interfacing to the language (implementation) represented by the convention. Any declarations useful for interfacing to any language on the given hardware architecture should be provided directly in Interfaces.

### B.3 Interfacing with C and C++

**Replace the title: [AI95-00376-01]**

Interfacing with C

**by:**

Interfacing with C and C++

**Replace paragraph 1: [AI95-00376-01]**

The facilities relevant to interfacing with the C language are the package Interfaces.C and its children; support for the Import, Export, and Convention pragmas with *convention\_identifier* C; and support for the Convention pragma with *convention\_identifier* C\_Pass\_By\_Copy.

**by:**

The facilities relevant to interfacing with the C language and the corresponding subset of the C++ language are the package Interfaces.C and its children; support for the Import, Export, and Convention pragmas with *convention\_identifier* C; and support for the Convention pragma with *convention\_identifier* C\_Pass\_By\_Copy.

**Replace paragraph 2: [AI95-00376-01]**

The package Interfaces.C contains the basic types, constants and subprograms that allow an Ada program to pass scalars and strings to C functions.

**by:**

The package Interfaces.C contains the basic types, constants and subprograms that allow an Ada program to pass scalars and strings to C and C++ functions. When this clause mentions a C entity, the reference also applies to the same entity in C++.

**Insert after paragraph 39: [AI95-00285-01]**

```

procedure To_Ada (Item      : in wchar_array;
                  Target    : out Wide_String;
                  Count     : out Natural;
                  Trim_Nul  : in Boolean := True);

```

**the new paragraphs:**

```

-- ISO/IEC 10646:2003 compatible types defined by SC22/WG14 document N1010.

type char16_t is <implementation-defined character type>;

char16_nul : constant char16_t := <implementation-defined>;

function To_C (Item : in Wide_Character) return char16_t;
function To_Ada (Item : in char16_t) return Wide_Character;

type char16_array is array (size_t range <>) of aliased char16_t;

pragma Pack(char16_array);

function Is_Nul_Terminated (Item : in char16_array) return Boolean;
function To_C (Item      : in Wide_String;
              Append_Nul : in Boolean := True)
  return char16_array;

function To_Ada (Item      : in char16_array;
                Trim_Nul  : in Boolean := True)
  return Wide_String;

procedure To_C (Item      : in Wide_String;
              Target    : out char16_array;
              Count     : out size_t;
              Append_Nul : in Boolean := True);

procedure To_Ada (Item      : in char16_array;
                Target    : out Wide_String;
                Count     : out Natural;
                Trim_Nul  : in Boolean := True);

type char32_t is <implementation-defined character type>;

```

```

char32_nul : constant char32_t := <implementation-defined>;

function To_C (Item : in Wide_Wide_Character) return char32_t;
function To_Ada (Item : in char32_t) return Wide_Wide_Character;

type char32_array is array (size_t range <>) of aliased char32_t;

pragma Pack(char32_array);

function Is_Nul_Terminated (Item : in char32_array) return Boolean;
function To_C (Item      : in Wide_Wide_String;
               Append_Nul : in Boolean := True)
  return char32_array;

function To_Ada (Item      : in char32_array;
                 Trim_Nul  : in Boolean := True)
  return Wide_Wide_String;

procedure To_C (Item      : in Wide_Wide_String;
                 Target    : out char32_array;
                 Count     : out size_t;
                 Append_Nul : in Boolean := True);

procedure To_Ada (Item      : in char32_array;
                  Target     : out Wide_Wide_String;
                  Count      : out Natural;
                  Trim_Nul   : in Boolean := True);

```

**Replace paragraph 43: [AI95-00285-01]**

The types `int`, `short`, `long`, `unsigned`, `ptrdiff_t`, `size_t`, `double`, `char`, and `wchar_t` correspond respectively to the C types having the same names. The types `signed_char`, `unsigned_short`, `unsigned_long`, `unsigned_char`, `C_float`, and `long_double` correspond respectively to the C types `signed char`, `unsigned short`, `unsigned long`, `unsigned char`, `float`, and `long double`.

**by:**

The types `int`, `short`, `long`, `unsigned`, `ptrdiff_t`, `size_t`, `double`, `char`, `wchar_t`, `char16_t`, and `char32_t` correspond respectively to the C types having the same names. The types `signed_char`, `unsigned_short`, `unsigned_long`, `unsigned_char`, `C_float`, and `long_double` correspond respectively to the C types `signed char`, `unsigned short`, `unsigned long`, `unsigned char`, `float`, and `long double`.

**Replace paragraph 50: [AI95-00258-01]**

The result of `To_C` is a `char_array` value of length `Item'Length` (if `Append_Nul` is `False`) or `Item'Length+1` (if `Append_Nul` is `True`). The lower bound is 0. For each component `Item(I)`, the corresponding component in the result is `To_C` applied to `Item(I)`. The value `nul` is appended if `Append_Nul` is `True`.

**by:**

The result of `To_C` is a `char_array` value of length `Item'Length` (if `Append_Nul` is `False`) or `Item'Length+1` (if `Append_Nul` is `True`). The lower bound is 0. For each component `Item(I)`, the corresponding component in the result is `To_C` applied to `Item(I)`. The value `nul` is appended if `Append_Nul` is `True`. If `Append_Nul` is `False` and `Item'Length` is 0, then `To_C` propagates `Constraint_Error`.

**Insert after paragraph 60: [AI95-00285-01]**

The `To_C` and `To_Ada` subprograms that convert between `Wide_String` and `wchar_array` have analogous effects to the `To_C` and `To_Ada` subprograms that convert between `String` and `char_array`, except that `wide_nul` is used instead of `nul`.

the new paragraphs:

```
function Is_Nul_Terminated (Item : in char16_array) return Boolean;
```

The result of Is\_Nul\_Terminated is True if Item contains char16\_nul, and is False otherwise.

```
function To_C (Item : in Wide_Character) return char16_t;
```

```
function To_Ada (Item : in char16_t ) return Wide_Character;
```

To\_C and To\_Ada provide mappings between the Ada and C 16-bit character types.

```
function To_C (Item      : in Wide_String;
               Append_Nul : in Boolean := True)
return char16_array;
```

```
function To_Ada (Item      : in char16_array;
               Trim_Nul   : in Boolean := True)
return Wide_String;
```

```
procedure To_C (Item      : in Wide_String;
               Target     : out char16_array;
               Count      : out size_t;
               Append_Nul : in Boolean := True);
```

```
procedure To_Ada (Item      : in char16_array;
               Target     : out Wide_String;
               Count      : out Natural;
               Trim_Nul   : in Boolean := True);
```

The To\_C and To\_Ada subprograms that convert between Wide\_String and char16\_array have analogous effects to the To\_C and To\_Ada subprograms that convert between String and char\_array, except that char16\_nul is used instead of nul.

```
function Is_Nul_Terminated (Item : in char32_array) return Boolean;
```

The result of Is\_Nul\_Terminated is True if Item contains char16\_nul, and is False otherwise.

```
function To_C (Item : in Wide_Wide_Character) return char32_t;
```

```
function To_Ada (Item : in char32_t ) return Wide_Wide_Character;
```

To\_C and To\_Ada provide mappings between the Ada and C 32-bit character types.

```
function To_C (Item      : in Wide_Wide_String;
               Append_Nul : in Boolean := True)
return char32_array;
```

```
function To_Ada (Item      : in char32_array;
               Trim_Nul   : in Boolean := True)
return Wide_Wide_String;
```

```
procedure To_C (Item      : in Wide_Wide_String;
               Target     : out char32_array;
               Count      : out size_t;
               Append_Nul : in Boolean := True);
```

```
procedure To_Ada (Item      : in char32_array;
               Target     : out Wide_Wide_String;
               Count      : out Natural;
               Trim_Nul   : in Boolean := True);
```

The To\_C and To\_Ada subprograms that convert between Wide\_Wide\_String and char32\_array have analogous effects to the To\_C and To\_Ada subprograms that convert between String and char\_array, except that char32\_nul is used instead of nul.

**Replace paragraph 60.2: [AI95-00216-01]**

The eligibility rules in B.1 do not apply to convention `C_Pass_By_Copy`. Instead, a type `T` is eligible for convention `C_Pass_By_Copy` if `T` is a record type that has no discriminants and that only has components with statically constrained subtypes, and each component is `C`-compatible.

**by:**

The eligibility rules in B.1 do not apply to convention `C_Pass_By_Copy`. Instead, a type `T` is eligible for convention `C_Pass_By_Copy` if `T` is an unchecked union type or if `T` is a record type that has no discriminants and that only has components with statically constrained subtypes, and each component is `C`-compatible.

**Replace paragraph 68.1: [AI95-00343-01]**

- An Ada parameter of a `C_Pass_By_Copy`-compatible (record) type `T`, of mode **in**, is passed as a `t` argument to a `C` function, where `t` is the `C` struct corresponding to the Ada type `T`.

**by:**

- An Ada parameter of a (record) type `T` of convention `C_Pass_By_Copy`, of mode **in**, is passed as a `t` argument to a `C` function, where `t` is the `C` struct corresponding to the Ada type `T`.

**Replace paragraph 69: [AI95-00343-01]**

- An Ada parameter of a record type `T`, of any mode, other than an **in** parameter of a `C_Pass_By_Copy`-compatible type, is passed as a `t*` argument to a `C` function, where `t` is the `C` struct corresponding to the Ada type `T`.

**by:**

- An Ada parameter of a record type `T`, of any mode, other than an **in** parameter of a type of convention `C_Pass_By_Copy`, is passed as a `t*` argument to a `C` function, where `t` is the `C` struct corresponding to the Ada type `T`.

**Insert after paragraph 71: [AI95-00337-01]**

- An Ada parameter of an access-to-subprogram type is passed as a pointer to a `C` function whose prototype corresponds to the designated subprogram's specification.

**the new paragraph:**

An Ada parameter of a private type is passed as specified for the type's full view.

## B.3.1 The Package Interfaces.C.Strings

**Replace paragraph 5: [AI95-00161-01]**

```
type Chars_Ptr is private;
```

**by:**

```
type Chars_Ptr is private;
pragma Preelaborable_Initialization(Chars_Ptr);
```

**Replace paragraph 6: [AI95-00276-01]**

```
type chars_ptr_array is array (size_t range <>) of chars_ptr;
```

**by:**

```
type chars_ptr_array is array (size_t range <>) of aliased chars_ptr;
```

**Replace paragraph 50: [AI95-00242-01]**

Equivalent to `Update(Item, Offset, To_C(Str), Check)`.

by:

Equivalent to Update(Item, Offset, To\_C(Str, Append\_Nul => False), Check).

### B.3.3 Pragma Unchecked\_Union

#### Insert new clause: [AI95-00216-01]

A pragma Unchecked\_Union specifies an interface correspondence between a given discriminated type and some C union. The pragma specifies that the associated type shall be given a representation that leaves no space for its discriminant(s).

##### *Syntax*

The form of a pragma Unchecked\_Union is as follows:

**pragma** Unchecked\_Union (*first\_subtype\_local\_name*);

##### *Legality Rules*

Unchecked\_Union is a representation pragma, specifying the unchecked union aspect of representation.

The *first\_subtype\_local\_name* of a pragma Unchecked\_Union shall denote an unconstrained discriminated record subtype having a *variant\_part*.

A type to which a pragma Unchecked\_Union applies is called an *unchecked union type*. A subtype of an unchecked union type is defined to be an *unchecked union subtype*. An object of an unchecked union type is defined to be an *unchecked union object*.

All component subtypes of an unchecked union type shall be C-compatible.

If a component subtype of an unchecked union type is subject to a per-object constraint, then the component subtype shall be an unchecked union subtype.

Any name that denotes a discriminant of an object of an unchecked union type shall occur within the declarative region of the type.

A component declared in a *variant\_part* of an unchecked union type shall not have a controlled, protected, or task part.

The completion of an incomplete or private type declaration having a *known\_discriminant\_part* shall not be an unchecked union type.

An unchecked union subtype shall only be passed as a generic actual parameter if the corresponding formal type has no known discriminants or is an unchecked union type.

##### *Static Semantics*

An unchecked union type is eligible for convention C.

All objects of an unchecked union type have the same size.

Discriminants of objects of an unchecked union type are of size zero.

Any check which would require reading a discriminant of an unchecked union object is suppressed (see 11.5). These checks include:

- The check performed when addressing a variant component (i.e., a component that was declared in a variant part) of an unchecked union object that the object has this component (see 4.1.3).
- Any checks associated with a type or subtype conversion of a value of an unchecked union type (see 4.6). This includes, for example, the check associated with the implicit subtype conversion of an assignment statement.
- The subtype membership check associated with the evaluation of a qualified expression (see 4.7) or an uninitialized allocator (see 4.8).

##### *Dynamic Semantics*

A view of an unchecked union object (including a type conversion or function call) has *inferable discriminants* if it has a constrained nominal subtype, unless the object is a component of an enclosing unchecked union object that is subject to a per-object constraint and the enclosing object lacks inferable discriminants.

An expression of an unchecked union type has inferable discriminants if it is either a name of an object with inferable discriminants or a qualified expression whose `subtype_mark` denotes a constrained subtype.

Program\_Error is raised in the following cases:

- Evaluation of the predefined equality operator for an unchecked union type if either of the operands lacks inferable discriminants.
- Evaluation of the predefined equality operator for a type which has a subcomponent of an unchecked union type whose nominal subtype is unconstrained.
- Evaluation of a membership test if the `subtype_mark` denotes a constrained unchecked union subtype and the expression lacks inferable discriminants.
- Conversion from a derived unchecked union type to an unconstrained non-unchecked-union type if the operand of the conversion lacks inferable discriminants.
- Execution of the default implementation of the Write or Read attribute of an unchecked union type.
- Execution of the default implementation of the Output or Input attribute of an unchecked union type if the type lacks default discriminant values.

#### Implementation Permissions

An implementation may require that `pragma Controlled` be specified for the type of an access subcomponent of an unchecked union type.

#### NOTES

15 The use of an unchecked union to obtain the effect of an unchecked conversion results in erroneous execution (see 11.5). Execution of the following example is erroneous even if `Float'Size = Integer'Size`:

```

type T (Flag : Boolean := False) is
  record
    case Flag is
      when False =>
        F1 : Float := 0.0;
      when True =>
        F2 : Integer := 0;
    end case;
  end record;
pragma Unchecked_Union (T);

X : T;
Y : Integer := X.F2; -- erroneous

```



## Annex C: Systems Programming

### C.3.1 Protected Procedure Handlers

**Replace paragraph 8:** [AI95-00321-01; AI95-00355-01]

The Interrupt\_Handler pragma is only allowed immediately within a `protected_definition`. The corresponding `protected_type_declaration` shall be a library level declaration. In addition, any `object_declaration` of such a type shall be a library level declaration.

**by:**

The Interrupt\_Handler pragma is only allowed immediately within a `protected_definition` where the corresponding subprogram is declared. The corresponding `protected_type_declaration` or `single_protected_declaration` shall be a library level declaration.

### C.4 Preelaboration Requirements

**Insert after paragraph 4:** [AI95-00161-01]

- Any `subtype_mark` denotes a statically constrained subtype, with statically constrained subcomponents, if any;

**the new paragraph:**

- No `subtype_mark` denotes a controlled type, a private type, a private extension, a generic formal private type, a generic formal derived type, or a descendant of such a type;

### C.5 Pragma Discard\_Names

**Replace paragraph 7:** [AI95-00285-01]

If the pragma applies to an enumeration type, then the semantics of the `Wide_Image` and `Wide_Value` attributes are implementation defined for that type; the semantics of `Image` and `Value` are still defined in terms of `Wide_Image` and `Wide_Value`. In addition, the semantics of `Text_IO Enumeration_IO` are implementation defined. If the pragma applies to a tagged type, then the semantics of the `Tags.Expanded_Name` function are implementation defined for that type. If the pragma applies to an exception, then the semantics of the `Exceptions.Exception_Name` function are implementation defined for that exception.

**by:**

If the pragma applies to an enumeration type, then the semantics of the `Wide_Wide_Image` and `Wide_Wide_Value` attributes are implementation defined for that type; the semantics of `Image`, `Wide_Image`, `Value`, and `Wide_Value` are still defined in terms of `Wide_Wide_Image` and `Wide_Wide_Value`. In addition, the semantics of `Text_IO Enumeration_IO` are implementation defined. If the pragma applies to a tagged type, then the semantics of the `Tags.Expanded_Name` function are implementation defined for that type. If the pragma applies to an exception, then the semantics of the `Exceptions.Exception_Name` function are implementation defined for that exception.

### C.6 Shared Variable Control

**Replace paragraph 7:** [AI95-00272-01]

An *atomic* type is one to which a pragma `Atomic` applies. An *atomic* object (including a component) is one to which a pragma `Atomic` applies, or a component of an array to which a pragma `Atomic_Components` applies, or any object of an atomic type.

by:

An *atomic* type is one to which a pragma Atomic applies. An *atomic* object (including a component) is one to which a pragma Atomic applies, or a component of an array to which a pragma Atomic\_Components applies, or any object of an atomic type, other than objects obtained by evaluating a slice.

**Insert after paragraph 21: [AI95-00259-01]**

If a pragma Pack applies to a type any of whose subcomponents are atomic, the implementation shall not pack the atomic subcomponents more tightly than that for which it can support indivisible reads and updates.

**the new paragraphs:**

*Implementation Advice*

A load or store of a volatile object whose size is a multiple of System.Storage\_Unit and whose alignment is nonzero, should be implemented by accessing exactly the bits of the object and no others.

A load or store of an atomic object should, where possible, be implemented by a single load or store instruction.

## C.7.1 The Package Task\_Identification

**Replace paragraph 2: [AI95-00362-01]**

```
package Ada.Task_Identification is
  type Task_ID is private;
  Null_Task_ID : constant Task_ID;
  function "=" (Left, Right : Task_ID) return Boolean;
```

by:

```
package Ada.Task_Identification is
  pragma Preelaborate(Task_Identification);
  type Task_ID is private;
  pragma Preelaborable_Initialization (Task_Id);
  Null_Task_ID : constant Task_ID;
  function "=" (Left, Right : Task_ID) return Boolean;
```

**Replace paragraph 17: [AI95-00237-01]**

It is a bounded error to call the Current\_Task function from an entry body or an interrupt handler. Program\_Error is raised, or an implementation-defined value of the type Task\_ID is returned.

by:

It is a bounded error to call the Current\_Task function from an entry body, interrupt handler, or finalization of a task attribute. Program\_Error is raised, or an implementation-defined value of the type Task\_ID is returned.

## C.7.2 The Package Task\_Attributes

**Insert after paragraph 13: [AI95-00237-01]**

For all the operations declared in this package, Tasking\_Error is raised if the task identified by T is terminated. Program\_Error is raised if the value of T is Null\_Task\_ID.

**the new paragraph:**

After a task has terminated, all of its attributes are finalized, unless they have been finalized earlier. When the master of an instantiation of Ada.Task\_Attributes is finalized, the corresponding attribute of each task is finalized, unless it has been finalized earlier.

**Replace paragraph 15.1: [AI95-00237-01]**

Accesses to task attributes via a value of type `Attribute_Handle` are erroneous if executed concurrently with each other or with calls of any of the operations declared in package `Task_Attributes`.

**by:**

An access to a task attribute via a value of type `Attribute_Handle` is erroneous with another such access or call of any of the operations declared in package `Task_Attributes`. An access to a task attribute is erroneous if executed concurrently with or after the finalization of the task attribute.

**Replace paragraph 17: [AI95-00237-01]**

When a task terminates, an implementation shall finalize all attributes of the task, and reclaim any other storage associated with the attributes.

**by:**

After task attributes are finalized, the implementation shall reclaim any other storage associated with the attributes.

**Insert before paragraph 30: [AI95-00237-01]**

Some implementations are targeted to domains in which memory use at run time must be completely deterministic. For such implementations, it is recommended that the storage for task attributes will be pre-allocated statically and not from the heap. This can be accomplished by either placing restrictions on the number and the size of the task's attributes, or by using the pre-allocated storage for the first N attribute objects, and the heap for the others. In the latter case, N should be documented.

**the new paragraph:**

Finalization of task attributes and reclamation of associated storage should be performed as soon as possible after task termination.

## C.7.3 Task Termination Procedures

**Insert new clause: [AI95-00266-02]**

This clause specifies a package for associating protected procedures with a task. One such procedure is invoked when the task is about to terminate.

*Static Semantics*

The following language-defined library package exists:

```

with System;
with Ada.Task_Identification;
with Ada.Exceptions;
package Ada.Task_Termination is
  type Cause_Of_Termination is (Normal, Abnormal, Unhandled_Exception);

  type Termination_Handler is access protected procedure(
    Cause : in Cause_Of_Termination;
    T      : in Ada.Task_Identification.Task_Id;
    X      : in Ada.Exceptions.Exception_Occurrence);

  procedure Set_Dependents_Fallback_Handler(Handler: in Termination_Handler);
  function Current_Task_Fallback_Handler return Termination_Handler;

  procedure Set_Specific_Handler(
    T      : in Ada.Task_Identification.Task_Id;
    Handler : in Termination_Handler);
  function Specific_Handler(T : Ada.Task_Identification.Task_Id)
    return Termination_Handler;
end Ada.Task_Termination;

```

*Dynamic Semantics*

A call of `Set_Dependents_Fallback_Handler` sets the fall-back handler for all dependent tasks. If a fall-back handler had previously been set it is replaced. A call with a null access parameter is equivalent to removing the fall-back handler. A call of `Current_Task_Fallback_Handler` returns the fall-back handler that is currently in effect for the calling task. If no fall-back handler has been set it returns null.

A call of `Set_Specific_Handler` sets a specific handler for the task identified by T. If a specific handler had previously been set it is replaced. A call with a null access parameter is equivalent to removing the specific handler. A call of `Specific_Handler` returns the specific handler if one has been set, otherwise the handler it returns null.

As part of the finalization of a `task_body`, after performing the actions specified in 7.6 for finalization of a master, the task specific handler, if not null, is called. If there is no such specific handler, a fall-back handler is determined by recursively searching for a non-null fall-back handler in the tasks upon which it depends. If such a fall-back handler is determined it is executed; otherwise no handler is executed.

If the task completed due to completing the last statement of the task body, or as a result of waiting on a terminate alternative then `Cause` is set to `Normal` and `X` is set to `Null_Occurrence`. If completion is due to abort then `Cause` is set to `Abnormal` and `X` is set to `Null_Occurrence`. If completion is due to an unhandled exception then `Cause` is set to `Unhandled_Exception` and `X` is set to the associated exception occurrence.

For all the operations defined in this package, `Tasking_Error` is raised if the task identified by T has already terminated. `Program_Error` is raised if the value of T is `Null_Task_ID`.

An exception propagated from a handler that is invoked as part of the termination of a task has no effect.

## Annex D: Real-Time Systems

### D.2 Priority Scheduling

#### Replace paragraph 1: [AI95-00321-01]

This clause describes the rules that determine which task is selected for execution when more than one task is ready (see 9.2). The rules have two parts: the task dispatching model (see D.2.1), and a specific task dispatching policy (see D.2.2).]

by:

This clause describes the rules that determine which task is selected for execution when more than one task is ready (see 9).

#### D.2.1 The Task Dispatching Model

##### Replace paragraph 1: [AI95-00321-01; AI95-00355-01]

The task dispatching model specifies preemptive scheduling, based on conceptual priority-ordered ready queues.

by:

The task dispatching model specifies task scheduling, based on conceptual priority-ordered ready queues.

*Static Semantics*

The following language-defined library package exists:

```
package Ada.Dispatching is
  pragma Pure(Dispatching);
  Dispatching_Policy_Error : exception;
end Ada.Dispatching;
```

Dispatching serves as the parent of other language-defined library units concerned with dispatching.

##### Replace paragraph 2: [AI95-00321-01]

A task runs (that is, it becomes a *running task*) only when it is ready (see 9.2) and the execution resources required by that task are available. Processors are allocated to tasks based on each task's active priority.

by:

A task can become a *running task* only if it is ready (see 9) and the execution resources required by that task are available. Processors are allocated to tasks based on each task's active priority.

##### Replace paragraph 4: [AI95-00321-01]

*Task dispatching* is the process by which one ready task is selected for execution on a processor. This selection is done at certain points during the execution of a task called *task dispatching points*. A task reaches a task dispatching point whenever it becomes blocked, and whenever it becomes ready. In addition, the completion of an *accept\_statement* (see 9.5.2), and task termination are task dispatching points for the executing task. Other task dispatching points are defined throughout this Annex.

by:

*Task dispatching* is the process by which one ready task is selected for execution on a processor. This selection is done at certain points during the execution of a task called *task dispatching points*. A task reaches a task dispatching point whenever it becomes blocked, and when it terminates. Other task dispatching points are defined throughout this Annex for specific policies.

**Replace paragraph 5: [AI95-00321-01]**

*Task dispatching policies* are specified in terms of conceptual *ready queues*, task states, and task preemption. A ready queue is an ordered list of ready tasks. The first position in a queue is called the *head of the queue*, and the last position is called the *tail of the queue*. A task is *ready* if it is in a ready queue, or if it is running. Each processor has one ready queue for each priority value. At any instant, each ready queue of a processor contains exactly the set of tasks of that priority that are ready for execution on that processor, but are not running on any processor; that is, those tasks that are ready, are not running on any processor, and can be executed using that processor and other available resources. A task can be on the ready queues of more than one processor.

**by:**

*Task dispatching policies* are specified in terms of conceptual *ready queues* and task states. A ready queue is an ordered list of ready tasks. The first position in a queue is called the *head of the queue*, and the last position is called the *tail of the queue*. A task is *ready* if it is in a ready queue, or if it is running. Each processor has one ready queue for each priority value. At any instant, each ready queue of a processor contains exactly the set of tasks of that priority that are ready for execution on that processor, but are not running on any processor; that is, those tasks that are ready, are not running on any processor, and can be executed using that processor and other available resources. A task can be on the ready queues of more than one processor.

**Replace paragraph 6: [AI95-00321-01]**

Each processor also has one *running task*, which is the task currently being executed by that processor. Whenever a task running on a processor reaches a task dispatching point, one task is selected to run on that processor. The task selected is the one at the head of the highest priority nonempty ready queue; this task is then removed from all ready queues to which it belongs.

**by:**

Each processor also has one *running task*, which is the task currently being executed by that processor. Whenever a task running on a processor reaches a task dispatching point it goes back to one or more ready queues; a task (possibly the same task) is then selected to run on that processor. The task selected is the one at the head of the highest priority nonempty ready queue; this task is then removed from all ready queues to which it belongs.

**Delete paragraph 7: [AI95-00321-01]**

A preemptible resource is a resource that while allocated to one task can be allocated (temporarily) to another instead. Processors are preemptible resources. Access to a protected object (see 9.5.1) is a nonpreemptible resource. {preempted task} When a higher-priority task is dispatched to the processor, and the previously running task is placed on the appropriate ready queue, the latter task is said to be *preempted*.

**Delete paragraph 8: [AI95-00321-01]**

A new running task is also selected whenever there is a nonempty ready queue with a higher priority than the priority of the running task, or when the task dispatching policy requires a running task to go back to a ready queue. These are also task dispatching points.

**Replace paragraph 9: [AI95-00321-01]**

An implementation is allowed to define additional resources as execution resources, and to define the corresponding allocation policies for them. Such resources may have an implementation defined effect on task dispatching (see D.2.2).

**by:**

An implementation is allowed to define additional resources as execution resources, and to define the corresponding allocation policies for them. Such resources may have an implementation-defined effect on task dispatching.

**Insert after paragraph 10: [AI95-00321-01]**

An implementation may place implementation-defined restrictions on tasks whose active priority is in the Interrupt\_Priority range.

**the new paragraph:**

For optimization purposes, an implementation may alter the points at which task dispatching occurs, in an implementation-defined manner. However, a `delay_statement` always corresponds to at least one task dispatching point.

**Insert after paragraph 16: [AI95-00321-01]**

12 The priority of a task is determined by rules specified in this subclause, and under D.1, "Task Priorities", D.3, "Priority Ceiling Locking", and D.5, "Dynamic Priorities".

**the new paragraph:**

13 The setting of a task's base priority as a result of a call to `Set_Priority` does not always take effect immediately when `Set_Priority` is called. The effect of setting the task's base priority is deferred while the affected task performs a protected action.

**D.2.2 Pragmas Task\_Dispatching\_Policy and Priority\_Specific\_Dispatching****Replace the title: [AI95-00321-01; AI95-00355-01]**

The Standard Task Dispatching Policy

**by:**

Pragmas Task\_Dispatching\_Policy and Priority\_Specific\_Dispatching

**Insert before paragraph 1: [AI95-00355-01]**

*Syntax*

The form of a `pragma Task_Dispatching_Policy` is as follows:

**the new paragraph:**

This clause allows a single task dispatching policy to be defined for all priorities, or the range of priorities to be split into subranges that are assigned individual dispatching policies.

**Insert after paragraph 2: [AI95-00355-01]**

**pragma** Task\_Dispatching\_Policy (*policy\_identifier*);

**the new paragraphs:**

The form of a `pragma Priority_Specific_Dispatching` is as follows:

**pragma** Priority\_Specific\_Dispatching (*policy\_identifier*, *first\_priority\_expression*, *last\_priority\_expression*);

*Name Resolution Rules*

The expected type for *first\_priority\_expression* and *last\_priority\_expression* is Integer.

**Replace paragraph 3: [AI95-00321-01; AI95-00355-01]**

The *policy\_identifier* shall either be FIFO\_Within\_Priorities or an implementation-defined identifier.

**by:**

The *policy\_identifier* used in a `pragma Task_Dispatching_Policy` shall be the name of a task dispatching policy.

The *policy\_identifier* *policy\_identifier* used in a `pragma Priority_Specific_Dispatching` shall be the name of a task dispatching policy.

Both *first\_priority\_expression* and *last\_priority\_expression* shall be static expressions in the range of System.Any\_Priority; *last\_priority\_expression* shall have a value greater than or equal to *first\_priority\_expression*.

*Static Semantics*

Pragma Task\_Dispatching\_Policy specifies the task dispatching policy.

Pragma Priority\_Specific\_Dispatching specifies the task dispatching policy for the specified range of priorities. Tasks within the range of priorities specified in a Priority\_Specific\_Dispatching pragma are dispatched according to the specified dispatching policy.

If a partition contains one or more Priority\_Specific\_Dispatching pragmas the dispatching policy for priorities not covered by any Priority\_Specific\_Dispatching pragmas is FIFO\_Within\_Priorities.

**Replace paragraph 4: [AI95-00333-01; AI95-00355-01]**

A Task\_Dispatching\_Policy pragma is a configuration pragma.

**by:**

A Task\_Dispatching\_Policy pragma is a configuration pragma. A Priority\_Specific\_Dispatching pragma is a configuration pragma.

The priority ranges specified in more than one Priority\_Specific\_Dispatching pragma within the same partition shall not be overlapping.

If a partition contains one or more Priority\_Specific\_Dispatching pragmas it shall not contain a Task\_Dispatching\_Policy pragma.

**Delete paragraph 5: [AI95-00321-01; AI95-00333-01]**

If the FIFO\_Within\_Priorities policy is specified for a partition, then the Ceiling\_Locking policy (see D.3) shall also be specified for the partition.

**Replace paragraph 6: [AI95-00355-01]**

A *task dispatching policy* specifies the details of task dispatching that are not covered by the basic task dispatching model. These rules govern when tasks are inserted into and deleted from the ready queues, and whether a task is inserted at the head or the tail of the queue for its active priority. The task dispatching policy is specified by a Task\_Dispatching\_Policy configuration pragma. If no such pragma appears in any of the program units comprising a partition, the task dispatching policy for that partition is unspecified.

**by:**

A *task dispatching policy* specifies the details of task dispatching that are not covered by the basic task dispatching model. These rules govern when tasks are inserted into and deleted from the ready queues. A single task dispatching policy is specified by a Task\_Dispatching\_Policy pragma. Pragma Priority\_Specific\_Dispatching assigns distinct dispatching policies to ranges of System.Any\_Priority.

If neither pragma applies to any of the program units comprising a partition, the task dispatching policy for that partition is unspecified.

If a partition contains one or more Priority\_Specific\_Dispatching pragmas a task dispatching point occurs for the currently running task of a processor whenever there is a non-empty ready queue for that processor with a higher priority than the priority of the running task.

A task that has its base priority changed may move from one dispatching policy to another. It is immediately dispatched according to the new policy.

**Delete paragraph 7: [AI95-00321-01]**

The language defines only one task dispatching policy, FIFO\_Within\_Priorities; when this policy is in effect, modifications to the ready queues occur only as follows:



**Delete paragraph 8: [AI95-00321-01]**

- When a blocked task becomes ready, it is added at the tail of the ready queue for its active priority.

**Delete paragraph 9: [AI95-00321-01]**

- When the active priority of a ready task that is not running changes, or the setting of its base priority takes effect, the task is removed from the ready queue for its old active priority and is added at the tail of the ready queue for its new active priority, except in the case where the active priority is lowered due to the loss of inherited priority, in which case the task is added at the head of the ready queue for its new active priority.

**Delete paragraph 10: [AI95-00321-01]**

- When the setting of the base priority of a running task takes effect, the task is added to the tail of the ready queue for its active priority.

**Delete paragraph 11: [AI95-00321-01]**

- When a task executes a `delay_statement` that does not result in blocking, it is added to the tail of the ready queue for its active priority.

**Delete paragraph 12: [AI95-00321-01]**

Each of the events specified above is a task dispatching point (see D.2.1).

**Replace paragraph 13: [AI95-00321-01; AI95-00333-01; AI95-00355-01]**

In addition, when a task is preempted, it is added at the head of the ready queue for its active priority.

by:

*Implementation Requirements*

An implementation shall allow specifying both the locking policy (see D.3) as `Ceiling_Locking` and one or more `Priority_Specific_Dispatching` pragmas for a single partition.

**Delete paragraph 14: [AI95-00321-01]**

*Priority inversion* is the duration for which a task remains at the head of the highest priority ready queue while the processor executes a lower priority task. The implementation shall document:

**Delete paragraph 15: [AI95-00321-01]**

- The maximum priority inversion a user task can experience due to activity of the implementation (on behalf of lower priority tasks), and

**Delete paragraph 16: [AI95-00321-01]**

- whether execution of a task can be preempted by the implementation processing of delay expirations for lower priority tasks, and if so, for how long.

**Replace paragraph 17: [AI95-00256-01; AI95-00321-01; AI95-00355-01]**

Implementations are allowed to define other task dispatching policies, but need not support more than one such policy per partition.

by:

Implementations are allowed to define other task dispatching policies, but need not support more than one task dispatching policy per partition.

An implementation need not support pragma `Priority_Specific_Dispatching` if it is infeasible to support it in the target environment.

**Delete paragraph 18: [AI95-00321-01]**

For optimization purposes, an implementation may alter the points at which task dispatching occurs, in an implementation defined manner. However, a *delay\_statement* always corresponds to at least one task dispatching point.

**Delete paragraph 19: [AI95-00321-01]**

13 If the active priority of a running task is lowered due to loss of inherited priority (as it is on completion of a protected operation) and there is a ready task of the same active priority that is not running, the running task continues to run (provided that there is no higher priority task).

**Delete paragraph 20: [AI95-00321-01]**

14 The setting of a task's base priority as a result of a call to *Set\_Priority* does not always take effect immediately when *Set\_Priority* is called. The effect of setting the task's base priority is deferred while the affected task performs a protected action.

**Delete paragraph 21: [AI95-00321-01]**

15 Setting the base priority of a ready task causes the task to move to the end of the queue for its active priority, regardless of whether the active priority of the task actually changes.

## D.2.3 Preemptive Dispatching

**Insert new clause: [AI95-00321-01; AI95-00333-01; AI95-00355-01]**

This clause defines a preemptive task dispatching policy.

*Static Semantics*

The *policy\_identifier* *FIFO\_Within\_Priorities* is a task dispatching policy.

*Dynamic Semantics*

When *FIFO\_Within\_Priorities* is in effect, modifications to the ready queues occur only as follows:

- When a blocked task becomes ready, it is added at the tail of the ready queue for its active priority.
- When the active priority of a ready task that is not running changes, or the setting of its base priority takes effect, the task is removed from the ready queue for its old active priority and is added at the tail of the ready queue for its new active priority, except in the case where the active priority is lowered due to the loss of inherited priority, in which case the task is added at the head of the ready queue for its new active priority.
- When the setting of the base priority of a running task takes effect, the task is added to the tail of the ready queue for its active priority.
- When a task executes a *delay\_statement* that does not result in blocking, it is added to the tail of the ready queue for its active priority.

Each of the events specified above is a task dispatching point (see D.2.1).

A task dispatching point occurs for the currently running task of a processor whenever there is a nonempty ready queue for that processor with a higher priority than the priority of the running task. The currently running task is said to be preempted and it is added at the head of the ready queue for its active priority.

*Implementation Requirements*

An implementation shall allow specifying both the task dispatching policy as *FIFO\_Within\_Priorities* and the locking policy (see D.3) as *Ceiling\_Locking* for a single partition.

*Documentation Requirements*

*Priority inversion* is the duration for which a task remains at the head of the highest priority nonempty ready queue while the processor executes a lower priority task. The implementation shall document:

- The maximum priority inversion a user task can experience due to activity of the implementation (on behalf of lower priority tasks), and
- whether execution of a task can be preempted by the implementation processing of delay expirations for lower priority tasks, and if so, for how long.

## NOTES

14 If the active priority of a running task is lowered due to loss of inherited priority (as it is on completion of a protected operation) and there is a ready task of the same active priority that is not running, the running task continues to run (provided that there is no higher priority task).

15 Setting the base priority of a ready task causes the task to move to the tail of the queue for its active priority, regardless of whether the active priority of the task actually changes.

## D.2.4 Non-Preemptive Dispatching

**Insert new clause: [AI95-00298-01; AI95-00333-01; AI95-00355-01]**

This clause defines a non-preemptive task dispatching policy.

*Static Semantics*

The *policy\_identifier* `Non_Preemptive_FIFO_Within_Priorities` is a task dispatching policy.

*Legality Rules*

`Non_Preemptive_FIFO_Within_Priorities` shall not be specified as the *policy\_identifier* of pragma `Priority_Specific_Dispatching` (see D.2.2).

*Dynamic Semantics*

When `Non_Preemptive_FIFO_Within_Priorities` is in effect, modifications to the ready queues occur only as follows:

- When a blocked task becomes ready, it is added at the tail of the ready queue for its active priority.
- When the active priority of a ready task that is not running changes, or the setting of its base priority takes effect, the task is removed from the ready queue for its old active priority and is added at the tail of the ready queue for its new active priority.
- When a task executes a `delay_statement` that does not result in blocking, it is added to the tail of the ready queue for its active priority. This is a task dispatching point (see D.2.1).

*Implementation Requirements*

An implementation shall allow specifying both the task dispatching policy as `Non_Preemptive_FIFO_Within_Priorities` and the locking policy (see D.3) as `Ceiling_Locking` for a single partition.

*Implementation Permissions*

Since implementations are allowed to round all ceiling priorities in subrange `System.Priority to System.Priority'Last` (see D.3), an implementation may allow a task to execute within a protected object without raising its active priority provided the protected object does not contain pragma `Interrupt_Priority`, `Interrupt_Handler` or `Attach_Handler`.

## D.2.5 Round Robin Dispatching

**Insert new clause: [AI95-00333-01; AI95-00355-01]**

This clause defines the task dispatching policy `Round_Robin_Within_Priorities` and the package `Round_Robin_Dispatching`.

*Static Semantics*

The *policy\_identifier* `Round_Robin_Within_Priorities` is a task dispatching policy.

The following language-defined library package exists:

```

with System;
with Ada.Real_Time;
package Ada.Dispatching.Round_Robin_Dispatching is
  Default_Quantum : constant Ada.Real_Time.Time_Span :=
    implementation-defined;
  procedure Set_Quantum (Pri      : in System.Priority;
                        Quantum  : in Ada.Real_Time.Time_Span);
  procedure Set_Quantum (Low, High : in System.Priority;
                        Quantum    : in Ada.Real_Time.Time_Span);
  function Actual_Quantum (Pri : System.Priority) return
Ada.Real_Time.Time_Span;
  function Is_Round_Robin (Pri : System.Priority) return Boolean;
end Ada.Dispatching.Round_Robin_Dispatching;

```

When task dispatching policy `Round_Robin_Within_Priorities` is the single policy in effect for a partition, each task with priority in the range of `System.Interrupt_Priority` is dispatched according to policy `FIFO_Within_Priorities`.

#### *Dynamic Semantics*

The procedures `Set_Quantum` set the required Quantum value for a single level `Pri` or a range of levels `Low .. High`. If no quantum is set for a Round Robin priority level, `Default_Quantum` is used.

The function `Actual_Quantum` returns the actual quantum used by the implementation for the priority level `Pri`.

The function `Is_Round_Robin` returns `True` if priority `Pri` is covered by task dispatching policy `Round_Robin_Within_Priorities`; otherwise it returns `False`.

A call of `Actual_Quantum` or `Set_Quantum` raises exception `Ada.Dispatching.Dispatching_Policy_Error` if a predefined policy other than `Round_Robin_Within_Priorities` applies to the specified priority.

For `Round_Robin_Within_Priorities`, the dispatching rules for `FIFO_Within_Priorities` apply with the following additional rules:

- When a task is added or moved to the tail of the ready queue for its base priority, it has an execution time budget equal to the quantum for that priority level. This will also occur when a blocked task becomes executable again.
- When a task is preempted (by a higher priority task) and is added to the head of the ready queue for its priority level, it retains its remaining budget.
- While a task is executing, its budget is decreased by the amount of execution time it uses. The accuracy of this accounting is the same as that for execution time clocks (see D.14).
- A task that has its base priority set to a Round Robin priority is moved to the tail of the ready queue for its new priority level.
- When a task has exhausted its budget and is without an inherited priority (and is not executing within a protected operation), it is moved to the tail of the ready queue for its priority level. This is a task dispatching point.

#### *Implementation Requirements*

An implementation shall allow specifying both the task dispatching policy as `Round_Robin_Within_Priorities` and the locking policy (see D.3) as `Ceiling_Locking` for a single partition.

#### *Documentation Requirements*

An implementation shall document the quantum values supported.

An implementation shall document the accuracy with which it detects the exhaustion of the budget of a task.

#### NOTES

17 Due to implementation constraints, the quantum value returned by `Actual_Quantum` might not be identical to the value set by `Set_Quantum`. However, if no value is set by `Set_Quantum`, then the value returned by `Actual_Quantum` will be identical to that of `Default_Quantum`.

18 A task that executes continuously with an inherited priority will not be subject to round robin dispatching.

## D.2.6 Earliest Deadline First Dispatching

### Insert new clause: [AI95-00357-01]

The deadline of a task is an indication of the urgency of the task; it represents a point on an ideal physical time line. Unless otherwise specified, whenever tasks compete for processors or other implementation-defined resources, the resources are allocated to the task with the earliest deadline.

This clause defines a package for representing a task's deadline and a dispatching policy that defines Earliest Deadline First (EDF) dispatching. A pragma is defined to assign an initial deadline to a task.

#### Static Semantics

The *policy\_identifier* `EDF_Across_Priorities` is a task dispatching policy.

The following language-defined library package exists:

```
with Ada.Real_Time;
with Ada.Task_Identification;
package Ada.Dispatching.EDF is
  subtype Deadline is Ada.Real_Time.Time;
  Default_Deadline : constant Deadline :=
    Ada.Real_Time.Time_Last;
  procedure Set_Deadline(D : in Deadline;
    T : in Ada.Task_Identification.Task_ID :=
      Ada.Task_Identification.Current_Task);
  procedure Delay_Until_And_Set_Deadline(
    Delay_Until_Time : in Ada.Real_Time.Time;
    Deadline_Offset : in Ada.Real_Time.Time_Span);
  function Get_Deadline(T : in Ada.Task_Identification.Task_ID :=
    Ada.Task_Identification.Current_Task) return Deadline;
end Ada.Dispatching.EDF;
```

#### Syntax

The form of a pragma `Relative_Deadline` is as follows:

**pragma** `Relative_Deadline` (*relative\_deadline\_expression*);

#### Name Resolution Rules

The expected type for *relative\_deadline\_expression* is `Ada.Real_Time.Time_Span`.

#### Legality Rules

A `Relative_Deadline` pragma is allowed only immediately within a `task_definition` or the `declarative_part` of a `subprogram_body`. At most one such pragma shall appear within a given construct.

#### Post-Compilation Rules

If the `EDF_Across_Priorities` policy is specified for a partition, then the `Ceiling_Locking` policy (see D.3) shall also be specified for the partition.

If the `EDF_Across_Priorities` policy appears in a `Priority_Specific_Dispatching` pragma (see D.2.2) in a partition, then the `Ceiling_Locking` policy (see D.3) shall also be specified for the partition.

#### Dynamic Semantics

A `Relative_Deadline` pragma has no effect if it occurs in the `declarative_part` of the `subprogram_body` of a subprogram other than the main subprogram.

The initial absolute deadline of a task containing pragma `Relative_Deadline` is the value of `Ada.Real_Time.Clock + relative_deadline_expression`, where the call of `Ada.Real_Time.Clock` is made

between task creation and the start of its activation. If there is no `Relative_Deadline` pragma then the initial absolute deadline of a task is the value of `Default_Deadline`. The environment task is also given an initial deadline by this rule.

The procedure `Set_Deadline` changes the absolute deadline of the task to `D`. The function `Get_Deadline` returns the absolute deadline of the task.

The procedure `Delay_Until_And_Set_Deadline` delays the calling task until time `Delay_Until_Time`. When the task becomes runnable again it will have deadline `Delay_Until_Time + Deadline_Offset`.

On a system with a single processor, the setting of a task's deadline to the new value occurs immediately at the first point that is outside the execution of an abort-deferred operation. If the task is currently on a ready queue it is removed and re-entered on to the ready queue determined by the rules defined below.

When `EDF_Across_Priorities` is specified for priority range *Low..High* all ready queues in this range are ordered by deadline. The task at the head of a queue is the one with the earliest deadline.

A task dispatching point occurs for the currently running task *T* to which policy `EDF_Across_Priorities` applies whenever:

- a change to the deadline of *T* occurs; or
- a decrease to the deadline of any task on a ready queue for that processor occurs and the new deadline is earlier than that of the running task; or
- there is a non-empty ready queue for that processor with a higher priority than the priority of the running task.

The currently running task is said to be preempted and is returned to the ready queue for its active priority.

Whenever a task *T* to which policy `EDF_Across_Priorities` applies is added to a ready queue, other than when it is preempted, it is placed on the ready queue with the highest priority *P*, if one exists, such that:

- a task is executing within a protected object with ceiling priority *P*; and
- task *T* has an earlier deadline than any task executing within a protected object with ceiling priority *P*; and
- the base priority of task *T* is greater than *P*.

If no such ready queue exists the task is added to the ready queue for the lowest priority in the range specified as `EDF_Across_Priorities`.

When the setting of the base priority of a task takes effect and the new priority is in the range specified as `EDF_Across_Priorities`, the task is added to the ready queue.

When a task is chosen for execution it runs with the active priority of the ready queue from which the task was taken. If it inherits a higher active priority it will return to its original active priority when it no longer inherits the higher level.

For all the operations defined in this package, `Tasking_Error` is raised if the task identified by *T* has terminated. `Program_Error` is raised if the value of *T* is `Null_Task_ID`.

#### *Bounded (Run-Time) Errors*

If `EDF_Across_Priorities` is specified for priority range *Low..High*, it is a bounded error to declare a protected object with ceiling priority *Low* or to assign the value *Low* to attribute `Priority`. In either case either `Program_Error` is raised or the ceiling of the protected object is assigned the value *Low*+1.

#### *Erroneous Execution*

If a value of `Task_ID` is passed as a parameter to any of the subprograms of this package and the corresponding task object no longer exists, the execution of the program is erroneous.

#### *Documentation Requirements*

On a multiprocessor, the implementation shall document any conditions that cause the completion of the setting of a task's deadline to be delayed later than what is specified for a single processor.

#### NOTES

16 If two adjacent priority ranges,  $A..B$  and  $B+1..C$  are specified to have policy EDF\_Across\_Priorities then this is not equivalent to this policy being specified for the single range,  $A..C$ .

17 The above rules implement the preemption-level protocol (also called Stack Resource Policy protocol) for resource sharing under EDF dispatching. The preemption-level for a task is denoted by its base priority. The definition of a ceiling preemption-level for a protected object follows the existing rules for ceiling locking.

## D.3 Priority Ceiling Locking

**Insert after paragraph 13: [AI95-00327-01]**

- When a task calls a protected operation, a check is made that its active priority is not higher than the ceiling of the corresponding protected object; Program\_Error is raised if this check fails.

**the new paragraphs:**

#### *Bounded (Run-Time) Errors*

Following any change of priority, it is a bounded error for the active priority of any task with a call queued on an entry of a protected object to be higher than the ceiling priority of the protected object. In this case one of the following applies:

- at any time prior to executing the entry body Program\_Error is raised in the calling task;
- when the entry is open the entry body is executed at the ceiling priority of the protected object;
- when the entry is open the entry body is executed at the ceiling priority of the protected object and then Program\_Error is raised in the calling task; or
- when the entry is open the entry body is executed at the ceiling priority of the protected object that was in effect when the entry call was queued.

**Replace paragraph 15: [AI95-00256-01]**

Implementations are allowed to define other locking policies, but need not support more than one such policy per partition.

**by:**

Implementations are allowed to define other locking policies, but need not support more than one locking policy per partition.

## D.4 Entry Queuing Policies

**Replace paragraph 7: [AI95-00355-01]**

Two queuing policies, FIFO\_Queueing and Priority\_Queueing, are language defined. If no Queuing\_Policy pragma appears in any of the program units comprising the partition, the queuing policy for that partition is FIFO\_Queueing. The rules for this policy are specified in 9.5.3 and 9.7.1.

**by:**

Two queuing policies, FIFO\_Queueing and Priority\_Queueing, are language defined. If no Queuing\_Policy pragma applies to any of the program units comprising the partition, the queuing policy for that partition is FIFO\_Queueing. The rules for this policy are specified in 9.5.3 and 9.7.1.

**Replace paragraph 15: [AI95-00188-02; AI95-00256-01]**

Implementations are allowed to define other queuing policies, but need not support more than one such policy per partition.

by:

Implementations are allowed to define other queuing policies, but need not support more than one queuing policy per partition.

Implementations are allowed to defer the reordering of entry queues following a change of base priority of a task blocked on the entry call if it is not practical to reorder the queue immediately.

## D.5 Dynamic Priorities

**Insert before paragraph 1: [AI95-00327-01]**

This clause specifies how the base priority of a task can be modified or queried at run time.

**the new paragraphs:**

This clause describes how the priority of an entity can be modified or queried at run time.

### D.5.1 Dynamic Priorities for Tasks

[This changes the subclause of all of the existing text.]

**Replace paragraph 3: [AI95-00362-01]**

```
with System;
with Ada.Task_Identification; -- See C.7.1
package Ada.Dynamic_Priorities is
```

by:

```
with System;
with Ada.Task_Identification; -- See C.7.1
package Ada.Dynamic_Priorities is
  pragma Preelaborate(Dynamic_Priorities);
```

**Replace paragraph 10: [AI95-00188-02]**

Setting the task's base priority to the new value takes place as soon as is practical but not while the task is performing a protected action. This setting occurs no later than the next abort completion point of the task T (see 9.8).

by:

On a system with a single processor, the setting of a task's base priority to the new value occurs immediately at the first point that is outside the execution of an abort-deferred operation.

**Delete paragraph 11: [AI95-00327-01]**

If a task is blocked on a protected entry call, and the call is queued, it is a bounded error to raise its base priority above the ceiling priority of the corresponding protected object. When an entry call is cancelled, it is a bounded error if the priority of the calling task is higher than the ceiling priority of the corresponding protected object. In either of these cases, either Program\_Error is raised in the task that called the entry, or its priority is temporarily lowered, or both, or neither.

**Insert after paragraph 12: [AI95-00188-02]**

If any subprogram in this package is called with a parameter T that specifies a task object that no longer exists, the execution of the program is erroneous.

**the new paragraph:**

*Documentation Requirements*

On a multiprocessor, the implementation shall document any conditions that cause the completion of the setting of a task's priority to be delayed later than what is specified for a single processor.



## D.5.2 Dynamic Priorities for Protected Objects

### Insert new clause: [AI95-00327-01]

This clause specifies how the priority of a protected object can be modified or queried at run time.

#### *Static Semantics*

The following attribute of a protected object is defined:

#### P'Priority

Denotes a non-aliased component of the enclosing protected object P. This component is of type System.Any\_Priority and its value is the priority of P. Reference to this attribute shall appear only inside the body of P.

The initial value of this attribute is set by pragmas Priority or Interrupt\_Priority, and can be changed by an assignment.

#### *Dynamic Semantics*

If the locking policy Ceiling\_Locking is in effect then the ceiling priority of a protected object P is set to the value of P'Priority at the end of each protected action of P.

#### *Metrics*

The implementation shall document the following metric:

- The difference in execution time of calls to the following procedures in protected object P,

```
protected P is
  procedure Do_Not_Set_Ceiling (Pr : System.Any_Priority);
  procedure Set_Ceiling (Pr : System.Any_Priority);
private
  null;
end P;

protected body P is
  procedure Do_Not_Set_Ceiling (Pr : System.Any_Priority) is
  begin
    null;
  end;
  procedure Set_Ceiling (Pr : System.Any_Priority) is
  begin
    P'Priority := Pr;
  end;
end P;
```

#### NOTES

38 Since P'Priority is a normal variable, the value following an assignment to the attribute immediately reflects the new value even though its impact on the ceiling priority of P is postponed until completion of the protected action in which it is executed.

## D.7 Tasking Restrictions

### Replace paragraph 4: [AI95-00360-01]

#### No\_Nested\_Finalization

Objects with controlled, protected, or task parts and access types that designate such objects, shall be declared only at library level.

by:

#### No\_Nested\_Finalization

Objects of a type that needs finalization (see 7.6) and access types that designate a type that needs finalization (see 7.6) shall be declared only at library level.

**Replace paragraph 9: [AI95-00327-01]**

No\_Dynamic\_Priorities

There are no semantic dependences on the package Dynamic\_Priorities.

**by:**

No\_Dynamic\_Priorities

There are no semantic dependences on the package Dynamic\_Priorities, and no occurrences of the attribute Priority.

**Insert after paragraph 10: [AI95-00305-01; AI95-00353-01]**

No\_Asynchronous\_Control

There are no semantic dependences on the package Asynchronous\_Task\_Control.

**the new paragraphs:**

No\_Calendar

There are no semantic dependencies on package Ada.Calendar.

No\_Dynamic\_Attachment

There is no call to any of the operations defined in package Ada.Interrupts (Is\_Reserved, Is\_Attached, Current\_Handler, Attach\_Handler, Exchange\_Handler, Detach\_Handler, and Reference).

No\_Local\_Protected\_Objects

Protected objects shall be declared only at library level.

No\_Protected\_Type\_Allocators

There are no allocators for protected types or types containing protected type components.

No\_Relative\_Delay

There are no `delay_relative_statements`.

No\_Requeue\_Statements

There are no `requeue_statements`.

No\_Select\_Statements

There are no `select_statements`.

No\_Synchronous\_Control

There are no semantic dependences on the package Synchronous\_Task\_Control.

No\_Task\_Attributes\_Package

There are no semantic dependencies on package Ada.Task\_Attributes.

Simple\_Barriers

The Boolean expression in an entry barrier shall be either a static Boolean expression or a Boolean component of the enclosing protected object.

**Replace paragraph 15: [AI95-00305-01]**

*This paragraph was deleted*

**by:**

No\_Task\_Termination

All tasks are non-terminating. It is implementation-defined what happens if a task attempts to terminate.

**Insert after paragraph 19: [AI95-00305-01]**

Max\_Tasks

Specifies the maximum number of task creations that may be executed over the lifetime of a partition, not counting the creation of the environment task. A value of zero prevents any task

creation and, if a program contains a task creation, it is illegal. If an implementation chooses to detect a violation of this restriction, `Storage_Error` should be raised; otherwise, the behavior is implementation defined.

the new paragraph:

`Max_Entry_Queue_Length`

`Max_Entry_Queue_Length` defines the maximum number of calls that are queued on an entry. Violation of this restriction results in the raising of `Program_Error` at the point of the call.

## D.8 Monotonic Time

Replace paragraph 14: [AI95-00386-01]

```
function Nanoseconds (NS : Integer) return Time_Span;
function Microseconds (US : Integer) return Time_Span;
function Milliseconds (MS : Integer) return Time_Span;
```

by:

```
function Nanoseconds (NS : Integer) return Time_Span;
function Microseconds (US : Integer) return Time_Span;
function Milliseconds (MS : Integer) return Time_Span;
function Seconds(S : Integer) return Time_Span;
function Minutes(M : Integer) return Time_Span;
```

Replace paragraph 26: [AI95-00386-01]

The functions `Nanoseconds`, `Microseconds`, and `Milliseconds` convert the input parameter to a value of the type `Time_Span`. `NS`, `US`, and `MS` are interpreted as a number of nanoseconds, microseconds, and milliseconds respectively. The result is rounded to the nearest exactly representable value (away from zero if exactly halfway between two exactly representable values).

by:

The functions `Nanoseconds`, `Microseconds`, `Milliseconds`, `Seconds`, and `Minutes` convert the input parameter to a value of the type `Time_Span`. `NS`, `US`, `MS`, `S`, and `M` are interpreted as a number of nanoseconds, microseconds, milliseconds, seconds, and minutes respectively. The result is rounded to the nearest exactly representable value (away from zero if exactly halfway between two exactly representable values).

## D.10 Synchronous Task Control

Replace paragraph 3: [AI95-00362-01]

```
package Ada.Synchronous_Task_Control is
```

by:

```
package Ada.Synchronous_Task_Control is
pragma Preelaborate(Synchronous_Task_Control);
```

## D.11 Asynchronous Task Control

Replace paragraph 3: [AI95-00362-01]

```
with Ada.Task_Identification;
package Ada.Asynchronous_Task_Control is
  procedure Hold(T : in Ada.Task_Identification.Task_ID);
  procedure Continue(T : in Ada.Task_Identification.Task_ID);
  function Is_Held(T : Ada.Task_Identification.Task_ID)
    return Boolean;
end Ada.Asynchronous_Task_Control;
```

by:

```
with Ada.Task_Identification;
package Ada.Asynchronous_Task_Control is
  pragma Preelaborate(Asynchronous_Task_Control);
  procedure Hold(T : in Ada.Task_Identification.Task_ID);
  procedure Continue(T : in Ada.Task_Identification.Task_ID);
  function Is_Held(T : Ada.Task_Identification.Task_ID)
    return Boolean;
end Ada.Asynchronous_Task_Control;
```

## D.13 Run-time Profiles and the Ravenscar Profile

**Insert new clause: [AI95-00249-01; AI95-00297-01]**

This clause specifies a mechanism for defining run-time profiles. It also defines one such profile, Ravenscar.

*Syntax*

The form of a pragma Profile is as follows:

**pragma** Profile (*profile\_identifier* {*profile\_pragma\_argument\_association*});

*Legality Rules*

The *profile\_identifier* shall be either Ravenscar or an implementation-defined identifier. For *profile\_identifier* Ravenscar, there shall be no *profile\_pragma\_argument\_associations*. For other *profile\_identifiers*, the semantics of any *profile\_pragma\_argument\_associations* are implementation-defined.

*Static Semantics*

A profile is equivalent to the set of configuration pragmas that is defined for each *profile\_identifier*. The *profile\_identifier* Ravenscar is equivalent to the following set of pragmas:

```
pragma Task_Dispatching_Policy (FIFO_Within_Priorities);
pragma Locking_Policy (Ceiling_Locking);
pragma Detect_Blocking;
pragma Restrictions (
  Max_Entry_Queue_Length => 1,
  Max_Protected_Entries => 1,
  Max_Task_Entries => 0,
  No_Abort_Statements,
  No_Asynchronous_Control,
  No_Calendar,
  No_Dynamic_Attachment,
  No_Dynamic_Priorities,
  No_Implicit_Heap_Allocations,
  No_Local_Timing_Events,
  No_Local_Protected_Objects,
  No_Protected_Type_Allocators,
  No_Relative_Delay,
  No_Requeue_Statements,
  No_Select_Statements,
  No_Task_Allocators,
  No_Task_Attributes_Package,
  No_Task_Hierarchy,
  No_Task_Termination,
  Simple_Barriers);
```

*Post-Compilation Rules*

A pragma Profile is a configuration pragma. There may be more than one pragma Profile for a partition.

NOTES

37 The effect of the Max\_Entry\_Queue\_Length => 1 restriction applies only to protected entry queues due to the accompanying restriction of Max\_Task\_Entries => 0.

## D.14 Execution Time

### Insert new clause: [AI95-00307-01]

This clause specifies an execution-time clock package.

*Static Semantics*

The following language-defined library package exists:

```
with Ada.Task_Identification;
with Ada.Real_Time; use Ada.Real_Time;
package Ada.Execution_Time is

  type CPU_Time is private;
  CPU_Time_First : constant CPU_Time;
  CPU_Time_Last  : constant CPU_Time;
  CPU_Time_Unit  : constant := implementation-defined-real-number;
  CPU_Tick       : constant Time_Span;

  function Clock
    (T : Ada.Task_Identification.Task_ID
     := Ada.Task_Identification.Current_Task)
    return CPU_Time;

  function "+" (Left : CPU_Time; Right : Time_Span) return CPU_Time;
  function "+" (Left : Time_Span; Right : CPU_Time) return CPU_Time;
  function "-" (Left : CPU_Time; Right : Time_Span) return CPU_Time;
  function "-" (Left : CPU_Time; Right : CPU_Time)  return Time_Span;

  function "<" (Left, Right : CPU_Time) return Boolean;
  function "<=" (Left, Right : CPU_Time) return Boolean;
  function ">" (Left, Right : CPU_Time) return Boolean;
  function ">=" (Left, Right : CPU_Time) return Boolean;

  procedure Split
    (T : in CPU_Time; SC : out Seconds_Count; TS : out Time_Span);

  function Time_Of (SC : Seconds_Count; TS : Time_Span) return CPU_Time;

private
  ... -- not specified by the language
end Ada.Execution_Time;
```

Execution time or CPU time of a given task is defined as the time spent by the system executing that task, including the time spent executing run-time or system services on behalf of it. The mechanism used to measure execution time is implementation defined. It is implementation defined which task, if any, is charged the execution time that is consumed by interrupt handlers and run-time services on behalf of the system.

The type CPU\_Time represents the execution time of a task. The set of values of the type CPU\_Time corresponds one-to-one with an implementation-defined range of mathematical integers.

The CPU\_Time value I represents the half-open execution-time interval that starts with I\*CPU\_Time\_Unit and is limited by (I+1)\*CPU\_Time\_Unit, where CPU\_Time\_Unit is an implementation-defined real number. For each task, the execution time value is set to zero at some unspecified point between the creation of the task and the start of the activation of the task.

CPU\_Time\_First and CPU\_Time\_Last are the smallest and largest values of the CPU\_Time type, respectively.

*Dynamic Semantics*

CPU\_Time\_Unit is the smallest amount of execution time representable by the CPU\_Time type; it is expressed in seconds. A CPU clock tick is an execution time interval during which the clock value (as observed by calling the Clock function) remains constant. CPU\_Tick is the average length of such intervals.

The effects of the operators on CPU\_Time and Time\_Span are as for the operators defined for integer types.

The function Clock returns the current execution time of the task T.

The effects of the Split and Time\_Of operations are defined as follows, treating values of type CPU\_Time, Time\_Span, and Seconds\_Count as mathematical integers. The effect of Split (T, SC, TS) is to set SC and TS to values such that  $T * \text{CPU\_Time\_Unit} = SC * 1.0 + TS * \text{CPU\_Time\_Unit}$ , and  $0.0 \leq TS * \text{CPU\_Time\_Unit} < 1.0$ . The value returned by Time\_Of(SC, TS) is the execution-time value T such that  $T * \text{CPU\_Time\_Unit} = SC * 1.0 + TS * \text{CPU\_Time\_Unit}$ .

For all the operations and types defined in this package, Tasking\_Error is raised if the task identified by T has terminated. Program\_Error is raised if the value of T is Null\_Task\_ID.

#### *Erroneous Execution*

If a value of Task\_ID is passed as a parameter to any of the subprograms of this package or used to define an object declared by a type provided by this package (or any language-defined child package of this package) and the corresponding task object no longer exists, the execution of the program is erroneous.

#### *Implementation Requirements*

The range of CPU\_Time values shall be sufficient to uniquely represent the range of execution times from the task start-up to 50 years of execution time later. CPU\_Tick shall be no greater than 1 millisecond.

#### *Documentation Requirements*

The implementation shall document the values of CPU\_Time\_First, CPU\_Time\_Last, CPU\_Time\_Unit, and CPU\_Tick.

The implementation shall document the properties of the underlying mechanism used to measure execution times, such as the range of values supported and any relevant aspects of the underlying hardware or operating system facilities used.

#### *Metrics*

The implementation shall document the following metrics:

- An upper bound on the execution-time duration of a clock tick. This is a value D such that if t1 and t2 are any execution times of a given task such that  $t1 < t2$  and  $\text{Clock}[t1] = \text{Clock}[t2]$  then  $t2 - t1 \leq D$ .
- An upper bound on the size of a clock jump. A clock jump is the difference between two successive distinct values of an execution-time clock (as observed by calling the Clock function with the same Task\_Id).
- An upper bound on the execution time of a call to the Clock function, in processor clock cycles.
- Upper bounds on the execution times of the operators of the type CPU\_Time, in processor clock cycles.

#### *Implementation Permissions*

Implementations targeted to machines with word size smaller than 32 bits need not support the full range and granularity of the CPU\_Time type.

#### *Implementation Advice*

When appropriate, implementations should provide configuration mechanisms to change the value of CPU\_Tick.

## D.14.1 Execution Time Timers

### Insert new clause: [AI95-00307-01]

This clause specifies a child of Execution\_Time that provides a facility for calling a handler when a task has used a defined quantity of CPU time.

#### *Static Semantics*

The following language-defined library package exists:

```

with Ada.Task_Identification;
with System;
with Ada.Real_Time; use Ada.Real_Time;
package Ada.Execution_Time.Timers is

    type Timer (T : access Ada.Task_Identification.Task_ID) is
        limited private;

    type Timer_Handler is access protected procedure (TM : in out Timer);

    Min_Handler_Ceiling : constant System.Any_Priority :=
        implementation-defined;

    procedure Set_Handler(TM: in out Timer; In_Time : in Time_Span;
        Handler : in Timer_Handler);
    procedure Set_Handler(TM: in out Timer; At_Time : in CPU_Time;
        Handler : in Timer_Handler);
    function Current_Handler(TM: Timer) return Timer_Handler;
    procedure Cancel_Handler(TM : in out Timer;
        Cancelled : in out Boolean);

    function Time_Remaining(TM : Timer) return Time_Span;

    Timer_Resource_Error : exception;

private
    ... -- not specified by the language
end Ada.Execution_Time.Timers;

```

The type Timer represents an execution-time event for a single task and is capable of detecting execution time overruns. The access discriminant T identifies the task concerned. The type Timer needs finalization (see 7.6).

An object of type Timer is said to be set if it is associated with a (non-null) Timer\_Handler and cleared otherwise. All Timer objects are initially cleared. The Timer\_Handler identifies a protected procedure to be executed by the implementation when the timer expires.

#### *Dynamic Semantics*

When a Timer object is created, or upon the first call of a Set\_Handler procedure with the timer as parameter, the resources required to operate a CPU-time timer based on the associated execution-time clock will be allocated and initialized. If this operation would exceed the limit of the maximum number of timers in the system, Timer\_Resource\_Error is raised.

A call of a procedure Set\_Handler associates a Timer\_Handler with a Timer. The first procedure Set\_Handler loads the timer with an interval specified by the Time\_Span parameter. In this state the timer counts execution time and, when the CPU clock associated with the timer measures the passage of In\_Time, it is said to have expired. The second procedure Set\_Handler loads the timer with the absolute value specified by At\_Time. In this state the timer monitors execution time and, when the CPU clock associated with the timer reaches the value At\_Time, it is said to have expired. If the value of At\_Time had already been reached by the clock at the time of the call, the timer is said to have expired.

A call of a procedure Set\_Handler for a Timer that is already set replaces the handler and the time of execution and the Timer remains set. A call with a null value of Handler clears the Timer.

When a Timer expires, the associated protected procedure `Timer_Handler` is executed with a parameter equal to the Timer. The initial action of the execution of the `Timer_Handler` is to clear the event.

The procedure `Cancel_Handler` clears the timer if it was set. `Cancelled` is assigned `True` if the timer was set prior to it being cleared, otherwise it is assigned `False`.

The function `Current_Handler` returns the `Timer_Handler` associated with the timer if the timer is set, otherwise it returns null.

The function `Time_Remaining` returns the CPU time interval that remains until the timer will expire if the timer is set, otherwise it returns `Time_Span_Zero`.

The constant `Min_Handler_Ceiling` is the priority value that will ensure that no ceiling violation will occur when a handler is executed.

For all the operations and types defined in this package, `Tasking_Error` is raised if the task identified by `T` has terminated. `Program_Error` is raised if the value of `T` is `Null_Task_ID`.

#### *Implementation Requirements*

For a given Timer object, the implementation shall perform the operations declared in this package atomically with respect to any of these operations on the same Timer object. The replacement of a handler by a call of `Set_Handler`, shall be performed atomically with respect to the execution of the `Timer_Handler`.

When an object of type `Timer` is finalized, the system resources used by the timer shall be deallocated.

#### *Implementation Permissions*

Implementations may limit the number of timers that can be defined for each task. If this limit is exceeded then `Timer_Resource_Error` is raised.

#### NOTES

A `Timer_Handler` can be associated with several Timer objects.

## D.14.2 Group Execution Time Budgets

### Insert new clause: [AI95-00354-01]

This clause specifies a group execution time control package.

#### *Static Semantics*

The following language-defined library package exists:

```

with System;
with Ada.Task_Identification;
package Ada.Execution_Time.Group_Budgets is
  type Group_Budget is limited private;

  type Group_Budget_Handler is access
    protected procedure (GB : in out Group_Budget);

  type Task_Array is array(Positive range <>) of
    Ada.Task_Identification.Task_ID;

  Min_Handler_Ceiling : constant System.Any_Priority :=
    implementation-defined;

  procedure Add_Task(GB: in out Group_Budget;
    T : in Ada.Task_Identification.Task_ID);
  procedure Remove_Task(GB: in out Group_Budget;
    T : in Ada.Task_Identification.Task_ID);
  function Is_Member(GB: Group_Budget;
    T : Ada.Task_Identification.Task_ID) return Boolean;
  function Is_A_Group_Member(
    T : Ada.Task_Identification.Task_ID) return Boolean;

```



```

function Members(GB: Group_Budget) return Task_Array;

procedure Replenish (GB: in out Group_Budget; To : in Time_Span);
procedure Add(GB: in out Group_Budget; Interval : in Time_Span);
function Budget_Has_Expired(GB: Group_Budget) return Boolean;
function Budget_Remaining(GB: Group_Budget) return Time_Span;

procedure Set_Handler(GB: in out Group_Budget;
                      Handler : in Group_Budget_Handler);
function Current_Handler(GB: Group_Budget)
                      return Group_Budget_Handler;
procedure Cancel_Handler(GB: in out Group_Budget;
                          Cancelled : out Boolean);

Group_Budget_Error : exception;
private
  -- not specified by the language
end Ada.Execution_Time.Group_Budgets;

```

The type `Group_Budget` represents a CPU budget to be used by a group of tasks. This type needs finalization (see 7.6). A task can belong to at most one group. Tasks of any priority can be added to a group.

An object of type `Group_Budget` is said to be *set* if it is associated with a (non-null) `Group_Budget_Handler` and *cleared* otherwise. All `Group_Budget` objects are initially cleared.

An object of type `Group_Budget` has an associated non-negative value of type `Time_Span` known as the *budget*. The `Group_Budget_Handler` identifies a protected procedure to be executed by the implementation when the budget is exhausted.

#### *Dynamic Semantics*

The procedure `Add_Task` adds a task to a group if the task is not a member of a group. Otherwise, `Group_Budget_Error` is raised.

The procedure `Remove_Task` removes a task from a group. If the task is not a member of the group `Group_Budget_Error` is raised; otherwise the task is no longer a member of any group.

The function `Is_Member` returns True if the task T is a member of the specified group. The function `Is_A_Group_Member` returns True if the task is a member of any group. Both return False otherwise.

The function `Members` returns an array of the task IDs of the members of the group. The order of the components of the array is not specified.

The procedure `Replenish` loads a `Group_Budget` with the `Time_Span` value passed as a parameter. Any execution of any member of the group of tasks results in the budget counting down. When the budget becomes exhausted (goes to `Time_Span_Zero`), the associated handler is called if the `Group_Budget` is set; the tasks continue to execute. A `Group_Budget` is initially loaded with zero budget.

The function `Budget_Remaining` returns the remaining budget. If the budget is exhausted it returns `Time_Span_Zero`. This is the minimum value for a budget. The function `Budget_Has_Expired` returns True if the budget is exhausted (equal to `Time_Span_Zero`), otherwise it returns False.

The procedure `Add` can be used to increase a budget. A negative value for the parameter reduces the budget, but never below `Time_Span_Zero`. A zero value for the parameter has no effect.

A call of procedure `Replenish` with a non-positive `Time_Span` value causes `Group_Budget_Error` to be raised. A call of procedure `Add` that results in the value of the budget going to `Time_Span_Zero` causes the associated handler to be called if the `Group_Budget` is set.

The procedure `Set_Handler` associates a `Group_Budget_Handler` with a `Group_Budget` and thereby sets the `Group_Budget`. A call of `Set_Handler` for a `Group_Budget` that is already set replaces the handler and the `Group_Budget` remains set. A call with a null value of `Handler` clears the `Group_Budget`.

The function `Current_Handler` returns the `Group_Budget_Handler` associated with the `Group Budget` if it is set, otherwise it returns null.

The procedure `Cancel_Handler` clears the `Group_Budget` if it was set. `Cancelled` is assigned `True` if the `Group_Budget` was set prior to it being cleared, otherwise it is assigned `False`.

The constant `Min_Handler_Ceiling` is the priority value that will ensure that no ceiling violation will occur when a handler is executed.

The precision of the accounting of task execution time to a `Group_Budget` is the same as that defined for execution-time clocks from the parent package.

As part of the finalization of an object of type `Group_Budget` all member tasks are removed from the group identified by the object.

If a task is a member of a `Group_Budget` when it terminates then as part of the finalization of the task it is removed from the group.

For all the operations and types defined in this package, `Tasking_Error` is raised if the task identified by `T` has terminated. `Program_Error` is raised if the value of `T` is `Null_Task_ID`.

#### *Implementation Requirements*

For a given `Group_Budget` object, the implementation shall perform the operations declared in this package atomically with respect to any of these operations on the same `Group_Budget` object. The replacement of a handler, by a call of `Set_Handler`, shall be performed atomically with respect to the execution of the `Group_Budget_Handler`.

#### NOTES

Clearing or setting of a handler does not change the current value of the budget. Exhaustion or loading of a budget does not change whether the handler is set or cleared.

A `Group_Budget_Handler` can be associated with several `Group_Budget` objects.

## D.15 Timing Events

### **Insert new clause: [AI95-00297-01]**

This clause introduces a language-defined child package of `Ada.Real_Time` to allow user-defined protected procedures to be executed at a specified time without the need to use a task or a delay statement.

#### *Static Semantics*

The following language-defined package exists:

```
package Ada.Real_Time.Timing_Events is
  type Timing_Event is limited private;
  type Timing_Event_Handler
    is access protected procedure(Event : in out Timing_Event);
  procedure Set_Handler(Event : in out Timing_Event;
    At_Time : in Time; Handler: in Timing_Event_Handler);
  procedure Set_Handler(Event : in out Timing_Event;
    In_Time: in Time_Span; Handler: in Timing_Event_Handler);
  function Current_Handler(Event : Timing_Event)
    return Timing_Event_Handler;
  procedure Cancel_Handler(Event : in out Timing_Event;
    Cancelled : out Boolean);
  function Time_Of_Event(Event : Timing_Event) return Time;
private
  ... -- not specified by the language
end Ada.Real_Time.Timing_Events;
```

The type `Timing_Event` represents a time in the future when an event is to occur. The type `Timing_Event` needs finalization (see 7.6).

An object of type `Timing_Event` is said to be *set* if it is associated with a (non-null) `Timing_Event_Handler` and *cleared* otherwise. All `Timing_Event` objects are initially cleared. The `Timing_Event_Handler` identifies a protected procedure to be executed by the implementation when the timing event occurs.

*Dynamic Semantics*

The procedures `Set_Handler` associate a `Timing_Event_Handler` with a `Timing_Event`. The first procedure `Set_Handler` sets the `Timing_Event_Handler` for execution at time `At_Time`. The second procedure `Set_Handler` sets the `Timing_Event_Handler` for execution at time `Ada.Real_Time.Clock + In_Time`.

A call of a procedure `Set_Handler` for a `Timing_Event` that is already set replaces the handler and the time of execution and the `Timing_Event` remains set. A call with a null value of `Handler` clears the event.

As soon as possible after the time set for the event, the `Timing_Event_Handler` is executed. The `Timing_Event_Handler` is only executed if the timing event is in the set state at the time of execution. The initial action of the execution of the `Timing_Event_Handler` is to clear the event.

If the `Ceiling_Locking` policy (see D.3) is in effect when a procedure `Set_Handler` is called, a check is made that the ceiling priority of `Timing_Event_Handler` is `Interrupt_Priority'Last`. If the check fails, `Program_Error` is raised.

If a procedure `Set_Handler` is called with zero or negative `In_Time` or with `At_Time` indicating a time in the past then `Timing_Event_Handler` is executed immediately by the task executing the call of `Set_Handler`. The `Timing_Event` denoted by `Event` is cleared.

An exception propagated from a `Timing_Event_Handler` invoked by a timing event has no effect.

The function `Current_Handler` returns the `Timing_Event_Handler` associated with the event if the event is set, otherwise it returns null.

The procedure `Cancel_Handler` clears the event if it was set. `Cancelled` is assigned `True` if the event was set prior to it being cleared, otherwise it is assigned `False`.

The function `Time_Of_Event` returns the time of the event if the event is set, otherwise it returns `Ada.Real_Time.Time_First`.

As the final step of finalization of an object of type `Timing_Event`, the `Timing_Event` is cleared.

If several timing events are set for the same time, they are executed in FIFO order of being set.

*Implementation Requirements*

For a given `Timing_Event` object, the implementation shall perform the operations declared in this package atomically with respect to any of these operations on the same `Timing_Event` object. The replacement of a handler, by a call of `Set_Handler`, shall be performed atomically with respect to the execution of the `Timing_Event_Handler`.

*Metrics*

The implementation shall document the following metric:

- An upper bound on the lateness of the execution of a handler. That is, the maximum time between when a handler is actually executed and the time specified when the event was set.

*Implementation Advice*

The protected handler procedure should be executed directly by the real-time clock interrupt mechanism.

## NOTES

Since a call of `Set_Handler` is not a blocking operation, it can be called from within a `Timing_Event_Handler`.

A `Timing_Event_Handler` can be associated with several `Timing_Event` objects.

## Annex E: Distributed Systems

### E.1 Partitions

**Replace paragraph 10: [AI95-00226-01]**

It is a bounded error for there to be cyclic elaboration dependences between the active partitions of a single distributed program. The possible effects are deadlock during elaboration, or the raising of Program\_Error in one or all of the active partitions involved.

**by:**

It is a bounded error for there to be cyclic elaboration dependences between the active partitions of a single distributed program. The possible effects, in each of the partitions involved, are deadlock during elaboration, or the raising of Communication\_Error or Program\_Error.

### E.2.2 Remote Types Library Units

**Replace paragraph 8: [AI95-00240-01; AI95-00366-01]**

- if the full view of a type declared in the visible part of the library unit has a part that is of a non-remote access type, then that access type, or the type of some part that includes the access type subcomponent, shall have user-specified Read and Write attributes.

**by:**

- the full view of each type declared in the visible part of the library unit shall support external streaming.

**Replace paragraph 14: [AI95-00240-01; AI95-00366-01]**

- The primitive subprograms of the corresponding specific limited private type shall only have access parameters if they are controlling formal parameters; each non-controlling formal parameter shall have either a nonlimited type or a type with Read and Write attributes specified via an `attribute_definition_clause`;

**by:**

- The primitive subprograms of the corresponding specific limited private type shall only have access parameters if they are controlling formal parameters; each non-controlling formal parameter shall support external streaming;

**Replace paragraph 17: [AI95-00366-01]**

- The Storage\_Pool and Storage\_Size attributes are not defined for remote access-to-class-wide types; the expected type for an allocator shall not be a remote access-to-class-wide type; a remote access-to-class-wide type shall not be an actual parameter for a generic formal access type.

**by:**

- The Storage\_Pool attribute is not defined for a remote access-to-class-wide type; the expected type for an allocator shall not be a remote access-to-class-wide type. A remote access-to-class-wide type shall not be an actual parameter for a generic formal access type. The Storage\_Size attribute of a remote access-to-class-wide type yields 0; it is not allowed in an `attribute_definition_clause`.

### E.2.3 Remote Call Interface Library Units

**Replace paragraph 14:** [AI95-00240-01; AI95-00366-01]

- it shall not be, nor shall its visible part contain, a subprogram (or access-to-subprogram) declaration whose profile has an access parameter, or a formal parameter of a limited type unless that limited type has user-specified Read and Write attributes;

**by:**

- it shall not be, nor shall its visible part contain, a subprogram (or access-to-subprogram) declaration whose profile has an access parameter, or a formal parameter of a limited type unless that limited type has available Read and Write attributes (see 13.13.2);

### E.5 Partition Communication Subsystem

**Replace paragraph 1:** [AI95-00273-01]

The *Partition Communication Subsystem* (PCS) provides facilities for supporting communication between the active partitions of a distributed program. The package System.RPC is a language-defined interface to the PCS. An implementation conforming to this Annex shall use the RPC interface to implement remote subprogram calls.

**by:**

The *Partition Communication Subsystem* (PCS) provides facilities for supporting communication between the active partitions of a distributed program. The package System.RPC is a language-defined interface to the PCS.

**Insert after paragraph 27:** [AI95-00273-01]

A body for the package System.RPC need not be supplied by the implementation.

**the new paragraph:**

An alternative declaration is allowed for package System.RPC as long as it provides a set of operations that is substantially equivalent to the specification defined in this clause.

## Annex F: Information Systems

### Replace paragraph 4: [AI95-00285-01]

- the child packages Text\_IO Editing and Wide\_Text\_IO Editing, which support formatted and localized output of decimal data, based on "picture String" values.

by:

- the child packages Text\_IO Editing, Wide\_Text\_IO Editing, and Wide\_Wide\_Text\_IO Editing, which support formatted and localized output of decimal data, based on "picture String" values.

### F.3 Edited Output for Decimal Types

#### Replace paragraph 1: [AI95-00285-01]

The child packages Text\_IO Editing and Wide\_Text\_IO Editing provide localizable formatted text output, known as *edited output*, for decimal types. An edited output string is a function of a numeric value, program-specifiable locale elements, and a format control value. The numeric value is of some decimal type. The locale elements are:

by:

The child packages Text\_IO Editing, Wide\_Text\_IO Editing, and Wide\_Wide\_Text\_IO Editing provide localizable formatted text output, known as *edited output*, for decimal types. An edited output string is a function of a numeric value, program-specifiable locale elements, and a format control value. The numeric value is of some decimal type. The locale elements are:

#### Replace paragraph 6: [AI95-00285-01]

For Text\_IO Editing the edited output and currency strings are of type String, and the locale characters are of type Character. For Wide\_Text\_IO Editing their types are Wide\_String and Wide\_Character, respectively.

by:

For Text\_IO Editing the edited output and currency strings are of type String, and the locale characters are of type Character. For Wide\_Text\_IO Editing their types are Wide\_String and Wide\_Character, respectively. For Wide\_Wide\_Text\_IO Editing their types are Wide\_Wide\_String and Wide\_Wide\_Character, respectively.

#### Replace paragraph 19: [AI95-00285-01]

The generic packages Text\_IO.Decimal\_IO and Wide\_Text\_IO.Decimal\_IO (see A.10.9, "Input-Output for Real Types") provide text input and non-edited text output for decimal types.

by:

The generic packages Text\_IO.Decimal\_IO, Wide\_Text\_IO.Decimal\_IO, and Wide\_Wide\_Text\_IO.Decimal\_IO (see A.10.9, "Input-Output for Real Types") provide text input and non-edited text output for decimal types.

#### Replace paragraph 20: [AI95-00285-01]

- 2 A picture String is of type Standard.String, both for Text\_IO Editing and Wide\_Text\_IO Editing.

by:

- 2 A picture String is of type Standard.String, for all of Text\_IO Editing, Wide\_Text\_IO Editing, and Wide\_Wide\_Text\_IO Editing.

### F.3.5 The Package Wide\_Wide\_Text\_IO.Editing

**Insert new clause: [AI95-00285-01]**

*Static Semantics*

The child package Wide\_Wide\_Text\_IO.Editing has the same contents as Text\_IO.Editing, except that:

- each occurrence of Character is replaced by Wide\_Wide\_Character,
- each occurrence of Text\_IO is replaced by Wide\_Wide\_Text\_IO,
- the subtype of Default\_Currency is Wide\_Wide\_String rather than String, and each occurrence of String in the generic package Decimal\_Output is replaced by Wide\_Wide\_String.

#### NOTES

6 Each of the functions Wide\_Wide\_Text\_IO.Editing.Valid, To\_Picture, and Pic\_String has String (versus Wide\_Wide\_String) as its parameter or result subtype, since a picture String is not localizable.

## Annex G: Numerics

### G.1.1 Complex Types

Replace paragraph 4: [AI95-00161-01]

```
type Imaginary is private;
```

by:

```
type Imaginary is private;  
pragma Preelaborable_Initialization(Imaginary);
```

### G.1.2 Complex Elementary Functions

Replace paragraph 15: [AI95-00185-01]

The real (resp., imaginary) component of the result of the Arcsin and Arccos (resp., Arctanh) functions is discontinuous as the parameter  $X$  crosses the real axis to the left of  $-1.0$  or the right of  $1.0$ .

by:

The imaginary component of the result of the Arcsin, Arccos, and Arctanh functions is discontinuous as the parameter  $X$  crosses the real axis to the left of  $-1.0$  or the right of  $1.0$ .

Replace paragraph 16: [AI95-00185-01]

The real (resp., imaginary) component of the result of the Arctan (resp., Arcsinh) function is discontinuous as the parameter  $X$  crosses the imaginary axis below  $-i$  or above  $i$ .

by:

The real component of the result of the Arctan and Arcsinh functions is discontinuous as the parameter  $X$  crosses the imaginary axis below  $-i$  or above  $i$ .

Replace paragraph 17: [AI95-00185-01]

The real component of the result of the Arccot function is discontinuous as the parameter  $X$  crosses the imaginary axis between  $-i$  and  $i$ .

by:

The real component of the result of the Arccot function is discontinuous as the parameter  $X$  crosses the imaginary axis below  $-i$  or above  $i$ .

Replace paragraph 20: [AI95-00185-01]

The computed results of the mathematically multivalued functions are rendered single-valued by the following conventions, which are meant to imply the principal branch:

by:

The computed results of the mathematically multivalued functions are rendered single-valued by the following conventions, which are meant to imply that the principal branch is an analytic continuation of the corresponding real-valued function in Ada.Numerics.Generic\_Elementary\_Functions. (For Arctan and Arccot, the single-argument function in question is that obtained from the two-argument version by fixing the second argument to be its default value.)



### G.1.3 Complex Input-Output

**Insert before paragraph 10:** [AI95-00328-01]

The semantics of the Get and Put procedures are as follows:

**the new paragraph:**

The library package `Complex_Text_IO` defines the same subprograms as `Text_IO.Complex_IO`, except that the predefined type `Float` is systematically substituted for `Real`, and the type `Numerics.Complex_Types.Complex` is systematically substituted for `Complex` throughout. Non-generic equivalents of `Text_IO.Complex_IO` corresponding to each of the other predefined floating point types are defined similarly, with the names `Short_Complex_Text_IO`, `Long_Complex_Text_IO`, etc.

### G.1.5 The Package `Wide_Wide_Text_IO.Complex_IO`

**Insert new clause:** [AI95-00285-01]

*Static Semantics*

Implementations shall also provide the generic library package `Wide_Wide_Text_IO.Complex_IO`. Its declaration is obtained from that of `Text_IO.Complex_IO` by systematically replacing `Text_IO` by `Wide_Wide_Text_IO` and `String` by `Wide_Wide_String`; the description of its behavior is obtained by additionally replacing references to particular characters (commas, parentheses, etc.) by those for the corresponding wide wide characters.

### G.2.2 Model-Oriented Attributes of Floating Point Types

**Replace paragraph 3:** [AI95-00256-01]

Yields the number of digits in the mantissa of the canonical form of the model numbers of  $T$  (see A.5.3). The value of this attribute shall be greater than or equal to  $\text{Ceiling}(d * \log(10) / \log(T'Machine\_Radix)) + 1$ , where  $d$  is the requested decimal precision of  $T$ . In addition, it shall be less than or equal to the value of  $T'Machine\_Mantissa$ . This attribute yields a value of the type *universal\_integer*.

**by:**

Yields the number of digits in the mantissa of the canonical form of the model numbers of  $T$  (see A.5.3). The value of this attribute shall be greater than or equal to

$$\text{ceiling}(d * \log(10) / \log(T'Machine\_Radix)) + g$$

where  $d$  is the requested decimal precision of  $T$ , and  $g$  is 0 if `Machine_Radix` is a positive power of 10 and 1 otherwise. In addition, it shall be less than or equal to the value of  $T'Machine\_Mantissa$ . This attribute yields a value of the type *universal\_integer*.

### G.3 Vector and Matrix Manipulation

**Insert new clause:** [AI95-00296-01]

Types and operations for the manipulation of real vectors and matrices are provided in `Generic_Real_Arrays`, which is defined in G.3.1. Types and operations for the manipulation of complex vectors and matrices are provided in `Generic_Complex_Arrays`, which is defined in G.3.2. Both of these library units are generic children of the predefined package `Numerics` (see A.5). Nongeneric equivalents of these packages for each of the predefined floating point types are also provided as children of `Numerics`.

### G.3.1 Real Vectors and Matrices

Insert new clause: [AI95-00296-01]

*Static Semantics*

The generic library package Numerics.Generic\_Real\_Arrays has the following declaration:

```

generic
  type Real is digits <>;
package Ada.Numerics.Generic_Real_Arrays is
  pragma Pure(Generic_Real_Arrays);

  -- Types

  type Real_Vector is array (Integer range <>) of Real'Base;
  type Real_Matrix is array (Integer range <>, Integer range <>) of
    Real'Base;

  -- Subprograms for Real_Vector types

  -- Real_Vector arithmetic operations

  function "+" (Right : Real_Vector) return Real_Vector;
  function "-" (Right : Real_Vector) return Real_Vector;
  function "abs" (Right : Real_Vector) return Real_Vector;

  function "+" (Left, Right : Real_Vector) return Real_Vector;
  function "-" (Left, Right : Real_Vector) return Real_Vector;

  function "*" (Left, Right : Real_Vector) return Real'Base;

  -- Real_Vector scaling operations

  function "*" (Left : Real'Base; Right : Real_Vector) return Real_Vector;
  function "*" (Left : Real_Vector; Right : Real'Base) return Real_Vector;
  function "/" (Left : Real_Vector; Right : Real'Base) return Real_Vector;

  -- Other Real_Vector operations

  function Unit_Vector (Index : Integer;
    Order : Positive;
    First : Integer := 1) return Real_Vector;

  -- Subprograms for Real_Matrix types

  -- Real_Matrix arithmetic operations

  function "+" (Right : Real_Matrix) return Real_Matrix;
  function "-" (Right : Real_Matrix) return Real_Matrix;
  function "abs" (Right : Real_Matrix) return Real_Matrix;
  function Transpose (X : Real_Matrix) return Real_Matrix;

  function "+" (Left, Right : Real_Matrix) return Real_Matrix;
  function "-" (Left, Right : Real_Matrix) return Real_Matrix;
  function "*" (Left, Right : Real_Matrix) return Real_Matrix;

  function "*" (Left, Right : Real_Vector) return Real_Matrix;

  function "*" (Left : Real_Vector; Right : Real_Matrix) return Real_Vector;
  function "*" (Left : Real_Matrix; Right : Real_Vector) return Real_Vector;

  -- Real_Matrix scaling operations

  function "*" (Left : Real'Base; Right : Real_Matrix) return Real_Matrix;
  function "*" (Left : Real_Matrix; Right : Real'Base) return Real_Matrix;

```

```

function "/" (Left : Real_Matrix; Right : Real'Base) return Real_Matrix;

-- Real_Matrix inversion and related operations

function Solve (A : Real_Matrix; X: Real_Vector) return Real_Vector;
function Solve (A, X : Real_Matrix) return Real_Matrix;
function Inverse (A : Real_Matrix) return Real_Matrix;
function Determinant (A : Real_Matrix) return Real'Base;

-- Eigenvalues and vectors of a real symmetric matrix

function Eigenvalues(A : Real_Matrix) return Real_Vector;

procedure Eigensystem(A      : in Real_Matrix;
                      Values : out Real_Vector;
                      Vectors : out Real_Matrix);

-- Other Real_Matrix operations

function Unit_Matrix (Order      : Positive;
                      First_1, First_2 : Integer := 1)
                      return Real_Matrix;

end Ada.Numerics.Generic_Real_Arrays;

```

The library package Numerics.Real\_Arrays is declared pure and defines the same types and subprograms as Numerics.Generic\_Real\_Arrays, except that the predefined type Float is systematically substituted for Real'Base throughout. Nongeneric equivalents for each of the other predefined floating point types are defined similarly, with the names Numerics.Short\_Real\_Arrays, Numerics.Long\_Real\_Arrays, etc.

Two types are defined and exported by Ada.Numerics.Generic\_Real\_Arrays. The composite type Real\_Vector is provided to represent a vector with components of type Real; it is defined as an unconstrained, one-dimensional array with an index of type Integer. The composite type Real\_Matrix is provided to represent a matrix with components of type Real; it is defined as an unconstrained, two-dimensional array with indices of type Integer.

The effect of the various functions is as described below. In most cases the functions are described in terms of corresponding scalar operations of the type Real; any exception raised by those operations is propagated by the array operation. Moreover, the accuracy of the result for each individual component is as defined for the scalar operation unless stated otherwise.

In the case of those operations which are defined to involve an inner product, Constraint\_Error may be raised if an intermediate result is outside the range of Real'Base even though the mathematical final result would not be.

```

function "+" (Right : Real_Vector) return Real_Vector;
function "-" (Right : Real_Vector) return Real_Vector;
function "abs" (Right : Real_Vector) return Real_Vector;

```

Each operation returns the result of applying the corresponding operation of the type Real to each component of Right. The index range of the result is Right'Range.

```

function "+" (Left, Right : Real_Vector) return Real_Vector;
function "-" (Left, Right : Real_Vector) return Real_Vector;

```

Each operation returns the result of applying the corresponding operation of the type Real to each component of Left and the matching component of Right. The index range of the result is Left'Range. Constraint\_Error is raised if Left'Length is not equal to Right'Length.

```

function "*" (Left, Right : Real_Vector) return Real'Base;

```

This operation returns the inner product of Left and Right. Constraint\_Error is raised if Left'Length is not equal to Right'Length. This operation involves an inner product.

```

function "*" (Left : Real'Base; Right : Real_Vector) return Real_Vector;

```

This operation returns the result of multiplying each component of *Right* by the scalar *Left* using the "\*" operation of the type *Real*. The index range of the result is *Right*'Range.

```
function "*" (Left : Real_Vector; Right : Real'Base) return Real_Vector;  
function "/" (Left : Real_Vector; Right : Real'Base) return Real_Vector;
```

Each operation returns the result of applying the corresponding operation of the type *Real* to each component of *Left* and to the scalar *Right*. The index range of the result is *Left*'Range.

```
function Unit_Vector (Index : Integer;  
                      Order : Positive;  
                      First : Integer := 1) return Real_Vector;
```

This function returns a *unit vector* with *Order* components and a lower bound of *First*. All components are set to 0.0 except for the *Index* component which is set to 1.0. *Constraint\_Error* is raised if *Index* < *First*, *Index* > *First* + *Order* - 1 or if *First* + *Order* - 1 > *Integer*'Last.

```
function "+" (Right : Real_Matrix) return Real_Matrix;  
function "-" (Right : Real_Matrix) return Real_Matrix;  
function "abs" (Right : Real_Matrix) return Real_Matrix;
```

Each operation returns the result of applying the corresponding operation of the type *Real* to each component of *Right*. The index ranges of the result are those of *Right*.

```
function Transpose (X : Real_Matrix) return Real_Matrix;
```

This function returns the transpose of a matrix *X*. The first and second index ranges of the result are *X*'Range(2) and *X*'Range(1) respectively.

```
function "+" (Left, Right : Real_Matrix) return Real_Matrix;  
function "-" (Left, Right : Real_Matrix) return Real_Matrix;
```

Each operation returns the result of applying the corresponding operation of the type *Real* to each component of *Left* and the matching component of *Right*. The index ranges of the result are those of *Left*. *Constraint\_Error* is raised if *Left*'Length(1) is not equal to *Right*'Length(1) or *Left*'Length(2) is not equal to *Right*'Length(2).

```
function "*" (Left, Right : Real_Matrix) return Real_Matrix;
```

This operation provides the standard mathematical operation for matrix multiplication. The first and second index ranges of the result are *Left*'Range(1) and *Right*'Range(2) respectively. *Constraint\_Error* is raised if *Left*'Length(2) is not equal to *Right*'Length(1). This operation involves inner products.

```
function "*" (Left, Right : Real_Vector) return Real_Matrix;
```

This operation returns the outer product of a (column) vector *Left* by a (row) vector *Right* using the operation "\*" of the type *Real* for computing the individual components. The first and second index ranges of the matrix result are *Left*'Range and *Right*'Range respectively.

```
function "*" (Left : Real_Vector; Right : Real_Matrix) return Real_Vector;
```

This operation provides the standard mathematical operation for multiplication of a (row) vector *Left* by a matrix *Right*. The index range of the (row) vector result is *Right*'Range(2). *Constraint\_Error* is raised if *Left*'Length is not equal to *Right*'Length(1). This operation involves inner products.

```
function "*" (Left : Real_Matrix; Right : Real_Vector) return Real_Vector;
```

This operation provides the standard mathematical operation for multiplication of a matrix *Left* by a (column) vector *Right*. The index range of the (column) vector result is *Left*'Range(1). *Constraint\_Error* is raised if *Left*'Length(2) is not equal to *Right*'Length. This operation involves inner products.

```
function "*" (Left : Real'Base; Right : Real_Matrix) return Real_Matrix;
```

This operation returns the result of multiplying each component of *Right* by the scalar *Left* using the "\*" operation of the type *Real*. The index ranges of the matrix result are those of *Right*.

```
function "*" (Left : Real_Matrix; Right : Real'Base) return Real_Matrix;
function "/" (Left : Real_Matrix; Right : Real'Base) return Real_Matrix;
```

Each operation returns the result of applying the corresponding operation of the type Real to each component of Left and to the scalar Right. The index ranges of the matrix result are those of Left.

```
function Solve (A : Real_Matrix; X: Real_Vector) return Real_Vector;
```

This function returns a vector Y such that X is (nearly) equal to A \* Y. This is the standard mathematical operation for solving a single set of linear equations. The index range of the result is X'Range. Constraint\_Error is raised if A'Length(1), A'Length(2) and X'Length are not equal. Constraint\_Error is raised if the matrix A is ill-conditioned.

```
function Solve (A, X : Real_Matrix) return Real_Matrix;
```

This function returns a matrix Y such that X is (nearly) equal to A \* Y. This is the standard mathematical operation for solving several sets of linear equations. The index ranges of the result are those of X. Constraint\_Error is raised if A'Length(1), A'Length(2) and X'Length(1) are not equal. Constraint\_Error is raised if the matrix A is ill-conditioned.

```
function Inverse (A : Real_Matrix) return Real_Matrix;
```

This function returns a matrix B such that A \* B is (nearly) equal to the unit matrix. The index ranges of the result are those of A. Constraint\_Error is raised if A'Length(1) is not equal to A'Length(2). Constraint\_Error is raised if the matrix A is ill-conditioned.

```
function Determinant (A : Real_Matrix) return Real'Base;
```

This function returns the determinant of the matrix A. Constraint\_Error is raised if A'Length(1) is not equal to A'Length(2).

```
function Eigenvalues(A : Real_Matrix) return Real_Vector;
```

This function returns the eigenvalues of the symmetric matrix A as a vector sorted into order with the largest first. Constraint\_Error is raised if A'Length(1) is not equal to A'Length(2). The index range of the result is A'Range(1). Argument\_Error is raised if the matrix A is not symmetric.

```
procedure Eigensystem(A      : in Real_Matrix;
                      Values : out Real_Vector;
                      Vectors : out Real_Matrix);
```

This procedure computes both the eigenvalues and eigenvectors of the symmetric matrix A. The out parameter Values is the same as that obtained by calling the function Eigenvalues. The out parameter Vectors is a matrix whose columns are the eigenvectors of the matrix A. The order of the columns corresponds to the order of the eigenvalues. The eigenvectors are normalized and mutually orthogonal (they are orthonormal), including when there are repeated eigenvalues. Constraint\_Error is raised if A'Length(1) is not equal to A'Length(2). The index ranges of the parameter Vectors are those of A. Argument\_Error is raised if the matrix A is not symmetric.

```
function Unit_Matrix (Order      : Positive;
                      First_1, First_2 : Integer := 1) return Real_Matrix;
```

This function returns a square *unit matrix* with Order\*\*2 components and lower bounds of First\_1 and First\_2 (for the first and second index ranges respectively). All components are set to 0.0 except for the main diagonal, whose components are set to 1.0. Constraint\_Error is raised if First\_1 + Order - 1 > Integer'Last or First\_2 + Order - 1 > Integer'Last.

#### Implementation Requirements

Accuracy requirements for the subprograms Solve, Inverse, Determinant, Eigenvalues and Eigensystem are implementation defined.

For operations not involving an inner product, the accuracy requirements are those of the corresponding operations of the type Real in both the strict mode and the relaxed mode (see G.2).

For operations involving an inner product, no requirements are specified in the relaxed mode. In the strict mode the modulus of the absolute error of the inner product  $X*Y$  shall not exceed  $g*\mathbf{abs}(X)*\mathbf{abs}(Y)$  where  $g$  is defined as

$$g = X'Length * Real'Machine\_Radix^{*(1-Real'Machine\_Mantissa)}$$

#### *Documentation Requirements*

Implementations shall document any techniques used to reduce cancellation errors such as extended precision arithmetic.

#### *Implementation Permissions*

The nongeneric equivalent packages may, but need not, be actual instantiations of the generic package for the appropriate predefined type.

#### *Implementation Advice*

Implementations should implement the Solve and Inverse functions using established techniques such as LU decomposition with row interchanges followed by back and forward substitution. Implementations are recommended to refine the result by performing an iteration on the residuals; if this is done then it should be documented.

It is not the intention that any special provision should be made to determine whether a matrix is ill-conditioned or not. The naturally occurring overflow (including division by zero) which will result from executing these functions with an ill-conditioned matrix and thus raise `Constraint_Error` is sufficient.

The test that a matrix is symmetric may be performed by using the equality operator to compare the relevant components.

## G.3.2 Complex Vectors and Matrices

### Insert new clause: [AI95-00296-01]

#### *Static Semantics*

The generic library package `Numerics.Generic_Complex_Arrays` has the following declaration:

```
with Ada.Numerics.Generic_Real_Arrays, Ada.Numerics.Generic_Complex_Types;
generic
  with package Real_Arrays is new Ada.Numerics.Generic_Real_Arrays (<>);
  use Real_Arrays;
  with package Complex_Types is new Ada.Numerics.Generic_Complex_Types
    (Real);
  use Complex_Types;
package Ada.Numerics.Generic_Complex_Arrays is
  pragma Pure(Generic_Complex_Arrays);

  -- Types

  type Complex_Vector is array (Integer range <>) of Complex;
  type Complex_Matrix is array (Integer range <>,
                                Integer range <>) of Complex;

  -- Subprograms for Complex_Vector types

  -- Complex_Vector selection, conversion and composition operations

  function Re (X : Complex_Vector) return Real_Vector;
  function Im (X : Complex_Vector) return Real_Vector;

  procedure Set_Re (X : in out Complex_Vector;
                    Re : in Real_Vector);
  procedure Set_Im (X : in out Complex_Vector;
                    Im : in Real_Vector);
```

```

function Compose_From_Cartesian (Re      : Real_Vector)
  return Complex_Vector;
function Compose_From_Cartesian (Re, Im : Real_Vector)
  return Complex_Vector;

function Modulus (X      : Complex_Vector) return Real_Vector;
function "abs"    (Right : Complex_Vector) return Real_Vector
  renames Modulus;

function Argument (X      : Complex_Vector) return Real_Vector;
function Argument (X      : Complex_Vector;
  Cycle : Real'Base) return Real_Vector;

function Compose_From_Polar (Modulus, Argument : Real_Vector)
  return Complex_Vector;
function Compose_From_Polar (Modulus, Argument : Real_Vector;
  Cycle : Real'Base)
  return Complex_Vector;

-- Complex_Vector arithmetic operations

function "+"      (Right : Complex_Vector) return Complex_Vector;
function "-"      (Right : Complex_Vector) return Complex_Vector;
function Conjugate (X      : Complex_Vector) return Complex_Vector;

function "+" (Left, Right : Complex_Vector) return Complex_Vector;
function "-" (Left, Right : Complex_Vector) return Complex_Vector;

function "*" (Left, Right : Complex_Vector) return Complex;

-- Mixed Real_Vector and Complex_Vector arithmetic operations

function "+" (Left : Real_Vector;
  Right : Complex_Vector) return Complex_Vector;
function "+" (Left : Complex_Vector;
  Right : Real_Vector) return Complex_Vector;
function "-" (Left : Real_Vector;
  Right : Complex_Vector) return Complex_Vector;
function "-" (Left : Complex_Vector;
  Right : Real_Vector) return Complex_Vector;

function "*" (Left : Real_Vector; Right : Complex_Vector)
  return Complex;
function "*" (Left : Complex_Vector; Right : Real_Vector)
  return Complex;

-- Complex_Vector scaling operations

function "*" (Left : Complex;
  Right : Complex_Vector) return Complex_Vector;
function "*" (Left : Complex_Vector;
  Right : Complex) return Complex_Vector;
function "/" (Left : Complex_Vector;
  Right : Complex) return Complex_Vector;

function "*" (Left : Real'Base;
  Right : Complex_Vector) return Complex_Vector;
function "*" (Left : Complex_Vector;
  Right : Real'Base) return Complex_Vector;
function "/" (Left : Complex_Vector;
  Right : Real'Base) return Complex_Vector;

-- Other Complex_Vector operations

function Unit_Vector (Index : Integer;
  Order : Positive;

```

```

        First : Integer := 1) return Complex_Vector;

-- Subprograms for Complex_Matrix types

-- Complex_Matrix selection, conversion and composition operations

function Re (X : Complex_Matrix) return Real_Matrix;
function Im (X : Complex_Matrix) return Real_Matrix;

procedure Set_Re (X : in out Complex_Matrix;
                  Re : in Real_Matrix);
procedure Set_Im (X : in out Complex_Matrix;
                  Im : in Real_Matrix);

function Compose_From_Cartesian (Re : Real_Matrix)
return Complex_Matrix;
function Compose_From_Cartesian (Re, Im : Real_Matrix)
return Complex_Matrix;

function Modulus (X : Complex_Matrix) return Real_Matrix;
function "abs" (Right : Complex_Matrix) return Real_Matrix
renames Modulus;

function Argument (X : Complex_Matrix) return Real_Matrix;
function Argument (X : Complex_Matrix;
                  Cycle : Real'Base) return Real_Matrix;

function Compose_From_Polar (Modulus, Argument : Real_Matrix)
return Complex_Matrix;
function Compose_From_Polar (Modulus, Argument : Real_Matrix;
                  Cycle : Real'Base)
return Complex_Matrix;

-- Complex_Matrix arithmetic operations

function "+" (Right : Complex_Matrix) return Complex_Matrix;
function "-" (Right : Complex_Matrix) return Complex_Matrix;
function Conjugate (X : Complex_Matrix) return Complex_Matrix;
function Transpose (X : Complex_Matrix) return Complex_Matrix;

function "+" (Left, Right : Complex_Matrix) return Complex_Matrix;
function "-" (Left, Right : Complex_Matrix) return Complex_Matrix;
function "*" (Left, Right : Complex_Matrix) return Complex_Matrix;

function "*" (Left, Right : Complex_Vector) return Complex_Matrix;

function "*" (Left : Complex_Vector;
              Right : Complex_Matrix) return Complex_Vector;
function "*" (Left : Complex_Matrix;
              Right : Complex_Vector) return Complex_Vector;

-- Mixed Real_Matrix and Complex_Matrix arithmetic operations

function "+" (Left : Real_Matrix;
              Right : Complex_Matrix) return Complex_Matrix;
function "+" (Left : Complex_Matrix;
              Right : Real_Matrix) return Complex_Matrix;
function "-" (Left : Real_Matrix;
              Right : Complex_Matrix) return Complex_Matrix;
function "-" (Left : Complex_Matrix;
              Right : Real_Matrix) return Complex_Matrix;
function "*" (Left : Real_Matrix;
              Right : Complex_Matrix) return Complex_Matrix;
function "*" (Left : Complex_Matrix;
              Right : Real_Matrix) return Complex_Matrix;

```



```

function "*" (Left  : Real_Vector;
               Right : Complex_Vector) return Complex_Matrix;
function "*" (Left  : Complex_Vector;
               Right : Real_Vector)    return Complex_Matrix;

function "*" (Left  : Real_Vector;
               Right : Complex_Matrix) return Complex_Vector;
function "*" (Left  : Complex_Vector;
               Right : Real_Matrix)    return Complex_Vector;
function "*" (Left  : Real_Matrix;
               Right : Complex_Vector) return Complex_Vector;
function "*" (Left  : Complex_Matrix;
               Right : Real_Vector)    return Complex_Vector;

-- Complex_Matrix scaling operations

function "*" (Left  : Complex;
               Right : Complex_Matrix) return Complex_Matrix;
function "*" (Left  : Complex_Matrix;
               Right : Complex)         return Complex_Matrix;
function "/" (Left  : Complex_Matrix;
               Right : Complex)         return Complex_Matrix;

function "*" (Left  : Real'Base;
               Right : Complex_Matrix) return Complex_Matrix;
function "*" (Left  : Complex_Matrix;
               Right : Real'Base)       return Complex_Matrix;
function "/" (Left  : Complex_Matrix;
               Right : Real'Base)       return Complex_Matrix;

-- Complex_Matrix inversion and related operations

function Solve (A : Complex_Matrix; X: Complex_Vector)
  return Complex_Vector;
function Solve (A, X : Complex_Matrix) return Complex_Matrix;
function Inverse (A : Complex_Matrix) return Complex_Matrix;
function Determinant (A : Complex_Matrix) return Complex;

-- Eigenvalues and vectors of a Hermitian matrix

function Eigenvalues(A : Complex_Matrix) return Real_Vector;

procedure Eigensystem(A      : in Complex_Matrix;
                      Values : out Real_Vector;
                      Vectors : out Complex_Matrix);

-- Other Complex_Matrix operations

function Unit_Matrix (Order      : Positive;
                      First_1, First_2 : Integer := 1)
  return Complex_Matrix;

end Ada.Numerics.Generic_Complex_Arrays;

```

The library package Numerics.Complex\_Arrays is declared pure and defines the same types and subprograms as Numerics.Generic\_Complex\_Arrays, except that the predefined type Float is systematically substituted for Real'Base, and the Real\_Vector and Real\_Matrix types exported by Numerics.Real\_Arrays are systematically substituted for Real\_Vector and Real\_Matrix, and the Complex type exported by Numerics.Complex\_Types is systematically substituted for Complex, throughout. Nongeneric equivalents for each of the other predefined floating point types are defined similarly, with the names Numerics.Short\_Complex\_Arrays, Numerics.Long\_Complex\_Arrays, etc.

Two types are defined and exported by Ada.Numerics.Generic\_Complex\_Arrays. The composite type Complex\_Vector is provided to represent a vector with components of type Complex; it is defined as an unconstrained one-dimensional array with an index of type Integer. The composite type Complex\_Matrix is provided to represent a matrix with components of type Complex; it is defined as an unconstrained, two-dimensional array with indices of type Integer.

The effect of the various subprograms is as described below. In many cases they are described in terms of corresponding scalar operations in Numerics.Generic\_Complex\_Types. Any exception raised by those operations is propagated by the array subprogram. Moreover, any constraints on the parameters and the accuracy of the result for each individual component are as defined for the scalar operation.

In the case of those operations which are defined to involve an inner product, Constraint\_Error may be raised if an intermediate result has a component outside the range of Real'Base even though the final mathematical result would not.

```
function Re (X : Complex_Vector) return Real_Vector;
function Im (X : Complex_Vector) return Real_Vector;
```

Each function returns a vector of the specified cartesian components of X. The index range of the result is X'Range.

```
procedure Set_Re (X : in out Complex_Vector; Re : in Real_Vector);
procedure Set_Im (X : in out Complex_Vector; Im : in Real_Vector);
```

Each procedure replaces the specified (cartesian) component of each of the components of X by the value of the matching component of Re or Im; the other (cartesian) component of each of the components is unchanged. Constraint\_Error is raised if X'Length is not equal to Re'Length or Im'Length.

```
function Compose_From_Cartesian (Re      : Real_Vector) return Complex_Vector;
function Compose_From_Cartesian (Re, Im : Real_Vector) return Complex_Vector;
```

Each function constructs a vector of Complex results (in cartesian representation) formed from given vectors of cartesian components; when only the real components are given, imaginary components of zero are assumed. The index range of the result is Re'Range. Constraint\_Error is raised if Re'Length is not equal to Im'Length.

```
function Modulus  (X      : Complex_Vector) return Real_Vector;
function "abs"    (Right : Complex_Vector) return Real_Vector renames
Modulus;
function Argument (X      : Complex_Vector) return Real_Vector;
function Argument (X      : Complex_Vector;
                  Cycle : Real'Base) return Real_Vector;
```

Each function calculates and returns a vector of the specified polar components of X or Right using the corresponding function in Numerics.Generic\_Complex\_Types. The index range of the result is X'Range or Right'Range.

```
function Compose_From_Polar (Modulus, Argument : Real_Vector)
                           return Complex_Vector;
function Compose_From_Polar (Modulus, Argument : Real_Vector;
                           Cycle               : Real'Base)
                           return Complex_Vector;
```

Each function constructs a vector of Complex results (in cartesian representation) formed from given vectors of polar components using the corresponding function in Numerics.Generic\_Complex\_Types on matching components of Modulus and Argument. The index range of the result is Modulus'Range. Constraint\_Error is raised if Modulus'Length is not equal to Argument'Length.

```
function "+" (Right : Complex_Vector) return Complex_Vector;
function "-" (Right : Complex_Vector) return Complex_Vector;
```

Each operation returns the result of applying the corresponding operation in Numerics.Generic\_Complex\_Types to each component of Right. The index range of the result is Right'Range.

```
function Conjugate (X : Complex_Vector) return Complex_Vector;
```

This function returns the result of applying the appropriate function Conjugate in Numerics.Generic\_Complex\_Types to each component of X. The index range of the result is X'Range.

```
function "+" (Left, Right : Complex_Vector) return Complex_Vector;
```

```
function "-" (Left, Right : Complex_Vector) return Complex_Vector;
```

Each operation returns the result of applying the corresponding operation in Numerics.Generic\_Complex\_Types to each component of Left and the matching component of Right. The index range of the result is Left'Range. Constraint\_Error is raised if Left'Length is not equal to Right'Length.

```
function "*" (Left, Right : Complex_Vector) return Complex;
```

This operation returns the inner product of Left and Right. Constraint\_Error is raised if Left'Length is not equal to Right'Length. This operation involves an inner product.

```
function "+" (Left : Real_Vector;  
              Right : Complex_Vector) return Complex_Vector;
```

```
function "+" (Left : Complex_Vector;  
              Right : Real_Vector) return Complex_Vector;
```

```
function "-" (Left : Real_Vector;  
              Right : Complex_Vector) return Complex_Vector;
```

```
function "-" (Left : Complex_Vector;  
              Right : Real_Vector) return Complex_Vector;
```

Each operation returns the result of applying the corresponding operation in Numerics.Generic\_Complex\_Types to each component of Left and the matching component of Right. The index range of the result is Left'Range. Constraint\_Error is raised if Left'Length is not equal to Right'Length.

```
function "*" (Left : Real_Vector; Right : Complex_Vector) return Complex;
```

```
function "*" (Left : Complex_Vector; Right : Real_Vector) return Complex;
```

Each operation returns the inner product of Left and Right. Constraint\_Error is raised if Left'Length is not equal to Right'Length. These operations involve an inner product.

```
function "*" (Left : Complex; Right : Complex_Vector) return Complex_Vector;
```

This operation returns the result of multiplying each component of Right by the complex number Left using the appropriate operation "\*" in Numerics.Generic\_Complex\_Types. The index range of the result is Right'Range.

```
function "*" (Left : Complex_Vector; Right : Complex) return Complex_Vector;
```

```
function "/" (Left : Complex_Vector; Right : Complex) return Complex_Vector;
```

Each operation returns the result of applying the corresponding operation in Numerics.Generic\_Complex\_Types to each component of the vector Left and the complex number Right. The index range of the result is Left'Range.

```
function "*" (Left : Real'Base; Right : Complex_Vector) return  
Complex_Vector;
```

This operation returns the result of multiplying each component of Right by the real number Left using the appropriate operation "\*" in Numerics.Generic\_Complex\_Types. The index range of the result is Right'Range.

```
function "*" (Left : Complex_Vector; Right : Real'Base) return  
Complex_Vector;
```

```
function "/" (Left : Complex_Vector; Right : Real'Base) return  
Complex_Vector;
```

Each operation returns the result of applying the corresponding operation in Numerics.Generic\_Complex\_Types to each component of the vector Left and the real number Right. The index range of the result is Left'Range.

```
function Unit_Vector (Index : Integer;  
                      Order : Positive;  
                      First : Integer := 1) return Complex_Vector;
```

This function returns a *unit vector* with Order components and a lower bound of First. All components are set to (0.0,0.0) except for the Index component which is set to (1.0,0.0). Constraint\_Error is raised if Index < First, Index > First + Order - 1, or if First + Order - 1 > Integer'Last.

```
function Re (X : Complex_Matrix) return Real_Matrix;  
function Im (X : Complex_Matrix) return Real_Matrix;
```

Each function returns a matrix of the specified cartesian components of X. The index ranges of the result are those of X.

```
procedure Set_Re (X : in out Complex_Matrix; Re : in Real_Matrix);  
procedure Set_Im (X : in out Complex_Matrix; Im : in Real_Matrix);
```

Each procedure replaces the specified (cartesian) component of each of the components of X by the value of the matching component of Re or Im; the other (cartesian) component of each of the components is unchanged. Constraint\_Error is raised if X'Length(1) is not equal to Re'Length(1) or Im'Length(1) or if X'Length(2) is not equal to Re'Length(2) or Im'Length(2).

```
function Compose_From_Cartesian (Re      : Real_Matrix) return Complex_Matrix;  
function Compose_From_Cartesian (Re, Im : Real_Matrix) return Complex_Matrix;
```

Each function constructs a matrix of Complex results (in cartesian representation) formed from given matrices of cartesian components; when only the real components are given, imaginary components of zero are assumed. The index ranges of the result are those of Re. Constraint\_Error is raised if Re'Length(1) is not equal to Im'Length(1) or Re'Length(2) is not equal to Im'Length(2).

```
function Modulus  (X      : Complex_Matrix) return Real_Matrix;  
function "abs"    (Right : Complex_Matrix) return Real_Matrix renames  
Modulus;  
function Argument (X      : Complex_Matrix) return Real_Matrix;  
function Argument (X      : Complex_Matrix;  
                  Cycle : Real'Base) return Real_Matrix;
```

Each function calculates and returns a matrix of the specified polar components of X or Right using the corresponding function in Numerics.Generic\_Complex\_Types. The index ranges of the result are those of X or Right.

```
function Compose_From_Polar (Modulus, Argument : Real_Matrix)  
                           return Complex_Matrix;  
function Compose_From_Polar (Modulus, Argument : Real_Matrix;  
                           Cycle               : Real'Base)  
                           return Complex_Matrix;
```

Each function constructs a matrix of Complex results (in cartesian representation) formed from given matrices of polar components using the corresponding function in Numerics.Generic\_Complex\_Types on matching components of Modulus and Argument. The index ranges of the result are those of Modulus. Constraint\_Error is raised if Modulus'Length(1) is not equal to Argument'Length(1) or Modulus'Length(2) is not equal to Argument'Length(2).

```
function "+" (Right : Complex_Matrix) return Complex_Matrix;  
function "-" (Right : Complex_Matrix) return Complex_Matrix;
```

Each operation returns the result of applying the corresponding operation in Numerics.Generic\_Complex\_Types to each component of Right. The index ranges of the result are those of Right.

```
function Conjugate (X : Complex_Matrix) return Complex_Matrix;
```

This function returns the result of applying the appropriate function `Conjugate` in `Numerics.Generic_Complex_Types` to each component of `X`. The index ranges of the result are those of `X`.

```
function Transpose (X : Complex_Matrix) return Complex_Matrix;
```

This function returns the transpose of a matrix `X`. The first and second index ranges of the result are `X'Range(2)` and `X'Range(1)` respectively.

```
function "+" (Left, Right : Complex_Matrix) return Complex_Matrix;
```

```
function "-" (Left, Right : Complex_Matrix) return Complex_Matrix;
```

Each operation returns the result of applying the corresponding operation in `Numerics.Generic_Complex_Types` to each component of `Left` and the matching component of `Right`. The index ranges of the result are those of `Left`. `Constraint_Error` is raised if `Left'Length(1)` is not equal to `Right'Length(1)` or `Left'Length(2)` is not equal to `Right'Length(2)`.

```
function "*" (Left, Right : Complex_Matrix) return Complex_Matrix;
```

This operation provides the standard mathematical operation for matrix multiplication. The first and second index ranges of the result are `Left'Range(1)` and `Right'Range(2)` respectively. `Constraint_Error` is raised if `Left'Length(2)` is not equal to `Right'Length(1)`. This operation involves inner products.

```
function "*" (Left, Right : Complex_Vector) return Complex_Matrix;
```

This operation returns the outer product of a (column) vector `Left` by a (row) vector `Right` using the appropriate operation `"*"` in `Numerics.Generic_Complex_Types` for computing the individual components. The first and second index ranges of the matrix result are `Left'Range` and `Right'Range` respectively.

```
function "*" (Left : Complex_Vector;  
             Right : Complex_Matrix) return Complex_Vector;
```

This operation provides the standard mathematical operation for multiplication of a (row) vector `Left` by a matrix `Right`. The index range of the (row) vector result is `Right'Range(2)`. `Constraint_Error` is raised if `Left'Length` is not equal to `Right'Length(1)`. This operation involves inner products.

```
function "*" (Left : Complex_Matrix;  
             Right : Complex_Vector) return Complex_Vector;
```

This operation provides the standard mathematical operation for multiplication of a matrix `Left` by a (column) vector `Right`. The index range of the (column) vector result is `Left'Range(1)`. `Constraint_Error` is raised if `Left'Length(2)` is not equal to `Right'Length`. This operation involves inner products.

```
function "+" (Left : Real_Matrix;  
             Right : Complex_Matrix) return Complex_Matrix;
```

```
function "+" (Left : Complex_Matrix;  
             Right : Real_Matrix) return Complex_Matrix;
```

```
function "-" (Left : Real_Matrix;  
             Right : Complex_Matrix) return Complex_Matrix;
```

```
function "-" (Left : Complex_Matrix;  
             Right : Real_Matrix) return Complex_Matrix;
```

Each operation returns the result of applying the corresponding operation in `Numerics.Generic_Complex_Types` to each component of `Left` and the matching component of `Right`. The index ranges of the result are those of `Left`. The exception `Constraint_Error` is raised if `Left'Length(1)` is not equal to `Right'Length(1)` or `Left'Length(2)` is not equal to `Right'Length(2)`.

```
function "*" (Left : Real_Matrix;  
             Right : Complex_Matrix) return Complex_Matrix;
```

```
function "*" (Left : Complex_Matrix;  
             Right : Real_Matrix) return Complex_Matrix;
```

Each operation provides the standard mathematical operation for matrix multiplication. The first and second index ranges of the result are Left'Range(1) and Right'Range(2) respectively. Constraint\_Error is raised if Left'Length(2) is not equal to Right'Length(1). These operations involve inner products.

```
function "*" (Left  : Real_Vector;
              Right : Complex_Vector) return Complex_Matrix;
function "*" (Left  : Complex_Vector;
              Right : Real_Vector)    return Complex_Matrix;
```

Each operation returns the outer product of a (column) vector Left by a (row) vector Right using the appropriate operation "\*" in Numerics.Generic\_Complex\_Types for computing the individual components. The first and second index ranges of the matrix result are Left'Range and Right'Range respectively.

```
function "*" (Left  : Real_Vector;
              Right : Complex_Matrix) return Complex_Vector;
function "*" (Left  : Complex_Vector;
              Right : Real_Matrix)    return Complex_Vector;
```

Each operation provides the standard mathematical operation for multiplication of a (row) vector Left by a matrix Right. The index range of the (row) vector result is Right'Range(2). Constraint\_Error is raised if Left'Length is not equal to Right'Length(1). These operations involve inner products.

```
function "*" (Left  : Real_Matrix;
              Right : Complex_Vector) return Complex_Vector;
function "*" (Left  : Complex_Matrix;
              Right : Real_Vector)    return Complex_Vector;
```

Each operation provides the standard mathematical operation for multiplication of a matrix Left by a (column) vector Right. The index range of the (column) vector result is Left'Range(1). Constraint\_Error is raised if Left'Length(2) is not equal to Right'Length. These operations involve inner products.

```
function "*" (Left : Complex; Right : Complex_Matrix) return Complex_Matrix;
```

This operation returns the result of multiplying each component of Right by the complex number Left using the appropriate operation "\*" in Numerics.Generic\_Complex\_Types. The index ranges of the result are those of Right.

```
function "*" (Left : Complex_Matrix; Right : Complex) return Complex_Matrix;
function "/" (Left : Complex_Matrix; Right : Complex) return Complex_Matrix;
```

Each operation returns the result of applying the corresponding operation in Numerics.Generic\_Complex\_Types to each component of the matrix Left and the complex number Right. The index ranges of the result are those of Left.

```
function "*" (Left : Real'Base; Right : Complex_Matrix) return
Complex_Matrix;
```

This operation returns the result of multiplying each component of Right by the real number Left using the appropriate operation "\*" in Numerics.Generic\_Complex\_Types. The index ranges of the result are those of Right.

```
function "*" (Left : Complex_Matrix; Right : Real'Base) return
Complex_Matrix;
function "/" (Left : Complex_Matrix; Right : Real'Base) return
Complex_Matrix;
```

Each operation returns the result of applying the corresponding operation in Numerics.Generic\_Complex\_Types to each component of the matrix Left and the real number Right. The index ranges of the result are those of Left.

```
function Solve (A : Complex_Matrix; X: Complex_Vector) return Complex_Vector;
```

This function returns a vector  $Y$  such that  $X$  is (nearly) equal to  $A * Y$ . This is the standard mathematical operation for solving a single set of linear equations. The index range of the result is  $X'Range$ . `Constraint_Error` is raised if  $A'Length(1)$ ,  $A'Length(2)$  and  $X'Length$  are not equal. `Constraint_Error` is raised if the matrix  $A$  is ill-conditioned.

```
function Solve (A, X : Complex_Matrix) return Complex_Matrix;
```

This function returns a matrix  $Y$  such that  $X$  is (nearly) equal to  $A * Y$ . This is the standard mathematical operation for solving several sets of linear equations. The index ranges of the result are those of  $X$ . `Constraint_Error` is raised if  $A'Length(1)$ ,  $A'Length(2)$  and  $X'Length(1)$  are not equal. `Constraint_Error` is raised if the matrix  $A$  is ill-conditioned.

```
function Inverse (A : Complex_Matrix) return Complex_Matrix;
```

This function returns a matrix  $B$  such that  $A * B$  is (nearly) equal to the unit matrix. The index ranges of the result are those of  $A$ . `Constraint_Error` is raised if  $A'Length(1)$  is not equal to  $A'Length(2)$ . `Constraint_Error` is raised if the matrix  $A$  is ill-conditioned.

```
function Determinant (A : Complex_Matrix) return Complex;
```

This function returns the determinant of the matrix  $A$ . `Constraint_Error` is raised if  $A'Length(1)$  is not equal to  $A'Length(2)$ .

```
function Eigenvalues(A : Complex_Matrix) return Real_Vector;
```

This function returns the eigenvalues of the Hermitian matrix  $A$  as a vector sorted into order with the largest first. `Constraint_Error` is raised if  $A'Length(1)$  is not equal to  $A'Length(2)$ . The index range of the result is  $A'Range(1)$ . `Argument_Error` is raised if the matrix  $A$  is not Hermitian.

```
procedure Eigensystem(A      : in Complex_Matrix;
                       Values : out Real_Vector;
                       Vectors : out Complex_Matrix);
```

This procedure computes both the eigenvalues and eigenvectors of the Hermitian matrix  $A$ . The out parameter `Values` is the same as that obtained by calling the function `Eigenvalues`. The out parameter `Vectors` is a matrix whose columns are the eigenvectors of the matrix  $A$ . The order of the columns corresponds to the order of the eigenvalues. The eigenvectors are mutually orthonormal, including when there are repeated eigenvalues. `Constraint_Error` is raised if  $A'Length(1)$  is not equal to  $A'Length(2)$ . The index ranges of the parameter `Vectors` are those of  $A$ . `Argument_Error` is raised if the matrix  $A$  is not Hermitian.

```
function Unit_Matrix (Order      : Positive;
                      First_1, First_2 : Integer := 1)
                      return Complex_Matrix;
```

This function returns a square *unit matrix* with  $Order**2$  components and lower bounds of  $First\_1$  and  $First\_2$  (for the first and second index ranges respectively). All components are set to (0.0,0.0) except for the main diagonal, whose components are set to (1.0,0.0). `Constraint_Error` is raised if  $First\_1 + Order - 1 > Integer'Last$  or  $First\_2 + Order - 1 > Integer'Last$ .

#### Implementation Requirements

Accuracy requirements for the subprograms `Solve`, `Inverse`, `Determinant`, `Eigenvalues` and `Eigensystem` are implementation defined.

For operations not involving an inner product, the accuracy requirements are those of the corresponding operations of the type `Real'Base` and `Complex` in both the strict mode and the relaxed mode (see G.2).

For operations involving an inner product, no requirements are specified in the relaxed mode. In the strict mode the modulus of the absolute error of the inner product  $X*Y$  shall not exceed  $g*abs(X)*abs(Y)$  where  $g$  is defined as

$g = X'Length * Real'Machine\_Radix**(1-Real'Machine\_Mantissa)$  for mixed complex and real operands

$g = \sqrt{2.0} * X'Length * Real'Machine\_Radix^{*(1-Real'Machine\_Mantissa)}$  for two complex operands

*Documentation Requirements*

Implementations shall document any techniques used to reduce cancellation errors such as extended precision arithmetic.

*Implementation Permissions*

The nongeneric equivalent packages may, but need not, be actual instantiations of the generic package for the appropriate predefined type.

Although many operations are defined in terms of operations from Numerics.Generic\_Complex\_Types, they need not be implemented by calling those operations provided that the effect is the same.

*Implementation Advice*

Implementations should implement the Solve and Inverse functions using established techniques. Implementations are recommended to refine the result by performing an iteration on the residuals; if this is done then it should be documented.

It is not the intention that any special provision should be made to determine whether a matrix is ill-conditioned or not. The naturally occurring overflow (including division by zero) which will result from executing these functions with an ill-conditioned matrix and thus raise Constraint\_Error is sufficient.

The test that a matrix is Hermitian may use the equality operator to compare the real components and negation followed by equality to compare the imaginary components (see G.2.1).

Implementations should not perform operations on mixed complex and real operands by first converting the real operand to complex. See G.1.1.



## Annex H: Safety and Security

**Replace the title:** [AI95-00347-01]

Safety and Security

**by:**

High Integrity Systems

**Replace paragraph 1:** [AI95-00347-01]

This Annex addresses requirements for systems that are safety critical or have security constraints. It provides facilities and specifies documentation requirements that relate to several needs:

**by:**

This Annex addresses requirements for high integrity systems (including safety-critical systems and security-critical systems). It provides facilities and specifies documentation requirements that relate to several needs:

### H.3.1 Pragma Reviewable

**Replace paragraph 8:** [AI95-00209-01]

- For each reference to a scalar object, an identification of the reference as either ``known to be initialized," or ``possibly uninitialized," independent of whether pragma Normalize\_Scalars applies;

**by:**

- For each read of a scalar object, an identification of the read as either ``known to be initialized," or ``possibly uninitialized," independent of whether pragma Normalize\_Scalars applies;

### H.3.2 Pragma Inspection\_Point

**Replace paragraph 9:** [AI95-00209-01]

7 The implementation is not allowed to perform ``dead store elimination" on the last assignment to a variable prior to a point where the variable is inspectable. Thus an inspection point has the effect of an implicit reference to each of its inspectable objects.

**by:**

7 The implementation is not allowed to perform ``dead store elimination" on the last assignment to a variable prior to a point where the variable is inspectable. Thus an inspection point has the effect of an implicit read of each of its inspectable objects.

## H.4 Safety and Security Restrictions

**Replace the title:** [AI95-00347-01]

Safety and Security Restrictions

**by:**

High Integrity Restrictions

**Replace paragraph 2:** [AI95-00347-01]

The following restrictions, the same as in D.7, apply in this Annex: No\_Task\_Hierarchy, No\_Abort\_Statement, No\_Implicit\_Heap\_Allocation, Max\_Task\_Entries is 0, Max\_Asynchronous\_Select\_Nesting is 0, and Max\_Tasks is 0. The last three restrictions are checked prior to program execution.

by:

The following restrictions, the same as in D.7, apply in this Annex: No\_Task\_Hierarchy, No\_Abort\_Statement, No\_Implicit\_Heap\_Allocation, Max\_Task\_Entries is 0, Max\_Asynchronous\_Select\_Nesting is 0, and Max\_Tasks is 0. The last three restrictions are checked prior to program execution. Pragma Profile(Ravenscar) applies in this Annex.

**Replace paragraph 20: [AI95-00285-01]**

No\_IO

Semantic dependence on any of the library units Sequential\_IO, Direct\_IO, Text\_IO, Wide\_Text\_IO, or Stream\_IO is not allowed.

by:

No\_IO

Semantic dependence on any of the library units Sequential\_IO, Direct\_IO, Text\_IO, Wide\_Text\_IO, Wide\_Wide\_Text\_IO, or Stream\_IO is not allowed.

## H.5 Pragma Detect\_Blocking

**Insert new clause: [AI95-00305-01]**

The following pragma forces an implementation to detect potentially blocking operations within a protected operation.

*Syntax*

The form of a pragma Detect\_Blocking is as follows:

**pragma** Detect\_Blocking;

*Dynamic Semantics*

An implementation is required to detect a potentially blocking operation within a protected operation, and to raise Program\_Error (see 9.5.1).

*Post-Compilation Rules*

A pragma Detect\_Blocking is a configuration pragma.

*Implementation Permissions*

An implementation is allowed to reject a compilation\_unit if a potentially blocking operation is present directly within an entry\_body or the body of a protected subprogram.

NOTES

10 An operation that causes a task to be blocked within a foreign language domain is not defined to be potentially blocking, and need not be detected.

## H.6 Pragma Partition\_Elaboration\_Policy

**Insert new clause: [AI95-00265-01]**

This clause defines a pragma for user control over elaboration policy.

*Syntax*

The form of a pragma Partition\_Elaboration\_Policy is as follows:

**pragma** Partition\_Elaboration\_Policy (*policy\_identifier*);

The *policy\_identifier* shall be either Sequential, Concurrent or an implementation-defined identifier.

*Post-Compilation Rules*

The pragma is a configuration pragma. It applies to all compilation units in a partition.

If the Sequential policy is specified for a partition then pragma Restrictions (No\_Task\_Hierarchy) shall also be specified for the partition.

*Dynamic Semantics*

Notwithstanding what this International Standard says elsewhere, this pragma allows partition elaboration rules concerning task activation and interrupt attachment to be changed. If the *policy\_identifier* is Concurrent, or if there is no pragma Partition\_Elaboration\_Policy defined for the partition, then the rules defined elsewhere in this Standard apply.

If the partition elaboration policy is Sequential, all task activations for library-level tasks and all interrupt handler attachments for library-level interrupt handlers are deferred. The deferred task activations and handler attachments occur after the elaboration of all *library\_items* prior to calling the main subprogram. At this point the Environment task is suspended until all deferred task activations and handler attachments are complete.

If any deferred task activation fails, Tasking\_Error is raised in the Environment task. The Environment task and all tasks whose activations fail are terminated. If a number of dynamic interrupt handler attachments for the same interrupt are deferred then the most recent call of Attach\_Handler or Exchange\_Handler determines which handler is attached.

*Implementation Advice*

If the partition elaboration policy is Sequential and the Environment task becomes permanently blocked during elaboration then the partition is deadlocked and it is recommended that the partition be immediately terminated.

*Implementation Permission*

If the partition elaboration policy is Sequential and any task activation fails then an implementation may immediately terminate the active partition to mitigate the hazard posed by continuing to execute with a subset of the tasks being active.

## Annex J: Obsolescent Features

### Replace paragraph 1: [AI95-00368-01]

This Annex contains descriptions of features of the language whose functionality is largely redundant with other features defined by this International Standard. Use of these features is not recommended in newly written programs.

by:

This Annex contains descriptions of features of the language whose functionality is largely redundant with other features defined by this International Standard. Use of these features is not recommended in newly written programs. Use of these features can be prevented by using pragma Restrictions(No\_Obsolescent\_Features), see 13.12.

## J.10 Specific Suppression of Checks

### Insert new clause: [AI95-00224-01]

Pragma Suppress can be used to suppress checks on specific entities.

*Syntax*

The form of a specific Suppress pragma is as follows:

**pragma** Suppress(identifier, [On =>] name);

*Legality Rules*

The identifier shall be the name of a check (see 11.5). The name shall statically denote some entity.

For a specific Suppress pragma that is immediately within a package\_specification, the name shall denote an entity (or several overloaded subprograms) declared immediately within the package\_specification.

*Static Semantics*

A specific Suppress pragma applies to the named check from the place of the pragma to the end of the innermost enclosing declarative region, or, if the pragma is given in a package\_specification, to the end of the scope of the named entity. The pragma applies only to the named entity, or, for a subtype, on objects and values of its type. A specific Suppress pragma suppresses the named check for any entities to which it applies (see 11.5). Which checks are associated with a specific entity is not defined by this International Standard.

*Implementation Permissions*

An implementation is allowed to place restrictions on specific Suppress pragmas.

NOTES

3 An implementation may support a similar On parameter on pragma Unsuppress (see 11.5).

## J.11 The Class Attribute of Untagged Incomplete Types

### Insert new clause: [AI95-00326-01]

For the first subtype S of a type T declared by an incomplete\_type\_declaration that is not tagged, the following attribute is defined:

S'Class

Denotes the first subtype of the incomplete class-wide type rooted at T. The completion of T shall declare a tagged type. Such an attribute reference shall occur in the same library unit as the incomplete\_type\_declaration.

## J.12 Pragma Interface

**Insert new clause: [AI95-00284-02]**

*Syntax*

In addition to an identifier, the reserved word **interface** is allowed as a pragma name, to provide compatibility with a prior edition of this International Standard.